



IEC 60086-1

Edition 14.0 2026-06

INTERNATIONAL STANDARD

COMMENTED VERSION

Primary batteries -
Part 1: General

Sample Document

get full document from standards.iteh.ai



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2026 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	5
INTRODUCTION	7
1 Scope	8
2 Normative references	8
3 Terms and definitions	8
4 Requirements	12
4.1 General	12
4.1.1 Design	12
4.1.2 Battery dimensions	12
4.1.3 Terminals	12
4.1.4 Classification (electrochemical system)	14
4.1.5 Designation	15
4.1.6 Marking	15
4.1.7 Interchangeability: battery voltage	16
4.1.8 Other requirements, conformity checklist	17
4.2 Performance	17
4.2.1 Discharge performance	17
4.2.2 Dimensional stability	17
4.2.3 Leakage	17
4.2.4 Open-circuit voltage limits	17
4.2.5 Service output	18
4.2.6 Safety	18
4.2.7 Validity of testing	18
5 Performance – Testing	18
5.1 Capacity testing versus application and service output testing	18
5.2 Discharge testing	19
5.2.1 General	19
5.2.2 Application tests	19
5.2.3 Service output tests	20
5.3 Conformance check to a specified minimum average duration	20
5.4 Guidance for considering proposed value of minimum average duration	20
5.5 OCV testing	21
5.6 Insulation resistance	21
5.7 Battery dimensions	21
5.8 Leakage and deformation	21
6 Performance – Test conditions	21
6.1 Storage and discharge conditions	21
6.2 Commencement of discharge tests after storage	22
6.3 Discharge test conditions	22
6.3.1 General	22
6.3.2 Compliance	22
6.4 Load resistance	22
6.5 Time periods	22
6.6 Test condition tolerances	23
6.7 Activation of 'P'-system batteries	23
6.8 Measuring equipment	23

6.8.1	Voltage measurement	23
6.8.2	Mechanical measurement	23
7	Sampling and quality assurance	23
8	Battery packaging	23
Annex A (normative) Criteria for the standardization of batteries		24
Annex B (informative) Recommendations for equipment design		25
B.1	Technical liaison	25
B.2	Battery compartment	25
B.2.1	General	25
B.2.2	Limiting access by children	26
B.3	Equipment voltage cut-off	26
Annex C (normative) Designation system (nomenclature)		27
C.1	General	27
C.2	Designation system in use up to October 1990	27
C.2.1	General	27
C.2.2	Cells	27
C.2.3	Electrochemical system	29
C.2.4	Batteries	29
C.2.5	Modifiers	30
C.2.6	Examples	30
C.3	Designation system in use since October 1990	30
C.3.1	General	30
C.3.2	Round batteries	31
C.3.3	Non-round batteries	35
C.3.4	Ambiguity	38
Annex D (informative) Standard discharge voltage U_S – Definition and method of determination		40
D.1	Definition	40
D.2	Determination	40
D.2.1	General considerations: the C/R -plot	40
D.2.2	Determination of the standard discharge resistor R_S	42
D.2.3	Determination of the standard discharge capacity C_S and standard discharge time t_S	42
D.3	Experimental conditions to be observed and test results	43
Annex E (informative) Preparation of standard methods of measuring performance (SMMP) of consumer goods		45
E.1	General	45
E.2	Performance characteristics	45
E.3	Criteria for the development of test methods	45
Annex F (informative) Guidance for proposing value of minimum average duration		46
F.1	General	46
F.2	Sampling	46
F.3	Calculation method	46
Annex G (normative) Code of practice for packaging, shipment, storage, use and disposal of primary batteries		47
G.1	General	47
G.2	Packaging	47

G.3	Transport and handling	47
G.4	Storage and stock rotation	47
G.5	Displays at sales points	48
G.6	Selection, use and disposal	48
G.6.1	Purchase	48
G.6.2	Installation	48
G.6.3	Use	49
G.6.4	Replacement	49
G.6.5	Disposal	49
Annex H (informative)	Common designation	50
Annex I (informative)	Measurement methods for the determination of the performance and durability of non-rechargeable portable batteries	52
I.1	Overview	52
I.2	Interoperability	52
I.3	IEC designations of portable batteries of general use	52
I.4	Performance and durability tests for non-rechargeable portable batteries of general use	53
I.4.1	Average duration of discharge	53
I.4.2	Delayed discharge performance	54
I.4.3	Resistance to leakage	55
I.5	Determination of average duration for the purpose of labelling	55
Annex J (informative)	Compliance checklist	56
Bibliography	57
List of comments	58
Figure 1	– Pulse tests with multiple load	20
Figure C.1	– Designation system for round batteries: diameter $d_1 < 100$ mm; height $h_1 < 100$ mm	32
Figure C.2	– Diameter code for non-recommended diameters	33
Figure C.3	– Height code for denoting the hundredths of a millimetre of height	34
Figure C.4	– Designation system for round batteries: diameter $d_1 \geq 100$ mm; height $h_1 \geq 100$ mm	35
Figure C.5	– Designation system for non-round batteries, dimensions < 100 mm	36
Figure C.6	– Designation system for non-round batteries, dimensions ≥ 100 mm	37
Figure C.7	– Height code for discrimination per tenth of a millimetre	38
Figure D.1	– Normalized C/R -plot (schematic)	41
Figure D.2	– Standard discharge voltage (schematic)	43
Table 1	– Standardized electrochemical systems	14
Table 2	– Marking requirements	16
Table 3	– Conditions for storage before and during discharge testing	21
Table 4	– Resistive loads for tests	22
Table 5	– Time periods for tests	22
Table 6	– Test condition tolerances	23
Table A.1	– Items necessary to standardize	24

Table C.1 – Physical designation and dimensions of round cells and batteries.....	28
Table C.2 – Physical designation and nominal overall dimensions of flat cells	29
Table C.3 – Physical designation and dimensions of square cells and batteries	29
Table C.4 – Examples of battery designations	30
Table C.5 – Diameter code for recommended diameter.....	33
Table C.6 – Physical designation and dimensions of round cell and batteries based on Clause C.2 C.3	38
Table C.7 – Physical designation and dimensions of non-round batteries based on Clause C.2 C.3	39
Table D.1 – Standard discharge voltage by system	44
Table H.1 – Index	50
Table I.1 – IEC and common formats of portable batteries of general use	52
Table I.2 – Discharge testing of non-rechargeable portable batteries of general use	53

Sample Document

get full document from standards.iteh.ai

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**Primary batteries -
Part 1: General**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

This commented version (CMV) of the official standard IEC 60086-1:2026 edition 14.0 allows the user to identify the changes made to the previous IEC 60086-1:2021 edition 13.0. Furthermore, comments from IEC TC 35 experts are provided to explain the reasons of the most relevant changes, or to clarify any part of the content.

A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text. Experts' comments are identified by a blue-background number. Mouse over a number to display a pop-up note with the comment.

This publication contains the CMV and the official standard. The full list of comments is available at the end of the CMV.

IEC 60086-1 has been prepared by IEC technical committee 35: Primary cells and batteries. It is an International Standard.

This fourteenth edition cancels and replaces the thirteenth edition published in 2021. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) In Clause 3, terms were reordered according to their functions: basic terms, electrochemical systems, battery shapes, electrical characteristics, specifications, failure modes;
- b) New letter "T" was added in Table 1, *Standardized electrochemical systems of 4.1.4 classification*;
- c) Maximum open circuit voltage of letter "F" was changed from 1,83 V to 1,90 V;
- d) Drawing of pulse tests with multiple load was moved from IEC 60086-2 to 5.2.2.2, *Application tests with multiple loads*;
- e) Annex F, *Guidance for proposing value of minimum average duration* was modified;
- f) Annex D of IEC 60086-2:2021, *Common designation*, has been transferred to Annex H of this document;
- g) Table H.1, *Common designation index*, was modified to provide reference to IEC 60086-2-1 and IEC 60086-2-2 for each battery;
- h) Annex I identifies the batteries of general use and the applicable tests to compare their performance, in support of Regulation (EU) 2023/1542 (Batteries Regulation).

The text of this International Standard is based on the following documents:

Draft	Report on voting
35/1590/FDIS	35/1600/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 60086 series, under the general title *Primary batteries*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INTRODUCTION

The technical content of this part of IEC 60086 provides fundamental requirements and information on primary cells and batteries. ~~All batteries within the IEC 60086 series are considered dry cell batteries.~~ In this sense, IEC 60086-1 is the main component of the IEC 60086 series and forms the basis for the subsequent parts. For example, this part includes elementary information on definitions, nomenclature, dimensions and marking. While specific requirements are included, the content of this part tends to explain methodology (how) and justification (why).

Over the years, this part has been changed to improve its content and remains under continual scrutiny to ensure that the publication is kept up to date with the advances in both battery and battery-powered device technologies.

Safety requirements and recommendations are available in IEC 60086-4, IEC 60086-5 and IEC 62281. Specifications are available in ~~IEC 60086-2~~ IEC 60086-2-1, IEC 60086-2-2 and IEC 60086-3. Environmental aspects are dealt with in IEC 60086-6.

Sample Document

get full document from standards.iteh.ai

1 Scope

This part of IEC 60086 is intended to standardize primary batteries with respect to dimensions, nomenclature, terminal configurations, markings, test methods, typical performance, safety and environmental aspects.

This document on one side specifies requirements for primary cells and batteries. On the other side, this document also specifies procedures of how requirements for these batteries are to be standardised.

As a classification tool for primary batteries, this document specifies system letters, electrodes, electrolytes, and nominal as well as maximum open circuit voltage of electrochemical systems.

The object of this part of IEC 60086 is to benefit primary battery users, device designers and battery manufacturers by ensuring that batteries from different manufacturers are interchangeable according to standard form, fit and function. Furthermore, to ensure compliance with the above, this document specifies standard test methods for testing primary cells and batteries.

This document also contains requirements in Annex A of this document justifying the inclusion or the ongoing retention of batteries in the IEC 60086 series.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

~~IEC 60086-2:2015, Primary batteries – Part 2: Physical and electrical specifications~~

IEC 60086-2-1:2026, *Primary batteries - Part 2-1: Physical and electrical specifications of batteries with aqueous electrolyte* **1**

IEC 60086-2-2:2026, *Primary batteries - Part 2-2: Physical and electrical specifications of lithium batteries* **1**

IEC 60086-3:2021, *Primary batteries - Part 3: Watch batteries*

IEC 60086-4, *Primary batteries - Part 4: Safety of lithium batteries*

IEC 60086-5, *Primary batteries - Part 5: Safety of batteries with aqueous electrolyte*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply. **2**

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1

cell

basic functional unit, consisting of an assembly of electrodes, electrolyte, container, terminals and usually separators, that is a source of electric energy obtained by direct conversion of chemical energy

[SOURCE: IEC 60050-482:2004, 482-01-01, modified – removal of Note]

3.2

battery

~~one or more cells electrically connected and fitted in a case, with terminals, markings and protective devices etc., as necessary for use~~

~~[SOURCE: IEC 60050-482:2004, 482-01-04, modified – removal of "fitted with devices necessary for use"]~~

one or more cells electrically connected and fitted with devices necessary for use, for example case, labels, terminals, marking and protective devices etc.

[SOURCE: IEC 60050-482:2004, 482-01-04, modified – addition of "electrically connected", "labels" and "etc."]

3.3

primary cell

primary battery

cell or battery that is not designed to be electrically recharged

3.4

round cell

round battery

cell or battery with circular cross section

3.5

button cell

button battery

small round cell or battery where the overall height is less than the diameter, containing aqueous electrolyte

Note 1 to entry: See coin cell, coin battery, lithium button cell, lithium button battery.

[SOURCE: IEC 60050-482:2004, 482-02-40, modified – addition of "small round", "or battery", removal of "e.g. in the shape of a button or a coin", addition of "containing aqueous electrolyte"]

3.6

coin cell

coin battery

lithium button cell

lithium button battery

small round cell or battery where the overall height is less than the diameter, containing non-aqueous electrolyte

Note 1 to entry: The nominal voltage of lithium batteries is typically greater than 2 V.

Note 2 to entry: See button cell, button battery.

3.7**cylindrical cell
cylindrical battery**

round cell or battery in which the overall height is equal to or greater than the diameter

[SOURCE: IEC 60050-482:2004, 482-02-39, modified – "cell with a cylindrical shape" replaced with "round cell or battery"]

3.8**nominal voltage** ~~(of a primary battery)~~ U_n

suitable approximate value of the voltage used to designate or identify a cell, a battery or an electrochemical system

[SOURCE: IEC 60050-482:2004, 482-03-31, modified – addition of "~~(of a primary battery)~~" and U_n]

3.9**open-circuit voltage****OCV**

voltage across the terminals of a cell or battery when it is off discharge

3.10**closed-circuit voltage****CCV**

voltage across the terminals of a battery when it is on discharge

[SOURCE: IEC 60050-482:2004, 482-03-28, modified – "voltage between the terminals of a cell or battery" replaced by "voltage across the terminals of a battery"]

~~**3.9**~~~~**dry (primary) battery**~~

~~primary battery in which the liquid electrolyte is essentially immobilized~~

~~[SOURCE: IEC 60050-482:2004, 482-04-14, modified — replacement of "containing an immobilized electrolyte."]~~

3.11**end-point voltage****EV**

specified voltage of a battery at which the battery discharge is terminated

[SOURCE: IEC 60050-482:2004, 482-03-30]

3.12**minimum average duration****MAD**

acceptable minimum average time on discharge, which is met by testing a sample of batteries according to specified methods, to be deemed compliant

Note 1 to entry: The discharge test is carried out according to the specified methods or standards and designed to show conformity with the standard applicable to the battery types.

3.13**application test**

simulation of the actual use of a battery in a specific application

3.14

discharge ~~(of a primary battery)~~

operation during which a battery delivers current to an external circuit

3.15

service output ~~(of a primary battery)~~

service life, or capacity, or energy output of a battery under specified conditions of discharge

3.16

service output test

test designed to measure the service output of a battery

~~Note 1 to entry:— A service output test may be prescribed, for example, when~~

~~a) — an application test is too complex to replicate;~~

~~b) — the duration of an application test would make it impractical for routine testing purposes.~~

3.17

storage life

duration under specified conditions at the end of which a battery retains its ability to perform a specified service output

[SOURCE: IEC 60050-482:2004, 482-03-47, modified – "function" replaced by "service output"]

3.18

terminal ~~(of a primary battery)~~

conductive parts of a battery providing connection to an external circuit

[SOURCE: IEC 60050-482:2004, 482-02-22, modified – "conductive part of a device, electric circuit or electric network, provided" replaced by "conductive parts of a battery providing" and "device, electric circuit or electric network to one or more external conductor" replaced by "an external circuit"]

3.19

leakage

unplanned escape of electrolyte, gas or other material from a cell or battery

~~Note 1 to entry:— Leakage in this sense should not be confused with the test evaluation criteria for leakage specified in Clause 4 and Clause 5 of this document.~~

[SOURCE: IEC 60050-482:2004, 482-02-32]

3.20

terms applicable to Annex I

3.20.1

non-rechargeable battery

battery that is not designed to be electrically recharged

Note 1 to entry: The term "non-rechargeable" is used in the European Batteries Regulation in place of "primary".

[SOURCE: Batteries Regulation, Article 2(1), point (6), modified — Note to entry has been added]

3.20.2**portable battery of general use**

portable battery specifically produced to be interoperable and with the following common formats: 4,5 Volts (3R12), button cell, D, C, AA, AAA, AAAA, A23, 9 Volts (PP3)

Note 1 to entry: See I.2 for more information on the meaning of "interoperable".

Note 2 to entry: See I.3 for a tabulation of portable non-rechargeable batteries of general use.

Note 3 to entry: (3R12) is not part of the common designation but part of some IEC designations. See Table I.1.

[SOURCE: Batteries Regulation, Article 2(1), point (10), modified — Notes to entry have been added]

4 Requirements**4.1 General****4.1.1 Design**

Primary batteries are sold mainly in consumer markets. In recent years, they have become more sophisticated in both chemistry and construction, for example both capacity and rate capability have increased to meet the growing demands from new, battery-powered equipment technology.

When designing primary batteries, the aforementioned considerations shall be taken into account. Specifically, their dimensional conformity and stability, their physical and electrical performance and their safe operation under normal use and foreseeable misuse conditions shall be assured.

Additional information on equipment design can be found in Annex B of this document.

4.1.2 Battery dimensions

The dimensions for individual types of batteries are given in ~~IEC 60086-2~~ IEC 60086-2-1, IEC 60086-2-2 and IEC 60086-3.

4.1.3 Terminals**4.1.3.1 General**

Terminals shall be in accordance with ~~Clause 6 of IEC 60086-2:2015~~ Clause 8 of IEC 60086-2-1:2026 and IEC 60086-2-2.

Their physical shape shall be designed in such a way that they ensure that the batteries make and maintain good electrical contact at all times.

They shall be made of materials that provide good electrical conductivity and resistance to corrosion.

4.1.3.2 Contact pressure resistance

Where stated in the battery specification tables or the individual specification sheets in ~~IEC 60086-2~~ IEC 60086-2-1 and IEC 60086-2-2, the following applies:

- a force of 10 N applied through a steel ball of 1 mm diameter at the centre of each contact area for a period of 10 s shall not cause any apparent deformation which might prevent satisfactory operation of the battery.

NOTE See also IEC 60086-3:2021, 4.5 for exceptions.

4.1.3.3 Cap and base

This type of terminal is used for batteries which have their dimensions specified according to ~~Figures 1 to 7 of IEC 60086-2:2015~~ Figures 1 to 6 of IEC 60086-2-1:2026 and Figures 1 to 4 of IEC 60086-2-2:2026 which have the cylindrical side of the battery insulated from the terminals.

4.1.3.4 Cap and case

This type of terminal is used for batteries which have their dimensions specified according to ~~Figures 8, 9, 10, 14, 15 and 16 of IEC 60086-2:2015~~ Figures 7, 8, 9, 13, 14 of IEC 60086-2-1:2026 and Figures 5, 6, 7 of IEC 60086-2-2:2026, but in which the cylindrical side of the battery forms part of the positive terminal.

4.1.3.5 Screw terminals

This contact consists of a threaded rod in combination with either a metal or insulated metal nut.

4.1.3.6 Flat contacts

These are essentially flat metal surfaces adapted to make electrical contact by suitable contact mechanisms bearing against them.

4.1.3.7 Flat or spiral springs

These contacts comprise flat metal strips or spirally wound wires which are in a form that provides pressure contact.

4.1.3.8 Plug-in-sockets

These are made up of a suitable assembly of metal contacts, mounted in an insulated housing or holding device and adapted to receive the corresponding pins of a mating plug.

4.1.3.9 Snap fasteners

4.1.3.9.1 General

These contacts are composed of a combination comprising a stud (non-resilient) for the positive terminal and a socket (resilient) for the negative terminal.

They shall be of suitable metal so as to provide efficient electrical connection when joined to the corresponding parts of an external circuit.

4.1.3.9.2 Snap fastener

This type of terminal consists of a stud for the positive terminal and a socket for the negative terminal. These shall be made from nickel plated steel or other suitable material. They shall be designed to provide a secure physical and electrical connection, when fitted with similar corresponding parts for connection to an electrical circuit.

4.1.3.10 Wire

Wire leads may be single or multi-strand flexible insulated tinned copper. The positive terminal wire covering shall be red and the negative black.