

# INTERNATIONAL STANDARD

COMMENTED VERSION

**Primary batteries -  
Part 2-1: Physical and electrical specifications of batteries with aqueous  
electrolyte**

get full document from [standards.iteh.ai](https://standards.iteh.ai)



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2026 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search -

[webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

#### IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	5
INTRODUCTION.....	8
1 Scope.....	9
2 Normative references .....	9
3 Terms and definitions .....	9
4 Battery dimensions – Symbols.....	11
5 Dimensional stability.....	11
6 Validity of testing.....	11
7 Constitution of the battery specification tables.....	12
8 Physical and electrical specifications.....	14
8.1 Category 1 batteries .....	14
8.1.1 General .....	14
8.1.2 Category 1 – Specifications: LR1, R1, LR8D425 .....	15
8.1.3 Category 1 – Specifications: LR03, TR03, R03 .....	16
8.1.4 Category 1 – Specifications: LR6, TR6, R6P, R6S .....	17
8.1.5 Category 1 – Specifications: LR14, R14P, R14S.....	19
8.1.6 Category 1 – Specifications: LR20, R20P, R20S.....	20
8.2 Category 2 battery – Void .....	21
8.3 Category 3 battery – Specification: LR9.....	21
8.4 Category 4 batteries .....	22
8.4.1 General .....	22
8.4.2 Category 4 – Specifications: PR70, PR41, PR48, PR44, PR1154 .....	22
8.4.3 Fit acceptance gauge for PR batteries.....	24
8.4.4 Category 4 – Specifications: LR41, LR55, LR54, LR43, LR44 .....	26
8.4.5 Category 4 – Specifications: SR62, SR63, SR65, SR64, SR60, SR67, SR66, SR58, SR68, SR59, SR69, SR41, SR57, SR55, SR48, SR54, SR42, SR43, SR44 .....	27
8.5 Category 5 batteries .....	29
8.5.1 Category 5 – Specifications: 4LR44, 4SR44.....	29
8.5.2 Category 5 – Specification: 8LR932.....	30
8.5.3 Category 5 – Specifications: AR40, 5AR40, 6AR40, 5PR175/172, 6PR225/155 .....	31
8.6 Category 6 batteries .....	32
8.6.1 Category 6 – Specification: 4LR61.....	32
8.6.2 Category 6 – Void.....	33
8.6.3 Category 6 – Void.....	33
8.6.4 Category 6 – Specifications: 3R12P, 3R12S, 3LR12.....	33
8.6.5 Category 6 – Specifications: AS4, AS6S, AS6P, AS8, AS10, AS12, PS8S, PS8P, PS10.....	34
8.6.6 Category 6 – Specification: 4R25Y .....	35
8.6.7 Category 6 – Specifications: 4R25X, 4LR25X .....	36
8.6.8 Category 6 – Specifications: 4R25-2, 4LR25-2.....	37
8.6.9 Category 6 – Specifications: 6AS4S, 6PS4S, 6PS4P .....	38
8.6.10 Category 6 – Specifications: 6F22, 6LR61, 6LP3146 .....	39
8.6.11 Category 6 – Configurations: Stud for 6F22, 6LR61 6LP3146 .....	40
8.6.12 Category 6 – Specifications: 6AS6P, 6AS6S, 6PS6P, 6PS6S .....	41

Annex A (informative) Tabulation of batteries by application .....	42
Annex B (informative) Cross-reference index .....	47
Annex C (informative) Index reference to subclause .....	49
Bibliography.....	50
List of comments.....	51
Figure 1 – Dimensional drawing: Category 1 .....	14
Figure 2 – Dimensional drawing: LR1, R1, LR8D425.....	15
Figure 3 – Dimensional drawing: LR03, TR03, R03 .....	16
Figure 4 – Dimensional drawing: LR6, TR6, R6P, R6S.....	17
Figure 5 – Dimensional drawing: LR14, R14P, R14S.....	19
Figure 6 – Dimensional drawing: LR20, R20P, R20S.....	20
Figure 7 – Dimensional drawing: LR9.....	21
Figure 8 – Dimensional drawing: Category 4 .....	22
Figure 9 – Dimensional drawing: PR70, PR41, PR48, PR44, PR1154 .....	22
Figure 10 – Gauge opening for P system batteries.....	24
Figure 11 – Suggested gauge layout.....	24
Figure 12 – Air hole placement diagram for P system batteries .....	25
Figure 13 – Dimensional drawing: LR41, LR55, LR54, LR43, LR44 .....	26
Figure 14 – Dimensional drawing: SR62, SR63, SR65, SR64, SR60, SR67, SR66, SR58, SR68, SR59, SR69, SR41, SR57, SR55, SR48, SR54, SR42, SR43, SR44 .....	27
Figure 15 – Dimensional drawing: 4LR44, 4SR44 .....	29
Figure 16 – Dimensional drawing: 8LR932.....	30
Figure 17 – Dimensional drawing: AR40, 5AR40, 6AR40, 5PR175/172, 6PR225/155 .....	31
Figure 18 – Dimensional drawing: 4LR61.....	32
Figure 19 – Dimensional drawing: 3R12P, 3R12S, 3LR12.....	33
Figure 20 – Dimensional drawing: AS4, AS6P/S, AS8, AS10, AS12, PS8P/S, PS10.....	34
Figure 21 – Dimensional drawing: 4R25Y .....	35
Figure 22 – Dimensional drawing: 4R25X, 4LR25X .....	36
Figure 23 – Dimensional drawing: 4R25-2, 4LR25-2 .....	37
Figure 24 – Dimensional drawing: 6AS4S, 6PS4S, 6PS4P .....	38
Figure 25 – Dimensional drawing: 6F22, 6LR61, 6LP3146 .....	39
Figure 26 – Dimensional drawing: Stud.....	40
Figure 27 – Dimensional drawing: 6AS6P, 6AS6S, 6PS6P, 6PS6S .....	41
Table 1 – Voltage and application test requirements for LR1, R1 and LR8D425 .....	15
Table 2 – Voltage and application test requirements for LR03, TR03 and R03 .....	16
Table 3 – Voltage and application test requirements for LR6, TR6, R6P and R6S .....	18
Table 4 – Voltage and application test requirements for LR14, R14P and R14S.....	19
Table 5 – Voltage and application test requirements for LR20, R20P and R20S.....	20
Table 6 – Voltage and application test requirements for LR9.....	21
Table 7 – Voltage and application test requirements for PR70, PR41, PR48, PR44 and PR1154 .....	23
Table 8 – Gauge opening dimension .....	24

Table 9 – Voltage and application test requirements for LR41, LR55, LR54, LR43 and LR44.....	26
Table 10 – Voltage and application test requirements for SR62, SR63, SR65, SR64, SR60, SR67, SR66, SR58, SR68, SR59, SR69, SR41, SR57, SR55, SR48, SR54, SR42, SR43 and SR44 .....	28
Table 11 – Voltage and application test requirements for 4LR44 and 4SR44.....	29
Table 12 – Voltage and application test requirements for 8LR932 .....	30
Table 13 – Voltage and application test requirements for AR40, 5AR40, 6AR40, 5PR175/172 and 6PR225/155.....	31
Table 14 – Voltage and application test requirements for 4LR61 .....	32
Table 15 – Voltage and application test requirements for 3R12P, 3R12S and 3LR12 .....	33
Table 16 – Voltage and application test requirements for AS4, AS6P/S, AS8, AS10, AS12, PS8P/S and PS10 .....	34
Table 17 – Voltage and application test requirements for 4R25Y.....	35
Table 18 – Voltage and application test requirements for 4R25X and 4LR25X .....	36
Table 19 – Voltage and application test requirements for 4R25-2 and 4LR25-2.....	37
Table 20 – Voltage and application test requirements for 6AS4S, 6PS4S and 6PS4P .....	38
Table 21 – Voltage and application test requirements for 6F22, 6LR61 and 6LP3146.....	39
Table 22 – Voltage and application test requirements for 6AS6P, 6AS6S, 6PS6P and 6PS6S .....	41
Table A.1 – Automatic camera .....	42
Table A.2 – Digital audio.....	42
Table A.3 – Electric equipment .....	42
Table A.4 – Electrical fence equipment, parking meters, light houses, beacons, railway signalling and road signalling.....	42
Table A.5 – Hearing aid .....	43
Table A.6 – Hearing aid standard.....	43
Table A.7 – High drain application .....	43
Table A.8 – Implant high drain .....	43
Table A.9 – Implant low drain.....	43
Table A.10 – Implant low drain with wireless.....	44
Table A.11 – Personal grooming .....	44
Table A.12 – Portable lighting (LED).....	44
Table A.13 – Portable stereo .....	44
Table A.14 – Radio .....	45
Table A.15 – Radio / Clock .....	45
Table A.16 – Radio/clock/remote control.....	45
Table A.17 – Remote control.....	45
Table A.18 – Road warning lamp .....	45
Table A.19 – Smoke detector .....	46
Table A.20 – Toy (motor) .....	46
Table A.21 – Toy (non-motorized).....	46
Table A.22 – Wireless streaming.....	46
Table B.1 – Category 1 batteries.....	47
Table B.2 – Category 4 batteries.....	48

Table B.3 – Category 5 batteries.....	48
Table B.4 – Category 6 batteries.....	48
Table C.1 – Index .....	49

# Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**Primary batteries -  
Part 2-1: Physical and electrical specifications  
of batteries with aqueous electrolyte**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

This commented version (CMV) of the official standard IEC 60086-2-1:2026 edition 1.0 provides the user with comments from IEC TC 35 experts explaining the reasons for the most relevant changes made to IEC 60086-2:2021. These changes are listed in the Foreword.

Experts' comments are identified by a blue-background number. Mouse over a number to display a pop-up note containing the comment.

This publication contains both the CMV and the official standard. The full list of comments is available at the end of the CMV.

IEC 60086-2-1 has been prepared by IEC technical committee 35: Primary cells and batteries. It is an International Standard.

This first edition cancels and replaces the fourteenth edition of IEC 60086-2 published in 2021. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) the physical and electrical specifications of IEC 60086-2:2021 were divided into two new standards based on their electrolyte types. IEC 60086-2-1 provides specifications for standardized primary batteries containing aqueous electrolyte. IEC 60086-2-2 covers specifications for standardized lithium-based primary batteries; **1**
- b) in Clause 3, terms were reordered according to their functions: basic terms, electrochemical systems, electrical characteristics and specifications; **2**
- c) TR03 and TR6 were added in Category 1, Round batteries; **3**
- d) load of digital audio test for LR03, TR03 and R03 was changed from 50 mA to 75 mA and MAD was modified; **4**
- e) personal grooming test of LR6 was added instead of high drain application test; **5**
- f) high drain application test was added for TR6; **6**
- g) radio /clock /remote control test was added for R6S; **7**
- h) CD, digital audio, wireless gaming and accessories test was removed for LR6, R6P and R6S; **8**
- i) 4.5V of common designation was added for 3LR12, 3R12P and 3R12S; **9**
- j) Annex D for common designation of IEC 60086-2:2021 was moved to IEC 60086-1:2026, as Annex H; **10**
- k) Annex E for Compliance checklist of IEC 60086-2:2021 was removed and merged into Annex J of IEC 60086-1:2026. **11**

The text of this International Standard is based on the following documents:

Draft	Report on voting
35/1591/FDIS	35/1599/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/publications](http://www.iec.ch/publications).

A list of all parts in the IEC 60086 series, under the general title *Primary batteries*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](https://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

# Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)

## INTRODUCTION

The technical content of this part of IEC 60086 provides physical dimensions, discharge test conditions and discharge performance requirements. IEC 60086-2-1 and IEC 60086-2-2 complement the general information and requirements of IEC 60086-1. Safety information of IEC 60086-2-1 is available in IEC 60086-5.

This document was prepared to benefit primary battery users, device designers and battery manufacturers by furnishing the specifics of form, fit and function for individual standardized primary cells and batteries. Over the years, this part of IEC 60086 has been changed to improve its contents and might again be revised in due course in the light of comments made by national committees and experts on the basis of practical experience and changing technology.

# Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)

## 1 Scope

This part of IEC 60086 is applicable to primary batteries which are based on standardised electrochemical systems using aqueous electrolytes.

It specifies

- the physical dimensions,
- the discharge test conditions and discharge performance requirements.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60086-1:2026, *Primary batteries - Part 1: General*

ISO 1101, *Geometrical product specifications (GPS) - Geometrical tolerancing - Tolerances of form, orientation, location and run-out*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60086-1:2026 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

### 3.1

#### **primary cell**

#### **primary battery**

cell or battery that is not designed to be electrically recharged

### 3.2

#### **round cell**

#### **round battery**

cell or battery with circular cross section

### 3.3

#### **button cell**

#### **button battery**

small round cell or battery where the overall height is less than the diameter, containing aqueous electrolyte

**3.4****coin cell****coin battery****lithium button cell****lithium button battery**

small round cell or battery where the overall height is less than the diameter, containing non-aqueous electrolyte

Note 1 to entry: The nominal voltage of lithium batteries is typically greater than 2 V.

Note 2 to entry: For the specifications, refer to IEC 60086-2-2.

**3.5****nominal voltage** $U_n$ 

suitable approximate value of the voltage used to designate or identify a cell, a battery or an electrochemical system

[SOURCE: IEC 60050-482:2004, 482-03-31, modified – addition of  $U_n$ ]

**3.6****open-circuit voltage****OCV**

voltage across the terminals of a cell or battery when it is off discharge

**3.7****end-point voltage****EV**

specified voltage of a battery at which the battery discharge is terminated

[SOURCE: IEC 60050-482:2004, 482-03-30]

**3.8****minimum average duration****MAD**

acceptable minimum average time on discharge, which is met by testing a sample of batteries according to specified methods, to be deemed compliant

Note 1 to entry: The discharge test is carried out according to the specified methods or standards and designed to show conformity with the standard applicable to the battery types.

**3.9****application test**

simulation of the actual use of a battery in a specific application

**3.10****service output**

service life, or capacity, or energy output of a battery under specified conditions of discharge

**3.11****service output test**

test designed to measure the service output of a battery

Note 1 to entry: A service output test may be prescribed, for example, when

- a) an application test is too complex to replicate;
- b) the duration of an application test would make it impractical for routine testing purposes.

**3.12****terminal**

conductive parts of a battery providing connection to an external circuit

[SOURCE: IEC 60050-482:2004, 482-02-22, modified – “conductive part of a device, electric circuit or electric network, provided” replaced by “conductive parts of a battery providing” and “device, electric circuit or electric network to one or more external conductor” replaced by “an external circuit”]

**4 Battery dimensions – Symbols**

The symbols used to denote the various dimensions are as follows:

- $h_1$  maximum overall height of the battery;
- $h_2$  minimum distance between the flats of the positive and negative contacts;
- $h_3$  minimum projection of the flat positive contact;
- $h_4$  maximum recess of the negative flat contact surface;
- $h_5$  minimum projection of the flat negative contact;
- $d_1$  maximum and minimum diameters of the battery;
- $d_2$  minimum diameter of the flat positive contact;
- $d_3$  maximum diameter of the positive contact within the specified projection height;
- $d_4$  minimum diameter of the flat negative contact;
- $d_5$  maximum diameter of the negative contact within the specified projection height;
- $d_6$  minimum outer diameter of the negative flat contact surface;
- $d_7$  maximum inner diameter of the negative flat contact surface;
- $\emptyset P$  concentricity of the positive contact.

**5 Dimensional stability**

Refer to IEC 60086-1 for dimensional stability.

**6 Validity of testing**

Portable primary batteries shall be subjected to the tests, as required in the IEC 60086 series. Testing remains valid until a design change or requirement revision has been made. Retesting is required when:

- a) a battery specification changes by more than 0,1 g or 20 % mass, whichever is greater, for the cathode, anode or electrolyte;
- b) a battery specification changes that would lead to a failure of any of the tests;
- c) there is an addition of new tests or requirements; or
- d) there is a requirement change that would lead to a failure on any of the tests.

## 7 Constitution of the battery specification tables

- Batteries are categorized into several groups according to their shapes.
- In each category, batteries having the same shape but belonging to a different electrochemical system are grouped together and shown in succession.
- Batteries are always listed in ascending order of nominal voltage and, within each nominal voltage, in ascending order of volume.
- One common shape drawing of these batteries which fall in the same group is exhibited.
- Designation, nominal voltage, dimensions, discharge conditions, minimum average duration and application for these batteries which fall into the same group are summarized in one table.
- When a drawing represents only one type of battery, the dimensions of the relevant battery may be directly shown on the drawing.
- Batteries are categorized into the following groups:
  - Category 1: Round batteries according to Figure 1  
R1, R03, R6P, R6S, R14P, R14S, R20P, R20S  
LR8D425, LR1, LR03, LR6, LR14, LR20  
TR03, TR6
  - Category 2: Round battery  
Void
  - Category 3: Round battery according to Figure 7  
LR9
  - Category 4: Round batteries according to Figure 8  
PR70, PR41, PR48, PR44, PR1154  
LR41, LR55, LR54, LR43, LR44  
SR62, SR63, SR65, SR64, SR60, SR67, SR66, SR58, SR68, SR59, SR69, SR41,  
SR57, SR55, SR48, SR54, SR42, SR43, SR44
  - Category 5: Other round batteries – Miscellaneous  
4LR44  
4SR44  
8LR932  
AR40  
5AR40  
6AR40  
5PR175/172  
6PR 225/155

- Category 6: Non-round batteries – Miscellaneous  
3R12P, 3R12S, 3LR12  
4LR61  
AS4, AS6P, AS6S, AS8, AS10, AS12, PS8S, PS8P, PS10  
4R25X, 4LR25X  
4R25Y  
4R25-2, 4LR25-2  
6F22, 6LR61, 6LP3146  
6AS4S, 6PS4S, 6PS4P  
6AS6P, 6AS6S, 6PS6P, 6PS6S

The specification drawings show the shape of the relevant batteries. Dimensions for each battery are shown in Table 8 and in Figure 1 to Figure 27.

NOTE 1 See Annex A, Annex B and Annex C for ease of locating battery sizes.

NOTE 2 For lithium batteries, see IEC 60086-2-2: Physical and electrical specifications of lithium batteries.

# Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)