



IEC 60127-7

Edition 3.0 2026-05

INTERNATIONAL STANDARD

**Miniature fuses -
Part 7: Miniature fuse-links for special application**

Sample Document

get full document from standards.iteh.ai



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2026 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	2
INTRODUCTION	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	6
4 General requirements	7
5 Standard ratings	7
6 Marking	7
7 General notes on tests	8
8 Dimensions and construction	15
9 Electrical requirements	16
10 Standard sheets	26
Annex AA (normative) Guidance on ratings to be specified by the manufacturer or to be agreed upon with the testing house	29
Bibliography	30
Figure 1 – Standard test board for fuse-links with wire terminations	10
Figure 2 – Test board for surface mount fuse-links	12
Figure 3 – Test fuse base	13
Figure 4 – Test fuse base for 35A and above	14
Figure 5 – Test circuits for breaking capacity tests	17
Table 101 – Cross-sections of conductors	10
Table 102 – Preferred copper track specifications for test board	14
Table 103 – Power factor and time constant	18
Table 104 – Testing schedule for individual current rating for AC or DC breaking capacity fuse-links	21
Table 105 – Testing schedule for individual current ratings for AC and DC breaking capacity fuse-links	22
Table 106 – Testing schedule for maximum current ratings of a homogeneous series (AC or DC breaking capacity fuse-links)	23
Table 107 – Testing schedule for maximum current ratings of a homogeneous series (AC and DC breaking capacity fuse-links)	24
Table 108 – Testing schedule for minimum currents rating of a homogeneous series	25
Table 109 – Testing schedule for all intermediate current ratings of a homogeneous series	25
Table AA.1 – Guidance on ratings to be specified by the manufacturer or to be agreed upon with the testing house	29

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**Miniature fuses -
Part 7: Miniature fuse-links for special application**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 60127-7 has been prepared by subcommittee 32C: Miniature fuses, of IEC technical committee 32: Fuses. It is an International Standard.

This third edition cancels and replaces the second edition published in 2015. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) alignment with IEC 60127-1:2023 (third edition);
- b) change of the rated current of miniature fuse-links for special application to 125A and provision of relevant requirements;
- c) addition of a test board for surface mount fuse-links (Figure 2);
- d) addition of test schedules for homogenous series.

This part of IEC 60127 is to be read in conjunction with Part 1. It supplements or modifies the corresponding clauses of Part 1. Where the text indicates an "addition" to or a "replacement" of the relevant provision of Part 1, these changes are made to the relevant text of Part 1. When a particular subclause of Part 1 is not mentioned in this part, that subclause applies as far as is reasonable.

Additional specific provisions to those in Part 1, given as individual clauses or subclauses, are numbered starting from 101.

NOTE The following numbering system is used:

- subclauses, tables and figures that are numbered starting from 101 are additional to those in Part 1;
- unless notes are in a new subclause or involve notes in Part 1, they are numbered starting from 101, including those in a replaced clause or subclause;
- additional annexes are lettered AA, BB, etc.

The text of this International Standard is based on the following documents:

Draft	Report on voting
32C/679/FDIS	32C/681/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

A list of all parts in the IEC 60127 series, published under the general title *Miniature fuses*, can be found on the IEC website.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INTRODUCTION

According to the wish expressed by the users of miniature fuses, all standards, recommendations and other documents relating to miniature fuses have the same publication number in order to facilitate reference to fuses in other specifications, for example, equipment specifications.

Furthermore, a single publication number and subdivision into parts would facilitate the establishment of new standards, because clauses and subclauses containing general requirements need not be repeated.

The new IEC 60127 series is thus subdivided as follows:

IEC 60127, *Miniature fuses* (general title)

IEC 60127-1, *Miniature fuses - Part 1: Definitions for miniature fuses and general requirements for miniature fuse-links*

IEC 60127-2, *Miniature fuses - Part 2: Cartridge fuse-links*

IEC 60127-3, *Miniature fuses - Part 3: Sub-miniature fuse-links*

IEC 60127-4, *Miniature fuses - Part 4: Universal modular fuse-links (UMF) - Through-hole and surface mount types*

IEC 60127-5, *Miniature fuses - Part 5: Guidelines for quality assessment of miniature fuse-links*

IEC 60127-6, *Miniature fuses - Part 6: Fuse-holders for miniature fuse-links*

IEC 60127-7, *Miniature fuses - Part 7: Miniature fuse-links for special applications*

IEC 60127-8, *Miniature fuses - Part 8: Fuse resistors with particular overcurrent protection*

IEC 60127-9, *Miniature fuses - Part 9: Miniature fuse-links for special applications with partial-range breaking capacity*

IEC 60127-10, (withdrawn)

This part of IEC 60127 covers additional requirements, test equipment and standard sheets. The SI system of units is used throughout this document.

1 Scope

This part of IEC 60127 covers requirements for miniature fuse-links for special applications.

This part of IEC 60127 is applicable to fuse-links with a rated voltage not exceeding 1 000 V, a rated current not exceeding 125 A and a rated breaking capacity not exceeding 50 kA.

NOTE Nominal currents above 20 A are intended for protection of low power electric devices at low voltage and not for energy distribution.

It does not apply to fuses completely covered by the subsequent parts of IEC 60269-1.

It does not apply to miniature fuse-links for appliances intended to be used under special conditions, such as in corrosive or explosive atmospheres.

This part of IEC 60127 applies in addition to the requirements of IEC 60127-1:2023.

Miniature fuse-links for special applications are not intended to be replaced by the end-user of an electrical / electronic appliance.

The object of this part of IEC 60127 is to establish uniform test methods for miniature fuse-links for special applications, so as to allow verification of the values (for example melting time and breaking capacity values) specified by the manufacturer.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-21:2021, *Environmental testing - Part 2-21: Tests - Test U: Robustness of terminations and integral mounting devices*

IEC 60127-1:2023, *Miniature fuses - Part 1: Definitions for miniature fuses and general requirements for miniature fuse-links*

IEC 60127-4:2026, *Miniature fuses - Part 4: Universal modular fuse-links (UMF) - Through-hole and surface mount types*

IEC 60127-6:2023, *Miniature fuses - Part 6: Fuse-holders for miniature fuse-links*

IEC 60664-1:2020, *Insulation coordination for equipment within low-voltage systems - Part 1: Principles, requirements and tests*

IEC 60695-2-12:2021, *Fire hazard testing - Part 2-12: Glowing/hot-wire based test methods - Glow-wire flammability index (GWFI) test method for materials*

IEC 60695-2-13:2021, *Fire hazard testing - Part 2-13: Glowing/hot-wire based test methods - Glow-wire ignition temperature (GWIT) test method for materials*

IEC 60695-4:2021, *Fire hazard testing - Part 4: Terminology concerning fire tests for electrotechnical products*

IEC 61249-2-7:2002, *Materials for printed boards and other interconnecting structures - Part 2-7: Reinforced base materials clad and unclad - Epoxide woven E-glass laminated sheet of defined flammability (vertical burning test), copper-clad*

ISO 3:1973, *Preferred numbers - Series of preferred numbers*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in Clause 3 of IEC 60127-1:2023, except 3.5, and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1

miniature fuse-link for special applications

enclosed fuse-link which is not covered in IEC 60127-2, IEC 60127-3 or IEC 60127-4 and of rated breaking capacity not exceeding 50 kA, with a width and height not exceeding 12 mm and a length not exceeding 50 mm

Note 1 to entry: Special precautions may be necessary to ensure that the fuse-links will be replaced by a fuse-link with the same technical parameters.

Note 2 to entry: For fuse-links having a metallic cap at each end, any member of terminals or terminations other than the metallic cap such as wire terminations, pins and bolt-in contacts may not be included in the total length of 50 mm and the width and height of 12 mm.

3.2

t_1 to t_8

limit values for time/current characteristic

3.3

I_{70}

test current for testing at elevated temperature of 70 °C

Note 1 to entry: Preferred values are 0,8 I_N or 1,0 I_N or 1,1 I_N .

3.4

I_{test} (A)

test current for endurance testing according to method A

Note 1 to entry: Preferred values are 1,0 I_N or 1,05 I_N or 1,2 I_N .

3.5

I_{test} (B)

test current for endurance testing according to method B

Note 1 to entry: Preferred values are 0,8 I_N or 1,0 I_N .

3.6 **I_{OVL} (A)**

test current for measuring the maximum sustained power dissipation according to method A

Note 1 to entry: Preferred values are $1,0 I_N$ or $1,25 I_N$ or $1,35 I_N$ or $1,5 I_N$. $1,0 I_N$ is allowable only for nominal currents above 20 A.

3.7 **I_{OVL} (B)**

test current for measuring the maximum sustained power dissipation according to method B

Note 1 to entry: Preferred values are $1,0 I_N$ or $1,25 I_N$.

4 General requirements

Clause 4 of IEC 60127-1:2023 applies.

5 Standard ratings

Replace Clause 5 of IEC 60127-1:2023 as follows:

The following ratings shall be agreed upon between the testing house and the manufacturer:

- rated voltage;
- rated current (see standard sheet 1 for preferred ratings);
- rated breaking capacity (AC and/or DC);
- time/current characteristic (at least at $2,0 I_N$ or $2,1 I_N$ and $10 I_N$).

The following may be agreed upon on an optional basis:

- test at elevated temperature;
- time/current characteristic (additionally at $2,75 I_N$ and $4 I_N$).

Any additional specified values are given in standard sheet 1. Guidance on ratings to be specified by the manufacturer or to be agreed upon with the testing house is given in Annex AA.

6 Marking

Clause 6 of IEC 60127-1:2023 applies except as follows.

6.1

Replace a) of Subclause 6.1 as follows:

- a) Not applicable.

NOTE A symbol denoting the time/current characteristic cannot be stated, because this part of IEC 60127 does not specify any values for this parameter.

Addition:

- e) Type designation.
f) Rated breaking capacity in amperes (A) or in kilo amperes (kA).