

INTERNATIONAL STANDARD

CONSOLIDATED VERSION

**Methods of measurement on radio receivers for various classes of emission -
Part 4: Receivers for frequency-modulated sound broadcasting emissions**

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

IEC 60315-4:1997

<https://standards.iteh.ai/catalog/standards/iec/231de1fa-75cb-4aba-8589-f6208d9a72c7/iec-60315-4-1997>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2025 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

[IEC 60315-4:1997](https://standards.iteh.ai/catalog/standards/iec/231de1fa-75cb-4aba-8589-f6208d9a72c7/iec-60315-4-1997)

<https://standards.iteh.ai/catalog/standards/iec/231de1fa-75cb-4aba-8589-f6208d9a72c7/iec-60315-4-1997>

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	6
1 General.....	8
1.1 Scope.....	8
1.2 Normative references.....	8
1.3 Definitions.....	9
1.4 Standard measuring conditions.....	10
1.4.1 Measurements at audio-frequency output terminals.....	10
1.4.2 Radio-frequency signal(s).....	11
1.4.3 Power supply and relevant measuring conditions.....	14
1.4.4 Tuning.....	14
1.5 General notes on measurements.....	15
1.5.1 Values for voltage and current.....	15
1.5.2 Audio-frequency measurement techniques.....	15
1.5.3 Presentation of radio-frequency signal level or voltage.....	15
1.5.4 Climatic and environmental conditions.....	16
1.5.5 Preconditioning and preliminary measurements.....	16
1.5.6 Test equipment and accuracy of measurements.....	16
1.5.7 Rated values.....	17
1.5.8 Presentation of measuring results.....	17
2 Sensitivity and internal noise.....	18
2.1 Explanation of terms.....	18
2.2 Signal-to-noise ratio (weighted and unweighted) and SINAD.....	18
2.2.1 Introduction.....	18
2.2.2 Method of measurement.....	18
2.2.3 Presentation of results.....	19
2.3 Noise-limited sensitivity.....	19
2.3.1 Introduction.....	19
2.3.2 Method of measurement.....	19
2.3.3 Presentation of results.....	19
2.4 Gain-limited sensitivity.....	19
2.4.1 Introduction.....	19
2.4.2 Method of measurement.....	20
2.4.3 Presentation of results.....	20
2.5 Usable sensitivity.....	20
2.5.1 Introduction.....	20
2.5.2 Method of measurement.....	20
2.5.3 Presentation of results.....	20
2.6 Deviation sensitivity.....	20
2.6.1 Introduction.....	20
2.6.2 Method of measurement.....	21
2.6.3 Presentation of results.....	21
2.7 Input-output characteristics.....	21
2.7.1 Introduction.....	21
2.7.2 Method of measurement.....	21
2.7.3 Presentation of results.....	22
3 Rejection of unwanted signals.....	22

3.1	Capture ratio	22
3.1.1	Introduction	22
3.1.2	Method of measurement	22
3.1.3	Presentation of results	23
3.2	Selectivity and nearby channel rejection (two-signal)	23
3.2.1	Introduction	23
3.2.2	Method of measurement	24
3.2.3	Rejection of adjacent and alternate channels	25
3.2.4	Presentation of the results	25
3.3	Rejection of intermediate and image frequencies, and spurious responses	25
3.3.1	Introduction	25
3.3.2	Methods of measurement	27
3.3.3	Presentation of results	28
3.4	Suppression of amplitude modulation	28
3.4.1	Introduction	28
3.4.2	Methods of measurement	28
3.4.3	Presentation of results	29
3.5	Rejection of r.f. signal intermodulation products	29
3.5.1	Introduction	29
3.5.2	Methods of measurement: two-signal methods	30
3.5.3	Methods of measurement: three-signal methods	31
3.6	Tuning and automatic frequency control (AFC) characteristics	33
3.6.1	Introduction	33
3.6.2	Method of measurement	33
3.6.3	Presentation of results	34
4	Interference due to internal sources	34
4.1	Single-signal whistles	34
4.1.1	Introduction	34
4.1.2	Method of measurement	34
4.1.3	Presentation of results	34
4.2	Modulation hum (interference at power supply frequency)	34
4.2.1	Introduction	34
4.2.2	Method of measurement	34
4.2.3	Presentation of results	35
4.3	Unwanted self-oscillations	35
4.3.1	Introduction	35
4.3.2	Method of measurement	35
4.3.3	Presentation of results	35
4.4	Acoustic feedback	35
4.4.1	Introduction	35
4.4.2	Method of measurement	35
4.4.3	Presentation of results	36
5	Overall audio-frequency characteristics	36
5.1	Fidelity	36
5.2	Harmonic distortion	36
5.2.1	Introduction	36
5.2.2	Method of measurement	37
5.2.3	Presentation of results	39

5.3	Intermodulation distortion	40
5.3.1	Introduction	40
5.3.2	Method of measurement	40
5.3.3	Presentation of results	41
5.4	Inter-channel characteristics	41
5.4.1	Introduction	41
5.4.2	Method of measurement	42
5.4.3	Presentation of results	42
5.5	Characteristics of the volume control	43
5.5.1	Introduction	43
5.5.2	Method of measurement	43
5.5.3	Presentation of results	43
5.6	Residual output	43
5.6.1	Introduction	43
5.6.2	Method of measurement	43
5.6.3	Presentation of the result	43
5.7	Crosstalk attenuation	43
5.7.1	Introduction	43
5.7.2	Method of measurement	44
5.7.3	Presentation of results	44
5.8	Overall audio-frequency response	44
5.8.1	Introduction	44
5.8.2	Method of measurement	44
5.8.3	Presentation of results	45
6	Effect of additional modulations of the input signal	45
6.1	Rejection of signals in the ranges 16 kHz to 22 kHz and 54 kHz to 99 kHz	45
6.1.1	Introduction	45
6.1.2	Method of measurement	45
6.1.3	Presentation of the results	45
6.2	Rejection of signals in the range 62 kHz to 73 kHz (SCA rejection)	45
6.2.1	Method of measurement	45
6.2.2	Presentation of the results	46
6.3	Measurement of interference caused by RDS signals	46
6.3.1	Introduction	46
6.3.2	Method of measurement	46
6.3.3	Presentation of results	46
6.4	Suppression of the fundamental, harmonics and sidebands of the subcarrier and the pilot-tone signal	46
6.4.1	Introduction	46
6.4.2	Method of measurement	47
6.4.3	Presentation of the results	47
6.5	Suppression of interference due to adjacent channel signals with a stereophonic receiver using the pilot-tone system	47
6.5.1	Introduction	47
6.5.2	Method of measurement	47
6.5.3	Presentation of the results	47
7	Sensitivity, antenna gain and directional response of receivers using rod, telescopic or built-in antennas	48

7.1	Introduction	48
7.2	Method of measurement of sensitivity and antenna gain for a receiver using a rod or telescopic antenna by the absorbing clamp described in CISPR 16-1	48
8	Characteristics whose methods of measurement are specified in IEC 60315-1	48
8.1	Introduction	48
8.2	List of characteristics and cross-references	48
Figure 1 – Frequency response limits of band-pass filter 200 Hz to 15 kHz		49
Figure 2 – Frequency response limits of band-pass filter 22,4 Hz to 15 kHz		50
Figure 3 – Frequency response limits of band-pass filter 200 Hz to 1,5 kHz		50
Figure 4 – Frequency response limits of the 1 kHz band-stop filter		51
Figure 5 – Weighting filter for converting white noise into special coloured noise for selectivity measurements		51
Figure 6 – Arrangement for various measurements with two r.f. input signals		52
Figure 7 – Antenna substitution networks for injecting one or two signals, for 50 Ω signal generators and 75 Ω unbalanced and 300 Ω balanced receiver inputs		53
Figure 8 – Arrangement for various measurements with one r.f. input signal		54
Figure 9 – Signal-to-noise ratio		55
Figure 10 – Noise-limited sensitivity as a function of signal frequency		55
Figure 11 – Gain-limited sensitivity as a function of signal frequency		56
Figure 12 – Output/input characteristics and noise output curves showing terms defined in 1.3		57
Figure 13 – Capture ratio		58
Figure 14a – Mono mode		59
Figure 14b – Stereo mode		59
Figure 14 – Selectivity curves		59
Figure 15 – Image and intermediate frequency rejection ratios		60
Frequency		61
Figure 16 – Spurious responses at a tuning frequency of 94 MHz (single-signal method)		61
Figure 17 – Arrangement for measuring rejection of unwanted signals simulating cable reception, using sinusoidal modulation		62
Figure 18 – Arrangement for various measurements using three r.f. input signals		63
Figure 19 – Tuning characteristics		64
Figure 20 – Tuning characteristics obtained by measuring the local oscillator frequency		65
Figure 21 – Measurement of acoustic feedback		66
Figure 22 – Arrangement for measuring fidelity		66
Figure 23 – Overall total harmonic distortion as a function of a.f. output power		67
Figure 24 – Distortion-limited output power as a function of modulation frequency		67
Figure 25 – Total harmonic distortion as a function of r.f. input signal level		68
Figure 26 – Total harmonic distortion as a function of the deviation		68
Figure 27 – Variation of distortion with detuning		69
Figure 28 – Total harmonic distortion as a function of the a.f. modulation frequency		69

Figure 29 – Cross-intermodulation between the channels of a stereo receiver (pilot-tone system).....	70
Figure A.1 – Example of a passive 1 kHz band-stop filter capable of meeting the limits shown in figure 4	71
Figure D.1 – Arrangement for r.f. signal injection into the antenna with an absorbing clamp	75
Figure D.2 – Correction curves for the insertion loss of the absorbing clamp	75
Table 1 – Audio-frequency filters.....	11
Table 2 – Standard values of deviation.....	12
Table 3 – Standard measuring frequencies.....	13
Table 4 – Presentation of radio-frequency signal level or voltage	16

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[IEC 60315-4:1997](https://standards.iteh.ai/catalog/standards/iec/231de1fa-75cb-4aba-8589-f6208d9a72c7/iec-60315-4-1997)

<https://standards.iteh.ai/catalog/standards/iec/231de1fa-75cb-4aba-8589-f6208d9a72c7/iec-60315-4-1997>