

INTERNATIONAL STANDARD

**Flexible insulating sleeving –
Part 2: Methods of test**

Itch Standards
(<https://standards.itech.ai>)
Document Preview

[IEC 60684-2:2025](https://standards.itech.ai/catalog/standards/iec/88129504-09fe-46f0-a161-35a9bf6efa7f/iec-60684-2-2025)

<https://standards.itech.ai/catalog/standards/iec/88129504-09fe-46f0-a161-35a9bf6efa7f/iec-60684-2-2025>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2025 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

[IEC 60684-2:2025](https://standards.iteh.ai/catalog/standards/iec/88129504-09fe-46f0-a161-35a9bf6efa7f/iec-60684-2-2025)

<https://standards.iteh.ai/catalog/standards/iec/88129504-09fe-46f0-a161-35a9bf6efa7f/iec-60684-2-2025>

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	12
INTRODUCTION.....	2
1 Scope.....	15
2 Normative references	15
3 Terms and definitions	17
4 Test conditions	18
4.1 Standard test conditions	18
4.2 Elevated temperature test conditions	18
4.3 Low temperature test conditions.....	18
5 Measurements of bore, wall thickness and concentricity	18
5.1 General.....	18
5.2 Bore.....	18
5.2.1 Number of test specimens	18
5.2.2 General method	18
5.2.3 Relaxed bore of expandable braided sleeving	18
5.2.4 Expanded bore of expandable braided sleeving	19
5.2.5 Result.....	19
5.3 Wall thickness for textile sleeving	19
5.3.1 Number of test specimens	19
5.3.2 Procedure.....	19
5.3.3 Result.....	20
5.4 Minimum/maximum wall thickness and concentricity for extruded sleeving	20
5.4.1 Number of test specimens	20
5.4.2 Wall thickness	20
5.4.3 Concentricity	20
5.4.4 Result.....	20
6 Density	21
6.1 Number of test specimens.....	21
6.2 Procedure	21
6.3 Result	21
7 Resistance to splitting after heating	21
7.1 Number of test specimens.....	21
7.2 Form of test specimen.....	21
7.3 Procedure	21
7.4 Result	21
8 Heat shock (resistance to heat)	22
8.1 Number of test specimens.....	22
8.2 Form of test specimens	22
8.3 Procedure	22
8.4 Result	22
9 Resistance to soldering heat.....	22
9.1 Number of test specimens.....	22
9.2 Form of test specimen.....	22
9.3 Procedure	23
9.4 Result	23
10 Loss in mass on heating of uncoated textile glass sleeving	23

10.1	Number and mass of test specimens.....	23
10.2	Procedure.....	23
10.3	Calculation.....	23
10.4	Result.....	23
11	Longitudinal change	23
11.1	Number of test specimens.....	23
11.2	Form of test specimen.....	23
11.3	Procedure.....	24
11.4	Calculation.....	24
11.5	Result.....	24
12	Deformation under load (resistance to pressure at elevated temperature).....	24
12.1	Method A	24
12.1.1	Number of test specimens	24
12.1.2	Form of test specimen	24
12.1.3	Apparatus.....	24
12.1.4	Procedure.....	25
12.1.5	Result.....	25
12.2	Method B	25
12.2.1	Number of test specimen	25
12.2.2	Form of test specimen	25
12.2.3	Apparatus.....	25
12.2.4	Procedure.....	26
12.2.5	Result.....	27
13	Thermal stability of PVC sleeving	27
13.1	Principle	27
13.2	Form of test specimen.....	27
13.2.1	ISO 182-1 method	27
13.2.2	ISO 182-2 method	27
13.3	Procedure	27
13.4	Result	27
14	Volatile content of silicone sleeving	27
14.1	Number and mass of test specimens.....	27
14.2	Procedure	27
14.3	Calculation.....	28
14.4	Result	28
15	Bending after heating	28
15.1	Number of test specimens.....	28
15.2	Form of test specimen.....	28
15.3	Procedure	28
15.4	Result	29
16	Bending at low temperature	29
16.1	Number and form of test specimens	29
16.2	Procedure	29
16.3	Result	29
17	Brittleness temperature	29
17.1	Form of test specimen.....	29
17.2	Procedure	29
17.3	Result	29

18	Dimensional stability on storage (applicable to heat-shrinkable sleeving only)	29
18.1	Number and length of test specimens	29
18.2	Procedure	30
18.3	Result	30
19	Hydrolysis of coating	30
19.1	Number of test specimens	30
19.2	Form of test specimen	30
19.3	Procedure	30
19.4	Result	30
20	Flexibility (extruded sleeving only)	31
20.1	Number and length of test specimens	31
20.2	Procedure	31
20.3	Report Result	31
21	Tensile strength, tensile stress at 100 % elongation, elongation at break and secant modulus at 2 % elongation	31
21.1	General	31
21.2	Tensile strength and elongation at break for full-section sleeving	31
21.2.1	Number of test specimens	31
21.2.2	Form of test specimen	31
21.2.3	Conditioning	32
21.2.4	Test temperature	32
21.2.5	Procedure	32
21.2.6	Calculations	32
21.2.7	Result	33
21.3	Tensile strength and elongation at break on dumb-bell specimens	33
21.3.1	General	33
21.3.2	Form of test specimen	33
21.3.3	Procedure	33
21.3.4	Result	34
21.4	Tensile strength of uncoated glass textile sleeving	34
21.4.1	General	34
21.4.2	Procedure	34
21.4.3	Results	34
21.5	Secant modulus at 2 % elongation	34
21.5.1	Number and form of test specimens	34
21.5.2	Procedure	34
21.5.3	Calculation	35
21.5.4	Result	35
21.6	Tensile stress at 100 % elongation	35
21.6.1	General	35
21.6.2	Calculation	35
21.6.3	Result	35
21.7	Tensile stress at 100 % elongation and at elevated temperature	35
22	Fraying resistance test	35
22.1	Principle General	35
22.2	Number and length form of test specimens	36
22.3	Procedure	36
22.4	Calculation	36

22.5	Result	36
23	Breakdown voltage	36
23.1	Principle	36
23.1.1	General	36
23.1.2	Number and form of test specimens	37
23.1.3	Conditioning	37
23.1.4	Application of voltage	37
23.1.5	Test method modification	37
23.1.6	Result	37
23.2	Straight mandrel test, 100 mm foil electrode	37
23.2.1	Test specimen	37
23.2.2	Electrodes	37
23.2.3	Procedure	37
23.2.4	Result	37
23.3	Test on cut-out specimens for large-size sleeving	37
23.3.1	Test specimen	37
23.3.2	Electrodes	38
23.3.3	Procedure	38
23.3.4	Result	38
23.4	Tests at elevated temperature	38
23.5	Tests after damp heat	38
23.6	Result	38
24	Insulation resistance	38
24.1	Conditioning	38
24.2	Form of test specimen	39
24.3	Measurement of insulation resistance	39
24.4	Test conditions	39
24.4.1	Number of test specimens	39
24.4.2	Tests at room temperature	39
24.4.3	Tests at elevated temperature	39
24.4.4	Tests after subjection to damp heat conditions	39
24.5	Result	39
25	Volume resistivity for insulating material	39
25.1	General	39
25.2	Conditioning	40
25.3	Form of test specimen	40
25.4	Measurement of volume resistivity	40
25.5	Test conditions	41
25.5.1	Number of test specimens	41
25.5.2	Tests at room temperature	41
25.5.3	Tests at elevated temperature	41
25.5.4	Tests after subjection to damp heat conditions	41
25.6	Result	41
26	Permittivity and dissipation factor	41
26.1	Number of test specimens	41
26.2	Form of test specimen	41
26.3	Electrodes	41
26.4	Procedure	42

26.5	Calculation.....	42
26.6	Result.....	42
27	Resistance to tracking	43
28	Flame propagation tests	43
28.1	Principle	43
28.2	Methods A and B	43
28.2.1	General	43
28.2.2	Number of test specimens	43
28.2.3	Method A, applicable to sleeving up to and including 10 mm bore only	43
28.2.4	Method B.....	43
28.2.5	Source of heat.....	43
28.2.6	Specimen arrangements	44
28.2.7	Result.....	44
28.3	Method C	44
28.3.1	Number of test specimens	44
28.3.2	Source of heat.....	44
28.3.3	Cabinet and arrangements within it.....	44
28.3.4	Procedure.....	45
28.3.5	Result.....	45
28.4	Method D	45
28.4.1	Number of test specimens	45
28.4.2	Cabinet and specimen arrangements.....	45
28.4.3	Source of heat.....	45
28.4.4	Procedure.....	45
28.4.5	Result.....	46
29	Oxygen index	46
29.1	Oxygen index at ambient temperature.....	46
29.2	Oxygen index at elevated temperature	46
29.3	Results	46
30	Transparency	46
30.1	Number of test specimens.....	46
30.2	Form of test specimen.....	46
30.3	Procedure	47
30.4	Result	47
31	Ionic impurities test	47
31.1	General.....	47
31.2	Result.....	47
32	Silver staining test.....	47
32.1	Principle	47
32.2	Number and form of test specimens	47
32.3	Stain tester	47
32.4	Procedure	47
32.5	Result.....	48
33	Electrolytic corrosion resistance	48
33.1	General.....	48
33.2	Number of test specimens.....	48
34	Corrosion resistance (tensile and elongation)	48
34.1	Principle	48