



IEC 60695-1-12

Edition 2.0 2026-09

INTERNATIONAL STANDARD

REDLINE VERSION

BASIC SAFETY PUBLICATION

HORIZONTAL PUBLICATION

**Fire hazard testing -
Part 1-12: Guidance for assessing the fire hazard of electrotechnical products -
Fire safety engineering**

ICS 13.220.40; 29.020

ISBN 978-2-8327-1539-0



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2026 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	3
INTRODUCTION	6
1 Scope	8
2 Normative references	8
3 Terms and definitions	9
4 The fire safety engineering process	15
4.1 General	15
4.2 Fire safety engineering calculations	16
4.3 Validity of methods	17
5 Benefits of fire safety engineering	18
6 Objectives, requirements and performance of fire safety engineering	19
6.1 General	19
6.2 Safety of life	19
6.3 Conservation of property	19
6.4 Continuity of operation	19
6.5 Protection of the natural environment	20
6.6 Preservation of heritage	20
7 Functional requirements	20
8 Performance criteria	20
8.1 General	20
8.2 Explicit performance criteria	20
8.3 Implicit performance criteria	21
9 Design fire scenarios and design fires	21
9.1 Design fire scenarios	21
9.2 Design fires	22
10 Data for fire safety engineering	22
11 Tests on electrotechnical products	23
11.1 General	23
11.2 Condition for evaluation in fire tests	23
11.3 Test selection and/or development	23
12 Evaluation of electrotechnical products	24
12.1 As the source of ignition of a fire	24
12.2 As the victim of a fire	26
Annex A (informative) A probabilistic fire risk assessment	27
Annex A (informative) An example of application of Fire Safety Engineering (FSE) Method for prediction of flammability of materials in microgravity environment	34
A.1 Background	34
A.2 Method of application of Fire Safety Engineering (FSE) to predict the flammability of materials in microgravity environment	34
A.3 Details of the application of FSE	34
Bibliography	35
Figure 1 — Flowchart illustrating an example of the fire safety engineering process as applied to a major project in the built environment	36
Figure 1 – FSE process – Design, implementation and management	16

Table 1 – Examples of design fire scenario21

Table 2 – Common ignition phenomena encountered in electrotechnical products25

~~Table A.1 — Long start-up mode: enclosure (shell) temperatures in the most heated up-point.....~~

~~Table A.2 — The enclosure temperature at the most heated point when working under abnormal conditions.....~~

~~Table A.3 — Failure data for abnormal operation~~

Sample Document

get full document from standards.iteh.ai

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**Fire hazard testing -
Part 1-12: Guidance for assessing the fire hazard
of electrotechnical products - Fire safety engineering**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 60695-1-12:2015. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

IEC 60695-1-12 has been prepared by IEC technical committee 89: Fire hazard testing. It is an International Standard.

This document has been given the status of a horizontal document in accordance with the ISO/IEC Directives, Part 1. It has the status of a basic safety publication in accordance with IEC Guide 104 and ISO/IEC Guide 51.

This second edition cancels and replaces the first edition published in 2015. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) whole text is renewed to contain the most recent technologies of fire safety engineering mainly developed by ISO/TC92 Fire safety SC4 Fire safety engineering.
- b) Annex A is changed to show example of application of FSE in an international standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
89/1631/CDV	89/1670/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/reference. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all the parts in the 60695 series, under the general title *Fire hazard testing*, can be found on the IEC web site.

IEC 60695-1 consists of the following parts:

Part 1-10: Guidance for assessing the fire hazard of electrotechnical products - General guidelines

Part 1-11: Guidance for assessing the fire hazard of electrotechnical products - Fire hazard assessment

Part 1-12: Guidance for assessing the fire hazard of electrotechnical products - Fire safety engineering

Part 1-30: Guidance for assessing the fire hazard of electrotechnical products - Preselection testing process - General guidelines

Part 1-40: Guidance for assessing the fire hazard of electrotechnical products - Insulating liquids.

This document is to be used in conjunction with IEC 60695-1-10 and IEC 60695-1-11.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

Sample Document

get full document from standards.iteh.ai

INTRODUCTION

Fire safety engineering

Fire safety engineering (FSE) is the application of engineering methods based on scientific principles to the development or assessment of designs in the built environment through the analysis of specific fire scenarios or through the quantification of risk for a group of fire scenarios.

Typical objectives of FSE are:

- a) to protect life safety,
- b) to protect property,
- c) to maintain the continuity of operations,
- d) to protect the natural environment, and
- e) to preserve heritage.

The analysis of FSE is usually based on calculations that use input data obtained principally from quantitative fire tests as described in IEC 60695-1-11.

Fire safety engineering (FSE) is a discipline increasingly being used in support of performance-based national fire safety regulations in many states and regional jurisdictions throughout the world. ~~The eight parts of ISO/TR 13387 (see Clause 2 and [1] to [6]) and ISO 23932 outline the fundamental methodologies and uses of FSE. Further detailed aspects of FSE are covered in ISO 16730 [7], ISO/TS 16732 [8], ISO/TS 16733, ISO 16734 [9], ISO 16735 [10], ISO 16736 [11], ISO 16737 [12] and ISO/TR 16738.~~ ISO 23932-1 [1]¹, developed by ISO TC 92/SC 4, outlines the fundamental methodologies and uses of FSE. Further detailed aspects of FSE are covered in ISO 16730-1 [2], ISO 16732-1 [3], ISO 16733-1 [4], ISO 24678-2 [5], ISO 24678-3 [6], ISO 24678-4 [7] and ISO/TR 16738 [8].

In addition to performance-based regulations, many nations are also using FSE to supplement prescriptive regulations by applying FSE principles to specific design aspects, where reduced costs, alternative practices, improved performance and improved safety are the objectives.

The International Maritime Organization (IMO) is using FSE and the ISO standards mentioned above to develop fire safety designs for ships as described in IMO MSC/Circ.1002[27]. These are considered to bring an improvement in the design ~~based on prescriptive fire safety requirements~~ of electrotechnical products.

There are handbooks, guides and literatures which give information with regards to FSE. See Bibliography [28], [29], [30], [31], [32], [33], [34], [35], [36], [37], [38].

Qualitative and quantitative fire tests

Many standardized qualitative fire test methods give information on the performance of a material or end product as measured in the test, ~~which may or may not be~~ related to a real fire scenario or real installation practices. Such information usually is not ~~be~~ related to a real fire scenario or real installation practices. These qualitative fire test methods result in a "pass" or "fail" and/or a product or material ranking. They play an important role in prescriptive regulations, and the results of a qualitative test can be used indirectly in fire hazard assessment of electrotechnical products, but they are not suitable for directly supporting performance-based design.

Most standardized test methods developed by IEC TC 89 for electrotechnical products are of the qualitative type. It is agreed within ISO TC 92 and IEC TC 89 that this type of fire test will

¹ Numbers in square brackets refer to the Bibliography.

continue to be maintained and, where necessary, developed. It is recognized that, even if the use of these standards is in prescriptive codes, product data from many of these standards ~~may~~ **can** be potentially adaptable for fire safety engineering purposes.

In contrast, quantitative fire tests are increasingly being developed and used, and these provide data that can be inputs to fire safety engineering calculations.

Various ISO standards [14] to [23] for quantitative fire tests have been developed by ISO TC 92/SC 1, *Fire safety - Initiation and growth of fire*, some of which can be used to assess the performance of electrotechnical products ~~(see 9.4)~~, and referred to in the series of IEC 60695, e.g. IEC TS 60695-5-2 [9], IEC 60695-6-2 [10], IEC 60695-7-2 [11], IEC 60695-8-2 [12] and IEC 60695-9-2 [13].

Sample Document

get full document from standards.iteh.ai

1 Scope

This part of IEC 60695 ~~is intended as a general guideline for IEC Product Committees and provides~~ specifies methodologies of fire safety engineering for electrotechnical products by providing:

- an explanation of the principles and uses of fire safety engineering;
- guidance on the use of fire safety engineering in the design of electrotechnical products;
- fire safety engineering terminology, and concepts;
- an indication of properties, data and tests needed for input into fire safety engineering assessment; and
- informative references.

This document ~~is not intended to be a detailed technical design guide, but~~ is intended to provide guidance for product committees on fire safety engineering methods and performance-based tests for use in performance-based designs and fire hazard assessments of electrotechnical materials, assemblies, products and systems. More detailed information on fire safety engineering is contained ~~in the ISO/TR 13387 series of documents (see Clause 2 and [1] to [6]) and in ISO 23932~~ in ISO 23932-1 [1].

NOTE Further detailed aspects of FSE are covered in ~~ISO 16730 [7], ISO/TS 16732 [8], ISO/TS 16733, ISO 16734 [9], ISO 16735 [10], ISO 16736 [11], ISO 16737 [12] and ISO/TR 16738~~ ISO 16730-1 [2], ISO 16732-1 [3], ISO 16733-1 [4], ISO 24678-2 [5], ISO 24678-3 [6], ISO 24678-4 [7] and ISO/TR 16738 [8].

This basic safety publication focusing on safety guidance is primarily intended for use by ~~technical~~ committees in the preparation of ~~standards~~ safety publications in accordance with the principles laid down in IEC Guide 104 [39] and ISO/IEC Guide 51 [40].

One of the responsibilities of a ~~technical~~ committee is, wherever applicable, to make use of basic safety publications in the preparation of its publications. ~~The requirements, test methods or test conditions of this basic safety publication will not apply unless specifically referred to or included in the relevant publications.~~

This document has the status of a horizontal publication in accordance with IEC Guide 108 [43].

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60695-1-10:2016, *Fire hazard testing - Part 1-10: Guidance for assessing the fire hazard of electrotechnical products - General guidelines*

IEC 60695-1-11, *Fire hazard testing - Part 1-11: Guidance for assessing the fire hazard of electrotechnical products - Fire hazard assessment*

IEC 60695-4:2021, *Fire hazard testing - Part 4: Terminology concerning fire tests for electrotechnical products*

~~IEC Guide 104, The preparation of safety publications and the use of basic safety publications and group safety publications~~

~~ISO/IEC Guide 51, Safety aspects — Guidelines for inclusion in standards~~

ISO 13943:20082017, *Fire safety - Vocabulary*

~~ISO/TR 13387-2: Fire safety engineering — Part 2: Design fire scenarios and design fires~~

~~ISO/TR 13387-8, Fire safety engineering — Part 8: Life safety: Occupant behaviour, location and condition~~

~~ISO/TS 16733, Fire safety engineering — Selection of design fire scenarios and design fires~~

~~ISO/TR 16738, Fire safety engineering — Technical information on methods for evaluating behaviour and movement of people~~

~~ISO/TR 17252:2008, Fire tests — Applicability of reaction to fire tests to fire modelling and fire safety engineering~~

~~ISO 23932:2009, Fire safety engineering — General principles~~

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60695-4:2021 and ISO 13943:2017 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

~~For the purposes of this document, the terms and definitions given in ISO 13943:2008 and IEC 60695-4:2012, some of which are reproduced below for the user's convenience, as well as the following apply.~~

3.1

absorptivity

~~fraction of the incident radiation that is absorbed by a surface on which it falls~~

~~Note 1 to entry: Absorptivity is dimensionless.~~

3.2

active fire protection

~~action taken to reduce or prevent the spread and effects of fire in response to the detection of the fire~~

~~Note 1 to entry: Examples include the application of agents (e.g. halon gas or water spray) to the fire, or the control of ventilation.~~

3.3

available safe escape time

ASET

~~time available for escape~~

~~for an individual occupant, the calculated time interval between the time of ignition and the time at which conditions become such that the occupant is estimated to be incapacitated, i.e. unable to take effective action to escape to a safe refuge or place of safety~~

~~see also required safe escape time (3.40).~~

~~Note 1 to entry: The time of ignition can be known, e.g. in the case of a fire model or a fire test, or it may be assumed, e.g. it may be based upon an estimate working back from the time of detection. The basis on which the time of ignition is determined is always stated.~~

~~Note 2 to entry:—This definition equates incapacitation with failure to escape. Other criteria for ASET are possible. If an alternate criterion is selected, it is necessary that it be stated.~~

~~Note 3 to entry:—Each occupant can have a different value of ASET, depending on that occupant's personal characteristics.~~

~~[SOURCE: ISO 13943:2008, definition 4.20]~~

3.4

built environment

~~building or other structure~~

~~EXAMPLES—(1) Off-shore platforms; (2) civil engineering works, such as tunnels, bridges and mines; and (3) means of transportation, such as motor vehicles and marine vessels.~~

~~Note 1 to entry:—ISO 6707-1 [13] contains a number of terms and definitions for concepts related to the built environment.~~

~~[SOURCE: ISO 13943:2008, definition 4.26]~~

3.5

compressive strength

~~maximum uniaxial compressive stress experienced by a material at its moment of rupture~~

3.6

density

~~mass per unit volume~~

3.7

design fire

~~quantitative description of assumed fire characteristics within the design fire scenario~~

~~Note 1 to entry:—It is typically, an idealised description of the variation with time of important fire variables such as heat release rate, flame spread rate, smoke production rate, toxic gas yields, and temperature.~~

~~[SOURCE: ISO 13943:2008, definition 4.64]~~

3.8

design fire scenario

~~specific fire scenario on which a deterministic fire safety engineering analysis is conducted~~

~~[SOURCE: ISO 13943:2008, definition 4.65]~~

3.9

emissivity

~~ratio of the radiation emitted by a radiant source to the radiation that would be emitted by a black body radiant source at the same temperature~~

~~Note 1 to entry:—Emissivity is dimensionless.~~

~~[SOURCE: ISO 13943:2008, definition 4.75]~~

3.10

environment

~~conditions and surroundings that can influence the behaviour of an item or persons when exposed to fire~~

~~[SOURCE: ISO 13943:2008, definition 4.80]~~

3.11**escape**

~~effective action taken to reach a safe refuge or place of safety~~

~~[SOURCE: ISO 13943:2008, definition 4.82]~~

3.12**fire decay**

~~stage of fire development after a fire has reached its maximum intensity and during which the heat release rate and the temperature of the fire are decreasing~~

~~[SOURCE: ISO 13943:2008, definition 4.104]~~

3.13**fire effluent**

~~totality of gases and aerosols, including suspended particles, created by combustion or pyrolysis in a fire~~

~~[SOURCE: ISO 13943:2008, definition 4.105]~~

3.14**fire growth**

~~stage of fire development during which the heat release rate and the temperature of the fire are increasing~~

~~[SOURCE: ISO 13943:2008, definition 4.111]~~

3.15**fire hazard**

~~physical object or condition with a potential for an undesirable consequence from fire~~

~~[SOURCE: ISO 13943:2008, definition 4.112]~~

3.16**fire hazard assessment**

~~evaluation of the possible causes of fire, the possibility and nature of subsequent fire growth, and the possible consequences of fire~~

~~[SOURCE: IEC 60695-4:2012, definition 3.2.10]~~

3.17**fire model****fire simulation**

~~calculation method that describes a system or process related to fire development, including fire dynamics and the effects of fire~~

~~[SOURCE: ISO 13943:2008, definition 4.116]~~

3.18**fire resistance**

~~ability of a test specimen to withstand fire or give protection from it for a period of time~~

~~Note 1 to entry:—Typical criteria used to assess fire resistance in a standard fire test are fire integrity, fire stability, and thermal insulation material.~~

~~Note 2 to entry:—"Fire resistant" (adj.) refers only to this ability.~~

~~[SOURCE: ISO 13943:2008, definition 4.121]~~

3.19**fire safety design**

~~quantitative description of the construction of a built environment intended to meet fire safety objectives~~

3.20**fire safety engineering**

~~application of engineering methods based on a scientific principles to the development or assessment of designs in the built environment through the analysis of specific fire scenarios or through the quantification of risk for a group of fire scenarios~~

~~[SOURCE: ISO 13943:2008, definition 4.126]~~

3.21**fire safety objective**

~~desired outcome with respect to the probability of an unwanted fire, relative to essential aspects of the built environment~~

~~Note 1 to entry: The essential aspects typically relate to the issues of life safety, conservation of property, continuity of operations, protection of the environment and preservation of heritage.~~

~~[SOURCE: ISO 13943:2008, definition 4.128]~~

3.22**fire scenario**

~~qualitative description of the course of a fire with respect to time, identifying key events that characterize the studied fire and differentiate it from other possible fires~~

~~Note 1 to entry: It typically defines the ignition and fire growth processes, the fully developed fire stage, the fire decay stage, and the environment and systems that impact on the course of the fire.~~

~~[SOURCE: ISO 13943:2008, definition 4.129]~~

3.23**fire test**

~~test that measures behaviour of a fire or exposes an item to the effects of a fire~~

~~Note 1 to entry: The results of a fire test can be used to quantify fire severity or determine the fire resistance or reaction to fire of the test specimen~~

~~[SOURCE: ISO 13943:2008, definition 4.132]~~

3.24**flame spread**

~~propagation of a flame front~~

~~[SOURCE: ISO 13943:2008, definition 4.142]~~

3.25**fully developed fire**

~~state of total involvement of combustible materials in a fire~~

~~[SOURCE: ISO 13943:2008, definition 4.164]~~

3.26**heat of combustion**

~~DEPRECATED: calorific potential~~

~~DEPRECATED: calorific value~~

~~thermal energy produced by combustion of unit mass of a given substance~~

~~Note 1 to entry:—The typical units are kilojoules per gram ($\text{kJ}\cdot\text{g}^{-1}$).~~

~~[SOURCE: ISO 13943:2008, definition 4.174]~~

3.27

heat of gasification

~~thermal energy required to change a unit mass of material from the condensed phase to the vapour phase at a given temperature~~

~~Note 1 to entry:—The typical units are kilojoules per gram ($\text{kJ}\cdot\text{g}^{-1}$).~~

~~[SOURCE: ISO 13943:2008, definition 4.175]~~

3.28

heat release

~~thermal energy released by combustion~~

~~Note 1 to entry:—The typical units are joules (J).~~

~~[SOURCE: ISO 13943:2008, definition 4.176]~~

3.29

heat release rate

~~DEPRECATED: burning rate~~

~~DEPRECATED: rate of burning~~

~~rate of thermal energy production generated by combustion~~

~~Note 1 to entry:—The typical units are watts (W).~~

~~[SOURCE: ISO 13943:2008, definition 4.177]~~

3.30

ignition

~~<general> initiation of combustion~~

~~[SOURCE: ISO 13943:2008, definition 4.187]~~

3.31

modulus of elasticity

~~ratio of stress to strain within the elastic range of a material, i.e. where Hooke's Law is obeyed~~

3.32

passive fire protection

~~action taken to reduce or prevent the spread and effects of fire by means not requiring an action~~

~~EXAMPLES—(1) The division of a space into compartments using materials with inherent fire resistance to fabricate walls, floors, doors and other barriers. (2) The use of materials with good fire behaviour.~~

3.33

performance criteria

~~quantitative criteria, which have been agreed with a building approval authority, and which form an acceptable basis for assessing the safety of a design for a built environment~~

3.34

performance-based design

~~design that is engineered to achieve specified objectives and performance criteria~~