

INTERNATIONAL STANDARD

**Automatic electrical controls -
Part 2-24: Particular requirements for displacement electrical controls**

Sample Document

get full document from standards.iteh.ai



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2026 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	2
1 Scope	4
2 Normative references	4
3 Terms and definitions	5
4 General	6
5 Required technical information	7
6 Protection against electric shock	8
7 Provision for protective earthing	9
8 Terminals and terminations.....	9
9 Constructional requirements	9
10 Threaded parts and connections.....	9
11 Creepage distances, clearances and distances through solid insulation.....	9
12 Components	10
13 Fault assessment on electronic circuits	10
14 Moisture and dust resistance	10
15 Electric strength and insulation resistance.....	10
16 Heating.....	10
17 Manufacturing deviation and drift.....	10
18 Environmental stress	10
19 Endurance	11
20 Mechanical strength	12
21 Resistance to heat, fire and tracking.....	13
22 Resistance to corrosion	13
23 Electromagnetic compatibility (EMC) requirements – Emission	13
24 Normal operation	13
25 Electromagnetic compatibility (EMC) requirements – Immunity	13
26 Abnormal operation tests.....	13
Annex H (normative) Requirements related to functional safety	16
Annex AA (informative) Guide to the application of displacement electrical controls within the scope of this standard.....	19
Bibliography.....	23
Figure 101 – Positions and travel distance of displacement electrical controls	14
Figure 102 – Drawing for measuring the disconnection travel distance.....	15
Figure 103 – An example of test fixture.....	15
Figure AA.1 – Diagram of example 1.....	20
Figure AA.2 – Diagram of example 2.....	21
Table 1 – Required technical information and methods of providing these information	7

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**Automatic electrical controls -
Part 2-24: Particular requirements for displacement electrical controls**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 60730-2-24 has been prepared by IEC technical committee 72: Automatic electrical controls. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
72/1506/CDV	72/1525/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

This part 2-24 is intended to be used in conjunction with IEC 60730-1. It was established on the basis of the sixth edition of that standard (2022). Consideration may be given to future editions of, or amendments to, IEC 60730-1.

This part 2-24 supplements or modifies the corresponding clauses in IEC 60730-1, so as to convert that publication into the IEC standard: Particular requirements for displacement electrical controls.

Where this part 2-24 states "addition", "modification" or "replacement", the relevant requirement, test specification or explanatory matter in Part 1 should be adapted accordingly.

Where no change is necessary, part 2-24 indicates that the relevant clause or subclause applies.

In the development of a fully international standard, it has been necessary to take into consideration the differing requirements resulting from practical experience in various parts of the world and to recognize the variation in national electrical systems and wiring rules.

In this publication:

- The following print types are used:
 - requirements proper: in roman type;
 - test specifications: *in italic type*;
 - explanatory matter: in smaller roman type.
 - Defined terms: **bold type**.
- Subclauses, notes or items which are additional to those in Part 1 are numbered starting from 101, additional annexes are lettered AA, BB, etc.

A list of all parts of the IEC 60730 series, under the general title *Automatic electrical controls*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

1 Scope

This clause of Part 1 is replaced by the following:

This part of IEC 60730 applies to automatic **displacement electrical controls**

- for use in, on, or in association with appliances for household and similar use;

NOTE 1 Through this document, the word "**control**" means "**displacement electrical control**".

EXAMPLE 1 **Displacement electrical controls** used in electrical pressure cookers with gross volume up to 25 l, with working pressure over 4 kPa and less than 150 kPa.

- that are AC or DC powered **controls** with a rated voltage not exceeding 690 V AC or 600 V DC;
- used in, on, or in association with equipment that use electricity;
- that are mechanically or electrically operated, responsive to change of position of **point of action**.

NOTE 2 Requirements for manual switches not forming part of an automatic **control** are covered in IEC 61058-1-1.

This document applies to

- inherent safety of automatic electro-mechanical **displacement electrical controls**;
- functional safety of automatic electro-mechanical **displacement electrical controls**;
- the operating values, operating times, and operating sequences where such are associated with equipment safety;
- **displacement electrical controls** having temperature sensing element(s), in which cases additional requirements can be considered to be necessary. Requirements for temperature sensing controls are included in IEC 60730-2-9.

This document specifies the requirements for construction, operation and testing of automatic **displacement electrical controls** used in, on, or in association with equipment.

This document does not

- apply to automatic electronic controls;
- take into account the response value of an automatic action of a control, if such a response value is dependent upon the method of mounting the control in the equipment. Where a response value is of significant purpose for the protection of the user, or surroundings, the value defined in the appropriate equipment standard or as determined by the manufacturer applies.

NOTE 3 For more information about guidance to the application of **displacement electrical controls**, see Annex AA.

2 Normative references

This clause of Part 1 is applicable.

3 Terms and definitions

This clause of Part 1 is applicable except as follows:

3.2 Definitions of types of control according to purpose

Additional definitions:

3.2.101

displacement electrical control

automatic control where the displacement of **point of action** occurs through the displacement of the container due to pressure change

Note 1 to entry: The container is an inner pot in the case of rice cooker.

Note 2 to entry: The **displacement electrical control** is considered an operating control with a **type 2 action** and normally a protective control is provided on the end product to prevent a hazard, therefore there is no need to verify the robustness of the self-locking mechanism.

3.2.102

position limiter

displacement electrical control which is intended to keep a position below one particular value during normal operating conditions and which may have provision for setting by the end-product manufacturer

Note 1 to entry: A **position limiter** can be manual reset type.

3.2.103

position regulator

cycling **displacement electrical control**, which is intended to keep a position between two particular values under normal operating conditions and which may have provision for setting by the end-product manufacturer

3.4 Definitions relating to disconnection and interruption

Additional definitions:

3.4.101

free position

P_f

initial state of the **point of action** of the **displacement electrical control**

Note 1 to entry: P_f is indicated as the position of 0 displacement in Figure 101.

Note 2 to entry: In general, **free position** is at located position.

3.4.102

disconnection position

P_d

position where the contact is disconnected from the circuit by the action mechanism under the external force

Note 1 to entry: P_d is indicated in Figure 101.

3.4.103

self-locking position

P_s

position in which the self-locking mechanism just operates while the displacement can continue to increase when the contact is disconnected