

# INTERNATIONAL STANDARD

## NORME INTERNATIONALE



**Optical fibre cables –  
Part 2-20: Indoor cables – Family specification for multi-fibre optical cables**

**Câbles à fibres optiques –  
Partie 2-20: Câbles intérieurs – Spécification de famille pour les câbles optiques  
multifibres**



**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2024 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

#### IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

---

#### A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

#### A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

#### Recherche de publications IEC -

#### [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

#### Service Clients - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: [sales@iec.ch](mailto:sales@iec.ch).

#### IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications, symboles graphiques et le glossaire. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 500 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 25 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



**Optical fibre cables –  
Part 2-20: Indoor cables – Family specification for multi-fibre optical cables**

**Câbles à fibres optiques –  
Partie 2-20: Câbles intérieurs – Spécification de famille pour les câbles optiques  
multifibres**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

ICS 33.180.01

ISBN 978-2-8327-0082-2

**Warning! Make sure that you obtained this publication from an authorized distributor.  
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

## CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references .....	6
3 Terms and definitions .....	7
4 Construction .....	7
4.1 General.....	7
4.2 Optical fibres .....	7
4.3 Buffer.....	8
4.4 Ruggedized fibre.....	8
4.5 Slotted core .....	8
4.6 Tube .....	8
4.7 Stranded tube .....	8
4.8 Ribbon structure .....	8
4.9 Strength and anti-buckling members .....	9
4.10 Ripcord.....	9
4.11 Sheath.....	9
4.12 Sheath marking.....	9
4.13 Identification .....	9
4.14 Examples of cable constructions.....	9
5 Tests.....	9
5.1 General.....	9
5.2 Dimensions .....	10
5.3 Mechanical requirements .....	10
5.3.1 Tensile performance .....	10
5.3.2 Crush .....	10
5.3.3 Impact .....	10
5.3.4 Bending .....	11
5.3.5 Repeated bending .....	11
5.3.6 Bending under tension.....	11
5.3.7 Bending at low temperature .....	11
5.3.8 Flexing .....	11
5.3.9 Torsion .....	12
5.3.10 Cable kink .....	12
5.4 Environmental requirements – Temperature cycling .....	12
5.5 Transmission requirements .....	13
5.5.1 General .....	13
5.5.2 Single-mode optical fibres .....	13
5.5.3 Single-mode dispersion unshifted (B-652.B) optical fibre .....	13
5.5.4 Single-mode dispersion unshifted (B-652.D) optical fibre .....	13
5.5.5 Single-mode (B-657.A) optical fibre .....	14
5.5.6 Single-mode (B-657.B) optical fibre .....	14
5.5.7 Multimode optical fibres.....	14
5.5.8 Multimode (A1-OM1 to A1-OM5) optical fibres .....	15
5.6 Fire performance .....	15
Annex A (informative) Examples of cable constructions .....	16
Annex B (informative) Family specification for multi-fibre optical cables – Blank detail specification and minimum requirements.....	21

B.1	Blank detail specification .....	21
B.1.1	General .....	21
B.1.2	Cable description.....	21
B.1.3	Cable element .....	22
B.1.4	Cable construction.....	23
B.1.5	Installation and operating conditions.....	24
B.1.6	Mechanical and environmental tests .....	24
B.2	Cables subject to the MICE environmental classification (ISO/IEC 11801-1 and related standards) .....	25
Bibliography.....		26
Figure A.1	– Example of cross-section of a 12-fibre cable.....	16
Figure A.2	– Example of cross-section of a 36-fibre cable.....	16
Figure A.3	– Example of cross-section of a 6-fibre break-out cable .....	17
Figure A.4	– Example of cross-section of a 24-fibre break-out cable .....	17
Figure A.5	– Example of cross-section of a slotted core type indoor cable with 4-fibre ribbons .....	18
Figure A.6	– Example of cross-section of an SZ (reverse oscillating lay) slotted core type indoor cable with 2-fibre ribbons.....	18
Figure A.7	– Example of cross-section of an SZ (reverse oscillating lay) slotted core type indoor cable with 4-fibre bundles.....	19
Figure A.8	– Example of multi-fibre unitube cable .....	19
Figure A.9	– Example of multi-fibre cable.....	19
Figure A.10	– Example of a retractable (micro-module) cable .....	20
Table 1	– Dimensions of buffered fibres.....	8
Table 2	– Typical values for temperature cycling.....	12
Table 3	– Common single-mode optical fibre requirements .....	13
Table 4	– Cabled fibre attenuation requirements for B-652.B optical fibre .....	13
Table 5	– Cabled fibre attenuation requirements for B-652.D optical fibre .....	14
Table 6	– Cabled fibre attenuation requirements for B-657.A optical fibre .....	14
Table 7	– Cabled fibre attenuation requirements for B-657.B optical fibre .....	14
Table 8	– Common multimode optical fibre requirements .....	14
Table 9	– Cabled fibre attenuation requirements for A1-OM1 to A1-OM5 optical fibres.....	15
Table B.1	– Cable description .....	21
Table B.2	– Cable element.....	22
Table B.3	– Cable construction .....	23
Table B.4	– Installation and operating conditions .....	24
Table B.5	– Tests applicable.....	24

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

## OPTICAL FIBRE CABLES –

**Part 2-20: Indoor cables –  
Family specification for multi-fibre optical cables**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 60794-2-20 has been prepared by subcommittee 86A: Fibres and cables, of IEC technical committee 86: Fibre optics. It is an International Standard.

This fourth edition cancels and replaces the third edition published in 2013. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) update of the normative references;
- b) review update of parameters and requirements for mechanical tests and environmental tests, maintaining alignment with additional relevant standards in the IEC 60794-2 series;
- c) addition of cabled fibre attenuation requirements;

d) addition of cable design examples.

This document is to be used in conjunction with IEC 60794-1-1:2023, IEC 60794-1-2:2021, IEC 60794-1-21:2015 and IEC 60794-1-21:2015/AMD:2020, IEC 60794-1-22:2017, IEC 60794-1-23:2019 and IEC 60794-2:2017.

The text of this International Standard is based on the following documents:

Draft	Report on voting
86A/2431/FDIS	86A/2520/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/publications](http://www.iec.ch/publications).

A list of all parts of IEC 60794 series, published under the general title *Optical fibre cables*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

**IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## OPTICAL FIBRE CABLES –

### Part 2-20: Indoor cables – Family specification for multi-fibre optical cables

#### 1 Scope

This part of IEC 60794 is a family specification covering multi-fibre optical cables for indoor use. The requirements of the sectional specification IEC 60794-2 are applicable to cables covered by this document. Annex B contains a blank detail specification and general guidance in case the cables are intended to be used in installations governed by the MICE table of ISO/IEC 11801-1.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60304, *Standard colours for insulation for low-frequency cables and wires*

IEC 60793-1-20, *Optical fibres – Part 1-20: Measurement methods and test procedures – Fibre geometry*

IEC 60793-1-21, *Optical fibres – Part 1-21: Measurement methods and test procedures – Coating geometry*

IEC 60793-1-40, *Optical fibres – Part 1-40: Attenuation measurement methods*

IEC 60793-1-44, *Optical fibres – Part 1-44: Measurement methods and test procedures – Cut-off wavelength*

IEC 60793-1-46, *Optical fibres – Part 1-46: Measurement methods and test procedures – Monitoring of changes in optical transmittance*

IEC 60793-2-10, *Optical fibres – Part 2-10: Product specifications – Sectional specification for category A1 multimode fibres*

IEC 60793-2-50, *Optical fibres – Part 2-50: Product specifications – Sectional specification for class B single-mode fibres*

IEC 60794-1-1:2023, *Optical fibre cables – Part 1-1: Generic specification – General*

IEC 60794-1-2:2021, *Optical fibre cables – Part 1-2: Generic specification – Basic optical cable test procedures – General guidance*

IEC 60794-1-21:2015, *Optical fibre cables – Part 1-21: Generic specification – Basic optical cable test procedures – Mechanical test methods*

IEC 60794-1-21:2015/AMD1:2020

IEC 60794-1-22:2017, *Optical fibre cables – Part 1-22: Generic specification – Basic optical cable test procedures – Environmental test methods*

IEC 60794-1-23:2019, *Optical fibre cables – Part 1-23: Generic specification – Basic optical cable test procedures – Cable element test methods*

IEC 60794-1-31, *Optical fibre cables – Part 1-31: Generic specification – Optical cable elements – Optical fibre ribbon*

IEC 60794-2:2017, *Optical fibre cables – Part 2: Indoor cables – Sectional specification*

IEC 60811-202, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 202: General tests – Measurement of thickness of non-metallic sheath*

IEC 60811-203, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 203: General tests – Measurement of overall dimensions*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60794-1-1 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

### 4 Construction

#### 4.1 General

In addition to the constructional requirements in IEC 60794-2, the following considerations apply to multi-fibre indoor cables.

The cable shall be designed and manufactured for an expected operating lifetime of at least 15 years. In this context, the attenuation at the operational wavelength(s) of the optical fibres contained in the installed cable shall not exceed values specified in 5.5. The materials in the cable shall not present a health or environmental hazard within its intended use.

Optical elements may comprise any of the cable elements described in 4.3 to 4.8 or in IEC 60794-1-3.

There shall be no fibre splice in a delivery length unless otherwise agreed by customer and supplier.

It shall be possible to identify each individual fibre throughout the length of the cable.

#### 4.2 Optical fibres

Multimode or single-mode optical fibres meeting the requirements of IEC 60793-2-10 sub-categories A1-OM1 to A1-OM5 or IEC 60793-2-50 categories B-652 and B-657 shall be used. The linear coefficient of optical fibre attenuation and attenuation point discontinuity may be affected by the cable manufacturing process. Maximum values for these optical characteristics shall be as specified in 5.5.

### 4.3 Buffer

If a buffer is required, it shall consist of one or more layers of inert material. The buffer shall be easily removable. For tight buffers, the buffer and fibre primary coating shall be removable in one operation over a minimum length of 15 mm, depending on customer requirements. For semi-tight buffers, the buffer shall be easily removable over a minimum length of 300 mm. For loose buffers, the buffer shall be easily removable over a length of not less than 1,0 m. Buffer dimensions are shown in Table 1.

**Table 1 – Dimensions of buffered fibres**

Buffer type	Nominal diameter mm	Tolerances mm
Semi-tight or loose buffer	0,3 to 1,3	±0,05
Tight buffer	0,3 to 1,0	±0,05

### 4.4 Ruggedized fibre

Further protection can be provided to tight or semi-tight buffered fibres by surrounding them with non-metallic strength members within a sheath of suitable material.

### 4.5 Slotted core

The slotted core is obtained by extruding a suitable material with a defined number of slots, providing helical or SZ (reverse-oscillating lay) configuration along the core. One or more primary coated fibres or optical elements such as ribbons or fibre bundles are located in each slot.

### 4.6 Tube

One or more primary coated or buffered fibres or ribbons are packaged (loosely or not) in a tube construction which may be filled. The tube may be reinforced with a composite wall. The polymeric tube may be hard, to provide some crush protection to the fibre bundle or soft to enable easy stripability of the tube without specialized tools.

### 4.7 Stranded tube

Multiple tubes, containing one or more primary coated or buffered fibres or ribbons, may be:

- stranded around a central member,
- non-stranded, or
- homogeneous optical tubes stranded using helical or SZ configurations.

For the sake of preserving cable geometry, some tubes may be "filler" or "empty" elements not containing optical fibres.

### 4.8 Ribbon structure

Ribbon structures shall conform to IEC 60794-1-31. Fibres shall be arranged to be parallel and formed into ribbons so that the fibres remain parallel and do not cross over.

Partially bonded ribbon structures enable the optical fibre ribbon to be rolled up easily and accommodated very tightly in cables. Unless otherwise specified, each ribbon shall be uniquely identified with a printed legend or by uniquely colouring the reference fibre and/or by colouring the matrix material of the ribbon.

#### 4.9 Strength and anti-buckling members

The cable shall be designed with sufficient strength members to meet installation and service conditions so that the fibres are not subjected to strain in excess of limits specified in 5.3.1.

The strength and anti-buckling members may be either metallic or non-metallic and may be located in the cable core or under the sheath or in the sheath.

#### 4.10 Ripcord

If required, a ripcord may be provided beneath the sheath.

#### 4.11 Sheath

The cable shall have an overall protective sheath. The cable diameter shall be specified in the relevant blank detail specification (or product) specification.

#### 4.12 Sheath marking

If required, the cable shall be marked as agreed between customer and supplier. The marking can include identifying marks regarding the manufacturer, fire resistance ratings, jacket length, date of manufacture, etc.

#### 4.13 Identification

Optical fibres, buffers and sub-unit sheaths shall be easily and uniquely identifiable through the use of a suitable colour code according to IEC 60304 and/or an easily visible numbering scheme to be agreed between customer and supplier.

#### 4.14 Examples of cable constructions

Examples of some types of cable construction are shown in Annex A. Other configurations (e.g. multi-layer constructions) are not precluded if they meet the mechanical, environmental and transmission requirements given in this document.

### 5 Tests

#### 5.1 General

Compliance with relevant detail specification requirements shall be verified by carrying out tests selected from 5.2 to 5.6. It is not intended that all tests be carried out; the frequency of testing shall be agreed between customer and supplier.

Unless otherwise specified, all tests shall be carried out at standard atmospheric conditions according to IEC 60794-1-2. These tests are not intended to define end-of-life performance.

The attenuation of cabled fibres shall be as specified in 5.5.

Measurements of attenuation shall be carried out according to IEC 60793-1-40. Change in attenuation measurements shall be carried out according to IEC 60793-1-46.

NOTE The optimized wavelength for multimode fibre sub-categories A1-OM3 and A1-OM4 is 850 nm and for A1-OM5 fibre, the targeted operational wavelength(s) is between 850 nm and 950 nm.

## 5.2 Dimensions

The fibre dimensions and tolerances shall be checked in accordance with the test method as specified in IEC 60793-1-20 or IEC 60793-1-21. The diameter of the buffer and of the cable, as well as the thickness of the sheath, shall be measured in accordance with the methods of IEC 60811-202 and IEC 60811-203.

## 5.3 Mechanical requirements

### 5.3.1 Tensile performance

Method:	IEC 60794-1-21, method E1
Diameter of chuck drums and transfer devices:	not smaller than the minimum bending diameter specified for the cable under load
Velocity of transfer device:	either 100 mm/min or 100 N/min
Load and duration:	400 N or $9,8 \times$ the mass of 1 km of cable, whichever is greater, and for a minimum period of 10 min
Length of sample:	$\geq 50$ m and sufficient to achieve the desired accuracy of measurement of attenuation change
Requirements:	there shall be no change in attenuation after the test; there shall be no visible damage to the cable elements

The fibre strain shall be less than 60 % of the proof test level of the fibre.

For certain applications specifying MICE classification of ISO/IEC 11801-1 and related standards, different load and duration values may be agreed between customer and supplier.

For exceptionally high fibre count cables, different load values may be agreed between customer and supplier.

### 5.3.2 Crush

Method:	IEC 60794-1-21, method E3A
Total force applied (short term):	500 N
Duration of application of the force:	1 min
Number of tests:	3
Spacing between test places:	500 mm
Requirements:	no change in attenuation during the operational test and after the installation test; there shall be no visible damage to the cable elements

NOTE For certain applications specifying MICE classification of ISO/IEC 11801-1 and related standards, different force values can be agreed between customer and supplier.

### 5.3.3 Impact

Method:	IEC 60794-1-21, method E4
Radius of striking surface:	300 mm
Impact energy:	1,0 J
Number of impacts:	at least 3, each separated at least 500 mm
Requirements:	no fibre breakage

NOTE For certain applications specifying MICE classification of ISO/IEC 11801-1 and related standards, impact energy values can be agreed between customer and supplier.

#### 5.3.4 Bending

Method:	IEC 60794-1-21, method E11A
Mandrel diameter:	20 times cable diameter
Number of turns:	6
Number of cycles:	10
Requirements:	no fibre breakage

NOTE For certain applications specifying MICE classification of ISO/IEC 11801-1 and related standards, different mandrel diameter values can be agreed between customer and supplier.

#### 5.3.5 Repeated bending

Method:	IEC 60794-1-21, method E6
Bending radius:	20 times cable diameter
Number of cycles:	25
Mass of weights:	sufficient to minimize specimen sag or bend – typically 4 kg
Requirements:	under visual examination without magnification, there shall be no damage to the sheath and to the cable elements

#### 5.3.6 Bending under tension

Method:	IEC 60794-1-21, method E18A
Bending radius:	20 times cable diameter
Load:	400 N or weight of 1 km of cable, whichever is greater
Requirements:	no change in attenuation after the test, and there shall be no visible damage to the cable elements

#### 5.3.7 Bending at low temperature

Method:	IEC 60794-1-21, method E11A
Bending radius:	10 times cable diameter
Test temperature:	0 °C, –10 °C or –15 °C depending on application and customer requirements
Number of turns:	4
Number of cycles:	2
Requirements:	no visible damage to cable sheath, and no fibre shall break during the test

#### 5.3.8 Flexing

Method:	IEC 60794-1-21, method E8
Number of cycles:	100
Pulley diameter:	20 times cable diameter
Mass of weights:	2 kg (minimum)
Requirements:	no fibre breakage

NOTE For certain applications specifying MICE classification of ISO/IEC 11801-1 and related standards, different pulley diameter values can be agreed between customer and supplier.

### 5.3.9 Torsion

Method:	IEC 60794-1-21, method E7
Number of cycles:	10
Distance between fixed and rotation clamp:	125 times cable diameter but not more than 2,0 m
Tension load:	20 N
Requirements:	no fibre breakage

NOTE For certain applications specifying MICE classification of ISO/IEC 11801-1 and related standards, different values for the number of cycles can be agreed between customer and supplier.

### 5.3.10 Cable kink

Method:	IEC 60794-1-21, method E10
Minimum loop diameter:	20 times cable diameter
Requirement:	no kink shall occur

## 5.4 Environmental requirements – Temperature cycling

For indoor multi-fibre cables, -10 °C and +60 °C are the recommended low and high temperatures. Based on different environment classifications, other operating temperatures may be agreed upon between customer and supplier. Table 2 gives the operating temperature limits based on environmental classification.

Table 2 – Typical values for temperature cycling

Low temperature TA2 °C	High temperature TB2 °C	Sources of temperature limits	
		Performance categories of connectors, components and protective housings <sup>a</sup>	Environmental classification of customer premises cabling <sup>b</sup>
-10	+60	C (recommended)	M <sub>x</sub> I <sub>x</sub> C1E <sub>x</sub>
-25	+70	OP	M <sub>x</sub> I <sub>x</sub> C2E <sub>x</sub>
-40	+70	I	M <sub>x</sub> I <sub>x</sub> C3E <sub>x</sub>

A suitable operating service environment (performance category) or environmental classification should be selected according to the application. A complete list of operating service environments can be found in IEC 60794-1-1:2023.

<sup>a</sup> Included in IEC 61753-1. The abbreviations represent:

- C: indoor controlled environment;
- OP: outdoor protected environment;
- I: industrial environment.

<sup>b</sup> Included in ISO/IEC 11801-1. For an introduction to the MICE environmental classification system, use ISO/IEC TR 29106. The abbreviation MICE represents: mechanical, ingress, climatic, electromagnetic.

Method:	IEC 60794-1-22, method F1
Period:	t1 = sufficient time such that the cable has reached thermal stability throughout its entire length at the specified temperature (for additional information, see IEC 60794-1-22:2017, Table 1 in method F1)
Number of cycles:	2
Length of sample:	sufficient to achieve the desired accuracy of measurement of attenuation
Requirements:	the maximum change in attenuation during the test shall be specified in the relevant detail specification; there shall be no change in attenuation after the test.

## 5.5 Transmission requirements

### 5.5.1 General

The transmission requirements shall be in accordance with one of the sectional specifications defined in IEC 60793-2-10 or IEC 60793-2-50. Maximum cabled fibre attenuation shall comply with this document.

### 5.5.2 Single-mode optical fibres

See Table 3.

**Table 3 – Common single-mode optical fibre requirements**

Characteristics	IEC 60794-2:2017, Subclause no.	Requirements	Test methods	Remarks
Uncabled optical fibre	4.2	IEC 60793-2-50		
Cabled fibre cut-off wavelength	4.2	$\lambda_{cc} < \lambda_{\text{operational}}$	IEC 60793-1-44	
Point discontinuities at 1 550 nm	4.2	$\leq 0,10$ dB	IEC 60793-1-40	

### 5.5.3 Single-mode dispersion unshifted (B-652.B) optical fibre

See Table 4.

**Table 4 – Cabled fibre attenuation requirements for B-652.B optical fibre**

Characteristics	IEC 60794-2:2017, Subclause no.	Requirements	Test methods	Remarks
Attenuation coefficient (cabled fibres)	7.3	According to the Detail Specification	IEC 60793-1-40	
at 1 310 nm at 1 550 nm at 1 625 nm		$\leq 1,0$ dB/km $\leq 1,0$ dB/km $\leq 1,0$ dB/km		

### 5.5.4 Single-mode dispersion unshifted (B-652.D) optical fibre

See Table 5.