

INTERNATIONAL STANDARD

**Electromagnetic compatibility (EMC) -
Part 4-30: Testing and measurement techniques - Power quality measurement
methods**

Document Preview

IEC 61000-4-30:2025

<https://standards.iteh.ai/catalog/standards/iec/f9b338ca-0425-4c32-a2d6-cbd2c071acc4/iec-61000-4-30-2025>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2025 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

[IEC 61000-4-30:2025](https://standards.iteh.ai/catalog/standards/iec/f9b338ca-0425-4c32-a2d6-cbd2c071acc4/iec-61000-4-30-2025)

<https://standards.iteh.ai/catalog/standards/iec/f9b338ca-0425-4c32-a2d6-cbd2c071acc4/iec-61000-4-30-2025>

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	6
INTRODUCTION	8
1 Scope	9
2 Normative references	9
3 Terms, definitions, and abbreviated terms	10
3.1 Terms and definitions	10
3.2 Abbreviated terms	16
4 General	17
4.1 Classes of measurement	17
4.2 Organization of the measurements	17
4.3 Electrical values to be measured	18
4.4 Measurement aggregation over time intervals	18
4.5 Measurement aggregation algorithm	19
4.5.1 Requirements	19
4.5.2 150/180-cycle aggregation	19
4.5.3 10 min aggregation	19
4.5.4 2 h aggregation	22
4.6 Maximum permissible error of the time clock	22
4.7 Maximum permissible errors of power quality parameters	22
4.8 Flagging concept	22
5 Power quality parameters	23
5.1 General	23
5.2 Power frequency	23
5.2.1 Measurement method	23
5.2.2 Maximum permissible measurement error and measuring range	23
5.2.3 Measurement evaluation	24
5.2.4 Aggregation	24
5.3 Magnitude of the supply voltage	24
5.3.1 Measurement method	24
5.3.2 Maximum permissible measurement error and measuring range	24
5.3.3 Measurement evaluation	24
5.3.4 Aggregation	24
5.4 Flicker	24
5.4.1 Measurement method	24
5.4.2 Maximum permissible measurement error and measuring range	25
5.4.3 Measurement evaluation	25
5.4.4 Aggregation	25
5.5 Supply voltage dip and swell events	25
5.5.1 Measurement method	25
5.5.2 Voltage dips on single-phase systems	26
5.5.3 Voltage swells on single-phase systems	27
5.5.4 Voltage dip and swell events on polyphase systems	28
5.5.5 Maximum permissible measurement error	30
5.5.6 Aggregation	31
5.6 Supply voltage interruptions	31
5.6.1 Measurement method	31

5.6.2	Detection and evaluation.....	31
5.6.3	Maximum permissible measurement error.....	32
5.6.4	Aggregation.....	32
5.7	Transient voltages	32
5.8	Supply voltage unbalance	32
5.8.1	Measurement method	32
5.8.2	Maximum permissible measurement error and measuring range.....	33
5.8.3	Measurement evaluation	33
5.8.4	Aggregation.....	33
5.9	Voltage harmonics	34
5.9.1	Measurement method	34
5.9.2	Maximum permissible measurement error and measuring range.....	34
5.9.3	Measurement evaluation	35
5.9.4	Aggregation.....	35
5.10	Voltage interharmonics.....	35
5.10.1	Measurement method	35
5.10.2	Maximum permissible measurement error and measuring range.....	35
5.10.3	Evaluation	35
5.10.4	Aggregation.....	35
5.11	MCS voltage on the supply voltage	36
5.11.1	Measurement method	36
5.11.2	Maximum permissible measurement error and measuring range.....	36
5.11.3	Aggregation.....	36
5.12	Rapid voltage changes (RVC)	36
5.12.1	General.....	36
5.12.2	RVC event detection.....	37
5.12.3	RVC event evaluation	39
5.12.4	Examples of RVC event evaluation	41
5.12.5	Maximum permissible measurement error	41
5.12.6	Aggregation.....	42
5.13	Current	42
5.13.1	General.....	42
5.13.2	Magnitude of current.....	42
5.13.3	Current recording	43
5.13.4	Harmonic currents.....	43
5.13.5	Interharmonic currents.....	44
5.13.6	Current unbalance.....	44
6	Performance verification	44
Annex A (informative)	Power quality measurements – Issues and guidelines	47
A.1	General	47
A.2	Installation precautions.....	47
A.2.1	General.....	47
A.2.2	Test leads	47
A.2.3	Guarding of live parts	48
A.2.4	Monitor placement.....	48
A.2.5	Earthing	49
A.2.6	Interference	49
A.3	Transducers	49

A.3.1	General.....	49
A.3.2	Signal levels.....	50
A.3.3	Frequency response of transducers	51
A.3.4	Transducers for measuring transients.....	51
A.4	Transient voltages and currents.....	52
A.4.1	General.....	52
A.4.2	Frequency and amplitude characteristics of AC mains transients.....	52
A.4.3	Transient voltage detection	53
A.4.4	Transient voltage evaluation.....	54
A.4.5	Effect of surge protective devices on transient measurements	54
A.5	Voltage dip characteristics	54
A.5.1	General.....	54
A.5.2	Rapidly updated RMS values.....	55
A.5.3	Phase angle/point-on-wave	55
A.5.4	Voltage dip unbalance	55
A.5.5	Phase shift during voltage dip.....	56
A.5.6	Missing voltage	56
A.5.7	Distortion during voltage dip.....	56
A.5.8	Other characteristics and references	56
Annex B (informative)	Power quality measurement – Guidance for applications.....	57
B.1	Contractual applications of power quality measurements.....	57
B.1.1	General.....	57
B.1.2	General considerations.....	57
B.1.3	Specific considerations.....	58
B.2	Statistical survey applications	61
B.2.1	General.....	61
B.2.2	Considerations.....	61
B.2.3	Power quality indices.....	62
B.2.4	Monitoring objectives.....	62
B.2.5	Economic aspects of power quality surveys	62
B.3	Locations and types of surveys	63
B.3.1	Monitoring locations	63
B.3.2	Pre-monitoring site surveys.....	64
B.3.3	Customer side site survey	64
B.3.4	Network side survey	64
B.4	Connections and quantities to measure.....	64
B.4.1	Equipment connection options	64
B.4.2	Priorities: quantities to measure.....	65
B.4.3	Current monitoring	65
B.5	Selecting the monitoring thresholds and monitoring period	66
B.5.1	Monitoring thresholds	66
B.5.2	Monitoring period	66
B.6	Statistical analysis of the measured data.....	67
B.6.1	General.....	67
B.6.2	Indices.....	67
B.7	Trouble-shooting applications.....	67
B.7.1	General.....	67
B.7.2	Power quality signatures.....	67

B.7.3	Waveform data format	68
Annex C (informative) Functional design and specification for measurements in the 2 kHz to 9 kHz range for Class A and Class S equipment.....		69
C.1	General	69
C.2	Voltage disturbances in the 2 kHz to 9 kHz range.....	69
C.2.1	Measurement method	69
C.2.2	Maximum permissible measurement error	69
C.2.3	Aggregation.....	70
Annex D (informative) Functional design and specifications for measurements in the 9 kHz to 150 kHz range		71
D.1	General	71
D.2	Background.....	71
D.3	Comparability requirements	72
D.4	Method overview.....	72
D.5	Signal input stage	74
D.5.1	General.....	74
D.5.2	Input filtering	74
D.5.3	Frequency response	74
D.5.4	Transducer compensation	74
D.5.5	Measuring range	75
D.5.6	Overload detection	75
D.6	Fourier transform stage	76
D.6.1	General.....	76
D.6.2	DFT window design.....	77
D.6.3	Application of the DFT	79
D.6.4	Selectivity and power bandwidth	80
D.7	Detector stage	80
D.7.1	General.....	80
D.7.2	RMS detector.....	81
D.7.3	Peak detector	81
D.7.4	Quasi-peak detector	81
D.7.5	Average detector.....	83
D.7.6	RMS-average detector	83
D.8	Indicator stage.....	84
D.9	Adjustment of time constants	86
D.10	Accuracy requirements	87
D.10.1	General.....	87
D.10.2	Accuracy requirements for measuring steady-state sinusoidal signals.....	87
D.10.3	Accuracy requirements for measuring impulsive signals	87
D.11	Aggregation.....	91
D.11.1	General.....	91
D.11.2	Aggregation time intervals.....	91
D.11.3	Aggregation methods.....	91
D.12	Integration of signal levels over frequency	92
Bibliography.....		93
Figure 1 – Measurement chain		17
Figure 2 – Synchronization of aggregation intervals for Class A.....		20

Figure 3 – Synchronization of aggregation intervals for Class S: parameters for which gaps are not permitted	21
Figure 4 – Synchronization of aggregation intervals for Class S: parameters for which gaps are permitted (see 4.5.2)	21
Figure 5 – Example of the MPE of a supply voltage unbalance measurement.....	33
Figure 6 – RVC event: example of a change in RMS voltage that results in an RVC event....	41
Figure 7 – Not an RVC event: example of a change in RMS voltage that does not result in an RVC event because the dip threshold is exceeded.....	41
Figure A.1 – Frequency spectrum of typical representative transient test waveforms	53
Figure D.1 – Block diagram of the 9 kHz to 150 kHz measurement method	73
Figure D.2 – Quasi-peak detector equivalent circuit.....	81
Figure D.3 – Indicator response to a 160 ms impulse pulse width when represented by a 2 nd order Linkwitz-Riley low-pass filter tuned to the frequency $f_c = 0,9947$ Hz	86
Figure D.4 – Impulses with an amplitude of 5,51 V and a width of 2,45 μ s to assess instrument compliance at 100 Hz.....	90
Table 1 – Summary of requirements (see subclauses for actual requirements).....	45
Table D.1 – Band A IF filter impulse response zero-crossing times	78
Table D.2 – Adjusted time constants for the quasi-peak detector	86
Table D.3 – Sinusoidal signal accuracy requirements from 9 kHz to 150 kHz	87
Table D.4 – Impulsive signal accuracy requirements from 9 kHz to 150 kHz.....	88
Table D.5 – Reference quasi-peak response to spectrally flat impulses.....	89

Document Preview

[IEC 61000-4-30:2025](https://standards.iteh.ai/catalog/standards/iec/f9b338ca-0425-4c32-a2d6-cbd2c071acc4/iec-61000-4-30-2025)

<https://standards.iteh.ai/catalog/standards/iec/f9b338ca-0425-4c32-a2d6-cbd2c071acc4/iec-61000-4-30-2025>