



IEC 61375-1

Edition 4.0 2026-03

INTERNATIONAL STANDARD

REDLINE VERSION

**Electronic railway equipment - Train communication network (TCN) -
Part 1: General architecture**

Sample Document

get full document from standards.iteh.ai



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2026 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references	8
3 Terms, definitions, abbreviated terms, acronyms, and conventions.....	8
3.1 Terms and definitions.....	8
3.2 Abbreviations and acronyms	18
3.3 Conventions.....	19
3.3.1 Requirement conventions	20
3.3.1 Base of numeric values	20
3.3.2 Naming conventions	20
3.3.3 State diagram conventions	20
4 Basic architecture.....	20
4.1 Contents of this clause General	20
4.2 General Technology and components	21
4.2.1 Technology classes	21
4.2.2 Component types.....	21
4.3 Hierarchical structure.....	21
4.3.1 Network levels	21
4.3.2 Train backbone level	22
4.3.3 Consist network level.....	22
4.3.4 Interface between train backbone and consist network	23
4.3.5 End devices connected to train backbone	24
4.4 Network configurations	24
4.5 Train to ground connection (option)	25
5 Train backbone.....	26
5.1 Contents of this clause General	26
5.2 Train backbone topology.....	26
5.2.1 General	26
5.2.2 Train backbone based on bus technology	26
5.2.3 Train backbone based on switched technology	27
5.2.4 Train Backbone based on wireless technology.....	28
5.3 Train compositions.....	30
5.4 Train backbone node numbering	30
5.5 Train directions	31
5.5.1 Vehicle	31
5.5.2 Consist	31
5.5.3 Closed train	32
5.5.4 Train.....	32
5.6 Train inauguration.....	34
5.6.1 Objectives	34
5.6.2 Node sequence and orientation discovery.....	34
5.6.3 Train network directory	34
5.6.4 Train directory	34
5.6.5 Train inauguration control.....	38
5.6.6 Node states	40

5.6.7	Node roles	44
5.6.8	Performance	44
5.6.9	Independent consist orientation check (Option)	44
6	Consist network	45
6.1	Contents of this clause General	45
6.2	Scope of standardization	45
6.3	Consist network topology	46
6.3.1	Consist network based on bus technology (MVB, CANopen CCN)	46
6.3.2	Consist network based on switched technology (ECN)	47
6.3.3	Consist network based on wireless technology (WLCN)	50
6.3.4	Sub-networks	50
6.3.5	Heterogeneous consist network	52
6.4	Gateway	52
6.4.1	General	52
6.4.2	Functional description	52
6.4.3	Application layer gateway	53
6.4.4	Gateway implemented by a router	55
6.4.5	Gateway implemented by a bridge	55
7	On-board data communication	56
7.1	General	56
7.2	Communication patterns	56
7.2.1	Purpose	56
7.2.2	Definitions	56
7.2.3	Push pattern	56
7.2.4	Pull pattern	58
7.2.5	Subscription pattern	59
7.3	Addressing	59
7.3.1	General	59
7.3.2	Network layer addressing	59
7.3.3	Application layer addressing	61
7.4	Availability of data communication	62
7.5	Data classes	62
7.5.1	General	62
7.5.2	Service parameters	62
7.5.3	TCN data class definition	64
7.6	Communication profile	65
7.7	Application profile	65
8	Cybersecurity	65
8.1	General	65
8.2	System under consideration	66
8.3	Lifecycle	66
8.3.1	General	66
8.3.2	Legacy systems	66
8.3.3	Protocol design	66
8.4	Guidelines	66
Annex A (informative)	High-level train architecture	68
A.1	General	68
A.2	Architectural realms	68

A.3 On-board network structures	70
Bibliography.....	72
Figure 1 – Train backbone and consist network	21
Figure 2 – Example of consist with 2 consist networks	22
Figure 3 – End device connected to the train backbone (example).....	24
Figure 4 – Communication between train and ground (example)	25
Figure 5 – Interfaces between consists	26
Figure 6 – Train backbone bus topology	27
Figure 7 – Train backbone switched topology (aggregated transmission media).....	27
Figure 8 – Train backbone switched topology (segregated transmission media).....	28
Figure 9 – Wireless train backbone mesh topology	28
Figure 10 – Wireless train backbone base station topology	29
Figure 11 – Wireless train backbone mesh topology for redundancy	29
Figure 12 – Wireless train backbone base station topology for redundancy	30
Figure 13 – Directions and orientation in a vehicle	31
Figure 14 – Directions and orientations in a consist (example).....	32
Figure 15 – Directions and orientations in a closed train	32
Figure 16 – Directions and orientations in train (TCN directions).....	33
Figure 17 – Structure of train-network directory (example)	36
Figure 18 – Train inauguration block diagram	41
Figure 19 – Train inauguration state chart.....	43
Figure 20 – Independent orientation check with BEACON telegrams.....	44
Figure 21 – Consist network standard interfaces.....	46
Figure 22 – Consist network (bus technology).....	46
Figure 23 – Local service.....
Figure 24 – Unconfirmed service.....
Figure 25 – Confirmed service
Figure 26 – Provider initiated services
Figure 23 – Consist switches	47
Figure 24 – Examples of consist network topologies (switched technology)	49
Figure 25 – End device connected to two consist switches	49
Figure 26 – Wireless consist network.....	50
Figure 27 – Sub-networks in a consist network	51
Figure 28 – Implementation example for two vehicle busses	52
Figure 29 – Example of heterogeneous train control network architecture	52
Figure 30 – Point to point communication pattern (push).....	57
Figure 31 – Point to multi-point communication pattern (push)	57
Figure 32 – Point to point communication pattern (pull).....	58
Figure 33 – Point to multi-point communication pattern (pushpull).....	58
Figure 34 – Subscription communication pattern.....	59
Figure A.1 – Example of architectural realm structure	69
Figure A.2 – Examples for network segregation of on-board physical networks	70

Table 1 – Train composition changes	30
Table 2 – Train-network specific parameters (example)	37
Table 3 – Consist-network specific parameters (example).....	37
Table 4 – Vehicle specific parameters (example)	38
Table 5 – Device specific parameters (example)	38
Table 6 – Point to point (Push).....	57
Table 7 – Point to multi-point (Push)	57
Table 8 – Point to point (Pull)	58
Table 9 – Point to multi-point (Pull)	59
Table 10 – Service parameters	62
Table 11 – Principal data classes.....	64

Sample Document

get full document from standards.iteh.ai

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**Electronic railway equipment - Train communication network (TCN) -
Part 1: General architecture**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 61375-1:2012. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

IEC 61375-1 has been prepared by IEC technical committee 9: Electrical equipment and systems for railways. It is an International Standard.

This fourth edition cancels and replaces the third edition published in 2012. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Extension of train backbone topologies: aggregated and segregated topology;
- b) Added independent consist orientation check with segregated train backbone topology;
- c) Introduction of wireless technologies: wireless train backbone and wireless consist network;
- d) Possibility of virtual networks;
- e) Definition of data classes and protocol requirements suitable for the OMTS domain;
- f) New clause about cybersecurity in train communication networks.

The text of this International Standard is based on the following documents:

Draft	Report on voting
9/3252/FDIS	9/3293/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts of IEC 61375 series, under the general title *Electronic railway equipment - Train communication network (TCN)*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INTRODUCTION

IEC 61375-1 defines the general architecture of the Train Communication Network (TCN) to achieve compatibility between consist networks and train backbones defined by the IEC 61375 series.

The creation of this fourth edition of the standard has been motivated by advances in technology, namely in the fields of Ethernet communication, wireless communication, and cybersecurity, which made it necessary to adapt or to extend some sections of the TCN general architecture. These changes will then further on be reflected in the detailed technical specifications given in subsequent parts of the IEC 61375 series.

The TCN has a hierarchical structure with two levels of networks, a train backbone and a consist network:

- a) for interconnecting vehicles in closed or open trains, this document specifies train backbones with different characteristics.
- b) for connecting standard on-board equipment, this document specifies consist networks with different characteristics.

The general architecture of the TCN, which is defined in this document, ~~shall~~ does

- c) establish the rules for interconnecting consist networks with train backbones, as
 - 1) identifying the interfaces;
 - 2) defining the principles of how train topology changes can be discovered;
 - 3) defining the basic communication services provided by train backbones to be used by consist networks;
- d) establish basic rules for the train backbone and for the consist network;
- e) establish rules for ~~communalities~~ commonalities in operation, as:
 - 1) patterns for the communication between users;
 - 2) addressing principles;
 - 3) data classes to be supported;
- e) establish rules to support cybersecurity of the TCN.

1 Scope

This part of IEC 61375 applies to the architecture of data communication systems in open trains, i.e. it covers the architecture of a communication system for the data communication between vehicles of the said open trains, the data communication within the vehicles and the data communication from train to the ground.

The applicability of this part of IEC 61375 to the train network technologies allows for interoperability of individual vehicles within open trains in international traffic. The data communication systems inside vehicles are given as recommended solutions to cope with the said TCN. In any case, proof of compatibility between a proposed train backbone and a proposed consist network will have to be brought by the supplier.

This part of IEC 61375 ~~may~~ might be additionally applicable to closed trains and multiple unit trains when so agreed between purchaser and supplier.

NOTE 1 For definitions of open trains, multiple unit trains and closed trains, see Clause 3.

NOTE 2 Road vehicles such as buses and trolley buses are not considered in this part of IEC 61375.

2 Normative references

~~The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.~~

~~ISO/IEC 7498-1, Information Technology — Open Systems Interconnection — Basic Reference Model: The Basic Model~~

~~ISO/IEC 8824-1:2002, Information technology — Abstract Syntax Notation One (ASN.1): specification of basic notation~~

~~ISO/IEC 9646-1:1994, Information technology — Open Systems Interconnection — Conformance testing methodology and framework — Part 1: General concepts~~

~~ISO/IEC 19501:2005, Information technology — Open Distributed Processing — Unified Modeling Language (UML) Version 1.4.2~~

~~UITC CODE 556, Information transmission in the train (train-bus)~~

There are no normative references in this document.

3 Terms, definitions, abbreviated terms, acronyms, and conventions

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1.1**active train backbone node**

train backbone node receiving a sequence number during train inauguration and forwarding user data packets between consist network and train backbone

3.1.2**application layer**

upper layer in the OSI model, interfacing directly to the application

[SOURCE: IEC 60050-811:2017, 811-37-03]

3.1.3**application layer interface**

~~definition of the services offered by the application layer~~

3.1.3**application process**

element within a real open system which performs the information processing for a particular application

[SOURCE: IEC 60050-811:2017, 811-37-05]

3.1.4**bridge**

<in a train communication network> device which stores and forwards frames from one bus to another on the base of their link layer addresses

[SOURCE: IEC 60050-811:2017, 811-37-09]

3.1.5**broadcast**

nearly simultaneous transmission of the same information to several destinations

Note 1 to entry: Broadcast in the TCN is not considered reliable, i.e. some destinations ~~may~~ can receive the information and others not.

[SOURCE: IEC 60050-811:2017, 811-37-10]

3.1.6**bus**

<in a train communication network> communication medium which broadcasts the same information to all attached participants at nearly the same time, allowing all devices to obtain the same sight of its state, at least for the purpose of arbitration

3.1.7**closed train**

train composed of one or a set of consists, where the train composition does not change during normal operation

EXAMPLE Metro, suburban train, or high-speed train unit.

Note 1 to entry: Consists are coupled in a workshop to establish a closed train for operation.

[SOURCE: IEC 60050-811:2017, 811-37-17]

3.1.8**communication device**

device connected to the consist network or train backbone with the ability to transport, source or sink data

[SOURCE: IEC 60050-811:2017, 811-37-18]

3.1.10

composition

~~number and characteristics of the vehicles forming a train~~

3.1.11

configuration

~~definition of the topology of a network, the devices connected to it, their capabilities and the traffic they produce; by extension, the operation of loading the devices with the configuration information before going to regular operation~~

3.1.9

consist

~~train set~~

~~rake of coaches~~

single vehicle or a group of vehicles which are not separated during normal operation, ~~and which contains no, one or several consist networks~~

~~EXAMPLE The vehicles of a consist are steadily connected in a workshop, and automatic couplers are mounted at both ends of the consist to facilitate the coupling and de-coupling of complete consists in the workshop or during operation.~~

Note 1 to entry: A consist can contain no, one or several consist networks.

[SOURCE: IEC 60050-811:2017, 811-37-20]

3.1.10

consist network

communication network interconnecting communication devices in one consist

Note 1 to entry: Consist networks do not spread beyond consist boundaries.

[SOURCE: IEC 60050-811:2017, 811-37-21]

3.1.11

consist network address

network address, which does not change after train inauguration and which is used to address communication device in the own consist network

3.1.12

consist sequence number

sequence number of the consist in the train as obtained during train inauguration

3.1.13

consist switch

~~consist network node~~

network component used in consist network based on switched technology ~~(ECN). See “switch” 3.1.58.~~

[SOURCE: IEC 60050-811:2017, 811-37-22]

3.1.17

consumer

~~receiver of a message at the transport layer (see: “producer” 3.1.47)~~

3.1.14 cybersecurity

<in railway application> set of activities and measures taken with the objective to identify, protect against, detect, respond to, and recover from unauthorized access or cyberattack which could lead to an accident, an unsafe situation, or railway application performance degradation

[SOURCE: CLC/TS 50701:2023, 3.1.32]

~~3.1.18 destination device receiver of a data packet (see: "source device" 3.1.55)~~

3.1.15 end device

unit connected to one consist network or to one set of consist networks prepared for redundancy reasons

[SOURCE: IEC 60050-811:2017, 811-37-33]

3.1.16 end node

node which terminates the train backbone

[SOURCE: IEC 60050-811:2017, 811-37-34]

3.1.17 essential function

function or capability that is required to maintain health, safety, the environment and availability for the equipment under control

Note 1 to entry: Essential functions include, but are not limited to, the safety instrumented function (SIF), the control function and the ability of the operator to view and manipulate the equipment under control. The loss of essential functions is commonly termed loss of protection, loss of control and loss of view respectively. In some industries additional functions such as history can be considered essential.

[SOURCE: IEC 62443-4-2:2019, 3.1.20]

3.1.18 function

<in a train communication network> application process which exchanges messages with another application process

3.1.19 gateway

~~connection between different communication technologies~~

<in a train communication network> connection between different busses at the application layer requiring application-dependent data analysis and protocol conversion

3.1.20 group address

address of a multicast group to which a device belongs

[SOURCE: IEC 60050-811:2017, 811-37-45]

~~3.1.24 inauguration~~

~~operation executed in case of composition change, which gives all nodes of the train backbone their train backbone address, their orientation and information about all named nodes on the same backbone~~

3.1.21**integrity**

<in a train communication network> property of a system to recognize and to reject wrong data in case of malfunction of its parts

3.1.22**intermediate node**

node which establishes continuity between two bus sections connected to it, but does not terminate them

[SOURCE: IEC 60050-811:2017, 811-37-49]

3.1.27**jumper cable**

~~cable connecting the trunk cables of two consecutive vehicles, possibly of a larger cross-section than the trunk cable, and which is plugged by hand in the case of the UIC cable. There are generally two jumper cables between vehicles~~

3.1.23**linear topology**

topology where the nodes are connected in series, with two nodes each connected to only one other node and all others each connected to two other nodes (i.e. connected in the shape of a line)

[SOURCE: ~~IEC 61784-2~~ IEC 60050-811:2017, 811-37-51]

3.1.24**local area network**

<in a train communication network> part of a network characterized by a common medium access and address space

[SOURCE: IEC 60050-811:2017, 811-37-60]

3.1.25**medium access control**

<in a train communication network> sublayer of the link layer, which controls the access to the medium (arbitration, mastership transfer, polling)

3.1.26**medium**

<in a train communication network> physical carrier of the signal: electrical wires, optical fibers, etc.

3.1.27**message**

~~data item transmitted in one or several packets~~

<in transmission systems> information which is transmitted in one or several packets from a sender to one or more receivers

[SOURCE: IEC 60050-821:2017, 821-11-29]

3.1.33**mobile train unit**

~~part of a train which shall be uniquely addressable from ground. A mobile train unit provides one active mobile communication gateway for train to ground communication.~~

3.1.28 multicast

transmission of the same message to a group of receivers, identified by their group address

Note 1 to entry: The term "multicast" is used even if the group includes all receivers.

[SOURCE: IEC 60050-811:2017, 811-37-66]

3.1.29 multimedia data

data used for onboard multimedia and telematic services (OMTS), like video/audio streams or file transfer

3.1.30 multiple unit train

~~a train consisting of a set of closed trains, where the composition of the set may change during normal operation~~

train comprising one or more train-units which can be controlled simultaneously from one cab and able to operate at normal speed in either direction without re-marshalling

[SOURCE: IEC 60050-811:2017, 811-02-12]

3.1.31 network

<in a train communication network> set of possibly different communication systems which interchange information in a commonly agreed way

[SOURCE: IEC 60050-811:2017, 811-37-68]

3.1.32 network address

address which identifies a communication device on network layer

[SOURCE: IEC 60050-811:2017, 811-37-69]

3.1.33 network device

component used to set up consist networks and train networks

Note 1 to entry: These components ~~may~~ can be passive components like cables or connectors, active unmanaged components like repeaters, media converters or (unmanaged) switches, or managed active components like gateways, routers and (managed) switches.

[SOURCE: IEC 60050-811:2017, 811-37-70, modified – Note 1 to entry has been modified.]

3.1.34 network layer

layer in the OSI model responsible for routing between different busses

[SOURCE: IEC 60050-811:2017, 811-37-72]

3.1.35 network management

<in a train communication network> operations necessary to remotely configure, monitor, diagnose and maintain the network

[SOURCE: IEC 60050-811:2017, 811-37-73]