



IEC 61375-1

Edition 4.0 2026-03

# INTERNATIONAL STANDARD

---

**Electronic railway equipment - Train communication network (TCN) -  
Part 1: General architecture**

Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2026 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat  
3, rue de Varembé  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search -

[webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

#### IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references .....	8
3 Terms, definitions, abbreviated terms, acronyms, and conventions.....	8
3.1 Terms and definitions.....	8
3.2 Abbreviations and acronyms .....	16
3.3 Conventions.....	17
3.3.1 Base of numeric values .....	17
3.3.2 Naming conventions .....	17
3.3.3 State diagram conventions .....	17
4 Basic architecture.....	17
4.1 General.....	17
4.2 Technology and components .....	18
4.2.1 Technology classes .....	18
4.2.2 Component types.....	18
4.3 Hierarchical structure.....	18
4.3.1 Network levels .....	18
4.3.2 Train backbone level .....	19
4.3.3 Consist network level.....	19
4.3.4 Interface between train backbone and consist network .....	20
4.3.5 End devices connected to train backbone .....	21
4.4 Network configurations .....	21
4.5 Train to ground connection (option) .....	22
5 Train backbone.....	23
5.1 General.....	23
5.2 Train backbone topology.....	23
5.2.1 General .....	23
5.2.2 Train backbone based on bus technology .....	23
5.2.3 Train backbone based on switched technology .....	24
5.2.4 Train Backbone based on wireless technology.....	25
5.3 Train compositions.....	27
5.4 Train backbone node numbering .....	27
5.5 Train directions .....	28
5.5.1 Vehicle .....	28
5.5.2 Consist .....	28
5.5.3 Closed train .....	29
5.5.4 Train.....	29
5.6 Train inauguration.....	31
5.6.1 Objectives .....	31
5.6.2 Node sequence and orientation discovery.....	31
5.6.3 Train network directory .....	31
5.6.4 Train directory .....	31
5.6.5 Train inauguration control.....	34
5.6.6 Node states .....	35
5.6.7 Node roles.....	38

5.6.8	Performance .....	38
5.6.9	Independent consist orientation check (Option) .....	38
6	Consist network .....	39
6.1	General .....	39
6.2	Scope of standardization .....	39
6.3	Consist network topology .....	40
6.3.1	Consist network based on bus technology (MVB, CCN) .....	40
6.3.2	Consist network based on switched technology (ECN) .....	41
6.3.3	Consist network based on wireless technology (WLCN) .....	43
6.3.4	Sub-networks .....	43
6.3.5	Heterogeneous consist network .....	44
6.4	Gateway .....	44
6.4.1	General .....	44
6.4.2	Functional description .....	45
6.4.3	Application layer gateway .....	45
6.4.4	Gateway implemented by a router .....	45
6.4.5	Gateway implemented by a bridge .....	46
7	On-board data communication .....	46
7.1	General .....	46
7.2	Communication patterns .....	46
7.2.1	Purpose .....	46
7.2.2	Definitions .....	47
7.2.3	Push pattern .....	47
7.2.4	Pull pattern .....	48
7.2.5	Subscription pattern .....	50
7.3	Addressing .....	50
7.3.1	General .....	50
7.3.2	Network layer addressing .....	50
7.3.3	Application layer addressing .....	52
7.4	Availability of data communication .....	53
7.5	Data classes .....	53
7.5.1	General .....	53
7.5.2	Service parameters .....	53
7.5.3	TCN data class definition .....	54
7.6	Communication profile .....	55
7.7	Application profile .....	56
8	Cybersecurity .....	56
8.1	General .....	56
8.2	System under consideration .....	56
8.3	Lifecycle .....	57
8.3.1	General .....	57
8.3.2	Legacy systems .....	57
8.3.3	Protocol design .....	57
8.4	Guidelines .....	57
Annex A (informative)	High-level train architecture .....	59
A.1	General .....	59
A.2	Architectural realms .....	59
A.3	On-board network structures .....	61

Bibliography.....	63
Figure 1 – Train backbone and consist network .....	18
Figure 2 – Example of consist with 2 consist networks .....	19
Figure 3 – End device connected to the train backbone (example).....	21
Figure 4 – Communication between train and ground (example) .....	22
Figure 5 – Interfaces between consists .....	23
Figure 6 – Train backbone bus topology .....	24
Figure 7 – Train backbone switched topology (aggregated transmission media).....	24
Figure 8 – Train backbone switched topology (segregated transmission media).....	25
Figure 9 – Wireless train backbone mesh topology .....	25
Figure 10 – Wireless train backbone base station topology .....	26
Figure 11 – Wireless train backbone mesh topology for redundancy .....	26
Figure 12 – Wireless train backbone base station topology for redundancy .....	27
Figure 13 – Directions and orientation in a vehicle .....	28
Figure 14 – Directions and orientations in a consist (example).....	29
Figure 15 – Directions and orientations in a closed train .....	29
Figure 16 – Directions and orientations in train (TCN directions).....	30
Figure 17 – Structure of train directory (example) .....	32
Figure 18 – Train inauguration block diagram .....	36
Figure 19 – Train inauguration state chart.....	37
Figure 20 – Independent orientation check with BEACON telegrams.....	38
Figure 21 – Consist network standard interfaces.....	40
Figure 22 – Consist network (bus technology).....	40
Figure 23 – Consist switches .....	41
Figure 24 – Examples of consist network topologies (switched technology) .....	42
Figure 25 – End device connected to two consist switches .....	42
Figure 26 – Wireless consist network.....	43
Figure 27 – Sub-networks in a consist network .....	44
Figure 28 – Implementation example for two vehicle busses .....	44
Figure 29 – Example of heterogeneous train control network architecture .....	45
Figure 30 – Point to point communication pattern (push).....	47
Figure 31 – Point to multi-point communication pattern (push) .....	48
Figure 32 – Point to point communication pattern (pull).....	49
Figure 33 – Point to multi-point communication pattern (pull) .....	49
Figure 34 – Subscription communication pattern.....	50
Figure A.1 – Example of architectural realm structure .....	60
Figure A.2 – Examples for network segregation of on-board physical networks.....	61
Table 1 – Train composition changes.....	27
Table 2 – Train specific parameters (example).....	33
Table 3 – Consist specific parameters (example).....	33
Table 4 – Vehicle specific parameters (example) .....	33

Table 5 – Device specific parameters (example) .....	34
Table 6 – Point to point (Push).....	48
Table 7 – Point to multi-point (Push) .....	48
Table 8 – Point to point (Pull) .....	49
Table 9 – Point to multi-point (Pull).....	50
Table 10 – Service parameters .....	53
Table 11 – Principal data classes.....	55

# Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**Electronic railway equipment - Train communication network (TCN) -  
Part 1: General architecture**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61375-1 has been prepared by IEC technical committee 9: Electrical equipment and systems for railways. It is an International Standard.

This fourth edition cancels and replaces the third edition published in 2012. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Extension of train backbone topologies: aggregated and segregated topology;
- b) Added independent consist orientation check with segregated train backbone topology;
- c) Introduction of wireless technologies: wireless train backbone and wireless consist network;
- d) Possibility of virtual networks;
- e) Definition of data classes and protocol requirements suitable for the OMTS domain;
- f) New clause about cybersecurity in train communication networks.

The text of this International Standard is based on the following documents:

Draft	Report on voting
9/3252/FDIS	9/3293/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/publications](http://www.iec.ch/publications).

A list of all parts of IEC 61375 series, under the general title *Electronic railway equipment - Train communication network (TCN)*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)

## INTRODUCTION

IEC 61375-1 defines the general architecture of the Train Communication Network (TCN) to achieve compatibility between consist networks and train backbones defined by the IEC 61375 series.

The creation of this fourth edition of the standard has been motivated by advances in technology, namely in the fields of Ethernet communication, wireless communication, and cybersecurity, which made it necessary to adapt or to extend some sections of the TCN general architecture. These changes will then further on be reflected in the detailed technical specifications given in subsequent parts of the IEC 61375 series.

The TCN has a hierarchical structure with two levels of networks, a train backbone and a consist network:

- a) for interconnecting vehicles in closed or open trains, this document specifies train backbones with different characteristics.
- b) for connecting standard on-board equipment, this document specifies consist networks with different characteristics.

The general architecture of the TCN, which is defined in this document, does

- c) establish the rules for interconnecting consist networks with train backbones, as
  - 1) identifying the interfaces;
  - 2) defining the principles of how train topology changes can be discovered;
  - 3) defining the basic communication services provided by train backbones to be used by consist networks;
- d) establish basic rules for the train backbone and for the consist network;
- e) establish rules for commonalities in operation, as:
  - 1) patterns for the communication between users;
  - 2) addressing principles;
  - 3) data classes to be supported;
- f) establish rules to support cybersecurity of the TCN.

## 1 Scope

This part of IEC 61375 applies to the architecture of data communication systems in open trains, i.e. it covers the architecture of a communication system for the data communication between vehicles of the said open trains, the data communication within the vehicles and the data communication from train to the ground.

The applicability of this part of IEC 61375 to the train network technologies allows for interoperability of individual vehicles within open trains in international traffic. The data communication systems inside vehicles are given as recommended solutions to cope with the said TCN. In any case, proof of compatibility between a proposed train backbone and a proposed consist network will have to be brought by the supplier.

This part of IEC 61375 might be additionally applicable to closed trains and multiple unit trains when so agreed between purchaser and supplier.

NOTE 1 For definitions of open trains, multiple unit trains and closed trains, see Clause 3.

NOTE 2 Road vehicles such as buses and trolley buses are not considered in this part of IEC 61375.

## 2 Normative references

There are no normative references in this document.

## 3 Terms, definitions, abbreviated terms, acronyms, and conventions

### 3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

#### 3.1.1

##### **active train backbone node**

train backbone node receiving a sequence number during train inauguration and forwarding user data packets between consist network and train backbone

#### 3.1.2

##### **application layer**

upper layer in the OSI model, interfacing directly to the application

[SOURCE: IEC 60050-811:2017, 811-37-03]

#### 3.1.3

##### **application process**

element within a real open system which performs the information processing for a particular application

[SOURCE: IEC 60050-811:2017, 811-37-05]

#### 3.1.4

##### **bridge**

<in a train communication network> device which stores and forwards frames from one bus to another on the base of their link layer addresses

[SOURCE: IEC 60050-811:2017, 811-37-09]

#### 3.1.5

##### **broadcast**

nearly simultaneous transmission of the same information to several destinations

Note 1 to entry: Broadcast in the TCN is not considered reliable, i.e. some destinations can receive the information and others not.

[SOURCE: IEC 60050-811:2017, 811-37-10]

#### 3.1.6

##### **bus**

<in a train communication network> communication medium which broadcasts the same information to all attached participants at nearly the same time, allowing all devices to obtain the same sight of its state, at least for the purpose of arbitration

#### 3.1.7

##### **closed train**

train composed of one or a set of consists, where the train composition does not change during normal operation

EXAMPLE Metro, suburban train, or high-speed train unit.

Note 1 to entry: Consists are coupled in a workshop to establish a closed train for operation.

[SOURCE: IEC 60050-811:2017, 811-37-17]

#### 3.1.8

##### **communication device**

device connected to the consist network or train backbone with the ability to transport, source or sink data

[SOURCE: IEC 60050-811:2017, 811-37-18]

#### 3.1.9

##### **consist**

single vehicle or a group of vehicles which are not separated during normal operation

Note 1 to entry: A consist can contain no, one or several consist networks.

[SOURCE: IEC 60050-811:2017, 811-37-20]

#### 3.1.10

##### **consist network**

communication network interconnecting communication devices in one consist

Note 1 to entry: Consist networks do not spread beyond consist boundaries.

[SOURCE: IEC 60050-811:2017, 811-37-21]

#### 3.1.11

##### **consist network address**

network address, which does not change after train inauguration and which is used to address communication device in the own consist network

**3.1.12**

**consist sequence number**

sequence number of the consist in the train as obtained during train inauguration

**3.1.13**

**consist switch**

network component used in consist network based on switched technology

[SOURCE: IEC 60050-811:2017, 811-37-22]

**3.1.14**

**cybersecurity**

<in railway application> set of activities and measures taken with the objective to identify, protect against, detect, respond to, and recover from unauthorized access or cyberattack which could lead to an accident, an unsafe situation, or railway application performance degradation

[SOURCE: CLC/TS 50701:2023, 3.1.32]

**3.1.15**

**end device**

unit connected to one consist network or to one set of consist networks prepared for redundancy reasons

[SOURCE: IEC 60050-811:2017, 811-37-33]

**3.1.16**

**end node**

node which terminates the train backbone

[SOURCE: IEC 60050-811:2017, 811-37-34]

**3.1.17**

**essential function**

function or capability that is required to maintain health, safety, the environment and availability for the equipment under control

Note 1 to entry: Essential functions include, but are not limited to, the safety instrumented function (SIF), the control function and the ability of the operator to view and manipulate the equipment under control. The loss of essential functions is commonly termed loss of protection, loss of control and loss of view respectively. In some industries additional functions such as history can be considered essential.

[SOURCE: IEC 62443-4-2:2019, 3.1.20]

**3.1.18**

**function**

<in a train communication network> application process which exchanges messages with another application process

**3.1.19**

**gateway**

<in a train communication network> connection between different busses at the application layer requiring application-dependent data analysis and protocol conversion

**3.1.20**

**group address**

address of a multicast group to which a device belongs

[SOURCE: IEC 60050-811:2017, 811-37-45]

**3.1.21**

**integrity**

<in a train communication network> property of a system to recognize and to reject wrong data in case of malfunction of its parts

**3.1.22**

**intermediate node**

node which establishes continuity between two bus sections connected to it, but does not terminate them

[SOURCE: IEC 60050-811:2017, 811-37-49]

**3.1.23**

**linear topology**

topology where the nodes are connected in series, with two nodes each connected to only one other node and all others each connected to two other nodes (i.e. connected in the shape of a line)

[SOURCE: IEC 60050-811:2017, 811-37-51]

**3.1.24**

**local area network**

<in a train communication network> part of a network characterized by a common medium access and address space

[SOURCE: IEC 60050-811:2017, 811-37-60]

**3.1.25**

**medium access control**

<in a train communication network> sublayer of the link layer, which controls the access to the medium (arbitration, mastership transfer, polling)

**3.1.26**

**medium**

<in a train communication network> physical carrier of the signal: electrical wires, optical fibers, etc.

**3.1.27**

**message**

<in transmission systems> information which is transmitted in one or several packets from a sender to one or more receivers

[SOURCE: IEC 60050-821:2017, 821-11-29]

**3.1.28**

**multicast**

transmission of the same message to a group of receivers, identified by their group address

Note 1 to entry: The term "multicast" is used even if the group includes all receivers.

[SOURCE: IEC 60050-811:2017, 811-37-66]

**3.1.29**

**multimedia data**

data used for onboard multimedia and telematic services (OMTS), like video/audio streams or file transfer

### 3.1.30

#### **multiple unit train**

train comprising one or more train-units which can be controlled simultaneously from one cab and able to operate at normal speed in either direction without re-marshalling

[SOURCE: IEC 60050-811:2017, 811-02-12]

### 3.1.31

#### **network**

<in a train communication network> set of possibly different communication systems which interchange information in a commonly agreed way

[SOURCE: IEC 60050-811:2017, 811-37-68]

### 3.1.32

#### **network address**

address which identifies a communication device on network layer

[SOURCE: IEC 60050-811:2017, 811-37-69]

### 3.1.33

#### **network device**

component used to set up consist networks and train networks

Note 1 to entry: These components can be passive components like cables or connectors, active unmanaged components like repeaters, media converters or (unmanaged) switches, or managed active components like gateways, routers and (managed) switches.

[SOURCE: IEC 60050-811:2017, 811-37-70, modified – Note 1 to entry has been modified.]

### 3.1.34

#### **network layer**

layer in the OSI model responsible for routing between different busses

[SOURCE: IEC 60050-811:2017, 811-37-72]

### 3.1.35

#### **network management**

<in a train communication network> operations necessary to remotely configure, monitor, diagnose and maintain the network

[SOURCE: IEC 60050-811:2017, 811-37-73]

### 3.1.36

#### **octet**

byte

ordered set of eight binary digits, operated on as an entity

[SOURCE: IEC 60050-171:2019, 171-02-12, modified – removal of Note to entry.]

### 3.1.37

#### **open train**

train composed of one or a set of consists, where the configuration can change during operation

EXAMPLE Locomotive-hauled international UIC (International Union of Railways, the international railways operators association) trains.

[SOURCE: IEC 60050-811:2017, 811-37-79]

**3.1.38**

**operator**

enterprise or organization which is operating trains

**3.1.39**

**operational data**

data critical for train operation (TCMS), like propulsion control, brake control, doors control, lighting control or heating, ventilation, and air conditioning control

**3.1.40**

**packet**

<in a train communication network> unit of a message (information, acknowledgement, or control) transmitted by protocols on network or transport layer

**3.1.41**

**realm**

logical concept structuring train functions along coherent boundaries

**3.1.42**

**receiver**

<in a train communication network> electronic device which can receive signals from the physical medium

**3.1.43**

**repeater**

< in a train communication network> connection at the physical layer between bus segments, providing an extension of the bus beyond the limits permitted by passive means

Note 1 to entry: The connected segments operate at the same speed and with the same protocol. The delay introduced by a repeater is in the order of one bit duration.

[SOURCE: IEC 60050-811:2017, 811-37-90]

**3.1.44**

**ring topology**

active network where each node is connected in series to two other nodes

Note 1 to entry: Ring can also be referred to as loop.

[SOURCE: IEC 60050-811:2017, 811-37-91]

**3.1.45**

**router**

<in a train communication network> connection between two busses at the network layer, which forwards datagrams from one bus to another on the base of their network address

**3.1.46**

**safety integrity**

ability of a safety-related system to achieve its required safety functions under all the stated conditions within a stated operational environment and within a stated duration

[SOURCE: IEC 60050-821:2017, 821-12-54]

**3.1.47**

**service**

<in a train communication network> capabilities and features of a sub-system (e.g. a communication layer) provided to a user

[SOURCE: IEC 60050-811:2017, 811-37-93]