

INTERNATIONAL STANDARD

**High frequency inductive components -
Part 1: Fixed surface mount inductors for use in electronic and
telecommunication equipment**

get full document from standards.iteh.ai



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2026 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	3
1 Scope	5
2 Normative references	5
3 Terms and definitions	6
4 Designation	6
5 Shape	7
6 Dimensions	9
6.1 Shape D	9
6.2 Shape K	11
6.3 Tolerance for outline dimensions	11
7 Ratings and characteristics	11
7.1 Nominal inductance or impedance	11
7.2 Tolerance for nominal inductance or impedance	12
7.3 Operating temperature range	12
8 Marking	13
9 Direction marking or shape of polarity	13
10 Tests and performance requirements	14
10.1 Standard atmospheric conditions for testing	14
10.1.1 Standard atmospheric conditions for measurements and tests	14
10.1.2 Referee conditions	14
10.2 Visual examination and check of dimensions	14
10.2.1 Visual examination	14
10.2.2 Dimensions	14
10.3 Electrical performance tests	15
10.3.1 Inductance	15
10.3.2 Q	18
10.3.3 Impedance	22
10.3.4 Self-resonant frequency	23
10.3.5 DC resistance	24
10.3.6 Rated current	25
10.4 Mechanical performance tests	25
10.4.1 General	25
10.4.2 Mounting to substrate	25
10.4.3 Body strength test	26
10.4.4 Robustness of terminations (electrodes)	26
10.4.5 Solderability	26
10.4.6 Resistance to soldering heat	27
10.4.7 Resistance to dissolution of metallization	27
10.4.8 Vibration	27
10.4.9 Resistance to shock	28
10.5 Environmental and climatic tests	28
10.5.1 General	28
10.5.2 Cold	28
10.5.3 Dry heat	29
10.5.4 Change of temperature	30
10.5.5 Damp heat (steady state)	30

10.5.6 Component solvent resistance	31
Bibliography	32
Figure 1 – Shapes of inductor and ferrite beads (examples).....	8
Figure 2 – Example of circuit for measurement by the bridge method.....	15
Figure 3 – Example of circuit for measurement by the vector voltage/current method.....	16
Figure 4 – Example of circuit for measurement by the automatic balancing bridge method	17
Figure 5 – Example of circuit for measurement by the series resonance method	19
Figure 6 – Example of circuit for measurement by the parallel resonance method	20
Figure 7 – Tuning characteristics of inductor.....	21
Figure 8 – Example of circuit for measurement by the minimum output method	23
Figure 9 – Example of measuring circuit for DC resistance	24
Table 1 – Letter code for inductance value.....	7
Table 2 – Dimensions for shape D	9
Table 3 – Dimensions of height for shape D greater than 1,00 mm (R 20 series).....	10
Table 4 – Dimensions of height for shape D less than 1,00 mm	10
Table 5 – Dimensions for shape K	11
Table 6 – Tolerance for outline dimension and height	11
Table 7 – E 24 series for nominal inductance or impedance.....	12
Table 8 – Tolerance for nominal inductance or impedance.....	12
Table 9 – Temperatures to be selected for operating temperature ranges	12
Table 10 – User reference / Examples of application and operating temperature range.....	13
Table 11 – Electrical performance.....	27
Table 12 – Combined test conditions for cold.....	28
Table 13 – Combined test conditions for dry heat	29
Table 14 – Test conditions for change of temperature	30
Table 15 – Test conditions for damp heat (steady state)	31

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**High frequency inductive components -
Part 1: Fixed surface mount inductors for use in electronic
and telecommunication equipment**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of a patent. IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of a patent, which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch> and/or www.iso.org/patents. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62674-1 has been prepared by IEC technical committee 51: Magnetic components, ferrite and magnetic powder materials. It is an International Standard.

This second edition cancels and replaces the first edition published in 2012. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) addition of dimensions for shape D;
- b) addition of upper temperature for operating temperature ranges.

The text of this International Standard is based on the following documents:

Draft	Report on voting
51/1623/FDIS	51/1628/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 62674 series, published under the general title *High frequency inductive components*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

Sample Document

get full document from standards.iteh.ai

1 Scope

This part of IEC 62674 applies to fixed surface mount inductors and fixed surface mount ferrite beads.

The object of this document is to define the terms necessary to describe the inductors covered by this document, provide recommendations for preferred characteristics, recommended performance, test methods and general guidance.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-1:2013, *Environmental testing - Part 1: General and guidance*

IEC 60068-2-1, *Environmental testing - Part 2-1: Tests - Test A: Cold*

IEC 60068-2-2, *Environmental testing - Part 2-2: Tests - Test B: Dry heat*

IEC 60068-2-14, *Environmental testing - Part 2-14: Tests - Test N: Change of temperature*

IEC 60068-2-45:1980, *Basic environmental testing procedures - Part 2-45: Tests - Test XA and guidance: Immersion in cleaning solvents*

IEC 60068-2-45:1980/AMD1:1993

IEC 60068-2-58:2015, *Environmental testing - Part 2-58: Tests - Test Td: Test methods for solderability, resistance to dissolution of metallization and to soldering heat of surface mounting devices (SMD)*

IEC 60068-2-58:2015/AMD1:2017

IEC 60068-2-78, *Environmental testing - Part 2-78: Tests - Test Cab: Damp heat, steady state*

IEC 62024-1:2024, *High frequency inductive components - Electrical characteristics and measuring methods - Part 1: Nanohenry range chip inductor*

IEC 62024-2:2024, *High frequency inductive components - Electrical characteristics and measuring methods - Part 2: Rated current of inductors for DC-to-DC converters*

IEC 62025-2:2019, *High frequency inductive components - Non-electrical characteristics and measuring methods - Part 2: Test methods for non-electrical characteristics*

IEC 62211:2017, *Inductive components - Reliability management*

ISO 3, *Preferred numbers - Series of preferred numbers*

ISO 3611:2023, *Geometrical product specifications (GPS) - Dimensional measuring equipment - Design and metrological characteristics of micrometers for external measurements*

ISO 13385-1:2019, *Geometrical product specifications (GPS) - Dimensional measuring equipment - Part 1: Design and metrological characteristics of callipers*

ISO 13385-2:2020, *Geometrical product specifications (GPS) - Dimensional measuring equipment - Part 2: Design and metrological characteristics of calliper depth gauges*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1

rated current

maximum current which can be loaded continuously by inductors at the rated ambient temperature

Note 1 to entry: A DC saturation limited current value or a temperature rise limited current value, whichever is less, has been adopted as the rated current (see IEC 62024-2:2024, Clause 7).

3.2

operating temperature range

range of ambient temperatures for which the inductor has been designed to operate continuously

Note 1 to entry: Unless otherwise specified in the detail specification, the operating temperature is ambient temperature plus temperature rise of components.

4 Designation

It is recommended to express the designation of the fixed surface mount inductors by the following 12-digit format. In the case of another format, designation shall be specified in the detail specifications.

The designation of ferrite beads shall be specified in the detail specifications.

□□□

a)

□□□□

b)

□

c)

□□□

d)

□

e)

a) Identification of the type of inductor

Fixed surface mount inductors shall be identified by the three alphabetic characters "LCL".

b) Indication of outline dimensions

The outline dimensions of the surface mount inductor shall be indicated by a four-digit number based on two significant figures for each dimension of L and W (or H). As for the dimensions of shape D, the first two digits indicate the longer side dimension L , and the last two digits indicate the shorter side dimension W , as shown in Figure 1. As for the dimensions of shape K, the first two digits indicate the outline dimension L , and the last two digits indicate the height dimension H .

c) Indication of shape

A single alphabetic character as given in Figure 1 indicates the shape for fixed surface mount inductors.

The shape codes are classified by the base shape of inductors.

D: rectangular

K: square

d) Indication of nominal inductance

Three alphanumeric characters specified in IEC 61605:2016, Table 3, indicate the nominal inductance value (see Table 1). The use of alphanumeric characters other than those specified in IEC 61605 shall be subject to agreement between the parties concerned.

Table 1 – Letter code for inductance value

Inductance values		Digit and letter code
0,1	nH	N10
0,47	nH	N47
1	nH	1N0
4,7	nH	4N7
10	nH	10N
47	nH	47N
0,1	µH	R10
0,47	µH	R47
1	µH	1R0
4,7	µH	4R7
10	µH	100
47	µH	470
100	µH	101
470	µH	471
1	mH	102
4,7	mH	472
10	mH	103
47	mH	473
100	mH	104
470	mH	474
1	H	105
4,7	H	475
10	H	106
47	H	476

e) Indication of tolerance for inductance

Single alphabetic characters specified in Table 8 indicate the tolerance for the inductance value.

5 Shape

The shapes of fixed surface mount inductors and ferrite beads are classified as shown in Figure 1.