

INTERNATIONAL STANDARD

**Universal Serial Bus interfaces for data and power -
Part 1-3: Common components - USB Type-C® cable and connector
specification**

get full document from standards.iteh.ai



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2026 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembeé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**Universal Serial Bus interfaces for data and power -
Part 1-3: Common components - USB Type-C® cable and connector
specification**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62680-1-3 has been prepared by technical area 18: Multimedia home systems and applications for end-user networks, of IEC technical committee 100: Audio, video and multimedia systems and equipment. It is an International Standard.

The text of this standard was prepared by the USB Implementers Forum (USB-IF). The structure and editorial rules used in this publication reflect the practice of the organization which submitted it.

The text of this International Standard is based on the following documents:

Draft	Report on voting
100/4332/CDV	100/4381/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

A list of all parts in the IEC 62680 series, published under the general title *Universal serial bus interfaces for data and power*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

Sample Document

get full document from standards.iteh.ai

Universal Serial Bus Type-C Cable and Connector Specification

Sample Document

Release 2.4
October 2024

get full document from standards.iteh.ai

Copyright © 2014-2024, USB 3.0 Promoter Group:

**Apple Inc., HP Inc., Intel Corporation, Microsoft Corporation,
Renesas, STMicroelectronics, and Texas Instruments**

All rights reserved.

NOTE: Adopters may only use the USB Type-C® cable and connector to implement USB or third-party functionality as expressly described in this Specification; all other uses are prohibited.

LIMITED COPYRIGHT LICENSE: The USB 3.0 Promoters grant a conditional copyright license under the copyrights embodied in the USB Type-C Cable and Connector Specification to use and reproduce the Specification for the sole purpose of, and solely to the extent necessary for, evaluating whether to implement the Specification in products that would comply with the specification. Without limiting the foregoing, use of the Specification for the purpose of filing or modifying any patent application to target the Specification or USB compliant products is not authorized. Except for this express copyright license, no other rights or licenses are granted, including without limitation any patent licenses. In order to obtain any additional intellectual property licenses or licensing commitments associated with the Specification a party must execute the USB 3.0 Adopters Agreement. NOTE: By using the Specification, you accept these license terms on your own behalf and, in the case where you are doing this as an employee, on behalf of your employer.

Sample Document

INTELLECTUAL PROPERTY DISCLAIMER

THIS SPECIFICATION IS PROVIDED TO YOU "AS IS" WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE AUTHORS OF THIS SPECIFICATION DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OF INFORMATION IN THIS SPECIFICATION. THE PROVISION OF THIS SPECIFICATION TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS.

All implementation examples and reference designs contained within this Specification are included as part of the limited patent license for those companies that execute the USB 3.0 Adopters Agreement.

USB Type-C®, USB-C® and USB4® are trademarks of the Universal Serial Bus Implementers Forum (USB-IF). DisplayPort™ is a trademark of VESA. All product names are trademarks, registered trademarks, or service marks of their respective owners.

Thunderbolt™ is a trademark of Intel Corporation. You may only use the Thunderbolt™ trademark or logo in conjunction with products designed to this specification that complete proper certification and executing a Thunderbolt™ trademark license – see <https://www.usb.org/compliance> for further information.

Contents

Specification Editor	20
Specification Work Group Contributors.....	20
Pre-Release Draft Industry Reviewing Companies That Provided Feedback.....	28
Revision History.....	29
1 Introduction.....	30
1.1 Purpose	30
1.2 Scope	30
1.3 Related Documents	30
1.4 Conventions.....	31
1.4.1 Precedence	31
1.4.2 Keywords	31
1.4.3 Numbering.....	32
1.5 Terms and Abbreviations	32
2 Overview	38
2.1 Introduction	38
2.2 USB Type-C Receptacles, Plugs and Cables	39
2.3 Configuration Process.....	40
2.3.1 Source-to-Sink Attach/Detach Detection.....	41
2.3.2 Plug Orientation/Cable Twist Detection.....	41
2.3.3 Initial Power (Source-to-Sink) Detection and Establishing the Data (Host-to-Device) Relationship 41	
2.3.4 USB Type-C VBUS Current Detection and Usage.....	42
2.3.5 USB PD Communications.....	42
2.3.6 Functional Extensions	43
2.4 VBUS.....	43
2.5 VCONN.....	43
2.6 Hubs.....	44
3 Mechanical.....	45
3.1 Overview.....	45
3.1.1 Compliant Connectors.....	45
3.1.2 Compliant Cable Assemblies	45
3.1.3 Compliant USB Type-C to Legacy Cable Assemblies.....	46
3.1.4 Compliant USB Type-C to Legacy Adapter Assemblies.....	47
3.2 USB Type-C Connector Mating Interfaces.....	47
3.2.1 Interface Definition.....	47
3.2.2 Reference Designs	71

3.2.3	Pin Assignments and Descriptions	78
3.3	Cable Construction and Wire Assignments	79
3.3.1	Cable Construction (<i>Informative</i>).....	79
3.3.2	Wire Assignments	81
3.3.3	Wire Gauges and Cable Diameters (<i>Informative</i>).....	82
3.4	Standard USB Type-C Cable Assemblies.....	84
3.4.1	USB Full-Featured Type-C Cable Assembly.....	84
3.4.2	USB 2.0 Type-C Cable Assembly	86
3.4.3	USB Type-C Captive Cable Assembly	86
3.4.4	USB Type-C Thumb Drive Assembly	87
3.5	Legacy Cable Assemblies.....	87
3.5.1	USB Type-C to USB 3.1 Standard-A Cable Assembly	88
3.5.2	USB Type-C to USB 2.0 Standard-A Cable Assembly	89
3.5.3	USB Type-C to USB 3.1 Standard-B Cable Assembly	90
3.5.4	USB Type-C to USB 2.0 Standard-B Cable Assembly	91
3.5.5	USB Type-C to USB 2.0 Mini-B Cable Assembly.....	92
3.5.6	USB Type-C to USB 3.1 Micro-B Cable Assembly.....	93
3.5.7	USB Type-C to USB 2.0 Micro-B Cable Assembly.....	94
3.6	Legacy Adapter Assemblies.....	94
3.6.1	USB Type-C to USB 3.1 Standard-A Receptacle Adapter Assembly	94
3.6.2	USB Type-C to USB 2.0 Micro-B Receptacle Adapter Assembly	96
3.7	Electrical Characteristics.....	96
3.7.1	Raw Cable (<i>Informative</i>).....	97
3.7.2	USB Type-C to USB Type-C Passive Cable Assemblies	98
3.7.3	Mated Connector (<i>Informative – USB 3.2 Gen2 and USB4 Gen2</i>).....	120
3.7.4	Receptacle Connector SI Requirements and Testing (<i>Normative – USB4 Gen3/Gen4</i>).....	124
3.7.5	USB Type-C to USB Legacy Cable Assemblies (<i>Normative</i>)	126
3.7.6	USB Type-C to USB Legacy Adapter Assemblies (<i>Normative</i>)	130
3.7.7	Shielding Effectiveness Requirements (<i>Normative</i>)	133
3.7.8	DC Electrical Requirements (<i>Normative</i>).....	135
3.8	Mechanical and Environmental Requirements (<i>Normative</i>).....	138
3.8.1	Mechanical Requirements	138
3.8.2	Environmental Requirements.....	143
3.9	Docking Applications (<i>Informative</i>)	144
3.10	Implementation Notes and Design Guides	145
3.10.1	EMC Management (<i>Informative</i>).....	145

3.10.2	Stacked and Side-by-Side Connector Physical Spacing (<i>Informative</i>)	148
3.10.3	Cable Mating Considerations (<i>Informative</i>)	148
3.11	Extended Power Range (EPR) Cables	150
3.11.1	Electrical Requirements.....	150
3.11.2	EPR Cable Identification Requirements.....	150
4	Functional	151
4.1	Signal Summary.....	151
4.2	Signal Pin Descriptions	151
4.2.1	USB 3.2/USB4 Pins	151
4.2.2	USB 2.0 Pins.....	152
4.2.3	Auxiliary Signal Pins	152
4.2.4	Power and Ground Pins	152
4.2.5	Configuration Pins	152
4.3	Sideband Use (SBU).....	152
4.4	Power and Ground.....	153
4.4.1	IR Drop.....	153
4.4.2	VBUS	154
4.4.3	VCONN.....	155
4.5	Configuration Channel (CC)	160
4.5.1	Architectural Overview.....	160
4.5.2	CC Functional and Behavioral Requirements	172
4.5.3	USB Port Interoperability Behavior	208
4.6	Power	226
4.6.1	Power Requirements during USB Suspend.....	227
4.6.2	VBUS Power Provided Over a USB Type-C Cable	228
4.7	USB Hubs	233
4.8	Power Sourcing and Charging.....	234
4.8.1	DFP as a Power Source.....	234
4.8.2	Non-USB Charging Methods	236
4.8.3	Sinking Host.....	237
4.8.4	Sourcing Device.....	237
4.8.5	Charging a System with a Dead Battery	237
4.8.6	USB Type-C Multi-Port Chargers	237
4.9	Electronically Marked Cables	241
4.9.1	Parameter Values.....	242
4.9.2	Active Cables.....	242

4.10	VCONN-Powered Accessories (VPAs) and VCONN-Powered USB Devices (VPDs).....	243
4.10.1	VCONN-Powered Accessories (VPAs).....	243
4.10.2	VCONN-Powered Devices (VPDs).....	243
4.11	Parameter Values.....	245
4.11.1	Termination Parameters.....	245
4.11.2	Timing Parameters.....	247
4.11.3	Voltage Parameters.....	251
5	USB4 Discovery and Entry.....	258
5.1	Overview of the Discovery and Entry Process.....	258
5.2	USB4 Functional Requirements.....	259
5.2.1	USB4 Host Functional Requirements.....	259
5.2.2	USB Device Functional Requirements.....	259
5.2.3	USB4 Alternate Mode Support.....	259
5.3	USB4 Power Requirements.....	260
5.3.1	Source Power Requirements.....	260
5.3.2	Sink Power Requirements.....	260
5.3.3	Device Power Management Requirements.....	260
5.4	USB4 Discovery and Entry Flow Requirements.....	261
5.4.1	USB Type-C Initial Connection.....	261
5.4.2	USB Power Delivery Contract.....	261
5.4.3	USB4 Discovery and Entry Flow.....	261
5.4.4	USB4 Post-Entry Operation.....	267
5.5	USB4 Hub Connection Requirements.....	267
5.5.1	USB4 Hub Port Initial Connection Requirements.....	267
5.5.2	USB4 Hub UFP and Host Capabilities Discovery.....	267
5.5.3	Hub DFP Connection Requirements.....	268
5.5.4	Hub Ports Connection Behavior Flow Examples.....	269
5.5.5	Connecting to Downstream USB4 Hubs.....	275
5.5.6	Fallback Functional Requirements for USB4 Hubs.....	275
5.6	USB4 Device Connection Requirements.....	276
5.6.1	Fallback Mapping of USB4 Peripheral Functions of USB Device Class Types.....	276
5.7	Parameter Values.....	277
5.7.1	Timing Parameters.....	277
6	Active Cables.....	278
6.1	General Specifications for All Active Cables.....	278
6.1.1	Discovering Active Cable Characteristics.....	278

6.1.2	Electrical Requirements	280
6.1.3	Mechanical Requirements	312
6.2	Additional Specifications for Copper and Hybrid-Optical Active Cables.....	313
6.2.1	Active Cable Block Diagram	314
6.2.2	<i>USB4</i> Asymmetric Mode Support	314
6.2.3	Active Cable <i>USB PD</i> Requirements.....	314
6.2.4	Active Cable Behaviors in Response to <i>USB PD</i> Events.....	314
6.2.5	Active Cable Power Requirements.....	315
6.3	Additional Specifications for Optically Isolated Active Cables	315
6.3.1	OIAC Block Diagrams	316
6.3.2	OIAC Limitations and General Requirements	318
6.3.3	OIAC Cable Power Requirements	319
6.3.4	OIAC <i>USB PD</i> Requirements.....	319
6.3.5	OIAC Connection Flow and State Diagrams	329
6.3.6	Additional Electrical Requirements for OIAC	348
6.3.7	Additional Mechanical Requirements for OIAC	351
A	Liquid Corrosion Mitigation Mode.....	352
A.1	Overview.....	352
A.2	Detail	352
A.3	Liquid Detection Methods.....	354
A.3.1	Liquid Measurement Method	354
A.3.2	Pulsed Measurement Method.....	354
A.3.3	Impedance Measurement Method.....	355
A.4	Liquid Detection Pins in the Connector	358
B	Debug Accessory Mode	361
B.1	Overview.....	361
B.2	Functional	361
B.2.1	Signal Summary	361
B.2.2	Port Interoperability.....	362
B.2.3	Debug Accessory Mode Entry.....	362
B.2.4	Connection State Diagrams.....	362
B.2.5	DTS Port Interoperability Behaviors.....	371
B.2.6	Orientation Detection.....	380
B.3	Security/Privacy Requirements.....	380
C	USB Type-C Digital Audio.....	381
C.1	Overview.....	381

C.2	USB Type-C Digital Audio Specifications.....	381
D	Thermal Design Considerations for Active Cables.....	382
D.1	Introduction	382
D.2	Model.....	382
D.2.1	Assumptions.....	382
D.2.2	Model Architecture.....	383
D.2.3	Heat Sources.....	383
D.2.4	Heat Flow.....	384
D.3	USB 3.2 Single-Lane Active Cable.....	385
D.3.1	USB 3.2 Single-Lane Active Cable Design Considerations	385
D.4	Dual-Lane Active Cables.....	388
D.4.1	USB 3.2 Dual-Lane Active Cable Design Considerations	388
D.4.2	USB 3.2 Dual-Lane Active Cable in a Multiple Port Configuration.....	390
D.5	USB 3.2 Host and Device Design Considerations	391
D.5.1	Heat Spreading or Heat Sinking from Host or Device.....	391
D.5.2	Motherboard Temperature Control	392
D.5.3	Wider Port Spacing for Multi-Port Applications	392
D.5.4	Power Policies	392
E	Alternate Modes.....	393
E.1	Alternate Mode Architecture	393
E.2	Alternate Mode Requirements.....	393
E.2.1	Alternate Mode Pin Reassignment.....	394
E.2.2	Alternate Mode Electrical Requirements.....	394
E.3	Parameter Values	397
E.4	Example Alternate Mode – USB DisplayPort™ Dock	398
E.4.1	USB DisplayPort™ Dock Example.....	398
E.4.2	Functional Overview.....	398
E.4.3	Operational Summary	399
E.5	Example Alternate Mode Entry Flow with Cable Warnings.....	400
E.5.1	Operational Summary	401
F	Thunderbolt™ 3 Compatibility Discovery and Entry.....	402
F.1	TBT3 Compatibility Mode Functional Requirements	402
F.1.1	TBT3-Compatible Power Requirements.....	402
F.1.2	TBT3-Compatible Host Requirements	402
F.1.3	TBT3-Compatible Device Upstream Requirements.....	402
F.1.4	TBT3-Compatible Device Downstream Requirements.....	402

F.1.5	<i>TBT3</i> -Compatible Self-Powered Device Without Predefined Upstream Port Rules	403
F.1.6	<i>TBT3</i> -Compatible Devices with a Captive Cable	403
F.2	<i>TBT3</i> Discovery and Entry Flow.....	403
F.2.1	<i>TBT3</i> Passive Cable Discover Identity Responses	404
F.2.2	<i>TBT3</i> Active Cable Discover Identity Responses.....	407
F.2.3	<i>TBT3</i> Device Discover Identity Responses	410
F.2.4	<i>TBT3</i> Discover SVID Responses.....	411
F.2.5	<i>TBT3</i> Device Discover Mode Responses	412
F.2.6	<i>TBT3</i> Cable Discover Mode Responses	413
F.2.7	<i>TBT3</i> Cable Enter Mode Command.....	414
F.2.8	<i>TBT3</i> Device Enter Mode Command	415
F.2.9	<i>TBT3</i> Cable Functional Difference Summary	417
G	Extracting Pulse Response from Sampled Data and Calculating Non-Linearity Noise.....	418
H	<i>USB PD</i> High-Voltage Design Considerations	420
H.1	Potential for Arcing Damage During Cable Withdrawal.....	420
H.2	Arcing During <i>USB Type-C</i> Cable Withdrawal	420
H.3	Mitigating Arcing Damage During Cable Withdrawal Due to Sink Discharge.....	422
H.3.1	Limiting Sink Discharge Rate.....	423
H.3.2	Load Removal	424
H.3.3	Limiting Source Current Capability	427
I	<i>USB PD</i> Encoding Guidelines for <i>USB Type-C</i> Product Types	428
I.1	<i>USB Type-C</i> Product Type Definitions and <i>USB PD</i> Encodings.....	428
I.2	<i>USB PD</i> Encoding Guidelines Tables.....	429
I.3	Detailed Examples.....	436
I.3.1	<i>USB 3.2</i> Host – no DC – Power Consumer : DRP (Source or Sink) / Not DRD (DFP).....	436
I.3.2	<i>USB 3.2</i> Peripheral – Power Provider : DRP (Source or Sink) / Not DRD (UFP).....	436
I.3.3	<i>USB4</i> Host – Power Consumer : DRP (Source or Sink) / Not DRD (DFP)	437
I.3.4	<i>USB4</i> Host – <i>USB4</i> DC – Partial or no <i>USB</i> Equivalent : DRP (Source or Sink) / DRD.....	437
I.3.5	<i>USB4</i> Peripheral : UFP (Sink)	438
I.3.6	<i>USB4</i> Dock (Upstream) – Power Provider : DRP (Source or Sink) / Not DRD (UFP)	439
I.3.7	<i>USB4</i> Hub (Downstream) – DFP (Source)	439
J	Design Assumptions for the <i>USB4</i> Gen4 LRD Cable Specification	441

Figures

Figure 2-1	<i>USB Type-C</i> Receptacle Interface (Front View).....	38
Figure 2-2	<i>USB Full-Featured Type-C</i> Plug Interface (Front View).....	39
Figure 3-1	<i>USB Type-C</i> Receptacle Interface Dimensions.....	50
Figure 3-2	Reference Design <i>USB Type-C</i> Plug External EMC Spring Contact Zones.....	54

Figure 3-3 USB Full-Featured Type-C Plug Interface Dimensions.....	55
Figure 3-4 Right-Angle USB Type-C Plug Dimensional Requirements.....	58
Figure 3-5 Reference Footprint for a USB Type-C Vertical Mount Receptacle (<i>Informative</i>).....	59
Figure 3-6 Reference Footprint for a USB Type-C Dual-Row SMT Right-Angle Receptacle (<i>Informative</i>).....	60
Figure 3-7 Reference Footprint for a USB Type-C Hybrid Right-Angle Receptacle (<i>Informative</i>).....	61
Figure 3-8 Reference Footprint for a USB Type-C Mid-Mount Dual-Row SMT Receptacle (<i>Informative</i>).....	62
Figure 3-9 Reference Footprint for a USB Type-C Mid-Mount Hybrid Receptacle (<i>Informative</i>).....	63
Figure 3-10 Reference Footprint for a <i>USB 2.0</i> Type-C Through Hole Right Angle Receptacle (<i>Informative</i>).....	64
Figure 3-11 Reference Footprint for a <i>USB 2.0</i> Type-C Single Row Right Angle Receptacle (<i>Informative</i>).....	65
Figure 3-12 <i>USB 2.0</i> Type-C Plug Interface Dimensions.....	67
Figure 3-13 USB Type-C Plug EMC Shielding Spring Tip Requirements.....	70
Figure 3-14 Reference Design of Receptacle Mid-Plate.....	71
Figure 3-15 Reference Design of Retention Latch.....	72
Figure 3-16 Illustration of the Latch Soldered to the Paddle Card Ground.....	72
Figure 3-17 Reference Design of the USB Full-Featured Type-C Plug Internal EMC Spring.....	73
Figure 3-18 Reference Design of the <i>USB 2.0</i> Type-C Plug Internal EMC Spring.....	74
Figure 3-19 Reference Design of Internal EMC Pad.....	75
Figure 3-20 Reference Design of a USB Type-C Receptacle with External EMC Springs.....	76
Figure 3-21 Reference Design of a USB Full-Featured Type-C Plug Paddle Card.....	77
Figure 3-22 Illustration of a USB Full-Featured Type-C Cable Cross Section, a Coaxial Wire Example with VCONN.....	80
Figure 3-23 Illustration of a USB Full-Featured Type-C Cable Cross Section, a Coaxial Wire Example without VCONN.....	80
Figure 3-24 USB Full-Featured Type-C Standard Cable Assembly.....	84
Figure 3-25 USB Type-C to <i>USB 3.1</i> Standard-A Cable Assembly.....	88
Figure 3-26 USB Type-C to <i>USB 2.0</i> Standard-A Cable Assembly.....	89
Figure 3-27 USB Type-C to <i>USB 3.1</i> Standard-B Cable Assembly.....	90
Figure 3-28 USB Type-C to <i>USB 2.0</i> Standard-B Cable Assembly.....	91
Figure 3-29 USB Type-C to <i>USB 2.0</i> Mini-B Cable Assembly.....	92
Figure 3-30 USB Type-C to <i>USB 3.1</i> Micro-B Cable Assembly.....	93
Figure 3-31 USB Type-C to <i>USB 2.0</i> Micro-B Cable Assembly.....	94
Figure 3-32 USB Type-C to <i>USB 3.1</i> Standard-A Receptacle Adapter Assembly.....	95
Figure 3-33 USB Type-C to <i>USB 2.0</i> Micro-B Receptacle Adapter Assembly.....	96
Figure 3-34 Illustration of Test Points for a Mated Cable Assembly.....	98
Figure 3-35 Recommended Differential Insertion Loss Requirement (<i>USB 3.2</i> Gen2 and <i>USB4</i> Gen2).....	99
Figure 3-36 Recommended Differential Return Loss Requirement.....	99
Figure 3-37 Recommended Differential Crosstalk Requirement.....	100
Figure 3-38 Recommended Differential Near-End and Far-End Crosstalk Requirement between USB D+/D- Pair and TX/RX Pair.....	101
Figure 3-39 Recommended Differential Insertion Loss Requirement (<i>USB4</i> Gen3/Gen4).....	101
Figure 3-40 Illustration of Insertion Loss Fit at Nyquist Frequency.....	102
Figure 3-41 Input Pulse Spectrum.....	103
Figure 3-42 IMR Limit as Function of ILfitatNq.....	104
Figure 3-43 IRL Limit as Function of ILfitatNq.....	106
Figure 3-44 Differential-to-Common Mode Conversion Requirement.....	106
Figure 3-45 IMR Limit as Function of ILfit at 10 GHz (<i>USB4</i> Gen3/Gen4).....	110
Figure 3-46 Definition of Port, Victim, and Aggressor.....	111
Figure 3-47 IXT_DP and IXT_USB Limit as Function of ILfit at 10 GHz (<i>USB4</i> Gen3/Gen4).....	111
Figure 3-48 IRL Limit as Function of ILfit at 10 GHz (<i>USB4</i> Gen3/Gen4).....	112
Figure 3-49 Differential-to-Common Mode Conversion Requirement (<i>USB4</i> Gen3/Gen4).....	112
Figure 3-50 Cable Assembly in System.....	113

Figure 3-51 Requirement for Differential Coupling between CC and D+/D-	116
Figure 3-52 Requirement for Single-Ended Coupling between CC and D- in <i>USB 2.0</i> Type-C Cables.....	116
Figure 3-53 Requirement for Single-Ended Coupling between CC and D- in USB Full-Featured Type-C Cables	117
Figure 3-54 Requirement for Differential Coupling between VBUS and D+/D-	117
Figure 3-55 Requirement for Single-Ended Coupling between SBU_A and SBU_B.....	118
Figure 3-56 Requirement for Single-Ended Coupling between SBU_A/SBU_B and CC.....	119
Figure 3-57 Requirement for Coupling between SBU_A and differential D+/D-, and SBU_B and differential D+/D-	119
Figure 3-58 Illustration of USB Type-C Mated Connector.....	120
Figure 3-59 Recommended Impedance Limits of a USB Type-C Mated Connector.....	121
Figure 3-60 Recommended Ground Void Dimensions for USB Type-C Receptacle	121
Figure 3-61 Recommended Differential Near-End and Far-End Crosstalk Limits between D+/D- Pair and TX/RX Pairs.....	123
Figure 3-62 Recommended Limits for Differential-to-Common-Mode Conversion.....	124
Figure 3-63 IMR Limit as Function of ILfitatNq for USB Type-C to Legacy Cable Assembly	129
Figure 3-64 IRL Limit as Function of ILfitatNq for USB Type-C to Legacy Cable Assembly.....	129
Figure 3-65 Cable Assembly Shielding Effectiveness Testing.....	133
Figure 3-66 Shielding Effectiveness Pass/Fail Criteria.....	134
Figure 3-67 LLCR Measurement Diagram.....	135
Figure 3-68 Temperature Measurement Point.....	136
Figure 3-69 Example Current Rating Test Fixture Trace Configuration	137
Figure 3-70 Example of 4-Axis Continuity Test Fixture	139
Figure 3-71 Torque Force Application Distance for Right-Angle Plugs.....	141
Figure 3-71 Example Wrenching Strength Test Fixture for Plugs without Overmold.....	142
Figure 3-72 Reference Wrenching Strength Continuity Test Fixture.....	142
Figure 3-73 Example of Wrenching Strength Test Mechanical Failure Point.....	143
Figure 3-74 Wrenching Strength Test with Cable in Fixture.....	143
Figure 3-75 USB Type-C Cable Receptacle Flange Example.....	145
Figure 3-76 EMC Guidelines for Side Latch and Mid-Plate.....	146
Figure 3-77 EMC Finger Connections to Plug Shell.....	147
Figure 3-78 EMC Pad Connections to Receptacle Shell	147
Figure 3-79 Examples of Connector Apertures.....	148
Figure 3-80 Recommended Minimum Spacing between Connectors.....	148
Figure 3-81 Recommended Minimum Plug Overmold Clearance	149
Figure 3-82 Cable Plug Overmold and an Angled Surface.....	149
Figure 4-1 Cable IR Drop.....	153
Figure 4-2 Cable IR Drop for powered cables.....	153
Figure 4-3 Logical Model for Single-Lane Data Bus Routing across USB Type-C-based Ports.....	161
Figure 4-4 Logical Model for USB Type-C-based Ports for a Single-Lane Direct Connect Device.....	161
Figure 4-5 Pull-Up/Pull-Down CC Model.....	163
Figure 4-6 Current Source/Pull-Down CC Model.....	163
Figure 4-7 Source Functional Model for CC1 and CC2	166
Figure 4-8 Source Functional Model Supporting <i>USB PD</i> PR_Swap.....	167
Figure 4-9 Sink Functional Model for CC1 and CC2	167
Figure 4-10 Sink Functional Model Supporting <i>USB PD</i> PR_Swap and VCONN_Swap.....	168
Figure 4-11 DRP Functional Model for CC1 and CC2.....	169
Figure 4-12 Connection State Diagram: Source.....	174
Figure 4-13 Connection State Diagram: Sink.....	175
Figure 4-14 Connection State Diagram: Sink with Accessory Support	176
Figure 4-15 Connection State Diagram: DRP	177