

INTERNATIONAL STANDARD

REDLINE VERSION

~~Low-voltage switchgear and controlgear~~ Switchgear, controlgear and their assemblies for low-voltage - Product data and properties for information exchange - Part 1: Catalogue data

get full document from standards.iteh.ai



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2026 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	10
2 Normative references	10
3 Terms and definitions	10
4 General	11
5 Properties.....	11
5.1 Criteria for naming properties.....	11
5.2 Attributes of a property	12
6 Block of properties.....	12
7 Device classes	14
7.1 Device class attributes	14
7.2 Classification of low-voltage switchgear and controlgear.....	14
7.3 Classification of low-voltage switchgear and controlgear assembly	24
7.4 Properties of circuit-breaker classes	29
7.4.1 General	29
7.4.2 Circuit-breaker.....	29
7.4.3 Release for circuit-breaker.....	31
7.4.4 Residual current release for circuit-breaker	32
7.4.5 Shunt release for circuit-breaker.....	33
7.4.6 Under-voltage release for circuit-breaker.....	34
7.4.7 Motor-operator for circuit-breaker	34
7.4.8 Plug-in base for circuit-breaker.....	35
7.4.9 Draw-out cradle for circuit-breaker.....	36
7.5 Properties of switch classes.....	36
7.5.1 General	36
7.5.2 Switch-disconnector	37
7.5.3 Switch-disconnector-fuse.....	38
7.5.4 Fuse-switch-disconnector	40
7.5.5 Operating handle (of a mechanical switching device).....	42
7.5.6 Shaft of operating handle.....	43
7.6 Properties of contactors, starters and similar equipment classes.....	43
7.6.1 General	43
7.6.2 Motor protection circuit-breaker protective switching device.....	44
7.6.3 Motor management device starter.....	45
7.6.4 Motor management device starter, extension module	47
7.6.5 Motor management device starter, operator panel	48
7.6.6 Motor-starter combination.....	48
7.6.7 AC Semiconductor motor controller	50
7.6.8 Power contactor, AC switching	51
7.6.9 Capacitor contactor	53
7.6.10 Combination of contactors	54
7.6.11 Power contactor, DC switching	55
7.6.12 Thermal overload relay	56
7.6.13 Electronic overload relay	57
7.6.14 Relay for thermistor protection (PTC)	59

7.6.15	Electromechanical contactor for household and similar purposes.....	60
7.6.16	Motor-starter.....	61
7.6.17	Transient suppressor	62
7.6.18	Mechanical interlocking device	63
7.6.19	Motor-starter enclosure.....	63
7.6.20	Coil for contactor or contactor relay	64
7.6.21	Electromechanical latching device	65
7.6.22	Control interface for contactor	66
7.7	Properties of control switch classes	66
7.7.1	General	66
7.7.2	Inductive proximity switch	67
7.7.3	Capacitive proximity switch.....	68
7.7.4	Non-mechanical magnetic proximity switch	69
7.7.5	Ultrasonic proximity switch	71
7.7.6	Through beam photoelectric proximity switch.....	72
7.7.7	Emitter for through beam photoelectric proximity switch	74
7.7.8	Retroreflective photoelectric proximity switch	75
7.7.9	Diffuse reflective photoelectric proximity switch	76
7.7.10	Diffuse reflective photoelectric proximity switch with background suppression.....	78
7.7.11	Auxiliary contact block	79
7.7.12	Contactor relay	80
7.7.13	Position switch	81
7.6.13	Rotary limit switch	81
7.7.14	Coded magnetic switch.....	83
7.7.15	Safety position switch with separate actuator.....	84
7.7.16	Guard locking safety position switch	85
7.7.17	Trip wire switch	87
7.6.17	Hinge switch	88
7.7.18	Safety switch for hinge door	88
7.7.19	Push-button.....	89
7.7.20	Rotary button.....	91
7.7.21	Front element for rotary button	92
7.7.22	Joy stick	93
7.7.23	Foot switch	94
7.7.24	Emergency stop push-button	96
7.7.25	Indicator light.....	97
7.7.26	Indicating tower	98
7.7.27	Front element for push-button.....	99
7.7.28	Contact block for control circuit.....	100
7.7.29	Front element for emergency stop push-button	101
7.7.30	Module for indicating tower.....	102
7.7.31	Reflector for reflective photoelectric proximity switch.....	103
7.7.32	Lamp for control device	104
7.7.33	Label holder for push-button and indicator light	105
7.7.34	Label plate for control operation	105
7.7.35	Protective cover for control device.....	106
7.7.36	Pneumatic time delay auxiliary contact block	107
7.7.37	Electronic time delay auxiliary block	108

7.7.38	Time relay	109
7.7.39	Panel mounted audible signalling device	110
7.7.40	Rotary encoder	111
7.7.41	Linear encoder	112
7.7.42	Control station, empty	113
7.7.43	Control station, complete	114
7.7.44	Pendant control station, empty	115
7.7.45	Pendant control station, complete	116
7.7.46	Two-hand control device	117
7.7.47	Cable connection assembly for control device	118
7.7.48	Actuator for coded magnetic switch	119
7.8	Properties of multiple function equipment classes	119
7.8.1	Transfer switching equipment	119
7.8.2	Control and protective switching device (CPS)	119
7.9	Properties of terminal block classes	119
7.9.1	General	119
7.9.2	Feed-through terminal block	120
7.9.3	Disconnect terminal block	121
7.9.4	Protective conductor terminal block	122
7.9.5	Fuse terminal block	123
8	Products Device properties	125
	Bibliography	179
	Figure 1 – Operating distances of inductive and capacitive proximity switches	172
	Figure 2 – Ultrasonic proximity switch operating distance (IEC 60947-5-2:2019, Figure 2)	173
	Figure 3 – Height of the device	173
	Figure 4 – Width of the device	174
	Figure 5 – Length of the device	174
	Table 1 – Library of blocks used in the device classes of low-voltage switchgear and controlgear	12
	Table 2 – Low-voltage switchgear and controlgear classification	14
	Table 3 – Low-voltage switchgear and controlgear assembly classification	24
	Table 4 – Circuit-breaker	29
	Table 5 – Release for circuit-breaker	31
	Table 6 – Residual current release for circuit-breaker	32
	Table 7 – Shunt release for circuit-breaker	33
	Table 8 – Under-voltage release for circuit-breaker	34
	Table 9 – Motor-operator for circuit-breaker	34
	Table 10 – Plug-in base for circuit-breaker	35
	Table 11 – Draw-out cradle for circuit-breaker	36
	Table 12 – Switch-disconnector	37
	Table 13 – Switch-disconnector-fuse	38
	Table 14 – Fuse-switch-disconnector	40
	Table 15 – Operating handle (of a mechanical switching device)	42

Table 16 – Shaft of operating handle	43
Table 17 – Motor protection circuit breaker protective switching device	44
Table 18 – Motor management device starter	45
Table 19 – Motor management device starter, extension module	47
Table 20 – Motor management device starter, operator panel	48
Table 21 – Motor-starter combination	48
Table 22 – AC Semiconductor motor controller	50
Table 23 – Power contactor, AC switching	51
Table 24 – Capacitor contactor	53
Table 25 – Combination of contactors	54
Table 26 – Power contactor, DC switching	55
Table 27 – Thermal overload relay	56
Table 28 – Electronic overload relay	57
Table 29 – Relay for thermistor protection (PTC)	59
Table 30 – Electromechanical contactor for household and similar purposes	60
Table 31 – Motor-starter	61
Table 32 – Transient suppressor	62
Table 33 – Mechanical interlocking device	63
Table 34 – Motor-starter enclosure	63
Table 35 – Coil for contactor or contactor relay	64
Table 36 – Electromechanical latching device	65
Table 37 – Control interface for contactor	66
Table 38 – Inductive proximity switch	67
Table 39 – Capacitive proximity switch	68
Table 40 – Non-mechanical magnetic proximity switch	69
Table 41 – Ultrasonic proximity switch	71
Table 42 – Through beam photoelectric proximity switch	72
Table 43 – Emitter for through beam photoelectric proximity switch	74
Table 44 – Retroreflective photoelectric proximity switch	75
Table 45 – Diffuse reflective photoelectric proximity switch	76
Table 46 – Diffuse reflective photoelectric proximity switch with background suppression	78
Table 47 – Auxiliary contact block	79
Table 48 – Contactor relay	80
Table 49 – Position switch	81
Table 50 – Coded magnetic switch	83
Table 51 – Safety position switch with separate actuator	84
Table 52 – Guard locking safety position switch	85
Table 53 – Trip wire switch	87
Table 54 – Safety switch for hinge door	88
Table 55 – Push-button	89
Table 56 – Rotary button	91
Table 57 – Front element for rotary button	92

Table 58 – Joy stick	93
Table 59 – Foot switch	94
Table 60 – Emergency stop push-button	96
Table 61 – Indicator light	97
Table 62 – Indicating tower	98
Table 63 – Front element for push-button	99
Table 64 – Contact block for control circuit	100
Table 65 – Front element for emergency stop push-button	101
Table 66 – Module for indicating tower	102
Table 67 – Reflector for reflective photoelectric proximity switch	103
Table 68 – Lamp for control device	104
Table 69 – Label holder for push-button and indicator light	105
Table 70 – Label plate for control operation	105
Table 71 – Protective cover for control device	106
Table 72 – Pneumatic time delay auxiliary contact block	107
Table 73 – Electronic time delay auxiliary block	108
Table 74 – Time relay	109
Table 75 – Panel mounted audible signalling device	110
Table 76 – Rotary encoder	111
Table 77 – Linear encoder	112
Table 78 – Control station, empty	113
Table 79 – Control station, complete	114
Table 80 – Pendant control station, empty	115
Table 81 – Pendant control station, complete	116
Table 82 – Two-hand control device	117
Table 83 – Cable connection assembly for control device	118
Table 84 – Actuator for coded magnetic switch	119
Table 85 – Feed-through terminal block	120
Table 86 – Disconnect terminal block	121
Table 87 – Protective conductor terminal block	122
Table 88 – Fuse terminal block	123
Table 89 – Library of properties used in the device classes	125
Table 90 – Value lists of properties	174

INTERNATIONAL ELECTROTECHNICAL COMMISSION

~~Low-voltage switchgear and controlgear~~ **Switchgear, controlgear and their assemblies for low-voltage - Product data and properties for information exchange - Part 1: Catalogue data**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 62683-1:2017. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

IEC 62683-1 has been prepared by committee 121: Switchgear and controlgear and their assemblies for low voltage. It is an International Standard.

This second edition cancels and replaces the first edition published in 2017. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition for reflecting the content of the IEC CDD 62683DB which has been updated with the change requests C00073, C00074, C00081, C00087, C00089, C00098, C00100, C00107, C00111, C00116, C00119, C00122, C00146, C00148, C00159, C00167, C00174 and C00135:

- a) New device class descriptions: ACC304, ACC305, ACC413, ACC417, ACC503, ACC504, ACC505, ACC512, ACC516, ACC536, ACC537, ACC538, ACC540, ACC541, ACC542, ACC543, ACC544, ACC545, ACC546, ACC547, ACC548.
- b) New associated properties.
- c) New assembly class structure: ACC101, ACC102, ACC103, ACC104, ACC106, ACC110, ACC111, ACC112, ACC113, ACC114, ACC115, ACC116, ACC117, ACC118, ACC119, ACC120, ACC121, ACC123, ACC124, ACC125, ACC126, ACC127, ACC131, ACC132, ACC133, ACC135, ACC141, ACC142, ACC143, ACC144, ACC145, ACC146, ACC147, ACC148, ACC150, ACC151, ACC152, ACC153, ACC154, ACC155, ACC156, ACC157, ACC158, ACC159, ACC160, ACC161, ACC162, ACC163, ACC164, ACC165, ACC166, ACC167, ACC170, ACC171, ACC172, ACC173, ACC174, ACC175.

The text of this International Standard is based on the following documents:

Draft	Report on voting
121/237/FDIS	121/241/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 62683 series, published under the general title *Switchgear, controlgear and their assemblies for low-voltage - Product data and properties for information exchange*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INTRODUCTION

Mainly large customers and wholesalers are requesting standardized product descriptions and product properties to product manufacturers. However, all stakeholders ~~will~~ can benefit from this standardised presentation and data exchange.

Multiple associations or groups of actors launched different initiatives to try to respond to this demand but, due to the lack of standardisation of classes and properties, the situation remains unsatisfactory for both customers and manufacturers.

In order to keep the lead of product description, IEC proposes a consistent solution within its product standards.

The purpose of this document is to:

- define device classes and properties for low-voltage switchgear and controlgear **and their assemblies** in a dedicated standard,
- provide a basis ~~for introduction~~ of **classes** of the low-voltage switchgear and controlgear **classes** **and their assemblies**, and properties introduced into the **IEC 61360 database** maintained by IEC/SC3D (see <http://std.iec.ch/iec61360>).

This document is not intended to establish a hierarchy of product classes called classification.

The intended benefits of this document are to:

- reduce the costs, time and efforts of mapping data for each customer request;
- optimize the workflow of B2B exchanges;
- minimize duplication of articles in customer inventories and in databases;
- minimize losses and misinterpretation of data during exchanges;
- facilitate the selection of a product, especially regarding reliability and safety;
- give access to product data everywhere regardless of country, language and culture;
- provide product data related to environmental aspects such as material declaration;
- contribute to the fast growth of the e-business by simplifying the development of:
 - e-Catalogue allowing the differentiation of products performances, certificates, etc;
 - e-Commerce: use of electronic networks to exchange information, products, services and payments for commercial and communication purposes between individuals (consumers) and businesses, between businesses themselves.

The output of this document consists of:

- reference dictionary of low-voltage switchgear and controlgear **and their assemblies** using existing terms from IEC documents. However, terminology used in e-business ~~may~~ can be relevant for the purpose of naming classes in this document to get a high level of acceptance;
- properties for e-commerce purposes, conformity of properties with product standards being the main goal of this document.

NOTE The classes "under consideration" are for information only and are intended to be completed during the next maintenance cycle.

~~For this project, the introduction~~The description of low-voltage switchgear and controlgear and their assemblies within the IEC 61360 database ~~needs to address~~ addresses the following technical aspects:

- IEC 61360 requires mandatory attributes. ~~The complete set of mandatory attributes with additional relevant attributes for low-voltage switchgear and controlgear will be available within the IEC 61360 database. At the development stage, the CDD 62683 database is available at the following address: <https://cdd.iec.ch/cdd/iec62683/iec62683.nsf>.~~ The complete sets of attributes for low-voltage switchgear and controlgear and their assemblies are available in the IEC 62683DB domain at <https://cdd.iec.ch/cdd/iec62683/iec62683.nsf/TreeFrameset?OpenFrameSet>. Within the present document, only the most useful attributes are presented.
- The switchgear and controlgear and their assemblies data models are implemented in ~~an appropriate~~ the IEC 62683DB domain of the IEC Component Data Dictionary (CDD), ~~IEC 61360~~, by creating dictionaries of blocks, classes and properties.

Sample Document

get full document from standards.iteh.ai

1 Scope

This part of IEC 62683 establishes the reference dictionary of the general description of **classes of low-voltage switchgear and controlgear** ~~classes~~ and **their assemblies** based on defined properties.

This dictionary is used to facilitate the exchange in electronic format of data describing low-voltage switchgear and controlgear, **their accessories and their assemblies**.

This document provides clear and unambiguous definitions of a limited number of properties and classes which are mainly used for presentation, selection and identification of products particularly in electronic catalogues.

Each property has an unambiguously defined meaning and ~~naming~~ **name**, and where relevant, a defined value list, a defined format, and a defined unit.

~~The intention is not to cover manufacturer specific features.~~

Manufacturer specific features are not covered.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60947-1:~~2007~~2020, *Low-voltage switchgear and controlgear - Part 1: General rules*
~~IEC 60947-1:2007/AMD1:2010~~
~~IEC 60947-1:2007/AMD2:2014~~

IEC 61360-1, *Standard data element types with associated classification scheme* ~~for electric items~~ - Part 1: Definitions - Principles and methods

IEC 61439-1:2020, *Low-voltage switchgear and controlgear assemblies - Part 1: General rules*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60947-1, IEC 61439-1 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1 attribute

data element for description of a property, a relation or a device class

EXAMPLE The name of a property, the code of a class, the measure unit of a property

3.2**block**

<properties>collection of properties describing one common aspect of the device class

Note 1 to entry: A block is a feature class in the sense of IEC 61360-1 and ISO 13584-42.

EXAMPLE Diagnostic functions, control circuit.

3.3**cardinality**

pattern defining the number of times a concept reoccurs within a description

Note 1 to entry: Cardinality allows a block of properties contained in a list of properties to be used more than once for a particular transaction in order to describe, for example, a device with several different outputs or more than one process cases.

Note 2 to entry: Cardinality is defined by IEC 61987-10.

3.4**device**

material element or assembly of such elements intended to perform a required function

Note 1 to entry: In this document, a device corresponds to a low voltage switchgear and controlgear.

[SOURCE: IEC 60050-151:2001, 151-11-20, modified – the note has been ~~modified~~ replaced by a new note to entry.]

3.5**device class**

set of properties which gives a description of a device

3.6**polymorphism**

pattern that allows substitution of a single concept in the same context by a different more specific (specialized) concept

Note 1 to entry: A specialised polymorphic block of properties can replace a more generic one in the same context. A polymorphic operator (control property) can act in selecting between of various specialisations.

Note 2 to entry: Polymorphism is defined by IEC 61987-10.

3.7**property**

defined parameter suitable for the description and differentiation of **device class** specific characteristic describing an aspect of device class

4 General

The attributes shall follow IEC 61360-1.

Based on IEC 61360-1 data model, the structured data called cardinality and polymorphism may be used.

5 Properties**5.1 Criteria for naming properties**

In order to maintain consistency and clarity in the naming of properties, terms from product standards shall be used when they are available.

Synonymous names may be associated with the property name when well established terms are used on the market.

5.2 Attributes of a property

The following attributes of a property are considered in this document: identifier, preferred name, definition, source document, data type, unit of measure, value format, and value list.

6 Block of properties

A property within a block shall describe one common aspect covered by the definition of this block.

A property may be reused in different blocks. In this case, this property is applicable within the context of the definition of each block.

The list of blocks of properties is defined in Table 1.

Table 1 – Library of blocks used in the device classes of low-voltage switchgear and controlgear

Block name	Definition	Source	Class ID
Identification	information necessary for unambiguous identification of the device		ACC011
General technical data	general technical aspects of the device		ACC012
Diagnostic functions	ability to analyse a situation corresponding to a predefined set of parameters of the device		ACC013
Main circuit (of a switching device)	all the conductive parts of a switching device or an assembly included in the circuit which it is designed to close or open	IEC 60050-441:1984, 441-15-02, modified	ACC014
Input/output circuit	circuit of the device used to receive or to send signals or data		ACC015
Control and auxiliary circuits	all the conductive parts of the device which are intended to be included in a circuit other than the main circuit		ACC016
Head of the control circuit device	part which contains and supports the actuator or contains the lens of an indicator light, fixed on an enclosure or on the body of the device		ACC017
Light block of the control circuit device	part which contains and supports the lamp, fixed on an enclosure or on the body of the device		ACC018
Equipment of control station	set of control devices and indicators mounted on a control station		ACC019
Emitting source of proximity switch	radiation source which provides the beam operating the proximity switch		ACC020
Short-circuit	short-circuit conditions, stated by the manufacturer, which the device can make, withstand or break satisfactorily		ACC040
Overcurrent release	release which causes a mechanical switching device to open with or without time delay when the current in the release exceeds a predetermined value NOTE This value can in some cases depend upon the rate-of-rise of current.	2-4-25 of IEC 60947-1: 2007 2020, 3.6.26, modified	ACC041
Data communication Communication interfaces	communication functions for the transfer of information between the device and the system		ACC050

Installation, mounting and dimensions	physical information of the device for installation		ACC066
Connection facilities	terminals, screws or other parts, used for the electrical connection of conductors of external circuits of the device	IEC 60050-426:2008, 426-04-25, modified	ACC068
Product certificates and standards	conformity of a device with specified requirements and compliance with recognised product standards		ACC070

7 Device classes

7.1 Device class attributes

The attributes of the device class shall follow IEC 61360-1.

The following attributes of a device class are considered in this document: identifier, preferred name, definition, synonymous name and source document.

NOTE The synonymous names are limited to those necessary to avoid confusion when selecting a device class.

7.2 Classification of low-voltage switchgear and controlgear

Table 2 gives the classification of low-voltage switchgear and controlgear ~~domain~~ based on the corresponding product standards. The class name column is structured in four levels of hierarchy using indent alignments.

Table 2 – Low-voltage switchgear and controlgear classification

Class name	Synonymous name	Definition	Source	Class ID
LV switchgear and controlgear domain		domain covering switching devices and their combination with associated control, measuring, protective and regulating equipment, also assemblies of such devices and equipment with associated interconnections, accessories, enclosures and supporting structures	2.1.1 of IEC 60947-1:2007 2020, 3.3.1, modified	ACC001
LV switchgear and controlgear classes		set of switching devices and their combination with associated control, measuring, protective and regulating equipment, also assemblies of such devices and equipment with associated interconnections, accessories, enclosures and supporting structures	2.1.1 of IEC 60947-1:2007 2020, 3.3.1, modified	ACC100
Circuit-breaker classes		set of circuit-breakers, their releases and accessories		ACC200
Circuit-breaker	Moulded case circuit breaker	mechanical switching device, capable of making, carrying and breaking currents under normal circuit conditions and also making, carrying for a specified time and breaking currents under specified abnormal circuit conditions such as those of short-circuit	IEC 60050-441:1984, 441-14-20	ACC201