

INTERNATIONAL STANDARD

CONSOLIDATED VERSION

Photovoltaic systems - Design qualification of solar trackers

Sample Document

get full document from standards.iteh.ai



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2026 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	5
1 Scope and object	7
2 Normative references	7
3 Terms and definitions	8
4 Specifications for solar trackers for PV applications	9
5 Report	11
6 Tracker definitions and taxonomy	12
6.1 General	12
6.2 Payload types	12
6.2.1 Standard photovoltaic (PV) module trackers	12
6.2.2 Concentrator photovoltaic (CPV) module trackers	13
6.3 Rotational axes	13
6.3.1 General	13
6.3.2 Single-axis trackers	13
6.3.3 Dual-axis trackers	15
6.4 Actuation and control	16
6.4.1 Architecture	16
6.4.2 Drive train	17
6.4.3 Drive types	17
6.4.4 Drive train torque	17
6.5 Types of tracker control	18
6.5.1 Passive control	18
6.5.2 Active control	18
6.5.3 Backtracking	18
6.6 Structural characteristics	19
6.6.1 Vertical supports	19
6.6.2 Foundation types	19
6.6.3 Tracker positions	20
6.6.4 Stow time	20
6.7 Energy consumption	20
6.7.1 Daily energy consumption	20
6.7.2 Stow energy consumption	20
6.8 External elements and interfaces	21
6.8.1 Foundation	21
6.8.2 Foundation interface	21
6.8.3 Payload	21
6.8.4 Payload interface	21
6.8.5 Payload mechanical interface	21
6.8.6 Payload electrical interface	21
6.8.7 Grounding interface	21
6.8.8 Installation effort	21
6.8.9 Control interface	22
6.9 Internal tolerances	22
6.9.1 Primary-axis tolerance	22
6.9.2 Secondary axis tolerance	22
6.9.3 Backlash	22

6.9.4	Stiffness	23
6.10	Tracker system elements	23
6.10.1	Mechanical structure	23
6.10.2	Tracker controller	23
6.10.3	Sensors	23
6.11	Reliability terminology	23
6.11.1	General	23
6.11.2	Mean time between failures (MTBF)	24
6.11.3	Mean time between critical failures (MTBCF)	24
6.11.4	Mean time to repair (MTTR)	24
6.12	Environmental conditions	24
6.12.7	General	24
6.12.1	Operating temperature range	25
6.12.2	Survival temperature range	26
6.12.8	Humidity	26
6.12.9	Rain	27
6.12.10	Air pressure (altitude)	27
6.12.11	Flooding	28
6.12.12	Seismic (earthquake)	28
6.12.13	Dust and sand	28
6.12.14	Corrosion	28
6.12.15	Electromagnetic compatibility (EMC)	29
6.12.16	Shock and vibration	29
6.12.17	Ingress	29
6.12.18	Electrical supply	30
6.12.3	Wind speed	30
6.12.4	Maximum wind during operation	30
6.12.5	Maximum wind during stow	31
6.12.6	Snow load	31
11	Tracker construction requirements	31
11.1	Cables, conductors and wiring requirements	31
11.2	Wiring practices: connections and routing	31
11.3	Motors	31
11.4	Control gear: location, mounting and enclosures	31
7	Tracker accuracy characterization	31
7.1	Overview	31
7.2	Pointing error (instantaneous)	32
7.3	Measurement	32
7.3.1	Overview	32
7.3.2	Example of experimental method to measure pointing error	32
7.3.3	Calibration of pointing error measurement tool	33
7.4	Calculation of tracker accuracy	35
7.4.1	Overview	35
7.4.2	Data collection	35
7.4.3	Data binning by wind speed	36
7.4.4	Data filtering	36
7.4.5	Data quantity	37
7.4.6	Accuracy calculations	37
8	Tracker test procedures	37

8.1	Visual inspection.....	37
8.1.1	Purpose.....	37
8.1.2	Procedure.....	38
8.1.3	Requirements	38
8.2	Functional validation tests.....	38
8.2.1	Purpose.....	38
8.2.2	Tracking limits verification	38
8.2.3	Hard limit switch operation.....	39
8.2.4	Automatic sun tracking after power outage and feedback sensor shadowing	39
8.2.5	Manual operation.....	39
8.2.6	Emergency stop.....	39
8.2.7	Maintenance mode	39
8.2.8	Operational temperature range	39
8.2.9	Wind stow.....	40
8.3	Performance tests.....	40
8.3.1	Purpose.....	40
8.3.2	Daily energy and peak power consumption	40
8.3.3	Stow time and stow energy and power consumption	40
8.4	Mechanical testing	41
8.4.1	Purpose.....	41
8.4.2	Control/drive train pointing repeatability test.....	41
8.4.3	Deflection under static load test.....	42
8.4.4	Torsional stiffness, mechanical drift, drive torque, and backlash testing	45
8.4.5	Moment testing under extreme wind loading	49
8.5	Environmental testing	51
8.5.1	Purpose.....	51
8.5.2	Procedure.....	51
8.5.3	Requirements	53
8.6	Accelerated mechanical cycling	54
8.6.1	Purpose.....	54
8.6.2	Procedure.....	54
8.6.3	Requirements	56
9	Design qualification testing specific to tracker electronic equipment	57
9.1	General purpose	57
9.2	Sequential testing for electronic components	57
9.2.1	General	57
9.2.2	Visual inspection of electronic components.....	58
9.2.3	Functioning test.....	59
9.2.4	Protection against dust, water, and foreign bodies (IP code).....	61
9.2.5	Protection against mechanical impacts (IK code)	61
9.2.6	Robustness of terminals test.....	61
9.2.7	Surge immunity test.....	62
9.2.8	Shipping vibration test	63
9.2.9	Shock test	63
9.2.10	UV test	64
9.2.11	Thermal cycling test.....	64
9.2.12	Humidity-freeze test.....	65
9.2.13	Damp heat.....	66

10	Additional optional accuracy calculations.....	67
10.1	Typical tracking accuracy range.....	67
10.2	Tracking error histogram.....	67
10.3	Percent of available irradiance as a function of pointing error	68
	Bibliography.....	69
	Figure 1 – Convention for elevation angle	15
	Figure 2 – Illustration of primary-axis tolerance for VPDAT	22
	Figure 20 – Climatogram showing interdependence of air temperature and absolute air humidity	27
	Figure 3 – General illustration of pointing error	32
	Figure 4 – Example of experimental method to measure pointing error	33
	Figure 5 – Example measurement locations for structural deflection	43
	Figure 6 – Load configurations while the payload is in the horizontal position	44
	Figure 7 – Load configuration when the payload is in the vertical position.....	44
	Figure 8 – Moment load applied to an elevation axis.....	46
	Figure 9 – Angular displacement versus applied torque to axis of rotation	47
	Figure 10 – Examples of characteristic length for (a) elevation torque, (b) azimuth torque	48
	Figure 11 – Two configurations for extreme wind moment loading.....	50
	Figure 12 – Representation of a tracker's discrete-movement profile	55
	Figure 13 – Representation of an accelerated discrete-movement profile for testing	55
	Figure 14 – Test sequence for electronic components.....	58
	Figure 15 – Electronic component thermal cycling test.....	65
	Figure 16 – Electronic component humidity-freeze test	66
	Figure 17 – Pointing-error frequency distribution for the entire test period	67
	Figure 18 – Available irradiance as a function of pointing error	68
	Figure 19 – Available irradiance as a function of pointing error with binning by wind speed	68
	Table 1 – Tracker specification template.....	9
	Table 3 – Classification of climatic conditions	25
	Table 2 – Alternate tracking-accuracy reporting template.....	37

INTERNATIONAL ELECTROTECHNICAL COMMISSION

Photovoltaic systems - Design qualification of solar trackers

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendments has been prepared for user convenience.

IEC 62817 edition 1.2 contains the first edition (2014-08) [documents 82/853/FDIS and 82/877/RVD], its amendment 1 (2017-07) [documents 82/1018/CDV and 82/1097/RVC] and its amendment 2 (2026-09) [documents 82/2651/FDIS and 82/2698/RVD].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendments 1 and 2. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

International Standard IEC 62817 has been prepared by IEC technical committee 82: Solar photovoltaic energy systems.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document and its amendments will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

Sample Document

get full document from standards.iteh.ai

1 Scope and object

This International Standard is a design qualification standard applicable to solar trackers for photovoltaic systems, but may be used for trackers in other solar applications. The standard defines test procedures for both key components and for the complete tracker system. In some cases, test procedures describe methods to measure and/or calculate parameters to be reported in the defined tracker specification sheet. In other cases, the test procedure results in a pass/fail criterion.

The objective of this design qualification standard is twofold.

First, this standard ensures the user of the said tracker that parameters reported in the specification sheet were measured by consistent and accepted industry procedures. This provides customers with a sound basis for comparing and selecting a tracker appropriate to their specific needs. This standard provides industry-wide definitions and parameters for solar trackers. Each vendor can design, build, and specify the functionality and accuracy with uniform definition. This allows consistency in specifying the requirements for purchasing, comparing the products from different vendors, and verifying the quality of the products.

Second, the tests with pass/fail criteria are engineered with the purpose of separating tracker designs that are likely to have early failures from those designs that are sound and suitable for use as specified by the manufacturer. Mechanical and environmental testing in this standard is designed to gauge the tracker's ability to perform under varying operating conditions, as well as to survive extreme conditions. Mechanical testing is not intended to certify structural and foundational designs, because this type of certification is specific to local jurisdictions, soil types, and other local requirements.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-6, *Environmental testing – Part 2-6: Tests – Test Fc: Vibration (sinusoidal)*

IEC 60068-2-21, *Environmental testing – Part 2-21: Tests – Test U: Robustness of terminations and integral mounting devices*

IEC 60068-2-27, *Environmental testing – Part 2-27: Tests – Test Ea and guidance: Shock*

IEC 60068-2-75, *Environmental testing – Part 2-75: Tests – Test Eh: Hammer tests*

IEC 60204-1:2016, *Safety of machinery - Electrical equipment of machines - Part 1: General requirements*

IEC 60204-1:2016/AMD1:2021

IEC 60228, *Conductors of insulated cables*

IEC 60664-1, *Insulation coordination for equipment within low-voltage supply systems - Part 1: Principles, requirements and tests*

IEC 60529, *Degrees of protection provided by enclosures (IP Code)*

IEC 60721-3-4:2019, *Classification of environmental conditions - Part 3-4: Classification of groups of environmental parameters and their severities - Stationary use at non-weatherprotected locations*

IEC 60904-3:20082019, *Photovoltaic devices – Part 3: Measurement principles for terrestrial photovoltaic (PV) solar devices with reference spectral irradiance data*

IEC 61000-4-5:20052014, *Electromagnetic compatibility (EMC) – Part 4-5: Testing and measurement techniques – Surge immunity test*

IEC 61000-6-1:2016, *Electromagnetic compatibility (EMC) - Part 6-1: Generic standards - Immunity standard for residential, commercial and light-industrial environments*

IEC 61000-6-2:2016, *Electromagnetic compatibility (EMC) - Part 6-2: Generic standards - Immunity standard for industrial environments*

IEC 61000-6-3:2020, *Electromagnetic compatibility (EMC) - Part 6-3: Generic standards - Emission standard for equipment in residential environments¹*

IEC 61000-6-4:2018, *Electromagnetic compatibility (EMC) - Part 6-4: Generic standards - Emission standard for industrial environments*

IEC 62262:2002, *Degrees of protection provided by enclosures for electrical equipment against external mechanical impacts (IK code)*

IEC TS 61836:2025, *Solar photovoltaic energy systems - Terms, definitions and symbols*

~~ISO/IEC 17025, General requirements for the competence of testing and calibration laboratories~~

ISO 9223, *Corrosion of metals and alloys - Corrosivity of atmospheres - Classification, determination and estimation*

ISO 12103-1, *Road vehicles – Test dust for filter evaluation – Part 1: Arizona test dust*

3 Terms and definitions

For the purposes of this document, ~~the following terms and definitions apply. For additional tracker-specific terminology, see Clause 6~~ the terms and definitions given in IEC TS 61836 and the following apply.

3.1 photovoltaics PV

devices that use solar radiation to directly generate electrical energy

3.2 concentrator photovoltaics CPV

devices that focus magnified sunlight on photovoltaics to generate electrical energy. The sunlight could be magnified by various different methods, such as reflective or refractive optics, in dish, trough, lens, or other configurations

¹ This publication has been withdrawn.

3.3**concentrator module****CPV module**

group of receivers (PV cells mounted in some way), optics, and other related components, such as interconnections and mechanical enclosures, integrated together into a modular package. The module is typically assembled in a factory and shipped to an installation site to be installed along with other modules on a solar tracker

Note 1 to entry: The module is typically assembled in a factory and shipped to an installation site to be installed along with other modules on a solar tracker.

Note 2 to entry: A CPV module typically does not have a field-adjustable focus point. In addition, a module could be made of several sub-modules. The sub-module is a smaller, modular portion of the full-size module, which might be assembled into the full module either in a factory or in the field.

3.4**concentrator assembly**

concentrator assembly consisting of receivers, optics, and other related components that have a field-adjustable focus point and are typically assembled and aligned in the field

EXAMPLE: A system that combines a single large dish with a receiver unit that is aligned with the focal point of the disk.

Note 1 to entry: This term is used to differentiate certain CPV designs from the CPV modules mentioned above.

4 Specifications for solar trackers for PV applications

The manufacturer shall provide the test lab, as part of its product marking and documentation, a table in the form specified below (see Table 1). The third column of Table 1 is for information purposes regarding this standard and is not intended to be part of an actual specification template provided to the test lab. See later clauses/subclauses of this standard for further explanation of individual specifications.

Some of the specifications within Table 1 are required to be provided by the manufacturer and verified by the test lab, whereas others are the sole responsibility of the test lab. Still other specifications in Table 1 are optional; however, if a tracker manufacturer chooses to include optional information, it shall be reported and measured in the specific way shown in Table 1 (and in some cases, reporting requirements are further described in the appropriate clause of this standard). Refer to the third column of Table 1 to determine the responsibility of the specification or optional status ("T" indicates test lab responsibility, "M" indicates manufacturer responsibility, and "O" indicates an optional parameter).

Table 1 – Tracker specification template

Characteristic	Example	Responsibility/Clause/Subclause
Manufacturer	The XYZ Company	(M)
Model number	XX1090	(M)
Type of tracker	CPV Tracker, Dual Axis	(M) 6.2, 6.3
Payload characteristics		
Minimum/maximum mass supported	100 kg/1 025 kg	(M) 6.8.3
Payload center of mass restrictions	0 m to 0,3 m distance perpendicular to mounting surface	(M) 6.8.3
Maximum payload surface area	30 m ²	(M) 6.8.3
Nominal payload surface area	28 m ²	(M)
Maximum dynamic torques allowed while moving	Azimuth (Θ_z): 10 kN m Θ_x , Θ_y : 5 kN m [shall provide a set of diagrams to	(M) 8.4.5

Characteristic	Example	Responsibility/Clause/Subclause
	clarify torques and which axes they are relative to]	
Maximum static torques allowed while in stow position	[shall provide a set of diagrams]	(M) 8.4.4, 8.4.5
Installation characteristics		
Allowable foundation	Reinforced concrete	(M) 6.6.2
Foundation tolerance in primary axis	$\pm 0,5^\circ$	(O) 6.9
Foundation tolerance in secondary axis	$\pm 0,5^\circ$	(O) 6.9
Installation effort	5 man-hours, 40 metric ton crane	(O) 6.8.8
Payload interface flexibility	The interface can be configured to mount modules from manufacturers "A", "B", and "C". Bolting configurations "X", "Y", and "Z" are allowable.	(O)
Electrical characteristics		
Includes backup power?	No	(M) N/A
Daily energy consumption	1,5 kWh	(T) 6.7.1
Stow energy consumption	1 kWh	(T) 6.7.2
Input power requirements	AC, 100 V to 240 V, 50 Hz to 60 Hz, 5 A	(M) No specifics defined
Effective (and apparent) peak power consumption tracking	500 W (550 VA)	(T) 8.3.2
Effective (and apparent) peak power consumption non-tracking	50 W (55 VA)	(T) 8.3.2
Effective (and apparent) peak power consumption stow positioning.	1 000 W (1 100 VA)	(T) 8.3.3
Tracking accuracy		
Accuracy, typical (low wind, min deflect point)	$0,1^\circ$	(T) 7.4.6
Accuracy, typical (low wind, max deflect point)	$0,3^\circ$	(T) 7.4.6
Accuracy, 95 th percentile (low wind, min deflect point)	$0,5^\circ$	(T) 7.4.6
Accuracy, 95 th percentile (low wind, max deflect point)	$0,8^\circ$	(T) 7.4.6
Mean wind speed during the "low wind" test conditions	3,1 m/s	(T) 7.4.6
Accuracy, typical (high wind, min deflect point)	$0,7^\circ$	(T) 7.4.6
Accuracy, typical (high wind, max deflect point)	$1,0^\circ$	(T) 7.4.6
Accuracy, 95 th percentile (high wind, min deflect point)	$1,1^\circ$	(T) 7.4.6
Accuracy, 95 th percentile (high wind, max deflect point)	$1,6^\circ$	(T) 7.4.6
Mean wind speed during the "high wind" test conditions	5,2 m/s	(T) 7.4.6
Weight and area of payload	500 kg payload evenly distributed	(T) 7.4.2.1

Characteristic	Example	Responsibility/Clause/Subclause
installed during testing	over a 50 m ² area	
Payload center of mass installed during testing	Payload center of mass 0,2 m above the module mounting surface	(T) 7.4.2.1
Control characteristics		
Control algorithm	Hybrid	(M) 6.5
Control interface	None	(M) 6.8.9
External communication interface	Ethernet/TCP-IP	(M) No specific description
Emergency stow provided?	Yes, at wind speeds 14 m/s	(M) 6.6.3.1
Stow time	4 min	(M) 6.6.4
Clock accuracy	1 s per year	(M) N/A
Hard limit switches	Not included	(M) 7.2.3
Mechanical design		
Actuation type	Distributed	(M) 6.4.1
Drive type	Electric	(M) 6.4.3
Actuators	DC motor, 185 W	(M) No specific description
Range of motion, primary axis	± 160° azimuth	(M) 6.6.3.3
Range of motion, secondary axis	10° to 90° elevation	(M) 6.6.3.3
System stiffness	See test lab report on measurement locations, applied loads, and measured deflections	(T),(O) 6.9.4, 8.4.3
Drive train torsional stiffness	See plot of angular displacement versus applied torque	(T) 8.4.4, Figure 9
Backlash	0,1° maximum	(T) 6.9.3, 8.4.4
Environmental conditions		
Maximum allowable wind speed during tracking	14 m/s	(M) 6.12.4
Maximum allowable wind speed in stow	40 m/s	(M) 6.12.5
Temperature operational range	−20 °C to +50 °C	(M) 6.12.1
Temperature survival range	−40 °C to +60 °C	(M) 6.12.2
Snow rating	Up to 20 kg/m ² of snow load allowed	(M) 6.12.6
Maintenance and Reliability		
Maintenance schedule	Grease application every 12 months (0,75 man-hours required) Drive train fluid change every 3 years (1,25 man-hours required)	(O)
MTBF	3,5 years	(O) 6.11.2
MTTR	2 h (azimuth or elevation motor) (list components that are expected to need repair or replacement within a 10-year period)	(O) 6.11.4

For an alternate template for the presentation of accuracy specifications, see Table 2.

5 Report

~~A certified report of the qualification tests, with measured performance characteristics and details of any failures and re-tests, shall be prepared by the test agency in accordance with~~

~~ISO/IEC 17025. The report shall contain the specification sheet per Table 1.~~ Each certificate or test report shall include at least the following information:

- a) a title;
- b) name and address of the test laboratory and location where the tests were carried out;
- c) unique identification of the certification or report and of each page;
- d) name and address of client, where appropriate;
- e) description and identification of the item tested;
- f) characterization and condition of the test item;
- g) date of receipt of test item and date(s) of test, where appropriate;
- h) identification of test method used;
- i) reference to sampling procedure, where relevant;
- j) any deviations from, additions to, or exclusions from, the test method and any other information relevant to a specific test;
- k) measurements, examinations and derived results supported by tables, graphs, sketches, and photographs as appropriate, and any failures observed;
- l) a statement of the estimated uncertainty of the test results (where relevant);
- m) a signature and title, or equivalent identification of the person(s) accepting responsibility for the content of the certificate or report, and the date of issue;
- n) where relevant, a statement to the effect that the results relate only to the items tested;
- o) a statement that the certificate or report shall not be reproduced except in full, without the written approval of the laboratory.

A copy of this report shall be kept by the manufacturer for reference purposes.

6 Tracker definitions and taxonomy

6.1 General

Solar trackers are mechanical devices used to track or follow the sun across the sky on a daily basis. Although a solar tracker can be used for many purposes, the scope of this standard is focused on solar trackers for photovoltaic (PV) applications. In PV applications, the primary purpose of the tracker is to enhance the capture of available solar irradiance to be converted to electricity. Photovoltaic trackers can be classified into two types: standard PV trackers and concentrator photovoltaic (CPV) trackers. Each of these tracker types can be further categorized by the number and orientation of their axes, their actuation architecture and drive type, their intended applications, and their vertical supports and foundation type.

6.2 Payload types

6.2.1 Standard photovoltaic (PV) module trackers

6.2.1.1 Uses

Standard PV trackers are used to minimize the angle of incidence between incoming light and a PV module. This increases the amount of energy produced from a fixed amount of power-generating capacity.

6.2.1.2 Type of light accepted

Photovoltaic modules accept both direct and diffuse light from all angles. This means that systems implementing standard PV trackers produce energy even when not directly pointed at the sun. Tracking in standard PV systems is used to increase the amount of energy produced by the direct component of the incoming light.

6.2.1.3 Accuracy requirements

In standard PV systems, the energy contributed by the direct beam drops off with the cosine of the angle between the incoming light and the module. Thus, trackers that have accuracies of $\pm 5^\circ$ can deliver 99,6 % of the energy supplied by the direct beam. As a result, high-accuracy tracking is not typically used.

6.2.2 Concentrator photovoltaic (CPV) module trackers

6.2.2.1 Uses

Concentrator photovoltaic trackers are used to enable the optics used in CPV systems. These trackers typically align CPV optical elements with the sun's direct beam with a higher degree of accuracy than standard PV trackers.

6.2.2.2 Type of light accepted

Direct solar radiation, as opposed to diffuse solar radiation, is the primary energy source for CPV modules. Optics are designed specifically to focus the direct radiation on PV cells. If this focus is not maintained, power output drops substantially.

If the CPV module concentrates in one dimension, then single-axis tracking is required. If the CPV module concentrates in two dimensions, then two-axis tracking is required.

6.2.2.3 Accuracy requirements

In concentrator modules, tracking accuracy requirements are typically related to energy production through the module acceptance angle. When the sun-pointing error is less than the acceptance angle, the modules will typically deliver 90 % or more of the rated power output.

6.3 Rotational axes

6.3.1 General

Photovoltaic trackers can be grouped into classes by the number axes and orientation of the primary axis.

6.3.2 Single-axis trackers

6.3.2.1 General

Single-axis trackers have one degree of freedom that acts as an axis of rotation.

6.3.2.2 Single-axis tracker implementations

6.3.2.2.1 General

There are several common implementations of single-axis trackers. These include horizontal single-axis trackers, vertical single-axis trackers, and inclined single-axis trackers.

6.3.2.2.2 Horizontal single-axis tracker (HSAT)

The axis of rotation for a horizontal single-axis tracker is horizontal with respect to the ground.