



IEEE

IEC/IEEE 62209-1528

Edition 1.1 2026-09

INTERNATIONAL STANDARD

CONSOLIDATED VERSION

**Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices -
Part 1528: Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)**

get full document from standards.iteh.ai



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2026 IEC, Geneva, Switzerland

Copyright © 2026 IEEE

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing being secured. Requests for permission to reproduce should be addressed to either IEC at the address below or IEC's member National Committee in the country of the requester or from IEEE.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue
New York, NY 10016-5997
United States of America
stds.ipr@ieee.org
www.ieee.org

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About the IEEE

IEEE is the world's largest professional association dedicated to advancing technological innovation and excellence for the benefit of humanity. IEEE and its members inspire a global community through its highly cited publications, conferences, technology standards, and professional and educational activities.

About IEC/IEEE publications

The technical content of IEC/IEEE publications is kept under constant review by the IEC and IEEE. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	14
INTRODUCTION	17
1 Scope	18
2 Normative references	18
3 Terms and definitions	18
4 Symbols and abbreviated terms	26
4.1 Physical quantities	26
4.2 Constants	26
4.3 Abbreviated terms	27
5 Quick start guide and evaluation plan checklist	28
6 Measurement system specifications	30
6.1 General requirements for full SAR testing	30
6.2 Phantom specifications	31
6.2.1 General	31
6.2.2 Basic phantom parameters	31
6.2.3 Head phantom	33
6.2.4 Flat phantom	34
6.2.5 Device-specific phantoms	35
6.3 Influence of hand on SAR in head	35
6.4 Scanning system requirements	36
6.5 Device holder specifications	36
6.6 Characteristics of the readout electronics	37
7 Protocol for SAR assessment	37
7.1 General	37
7.2 Measurement preparation	37
7.2.1 Preparation of tissue-equivalent medium and system check	37
7.2.2 Preparation of the wireless communication DUT	38
7.2.3 DUT operating mode requirements	38
7.2.4 Positioning of the DUT relative to the phantom	40
7.2.5 Antenna configurations	58
7.2.6 Options and accessories	58
7.2.7 DUTs with alternative form factor	58
7.2.8 Test frequencies for DUTs	59
7.3 Tests to be performed for DUTs	59
7.3.1 General	59
7.3.2 Basic approach for DUT testing	60
7.4 Measurement procedure	61
7.4.1 General	61
7.4.2 Full SAR testing procedure	61
7.4.3 Drift	65
7.4.4 SAR measurements of DUTs with multiple antennas or multiple transmitters	67
7.5 Post-processing of SAR measurement data	73
7.5.1 Interpolation	73
7.5.2 Extrapolation	73
7.5.3 Definition of the averaging volume	73

7.5.4	Searching for the maxima	74
7.6	Time-period averaged SAR considerations	74
7.6.1	General	74
7.6.2	RF conducted power	74
7.6.3	Time-period averaged SAR measurement settings for SAR measurement methods	74
7.6.2	Exposure conditions and test positions	76
7.6.3	SAR measurements	76
7.6.4	Time-period averaged SAR for simultaneous transmission.....	77
7.6.6	TX factor assessment	77
7.6.7	SAR measurements	77
7.6.5	Uncertainty in TPAS evaluations	79
7.7	Proximity sensors considerations	79
7.7.1	General	79
7.7.2	Procedures for determining proximity sensor triggering distances	81
7.7.3	Procedure for determining proximity sensor coverage area	84
7.7.4	SAR measurement procedure involving proximity sensors	85
7.8	SAR correction for deviations of complex permittivity from targets	85
7.8.1	General	85
7.8.2	SAR correction formula.....	86
7.8.3	Uncertainty of the correction formula	87
7.9	Minimization of testing time.....	87
7.9.1	General	87
7.9.2	Fast SAR testing	88
7.9.3	SAR test reductions	93
7.10	Motion sensors considerations	105
7.10.1	General	105
7.10.2	SAR measurement procedure involving motion sensors	106
7.11	Devices used next to the ear during voice calls	106
7.11.1	General	106
7.11.2	Operating mode characteristics	107
7.11.3	Applicability criteria	107
7.11.4	Hand SAR test procedure	108
7.11.5	Duty cycle and time-averaged output power considerations for hand SAR testing	108
8	Measurement uncertainty estimation	110
8.1	General.....	110
8.2	Requirements on the uncertainty evaluation.....	111
8.3	Description of uncertainty models	111
8.3.1	General	111
8.3.2	SAR measurement of a DUT	112
8.3.3	System validation and system check measurement.....	112
8.3.4	System check repeatability and reproducibility.....	112
8.3.5	Fast SAR testing (relative measurement).....	112
8.4	Parameters contributing to uncertainty	114
8.4.1	Measurement system errors	114
8.4.2	Phantom and device (DUT or validation antenna) errors	115
8.4.3	Corrections to the SAR result (if applied).....	117

9	Measurement report	118
9.1	General.....	118
9.2	Items to be recorded in the measurement report	118
Annex A	(normative) SAR measurement system verification	122
A.1	Overview	122
A.2	System check	122
A.2.1	Purpose	122
A.2.2	Phantom set-up	123
A.2.3	System check antenna.....	123
A.2.4	System check antenna input power measurement.....	124
A.2.5	System check procedure.....	125
A.2.6	System check acceptance criteria	126
A.3	System validation.....	126
A.3.1	Purpose	126
A.3.2	Phantom set-up	126
A.3.3	System validation antennas	126
A.3.4	Input power measurement	127
A.3.5	System validation procedure.....	127
A.4	Fast SAR testing system validation and system check	129
A.4.1	General	129
A.4.2	Fast SAR testing system validation.....	129
A.4.3	Fast SAR testing system check.....	130
Annex B	(informative) SAR test reduction supporting information.....	132
B.1	General.....	132
B.2	Test reduction based on characteristics of DUT design	132
B.2.1	General	132
B.2.2	Statistical analysis overview	132
B.2.3	Analysis results	133
B.2.4	Conclusions.....	136
B.2.5	Expansion to multi-transmission antennas	136
B.3	Test reduction based on analysis of SAR results on other signal modulations	136
B.3.1	General	136
B.3.2	Analysis results	137
B.4	Test reduction based on SAR level analysis.....	138
B.4.1	General	138
B.4.2	Statistical analysis	139
B.4.3	Test reduction applicability example	142
B.5	Other statistical approaches to search for the high SAR test configurations	144
B.5.1	General	144
B.5.2	Test reductions based on a DOE	144
B.5.3	One factor at a time (OFAT) search	144
B.5.4	Analysis of unstructured data.....	144
Annex C	(informative) Measurement uncertainty of results obtained from specific fast SAR testing methods	145
C.1	General.....	145
C.2	Measurement uncertainty evaluation – contributing parameters	145
C.2.1	General	145
C.2.2	Probe calibration and system calibration drift.....	146
C.2.3	Isotropy	146

C.2.4	Probe positioning	147
C.2.5	Mutual sensor coupling	148
C.2.6	Scattering within the probe array	149
C.2.7	Sampling error	149
C.2.8	Array boundaries	149
C.2.9	Probe or probe array coupling with the DUT	149
C.2.10	Measurement system immunity / secondary reception	149
C.2.11	Deviations in phantom shape	150
C.2.12	Spatial variation in dielectric properties	150
C.2.13	Reconstruction	150
C.3	Uncertainty budget	150
Annex D (normative)	SAR system validation antennas	153
D.1	General antenna requirements	153
D.2	Standard dipole antenna	153
D.2.1	Mechanical description	153
D.2.2	Numerical target SAR values	156
D.3	Standard waveguide	158
D.3.1	Mechanical description	158
D.3.2	Numerical target SAR values	159
D.4	System validation antennas for below 150 MHz	159
D.4.1	General	159
D.4.2	Confined loop antenna	160
D.4.3	Meander dipole antenna	162
D.5	Orthogonal E-field source – VPIFA	163
D.5.1	Mechanical description	163
D.5.2	Numerical target SAR values	166
Annex E (normative)	Calibration and characterization of dosimetric (SAR) probes	167
E.1	Introductory remarks	167
E.2	Linearity	168
E.3	Assessment of the sensitivity of the dipole sensors	168
E.3.1	General	168
E.3.2	Two-step calibration procedures	168
E.3.3	One-step calibration procedure – reference antenna method	174
E.3.4	One-step calibration procedure – coaxial calorimeter method	178
E.4	Isotropy	180
E.4.1	Axial isotropy	180
E.4.2	Hemispherical isotropy	180
E.5	Lower detection limit	185
E.6	Boundary effect	186
E.7	Response time	186
Annex F (informative)	Example recipes for phantom tissue-equivalent media	187
F.1	General	187
F.2	Ingredients	187
F.3	Tissue-equivalent medium liquid formulas (permittivity/conductivity)	188
Annex G (normative)	Phantom specifications	190
G.1	Rationale for the phantom characteristics	190
G.1.1	General	190
G.1.2	Rationale for the SAM phantom	190

G.1.3	Rationale for the flat phantom	190
G.2	SAM phantom specifications	191
G.2.1	General SAM phantom specifications	191
G.2.2	SAM phantom shell specification	195
G.3	Flat phantom specifications	197
G.4	Justification of flat phantom dimensions	198
G.5	Rationale for tissue-equivalent media	201
G.6	Definition of a phantom coordinate system and a DUT coordinate system	203
Annex H (informative)	Measurement of the dielectric properties of tissue-equivalent media and uncertainty estimation	205
H.1	Overview	205
H.2	Measurement techniques	205
H.2.1	General	205
H.2.2	Instrumentation	205
H.2.3	General principles	205
H.3	Slotted coaxial transmission line	206
H.3.1	General	206
H.3.2	Equipment set-up	206
H.3.3	Measurement procedure	207
H.4	Contact coaxial probe	207
H.4.1	General	207
H.4.2	Equipment set-up	208
H.4.3	Measurement procedure	209
H.5	TEM transmission line	209
H.5.1	General	209
H.5.2	Equipment set-up	210
H.5.3	Measurement procedure	210
H.6	Dielectric properties of reference liquids	211
Annex I (informative)	Studies for potential hand effects on head SAR	214
I.1	Overview	214
I.2	Background	214
I.2.1	General	214
I.2.2	Hand phantoms	215
I.3	Summary of experimental studies	215
I.3.1	Experimental studies using fully compliant SAR measurement systems	215
I.3.2	Experimental studies using other SAR measurement systems	215
I.4	Summary of computational studies	216
I.5	Conclusions	216
Annex J (informative)	Skin enhancement factor	217
J.1	Background	217
J.2	Rationale	218
J.3	Simulations	218
J.4	Recommendation	219
Annex K (normative)	Application-specific phantoms	221
K.1	General	221
K.2	Phantom basic requirements	221
K.3	Examples of specific alternative phantoms	221
K.3.1	Face-down SAM phantom	221
K.3.2	Head-stand SAM phantom	222

K.3.3	Wrist phantom	222
K.4	Scanning and evaluation requirements.....	223
K.5	Uncertainty assessment.....	223
K.6	Reporting	223
Annex L (normative) Fast compliance evaluations using a flat-bottom phantom with a curved corner (Uniphantom).....		224
L.1	General.....	224
L.2	Uniphantom	224
L.3	Device positions for compliance testing and definitions of handset shapes	224
L.3.1	General	224
L.3.2	Handsets with a straight form factor.....	225
L.3.3	Handsets with a clamshell form factor.....	225
L.4	Testing procedure.....	225
L.4.1	General	225
L.4.2	Handsets with straight form factors.....	225
L.4.3	Handsets with clamshell form factors	226
L.5	Uncertainty of SAR measurement results using Uniphantom	227
Annex M (informative) Wired hands-free headset testing		228
M.1	Concept	228
M.2	Example results	229
M.3	Discussion	230
Annex N (informative) Applying the head SAR test procedures		231
Annex O (normative) Uncertainty analysis for measurement system manufacturers and calibration laboratories		234
O.1	Probe linearity and detection limits	234
O.2	Broadband signal uncertainty.....	235
O.3	Boundary effect	235
O.4	Field-probe readout electronics uncertainty.....	236
O.5	Signal step-response time uncertainty.....	236
O.6	Probe integration-time uncertainty	237
O.6.1	General	237
O.6.2	Probe integration-time uncertainty for periodic pulsed signals.....	237
O.6.3	Probe integration-time uncertainty for non-periodic signals	238
O.7	Contribution of mechanical constraints.....	238
O.7.1	Mechanical tolerances of the probe positioner (directions parallel to phantom surface).....	238
O.7.2	Probe positioning with respect to phantom shell surface	238
O.7.3	First-order approximation of exponential decay.....	239
O.8	Contribution of post-processing.....	239
O.8.1	General	239
O.8.2	Evaluation test functions.....	240
O.8.3	Data-processing algorithm uncertainty evaluations	242
O.9	Tissue-equivalent medium properties uncertainty.....	245
O.9.1	General	245
O.9.2	Medium density	245
O.9.3	Medium conductivity uncertainty	245
O.9.4	Medium permittivity uncertainty	245
O.9.5	Assessment of dielectric properties measurement uncertainties.....	245
O.9.6	Medium temperature uncertainty.....	247

Annex P (normative) Post-processing techniques	249
P.1 Extrapolation and interpolation schemes	249
P.1.1 General	249
P.1.2 Extrapolation schemes	249
P.1.3 Interpolation schemes	249
P.2 Averaging scheme and maximum finding	249
P.2.1 Volume average schemes	249
P.2.2 Finding the psSAR and estimating the uncertainty	250
Annex Q (informative) Rationale for time-period averaged SAR test procedure	251
Annex R (normative) Measurement uncertainty analysis for testing laboratories	252
R.1 RF ambient conditions	252
R.2 Device positioning and holder uncertainties	252
R.2.1 General	252
R.2.2 Device holder perturbation uncertainty	253
R.2.3 DUT positioning uncertainty with a specific test device holder: Type A	254
R.3 Probe modulation response	254
R.4 Time-period averaged SAR	255
R.4.1 General	255
R.4.2 TX factor uncertainty	255
R.5 Measured SAR drift	256
R.5.1 General	256
R.5.2 Accounting for drift	256
R.6 SAR scaling uncertainty	257
Annex S (normative) Validation antenna SAR measurement uncertainty	258
S.1 Deviation of experimental antennas	258
S.2 Other uncertainty contributions when using system validation antennas	258
Annex T (normative) Interlaboratory comparisons	260
T.1 Purpose	260
T.2 Phantom set-up	260
T.3 Reference devices	260
T.4 Power set-up	260
T.5 Interlaboratory comparison – procedure	261
Annex U (informative) Determination of the margin for compliance evaluation using the Uniphantom	262
U.1 General	262
U.2 Deviation of the psSAR measured using the Uniphantom from the psSAR measured using the SAM phantom	262
U.3 Determination of margin based on 95 % confidence interval	263
U.4 Examples of the determination of the margin factor	263
U.4.1 Margin for handsets with straight form factors at flat-bottom position	263
U.4.2 Margin for handsets with straight form factors (except smart phones at flat-bottom position)	265
U.4.3 Margin for smart phones at flat-bottom position	267
U.4.4 Margin for smart phones at corner position	269
U.4.5 Margin for handsets with clamshell form factors at corner position	271
Annex V (informative) Automatic input power level control for system validation	274
V.1 General	274
V.2 Operational mechanism of AIPLC	274
Annex W (informative) LTE test configurations supporting information	276

W.1	General.....	276
W.2	Study 1	276
W.3	Study 2	278
W.4	Justifications of relative standard deviations	279
Annex X (informative) Rationale for head phantom test reductions based on flat phantom SAR data.....		281
X.1	General.....	281
X.2	Rationale for SAR level threshold	281
X.3	Rationale for distance threshold.....	282
Annex Y (normative) Validation of motion sensors		284
Y.1	General.....	284
Y.2	Procedure	284
Y.3	Validation report	285
Bibliography.....		287
Figure 1 – Quick start guide.....		29
Figure 2 – Dimensions of the elliptical phantom		35
Figure 3 – Mounting of the DUT in the device holder using low-permittivity and low-loss foam to avoid changes of DUT performance by the holder material.....		37
Figure 4 – Designation of DUT reference points.....		42
Figure 5 – Measurements performed by shifting a large device over the efficient measurement area of the system including overlapping areas – in this case: six tests performed		42
Figure 6 – Test positions for body-worn devices		43
Figure 7 – Device with swivel antenna		44
Figure 8 – Test positions for body supported devices.....		46
Figure 9 – Test positions for desktop devices		48
Figure 10 – Test positions for front-of-face devices.....		49
Figure 11 – Test position for hand-held devices, not used at the head or torso		50
Figure 12 – Test position for limb-worn devices		50
Figure 13 – Test position for clothing-integrated wireless communication devices.....		51
Figure 14 – Possible test positions for a generic device		52
Figure 15 – Vertical and horizontal reference lines and reference points A and B on two example device types: a full touch-screen smart phone (left) and a DUT with a keypad (right)		54
Figure 16 – Cheek position of the DUT on the left side of SAM where the device position shall be maintained for the phantom test set-up.....		57
Figure 17 – Tilt position of the DUT on the left side of SAM		57
Figure 18 – An alternative form factor DUT with reference points and reference lines		58
Figure 19 – Block diagram of the tests to be performed		61
Figure 20 – Orientation of the probe with respect to the line normal to the phantom surface, for head and flat phantoms, shown at two different locations		65
Figure 21 – Measurement procedure for different types of correlated signals		73
Figure 29 – Example illustration of the output power characteristics of a simple TPAS implementation		77
Figure 22 – Positioning of the surfaces and edges of the DUT for determining the proximity sensor triggering distance.....		83

Figure 23 – Positioning of the edges of the DUT to determine proximity sensor triggering distance variations with the edge positioned at different angles from the perpendicular position.....	84
Figure 24 – Fast SAR Procedure A	91
Figure 25 – Fast SAR Procedure B	93
Figure 26 – Modified chart of Figure 19.....	98
Figure 27 – Use of conducted power for LTE mode selection, for Band 1 (1 920 MHz to 1 980 MHz) (MPR values are in dB)	101
Figure 28 – Use of conducted power for LTE mode selection, for Band 17 (704 MHz to 716 MHz) (MPR values are in dB)	102
Figure A.1 – Test set-up for the system check	124
Figure B.1 – Distribution of Tilt/Cheek.....	134
Figure B.2 – SAR relative to SAR in position with maximum SAR in GSM mode.....	138
Figure B.3 – Two points identifying the minimum distance between the position of the interpolated maximum SAR and the points at $0,6 \times SAR_{max}$	140
Figure B.4 – Histogram for D_{min} in the case of GSM 900 and iso-level at $0,6 \times SAR_{max}$	140
Figure B.5 – Histogram for random variable $Factor_{1g,1800}$	142
Figure D.1 – Mechanical details of the standard dipoles.....	155
Figure D.2 – Standard waveguide (dimensions are according to Table D.3)	158
Figure D.3 – Drawing of the CLA that corresponds to a resonant loop integrated in a metallic structure to isolate the resonant structure from the environment	160
Figure D.4 – Mechanical details of the meander dipoles for 150 MHz.....	162
Figure D.5 – VPIFA validation antenna	165
Figure D.6 – Mask for positioning VPIFAs	165
Figure E.1 – Experimental set-up for assessment of the sensitivity (conversion factor) using a vertically-oriented rectangular waveguide	172
Figure E.2 – Illustration of the antenna gain evaluation set-up	175
Figure E.3 – Schematic of the coaxial calorimeter system.....	179
Figure E.4 – Set-up to assess hemispherical isotropy deviation in tissue-equivalent medium.....	181
Figure E.5 – Alternative set-up to assess hemispherical isotropy deviation in tissue-equivalent medium.....	182
Figure E.6 – Experimental set-up for the hemispherical isotropy assessment.....	183
Figure E.7 – Conventions for dipole position (ξ) and polarization (θ)	184
Figure E.8 – Measurement of hemispherical isotropy with reference antenna.....	185
Figure G.1 – Illustration of dimensions in Table G.1 and Table G.2.....	192
Figure G.2 – Close up side view of phantom showing the ear region.....	194
Figure G.3 – Side view of the phantom showing relevant markings	195
Figure G.4 – Sagittally bisected phantom with extended perimeter (shown placed on its side as used for device SAR tests)	196
Figure G.5 – Picture of the phantom showing the central strip.....	196
Figure G.6 – Cross-sectional view of SAM at the reference plane	197
Figure G.7 – Dimensions of the flat phantom set-up used for deriving the minimal phantom dimensions for W and L for a given phantom depth D	199
Figure G.8 – FDTD predicted error in the 10 g psSAR as a function of the dimensions of the flat phantom compared with an infinite flat phantom at 800 MHz	200

Figure G.9 – Complex permittivity of human tissues compared to the phantom target properties	203
Figure G.10 – Example reference coordinate system for the left-ear ERP of the SAM phantom	204
Figure G.11 – Example coordinate system on a DUT	204
Figure H.1 – Slotted line set-up	206
Figure H.2 – An open-ended coaxial probe with inner and outer radii a and b , respectively	208
Figure H.3 – TEM line dielectric properties test set-up [85]	210
Figure J.1 – SAR and temperature increase (ΔT) distributions simulated for a three-layer (skin, fat, muscle) planar torso model.....	217
Figure J.2 – Statistical approach to protect 90 % of the population	219
Figure J.3 – psSAR skin enhancement factors	220
Figure K.1 – SAM face-down phantom	222
Figure K.2 – SAM head-stand phantom.....	222
Figure K.3 – Wrist phantom	223
Figure L.1 – Cross section of the unified phantom (Uniphantom) with its dimensions	224
Figure L.2 – Measurement positions of handsets with straight and clamshell form factors	225
Figure L.3 – Flow chart of testing procedure for handsets with straight form factors.....	226
Figure L.4 – Flow chart of testing procedure for handsets with clamshell form factors.....	227
Figure M.1 – Configuration of a personal wired hands-free headset.....	228
Figure M.2 – Configuration without a personal wired hands-free headset.....	229
Figure O.1 – Orientation and surface of averaging volume relative to phantom surface.....	245
Figure U.1 – Categories (classes) for comparison of the measured psSAR between the Uniphantom (SAR_{uni}) and the SAM phantom (SAR_{SAM})	262
Figure U.2 – Histogram of the deviation of the 10 g psSAR of 45 handsets with straight form factors positioned at the flat bottom of the Uniphantom.....	264
Figure U.3 – Histogram of the deviation of the 1 g psSAR of 40 handsets with straight form factors positioned at the flat bottom of the Uniphantom.....	265
Figure U.4 – Histogram of the deviation of the 10 g psSAR of 25 handsets with straight form factors positioned at the flat bottom of the Uniphantom.....	266
Figure U.5 – Histogram of the deviation of the 1 g psSAR from 20 handsets with straight form factors positioned at the flat bottom of the Uniphantom	267
Figure U.6 – Histogram of the deviation of the 10 g psSAR of 20 handsets with straight form factors or smart phones positioned at the flat bottom of the Uniphantom.....	268
Figure U.7 – Histogram of the deviation of the 1 g psSAR of 20 handsets with straight form factors or smart phones positioned at the flat bottom of the Uniphantom.....	269
Figure U.8 – Histogram of the deviation of the 10 g psSAR of 20 handsets with straight form factors or smart phones positioned at the corner of the Uniphantom	270
Figure U.9 – Histogram of the deviation of the 1 g psSAR of 19 handsets with straight form factors or smart phones positioned at the corner of the Uniphantom	271
Figure U.10 – Histogram of the deviation of the 10 g psSAR of 20 handsets with clamshell form factors at the corner of the Uniphantom.....	272
Figure U.11 – Histogram of the deviation of the 1 g psSAR of 19 handsets with clamshell form factors at the corner of the Uniphantom.....	273
Figure V.1 – Generated RF input power variations to operation time without and with application of AIPLC	274

Figure V.2 – The system block diagram of the AIPLC.....	275
Figure V.3 – Power variation characteristics by adjusting the amplifier or signal generator outputs	275
Figure W.1 – Low, middle, and high channels at 2 GHz band (Band 1)	277
Figure W.2 – RF conducted power versus 10 g psSAR	278
Figure W.3 – 1 g SAR as a function of RF conducted power in various test conditions	279
Figure X.1 – Number of test cases where the psSAR at a specified distance to the flat phantom is more than 5 % higher than the psSAR at $d = 0$ mm, and the psSAR is at least 0,2 W/kg.....	282
Figure X.2 – Distance along a representation of a planar DUT between the ERP and a point that is 10 mm from the SAM phantom outer shell.....	283
Figure X.3 – Example of a measured region (red and blue regions), where the red region indicates where all spatial-average SAR values shall be at least 5 dB below the applicable head SAR limit, per the test reduction criteria in 7.9.3.7	283
Figure Y.1 – Procedure for the validation of the power reduction	285
Table 1 – Evaluation plan checklist	28
Table 2 – Dielectric properties of the tissue-equivalent medium	32
Table 3 – Area scan parameters	64
Table 4 – Zoom scan parameters	64
Table 5 – Example method to determine the combined SAR value using Alternative 1	71
Table 6 – Root-mean-squared error SAR correction formula as a function of the maximum change in permittivity or conductivity [28].....	87
Table 7 – Threshold values $TH(f)$ used in this proposed test reduction protocol	97
Table 8 – Divisors for common probability density functions (PDFs).....	111
Table 9 – Uncertainty budget template for evaluating the uncertainty in the measured value of 1 g or 10 g psSAR from a DUT or validation antenna (N = normal, R = rectangular)	113
Table 10 – Uncertainty of Formula (8) (see 7.8.2) as a function of the maximum change in permittivity or conductivity	117
Table B.1 – The number of DUTs used for the statistical study	133
Table B.2 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various x values	134
Table B.3 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for 1 g and 10 g psSAR	134
Table B.4 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various antenna locations	135
Table B.5 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various frequency bands	135
Table B.6 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various device types	136
Table B.7 – Distance $D_{\min}^*$ for various “iso-level” values	140
Table B.8 – Experimental thresholds to have a 95 % probability that the maximum measured SAR value from the area scan will also have a psSAR.....	142
Table B.9 – SAR values from the area scan (GSM 900 band): Example 1	143
Table B.10 – SAR values from the area scan (GSM 900 band): Example 2	143
Table C.1 – Measurement uncertainty budget for relative SAR measurements using Class 2 fast SAR testing, for tests performed within one frequency band and modulation	151
Table C.2 – Measurement uncertainty budget for system check using Class 2 fast SAR testing	152

Table D.1 – Mechanical dimensions of the reference dipoles	156
Table D.2 – Numerical target SAR values (W/kg) for standard dipole and flat phantom	157
Table D.3 – Mechanical dimensions of the standard waveguide	158
Table D.4 – Numerical target SAR values for waveguides	159
Table D.5 – Numerical target SAR values for CLAs	161
Table D.6 – Mechanical dimensions of the reference meander dipole	162
Table D.7 – Numerical target SAR value (W/kg) for meander dipole	163
Table D.8 – Dimensions for VPIFA antennas at different frequencies	164
Table D.9 – Electric properties for the dielectric layers for VPIFA antennas	165
Table D.10 – Numerical target SAR values for VPIFAs on the flat phantom	166
Table E.1 – Uncertainty analysis for transfer calibration using temperature probes	170
Table E.2 – Guidelines for designing calibration waveguides	173
Table E.3 – Uncertainty analysis of the probe calibration in waveguide	174
Table E.4 – Uncertainty template for evaluation of reference antenna gain	176
Table E.5 – Uncertainty template for calibration using reference antenna	177
Table E.6 – Uncertainty components for probe calibration using thermal methods	180
Table F.1 – Suggested recipes for achieving target dielectric properties, 30 MHz to 900 MHz	188
Table F.2 – Suggested recipes for achieving target dielectric properties, 1 800 MHz to 10 000 MHz	189
Table G.1 – Dimensions used in deriving SAM phantom from the ARMY 90th percentile male head data (Gordon et al. [61])	193
Table G.2 – Additional SAM dimensions compared with selected dimensions from the ARMY 90th percentile male head data (Gordon et al. [61]) – specialist head measurement section	193
Table G.3 – Parameters used for calculation of reference SAR values in Table D.2	200
Table H.1 – Parameters for calculating the dielectric properties of various reference liquids	212
Table H.2 – Dielectric properties of reference liquids at 20 °C	213
Table J.1 – psSAR correction factors	219
Table N.1 – SAR results tables for example test results in GSM 850 band	231
Table N.2 – SAR results tables for example test results in GSM 900 band	232
Table N.3 – SAR results tables for example test results in GSM 1800 band	232
Table N.4 – SAR results tables for example test results in GSM 1900 band	233
Table O.1 – Parameters for the reference function f_1 in Formula (O.12)	241
Table O.2 – Reference SAR values from the distribution functions f_1 , f_2 , and f_3	242
Table O.3 – Example uncertainty template and example numerical values for permittivity (ϵ_r') and conductivity (σ) measurement	247
Table S.1 – Uncertainties relating to the deviations of the parameters of the standard waveguide from theory	258
Table S.2 – Other uncertainty contributions relating to the dipole antennas specified in Annex D	259
Table S.3 – Other uncertainty contributions relating to the standard waveguides specified in Annex D	259
Table U.1 – Summary of information to determine the margin for handsets with straight form factors positioned at the flat bottom of the Uniphantom	264

Table U.2 – Summary of information to determine the margin for handsets with straight form factors, including slide-type and bar handsets (except smart phones), positioned at the flat bottom of the Uniphantom	266
Table U.3 – Summary of information to determine the margin for the smart phones positioned at the flat bottom of the Uniphantom	268
Table U.4 – Summary of information to determine the margin for smart phones positioned at the corner of the Uniphantom	270
Table U.5 – Statistical analysis results of $P(\text{Tilt/Cheek} > x)$ for various device types	271
Table U.6 – Summary of information to determine the margin for handsets with clamshell form factors positioned at the corner of the Uniphantom	272
Table W.1 – Relative standard deviation of α found in Study 1 (without MPR)	277
Table W.2 – Maximum relative standard deviation of α found in Study 2 (with MPR)	279

Sample Document

get full document from standards.iteh.ai