

TECHNICAL SPECIFICATION

**Nanomanufacturing - Key control characteristics -
Part 4-9: Nano-enabled energy storage - Electrochemical characteristics of
carbon nanomaterial for the electrodes of electric double-layer capacitors: Coin
cell preparation**

get full document from standards.iteh.ai



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2026 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	3
INTRODUCTION	5
1 Scope	6
2 Normative references	6
3 Terms and definitions, acronyms and abbreviated terms	6
3.1 Terms and definitions	6
3.2 Acronyms and abbreviated terms	9
4 General	9
4.1 Coin-cell EDLC preparation principle	9
4.2 Description of measurement equipment/apparatus	9
4.3 Standard atmospheric conditions	10
4.4 Supporting materials	10
5 Assembling procedure	10
5.1 Pre-treatment of the electrode material	10
5.2 Electrode slurry making	11
5.2.1 Design	11
5.2.2 Weighing	11
5.2.3 Mixing	11
5.3 Coating	12
5.3.1 Measure the thickness and surface density of the current collector	12
5.3.2 Electrode coating	12
5.4 Rolling	13
5.5 Cutting and weighing	13
5.6 Drying	13
5.7 Assembling	14
5.7.1 Pre-treatment of the cell components	14
5.7.2 Assembling	14
5.8 Standing	14
6 Data to be recorded	14
6.1 General	14
6.2 Sample information	14
6.3 Assembly conditions	14
6.4 Assembly information and data	15
Annex A (informative) Data recording	16
A.1 Format of the record	16
A.2 Format of assembly information and data	16
Annex B (informative) Structure of the coin cell	18
Annex C (informative) Case study – Nanoporous activated carbon	19
C.1 Coin cells preparation	19
C.1.1 Pre-treat of material	19
C.1.2 Slurry mixing	19
C.1.3 Coating	20
C.1.4 Rolling, cutting and weighing	22
C.1.5 Drying	23
C.1.6 Assembling	23
C.1.7 Standing	25

C.2 Data recording	25
Bibliography	27
Figure B.1 – Components and stacking structure for the coin-cell EDLC	18
Figure C.1 – Drying active material and conductor	19
Figure C.2 – Slurry preparation	20
Figure C.3 – The coating process of electrodes	21
Figure C.4 – Electrode cutting and weighing	22
Figure C.5 – Electrode drying	23
Figure C.6 – Assembly process of coin-cell EDLCs	25
Table 1 – Key measurement equipment/apparatus	9
Table A.1 – Sample identification (according to IEC 62565-5-1)	16
Table A.2 – Slurry information	16
Table A.3 – Current collector and separator information	16
Table A.4 – Electrode disc information	17
Table A.5 – Electrolyte information	17
Table A.6 – Coin-cell EDLC information	17
Table C.1 – Mass of disc electrode	20
Table C.2 – The mass of electrode disc	23
Table C.3 – Product identification	25
Table C.4 – Slurry information	25
Table C.5 – Current collector and separator Information	26
Table C.6 – Electrode disc Information	26
Table C.7 – Electrolyte Information	26
Table C.8 – Coin cell Information	26

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**Nanomanufacturing - Key control characteristics -
Part 4-9: Nano-enabled energy storage - Electrochemical characteristics
of carbon nanomaterial for the electrodes of electric double-layer
capacitors: Coin cell preparation**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 62607-4-9 has been prepared by IEC technical committee 113: Nanotechnology for electrotechnical products and systems. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

Draft	Report on voting
113/960/DTS	113/984/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts of the IEC TS 62607 series, published under the general title *Nanomanufacturing - Key control characteristics*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

Sample Document

get full document from standards.iteh.ai

INTRODUCTION

Electrochemical capacitors are widely used in electric vehicles, high-speed trains, aviation, photovoltaics, wind power and electronics, due to their ultra-fast charge/discharge capability, long cycle life, wide working temperature range, high safety and reliability and low maintenance costs.

Electric double-layer capacitors (EDLCs) are a type of electrochemical capacitors. The mechanism of energy storage for EDLCs relies on reversible ion adsorption at the active material-electrolyte interface. Therefore, materials with large specific surface area – such as nanoporous carbon materials – are commonly employed as active materials in EDLCs. Additionally, to improve the electrode conductivity, high-conductivity materials (e.g. carbon black, graphene, and carbon nanotubes/CNTs) serve as conductive agents in EDLCs. Thus, carbon nanomaterials play an irreplaceable and critical role in EDLCs, directly determining their electrochemical performance.

The electrochemical performance of carbon nanomaterials for EDLCs requires proper electrochemical characterization. Prior to such measurements, the carbon nanomaterials will be pre-assembled into devices such as coin cells, three-electrode cells, or cylindrical cells. Coin-cell-based characterization offers advantages including low cost, versatility, and high efficiency, making it widely used in both academic and industrial settings.

The assembly process of a coin-cell EDLC is time-consuming and complex, which typically involves electrode slurry preparation, slurry coating onto current collectors, electrode rolling, cutting the rolled electrodes into multiple electrode discs, and final EDLC assembly. Each step contains numerous factors that can exert a significant impact on the accuracy of subsequent electrochemical performance characterization of the materials. Therefore, standardizing the coin-cell preparation process is an essential prerequisite for achieving accurate, highly reproducible, and repeatable electrochemical performance determination.

This document introduces a standard method and process to assemble the coin-cell EDLCs of carbon nanomaterials.

1 Scope

This part of IEC TS 62607 establishes a standardized method for assembling

- coin-cell EDLCs

in order to characterize the electrochemical key control characteristic of carbon nanomaterials.

The coin-cell EDLC is fabricated through sequential steps: electrode slurry preparation (mixing), coating, rolling, cutting, weighing, and final assembly.

- The document specifies the assembly process and data recording.
- The document is applicable for carbon nanomaterials used in EDLC as active material or conductive agents, such as nanoporous activated carbon, carbon aerogel, carbon nanotube, carbon black, graphene, nano graphite sheet, vapour-grown carbon fibre and so on.
- Typical application areas of this method are research, manufacturer and downstream user to guide material processing and quality control.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC TS 62565-5-1:2023, *Nanomanufacturing - Product specifications - Part 5-1: Nanoporous activated carbon - Blank detail specification: Electrochemical capacitors*

3 Terms and definitions, acronyms and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1.1

electric double-layer capacitor

EDLC

device for electrostatic storage of electrical energy achieved by separation of charge in a double layer

[SOURCE: ISO 18300:2016, 3.8]

3.1.2

coin cell

cell with a cylindrical shape in which the overall height is less than the diameter e.g. in the shape of a button or a coin

Note 1 to entry: In practice, the term coin is used exclusively for non-aqueous lithium cells.

Note 2 to entry: Button cell is equivalent to coin cell.

[SOURCE: IEC 60050-482:2004, 482-02-40, modified – "button cell" has been moved to a note 2 to entry.]

3.1.3

active material

material that can be used to store energy by electrochemical double-layer or pseudo capacitance effect

Note 1 to entry: Typically, nonreactive carbon materials are electric double-layer capacitance active material, including activated carbon, pure carbon nanotube and pure graphene.

Note 2 to entry: Typically, carbon composites and carbons embedded with heteroatoms are pseudo capacitance active material.

[SOURCE: IEC TS 62565-5-2:2022, 3.3.1]

3.1.4

activated carbon

carbon, usually in the form of granules, treated to enhance its surface area and consequent ability to adsorb and desorb the ions through a highly developed pore structure

Note 1 to entry: Activated charcoal is equivalent to activated carbon.

[SOURCE: IEC TS 62565-5-1:2023, 3.2.5, modified – "activated charcoal" has been moved to a note 1 to entry.]

3.1.5

nanoporous activated carbon

activated carbon with nanopores

Note 1 to entry: The performance of such activated carbon application mainly depends on its nanoporous structure

[SOURCE: IEC TS 62565-5-1:2023, 3.2.6]

3.1.6

electrode

conductive part in electric contact with a medium of lower conductivity and intended to perform one or more of the functions of emitting charge carriers to or receiving charge carriers from that medium or to establish an electric field in that medium

[SOURCE: IEC 60050-151:2001, 151-13-01]

3.1.7

binder

resinous material which serves to bind the various component materials