

TECHNICAL SPECIFICATION

**Nanomanufacturing - Key control characteristics -
Part 6-27: Graphene-related products - Field-effect mobility for layers of two-
dimensional materials: field-effect transistor method**

Document Preview

IEC TS 62607-6-27:2025

<https://standards.iteh.ai/catalog/standards/iec/c6403e3d-284c-4e6b-baa4-6ddd08e34141/iec-ts-62607-6-27-2025>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2025 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

[IEC TS 62607-6-27:2025](https://standards.iteh.ai/catalog/standards/iec/c6403e3d-284c-4e6b-baa4-6ddd08c34141/iec-ts-62607-6-27-2025)

<https://standards.iteh.ai/catalog/standards/iec/c6403e3d-284c-4e6b-baa4-6ddd08c34141/iec-ts-62607-6-27-2025>

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	3
INTRODUCTION	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	6
3.1 General terms	6
3.2 Key control characteristics measured according to this standard	7
3.3 Terms related to the measurement method	7
4 General	8
4.1 Measurement principle	8
4.2 Description of the measurement equipment	9
4.3 Sample preparation method	9
4.3.1 Sample preparation	9
4.3.2 Fabrication of FETs with a 2D channel material	9
4.4 Description of measurement equipment	10
5 Measurement procedure	10
6 Data analysis	11
Annex A (informative) Worked example – 2PP and 4PP mobility measurements in bottom-contacted WSe ₂ FETs	13
A.1 Background	13
A.2 Results to be reported	14
Annex B (informative) Worked example – 2PP and 4PP mobility measurements in an organic FET	15
B.1 Background	15
B.2 Results to be reported	15
Annex C (informative) Worked example – Mobility measurements on WSe ₂ FETs	17
C.1 Background	17
C.2 Results to be reported	18
Bibliography	19

Figure 1 – Schematic of field-effect transistor where V_g and V_{ds} are the gate voltage and drain voltage applied with respect to source

8

Figure 2 – Determination of field-effect mobility using a current–voltage transfer curve of a FET

9

Figure 3 – Schematic (left) and optical microscope image (right) of the four-terminal configuration

11

Figure 4 – Transfer curve (a) and corresponding transconductance (b) used to obtain field-effect mobility which is extracted from the transconductance of a FET biased in the linear regime

11

Figure 5 – Mobilities obtained as a function of gate voltage

12

Figure A.1 – Schematic of FET WSe₂ used for 2PP mobility measurement

13

Figure A.2 – Cross-sectional schematic

13

Figure A.3 – Optical microscopic picture of a FET used for 4PP mobility measurement

14

Figure B.1 – Device structure used for 2PP and 4PP measurements

15

Figure B.2 – Comparison of the 2PP and 4PP mobility measurements in a rubrene single-crystal organic FET for different gate voltages	16
Figure C.1 – Colour-corrected optical image	17
Figure C.2 – Schematic cross section of the device	17
Figure C.3 – Temperature-dependent transfer characteristics showing the linear region of device operation for $V_{GS} < -80$ V	18
Figure C.4 – Extracted field-effect mobility at $V_{GS} = -95$ V at different temperatures	18
Table A.1 – Comparison of 2PP and 4PP mobilities	14

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[IEC TS 62607-6-27:2025](https://standards.iteh.ai/catalog/standards/iec/c6403e3d-284c-4e6b-baa4-6ddd08c34141/iec-ts-62607-6-27-2025)

<https://standards.iteh.ai/catalog/standards/iec/c6403e3d-284c-4e6b-baa4-6ddd08c34141/iec-ts-62607-6-27-2025>