



INTERNATIONAL STANDARD

Explosive atmospheres -

Part 38: Equipment and components in explosive atmospheres in underground mines

Sample Document

get full document from standards.iteh.ai



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2026 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search -

webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	4
INTRODUCTION	9
1 Scope	10
2 Normative references	10
3 Terms, definitions and abbreviated terms	12
4 Requirements for Ex Equipment and Ex Components	13
4.1 General	13
4.2 Ignition hazard assessment	13
4.3 Non-electrical Ex Equipment and Ex Components	14
4.4 Electrical Ex Equipment and Ex Components	14
4.4.1 General	14
4.4.2 Over-current protection	14
4.4.3 Earth-fault protection	15
4.4.4 Charging of cells or batteries	16
4.4.5 Mechanical protection of live parts	16
4.4.6 Electric cables that are part of the Ex Equipment	16
5 Additional requirements for specific Ex Equipment and Ex Components	17
5.1 Cutting and stripping equipment	17
5.1.1 General	17
5.1.2 Mining machines with cutting picks	17
5.1.3 Stripping mining machines	18
5.2 Rope haulages for level and inclined transport	18
5.3 Fans	18
5.3.1 Ventilating fans for use in underground parts of mine	18
5.3.2 Other fans	20
5.4 Internal combustion engines	21
5.5 Air compressors	21
5.6 Ex Equipment and Ex Components for drilling	21
5.7 Brakes	22
5.7.1 Brakes used only for stopping in emergency	22
5.7.2 Service brakes (including friction brakes and fluid based retarders)	22
5.8 Traction batteries, starter batteries and vehicle lighting batteries	22
5.9 Equipment and transmission systems using optical radiation	23
5.10 Electromagnetic and ultrasonic energy radiating equipment	23
5.11 Gas monitoring systems	23
6 EPL Ma equipment having the requisite Level of Protection using a second independent means	23
6.1 General	23
6.2 Requirements for an outer enclosure as the second independent means	23
6.2.1 Temperature rise limits	23
6.2.2 Outer enclosure with free space inside	23
6.2.3 Outer enclosure with no free space inside	24
6.2.4 Prevention of ingress of combustible dust and water	24
6.3 Restriction on internal equipment	24
6.4 Additional type testing for equipment meeting the requisite Level of Protection by a second independent means	24
6.5 Examples of EPL Ma Equipment having two forms of protection listed in 6.3	25

7	Fire protection	26
7.1	General.....	26
7.2	Non-metallic materials	27
7.3	Hydraulic and pneumatic equipment.....	27
7.3.1	Hydraulic equipment	27
7.3.2	Pneumatic equipment	27
7.4	Fire resistant fluids	27
7.5	Cable-reeling equipment	28
7.6	Fire prevention on electric cables that are part of the mining machine	29
8	Information for use	29
8.1	Signals and warning notices	29
8.2	Instructions	29
8.2.1	Information on use	29
8.2.2	Information on maintenance and repair	29
9	Marking	30
Annex A (informative) Example of an ignition hazard assessment for a shearer intended for use in an explosive atmosphere of a coal mine.....		31
A.1	General.....	31
A.2	EPL and intended use of equipment.....	31
A.3	Construction/description of the equipment with regard to ignition protection.....	31
A.4	Ignition control and monitoring system	32
A.5	Compliance with the basic methodology and requirements in IEC 60079-0 and ISO 80079-36.....	32
A.6	Ignition hazard assessment of the electrical parts of the equipment	33
A.7	Ignition hazard assessment of non-electrical ignition sources	33
A.8	Equipment marking	36
Annex B (informative) Additional guidance.....		37
B.1	Establishing maximum service temperature	37
B.2	Dust deposits and other material in the gap of moving parts	37
B.3	Short-circuit protection.....	37
B.4	Earth-fault protection	37
B.5	Electric cables that are part of the equipment	37
B.6	Cutting and stripping equipment.....	38
B.7	Cable-reeled equipment.....	38
Bibliography.....		39
Figure 1 – EPL Ma encapsulation "mb" or powder filling "q" equipment inside a flameproof enclosure "db" or pressurized enclosure "pxb" enclosure with optional intrinsically safe outputs		25
Figure 2 – EPL Ma increased safety "eb" or intrinsically safe "ib" apparatus inside a flameproof "db" or a pressurized "pxb" enclosure.....		25
Figure 3 – EPL Ma constructional safety "c" inside a flameproof "db" or pressurized "pxb" enclosure.....		26
Figure 4 – EPL Ma intrinsically safe "ib" or increased safety "eb" apparatus inside an enclosure with encapsulation "mb", or powder filling "q" or "qb"		26
Figure A.1 – Layout and construction of the coal face shearer		32

Table 1 – Combination of materials20

Table 2 – Limit values for hydraulic fluids28

Table A.1 – Example of an ignition hazard assessment for a shearer, EPL Mb (1 of 3)33

Sample Document

get full document from standards.iteh.ai

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**Explosive atmospheres -
Part 38: Equipment and components in explosive
atmospheres in underground mines**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC and ISO draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC and ISO take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC and ISO had not received notice of patents, which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch> and www.iso.org/patents. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 80079-38 has been prepared by IEC technical committee 31: Equipment for explosive atmospheres. It is an International Standard.

It is published as a double logo International Standard.

This second edition cancels and replaces the first edition, published in 2016. This edition constitutes a technical revision.

Users of this document are advised that interpretation sheets clarifying the interpretation of this document can be published. Interpretation sheets are available from the IEC webstore and can be found in the "history" tab of the page for each document.

The significance of changes between ISO/IEC 80079-38:2016 (Edition 1) and ISO/IEC 80079-38: (Edition 2) is as listed below:

Changes	Clause	Type		
		Minor and editorial changes	Extension	Major technical changes
Throughout document where appropriate changed "equipment" and "components" to "Ex Equipment" and "Ex Components"	General	X		
Throughout the document "machine" changed to "mining machine"	General	X		
Throughout the body of the document removed the use of "should" by, in most cases, moving the clause to Annex B as guidance	General			C1
References to "standard" changed to "document" where appropriate in accordance with ISO/IEC Directives	General	X		
Throughout the document changed "e.g." to "for example" in accordance with TC 31 Good Working Practice	General	X		
Scope changed to cover "construction, testing and marking for use in Group I" from "design, construction, assessment and information for use (maintenance, repair, marking)". Hand tools are no longer covered by the standard	1			C2
Note added to scope to clarify that Group I takes account that coal dust can be present with or without methane	1	X		
Note added to scope to clarify that Group I also covers mines other than coal mines	1	X		
Note added to scope to clarify that "assembly" is not identical to the meaning in IEC 60079-46	1	X		
Scope expanded to cover EPL Ma as well as EPL Mb	1			C3
Scope changed to allow this document to be used for guidance on underground applications where firedamp or coal dust can be present but which are not Group I mines, for example tunnels	1		X	
Deletion of definitions in IEC 60079-0	Former 3.1, 3.7, 3.10, 3.14, 3.15 and 3.16	X		
Deletion of definition "protection against firedamp explosions"	Former 3.2	X		
Change of definition of "flammable substance" to align with definition in IEC 60079-10-1.	3.1	X		
Deletion of definition "component" and introduction of use of term "Ex Component" from IEC 60079-0	Former 3.4	X		
Deletion of definition of "equipment" and introduction of use of term "Ex Equipment" from IEC 60079-0	Former 3.5	X		
Deletion of definition "explosion"	Former 3.6	X		
Deletion of definition "intended use"	Former 3.8	X		
Change of definition of "machinery" to "mining machinery" with added admitted term of "mining machine"	3.2	X		
Deletion of definition "minimum ignition energy"	Former 3.11	X		

		Type		
Changes	Clause	Minor and editorial changes	Extension	Major technical changes
Deletion of definition "potentially explosive atmospheres"	Former 3.12	X		
Deletion of definition "self-ignition of dust in bulk"	Former 3.13	X		
Deletion of definition of mechanical sparks	Former 3.19	X		
Deletion of definition of incendive sparks	Former 3.20	X		
Introduction of definition of "safety device" from IEC TS 60079-42	3.5	X		
Introduction of requirements regarding Specific Conditions of Use	4.1		X	
Rewording of requirements for ignition hazard assessment including reference to ISO 80079-36	4.2	X		
Revision of requirements regarding insulation faults to provide two options.	4.4.3		X	
Introduction of requirements for temperature rating of cables	4.4.6.1		X	
Rewording of requirements for ventilating fans	5.3.1	X		
Reference to standard for internal combustion engines – ISO/IEC 80079-41	5.4		X	
Reference to requirements in IEC 60079-0 for traction batteries, starter batteries and vehicle lighting batteries	5.8	X		
Additional requirement for batteries not complying with IEC 60079-11 Ex ia Ma to comply with IEC 60079-33 Ex sa Ma	5.8		X	
Optical radiation requirements in standard replaced with requirement to comply with IEC 60079-28	5.9	X		
Electromagnetic and ultrasonic energy radiating equipment requirements in standard replaced with requirement to comply with IEC 60079-0	5.10	X		
Gas monitoring now refers to IEC 60079-29-0 and does not include any other requirements.	5.11			C4
Note added to state that gas detector can be required on mobile mining machines	5.11	X		
New clause "EPL Ma equipment having the requisite Level of Protection using a second independent means" has been added	6			C5
Subclause headings added for General and Fire resistant fluids and clause reorganised to separate requirements for hydraulic and pneumatic equipment. Compliance with ISO 4413 and ISO 4413 introduced	7.3	X		C6
Requirements for conveyor belting deleted	Former 6.7			C7
Marking requirements revised including for EPL Ma and EPL Mb situations	9			C8
Example of an ignition hazard assessment for a conveyor belt intended for use in a coal mine deleted as conveyor belts are no longer part of the standard	Former Annex A			C9
Deletion of Annex on ignition sources as information is in ISO 80079-36	Former Annex C			C10

		Type		
Changes	Clause	Minor and editorial changes	Extension	Major technical changes
Deletion of Annex on Guidance on potential risks for converter-fed motors	Former Annex D			C11
Tests for surface protective coating for Group I hand tools of EPL Mb deleted as hand tools are not part of this edition	Former Annex E			C12
Inclusion of informative guidance material, most of which was formerly in body of standard	Annex B			C13

NOTE The technical changes referred to include the significance of technical changes in the revised IEC Standard, but they do not form an exhaustive list of all modifications from the previous version. More guidance can be found by referring to the Redline Version of the standard.

Explanations:

a) Definitions

Minor and editorial changes clarification
decrease of technical requirements
minor technical change
editorial corrections

These are changes which modify requirements in an editorial or a minor technical way. They include changes of the wording to clarify technical requirements without any technical change, or a reduction in level of existing requirement.

Extension addition of technical options

These are changes which add new or modify existing technical requirements, in a way that new options are given, but without increasing requirements for equipment that was fully compliant with the previous standard. Therefore, these will not have to be considered for products in conformity with the preceding edition.

Major technical changes addition of technical requirements
increase of technical requirements

These are changes to technical requirements (addition, increase of the level or removal) made in a way that a product in conformity with the preceding edition will not always be able to fulfil the requirements given in the later edition. These changes have to be considered for products in conformity with the preceding edition.

NOTE These changes represent current technological knowledge. However, these changes should not normally have an influence on equipment already placed on the market.

b) Information about the background of changes

- C1 The body of the document has been changed to only mandatory text to make it more suitable to use for conformity assessment.
- C2 The scope was made clearer for the application and to remove hand tools from the scope.
- C3 The scope was expanded to include EPL Ma equipment as well as EPL Mb equipment.
- C4 The relevant standard for gas monitoring has changed from IEC 60079-29 to IEC 60079-29-0 and hence the latest standard is referenced.
- C5 The new section now provides requirements relevant to EPL Ma.
- C6 Reference to compliance with ISO 4413 and ISO 4414 introduces additional requirements for hydraulic and pneumatic equipment.

- C7 Conveyor belts are no longer part of the scope and so requirements were deleted.
- C8 Marking updated to address both EPL Ma and EPL Mb with the introduction of EPL Ma in the scope.
- C9 See C6 regarding conveyor belts and hence example no longer relevant.
- C10 The information on ignition sources is available in ISO 80079-36 and so there is no need to duplicate the information here.
- C11 There is no calling clause to this annex and the information is of a general nature not specific to mines
- C12 With hand tools now longer in the scope, this test is no longer needed.
- C13 Most of the guidance material from the body of the previous edition of the standard is now in this annex.

The text of this International Standard is based on the following documents:

Draft	Report on voting
31M/302/FDIS	31M/315/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts of the IEC 60079 series, under the general title *Explosive atmospheres*, as well as the ISO/IEC 80079 series, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INTRODUCTION

This part of ISO/IEC 80079 specifies requirements for the constructional features of Ex Equipment and Ex Components that can be an individual item or form an assembly, to enable them to be used in mines, or parts of mines, susceptible to explosive atmospheres of firedamp, combustible dust or a combination of the two.

Most of the Ex Equipment used on mining machinery complies with the Type of Protection standards as an individual item of equipment, for example motors and switchgear, and they have their own marking requirements. The Type of Protection standards, however, do not deal with the interconnection of Ex Equipment and Ex Components.

Both non-electrical Ex Equipment and the interconnection of electrical/non-electrical Ex Equipment can require an ignition hazard assessment.

The need for this document arises because of major operational differences between underground mining operations and those in other industries working with, or in, explosive atmospheres. Examples of these differences are:

- firedamp can be released during the extraction of coal or other mining where firedamp is trapped;
- the ignitability of the atmosphere around Ex Equipment and Ex Components usually depends upon the amount of dilution offered by an active ventilating system;
- the atmosphere in the general body of mine air in which machinery is working can change from one that is not explosive to one that is explosive (for example, during an outburst of firedamp) and, depending on the likelihood, this can impact on the EPL required (Ma versus Mb);
- persons working in the mine can be situated in an explosive atmosphere if there is an increase in the concentration of firedamp; there is a need to monitor constantly the mine atmosphere at strategic places to ensure that power can be disconnected from all Ex Equipment except EPL Ma Ex Equipment which is suitable for use in a constantly present explosive atmosphere;
- in gassy coal mines, an initial explosion of firedamp can raise combustible dust clouds that when ignited commonly provide a significantly more serious explosion;
- some mining machinery contains cutting devices and drilling devices that can produce an ignition risk from sparks generated from contact with strata containing high concentrations of quartz or iron pyrites; and
- long roadways in coal mines are equipped with mineral conveying systems carrying a product that has a potential for raising a combustible dust cloud and the release of firedamp.

1 Scope

This part of ISO/IEC 80079 is applicable for the explosion protection requirements for the construction, testing and marking for Group I Ex Equipment that can be an individual item, or be an assembly of multiple items of Ex Equipment and Ex Components forming mining machinery.

NOTE 1 The Group I designation takes account of the fact coal dust (which is a combustible dust) is expected to be present, with or without the presence of firedamp, which is predominately methane.

NOTE 2 The definition of Group I also covers mines other than coal mines that are susceptible to firedamp.

NOTE 3 The term "assembly" as used in this document is not identical in meaning to the term "Equipment Assembly" as defined in IEC 60079-46.

The standard atmospheric conditions (relating to the explosion characteristics of the atmosphere) under which it can be assumed that Ex Equipment can be operated are:

- temperature $-20\text{ }^{\circ}\text{C}$ to $+60\text{ }^{\circ}\text{C}$;
- pressure 80 kPa (0,8 bar) to 110 kPa (1,1 bar); and
- air with normal oxygen content, typically a volume fraction of 21 %.

This part of ISO/IEC 80079 applies for Ex Equipment and Ex Components with Explosion Protection Levels (EPLs) Ma and Mb.

This document supplements and modifies the general requirements of IEC 60079-0. Where a requirement of this document conflicts with a requirement of IEC 60079-0, the requirement of this document takes precedence.

This document can be used for guidance on underground applications where firedamp or coal dust can be present, but which are not Group I mines, for example tunnels.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60079-0, *Explosive atmospheres - Part 0: Equipment - General requirements*

IEC 60079-5, *Explosive atmospheres - Part 5: Equipment protection by powder filling "q"*

IEC 60079-7, *Explosive atmospheres - Part 7: Equipment protection by increased safety "e"*

IEC 60079-11, *Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"*

IEC 60079-18, *Explosive atmospheres - Part 18: Equipment protection by encapsulation "m"*

IEC 60079-25, *Explosive atmospheres - Part 25: Intrinsically safe electrical systems*

IEC 60079-28, *Explosive atmospheres - Part 28: Protection of equipment and transmission systems using optical radiation*

IEC 60079-29-0, *Explosive atmospheres - Part 29-0: Gas detection equipment - General requirements and test methods*