
**Rubber hoses and hose assemblies for
automobile power-steering systems —
Specification**

*Tuyaux et flexibles en caoutchouc pour circuits de direction
assistée — Spécifications*

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 11425:2018

<https://standards.iteh.ai/catalog/standards/iso/0f19a052-9472-44f0-ac83-24163f9a9654/iso-11425-2018>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 11425:2018

<https://standards.iteh.ai/catalog/standards/iso/0f19a052-9472-44f0-ac83-24163f9a9654/iso-11425-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Types of hose	2
5 Construction and materials	2
6 Dimensions and tolerances	2
7 Performance requirement	3
7.1 Impulse resistance	3
7.2 Burst pressure requirement	3
7.3 Change in length	3
7.4 Low-temperature flexibility	3
7.5 Adhesion	4
7.6 Ozone resistance	4
7.7 Volumetric expansion	4
7.8 Contamination	4
7.9 Corrosion of end fittings	4
7.10 Proof pressure requirement	4
7.11 Cold-start requirement (type approval test for type 4 hose assemblies only)	4
7.11.1 Requirement	4
7.11.2 Test method	5
7.12 Low-pressure burst pressure requirement (type 4 hose assemblies only)	5
8 Marking	5
Annex A (normative) Method of test for volumetric expansion	6
Annex B (normative) Method of test for contamination	8
Annex C (informative) Typical outside-diameter ranges	10