
**Soil quality — Assessment of
impact from soil contaminated with
petroleum hydrocarbons**

*Qualité du sol — Évaluation de l'impact du sol contaminé avec des
hydrocarbures pétroliers*

Sample Document

get full document from standards.iteh.ai



Reference number
ISO 11504:2017(E)

© ISO 2017

Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	3
5 Relevant fractions and individual compounds	4
5.1 General.....	4
5.2 Fractions.....	4
5.3 Individual compounds.....	5
6 Petroleum hydrocarbons in soil	6
7 Exposure assessment of petroleum hydrocarbons in soil	8
7.1 General.....	8
7.2 Relevant exposure routes for petroleum hydrocarbons.....	9
7.3 Exposure assessment methods.....	9
7.4 Toxicity assessment methods.....	10
7.5 Relations between oil fractions in different media related to exposure.....	11
8 Issues related to sampling and investigation	13
8.1 General.....	13
8.2 Issues related to analysis.....	13
Annex A (informative) Physico-chemical properties of different petroleum hydrocarbons, etc.	15
Annex B (informative) Examples of suggested tolerated concentration in air (TCA) and tolerable daily intake (TDI) values for different specific petroleum hydrocarbons	19
Annex C (informative) Overview of suggested fractionations in different countries	20
Bibliography	22

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 190, *Soil quality*, Subcommittee SC 7, *Soil and site assessment*.

This second edition cancels and replaces the first edition, which has been technically revised.

Introduction

Petroleum hydrocarbons (PHCs) are common environmental contaminants. They are components of crude oil and products derived from it and are consequently found on a variety of sites including refineries, sites where they are used as feedstock (e.g. for manufacture of plastics), manufactured gas production sites, sites where hydrocarbons are used as fuel or lubricants and retail service stations. They may also be present as a result of spills and leaks during transportation or related to vehicle accidents.

Petroleum hydrocarbons can present unacceptable risks to the health and safety of humans, ecological systems, surface water, groundwater resources and to structures and building materials. Measuring the total concentration of petroleum hydrocarbons (TPH) in soil (and pore water and pore gas) does not give a useful basis for the evaluation of the potential risks to man and the environment. The variety of physical-chemical properties, and thus differences in the migration and fate of individual compounds, and the toxicity and carcinogenicity of different fractions and compounds in oil products, need to be taken into account in human health and environmental risk assessments.

Only a limited number of individual compounds can be routinely identified and quantified. It is, consequently, important to adopt methods of analysis that provide information about the amount of different hydrocarbon fractions present, preferably distinguishing between aliphatic and aromatic fractions, and the concentrations of single compounds of particular concern with respect to the potential health and environmental risks that they pose.

Although most petroleum hydrocarbons found in soil are of anthropogenic nature, there are some natural sources of these materials and other organic substances (e.g. peat and coal). The analytical methods historically used for the measurement of total petroleum hydrocarbons (TPH) tend to measure natural materials as TPH. This issue will not be dealt with in this document, except to note that a method which is able to give a more precise determination of the petroleum hydrocarbons is less prone to giving results that can be misinterpreted and potentially lead to unnecessary or unsustainable remedial actions.

The purpose of this document is to give recommendations with respect to the choice of relevant fractions and individual compounds, and to give guidance on the appropriate use of the results. Decisions about which analytical methods to adopt are based primarily on the need to provide the right type and quality of data for use in risk assessments. This requires consideration of how the results of the analysis are most appropriately used in a risk assessment, e.g. how can the fractions be used in exposure models and assessments, and how sufficient it is to analyse soil or necessary to obtain related values in other media as well (pore water and pore gas).

There are five existing International Standards covering the analysis of the range of petroleum hydrocarbons of interest. ISO 16703, ISO 16558-1 and ISO/TS 16558-2 can be used to measure mineral oil (C10 to C40) and ISO 22155 or ISO 15009 to measure volatiles. However, methods need to be able to properly measure the fractions and compounds recommended for determination in this document. ISO/TC190 has thus developed standards for methods of analysis designed to be compatible with the recommendations provided in this document: ISO 16558-1, which describes a method for determination of aliphatic and aromatic fractions of volatile petroleum hydrocarbons, and ISO 16558-2, which describes a method for the determination of aliphatic and aromatic fractions of semi-volatile petroleum hydrocarbons.

Sample Document

get full document from standards.iteh.ai

Soil quality — Assessment of impact from soil contaminated with petroleum hydrocarbons

1 Scope

This document gives guidelines with regard to the choice of fractions and individual compounds when carrying out analysis for petroleum hydrocarbons in soils, soil materials and related materials, including sediments, for the purpose of assessing risks to human health, the environment and other possible receptors. Since many products based on petroleum hydrocarbons often contain substances that are not hydrocarbons, the recommendations also encompass such compounds where relevant.

This document also includes relevant background information on which the recommendations are based together with guidance on the use of the fractions recommended in the assessment of risk.

This document does not set criteria or guidelines for use as assessment criteria, since this is typically a national or regional regulatory issue. This document also does not include recommendations as to the specific model for the exposure assessment or the specific parameter values to be used; with respect to guidance on this matter, reference is made to ISO 15800.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 11074, *Soil quality — Vocabulary*

ISO 15800, *Soil quality — Characterization of soil with respect to human exposure*

ISO 16558-1, *Soil quality — Risk-based petroleum hydrocarbons — Part 1: Determination of aliphatic and aromatic fractions of volatile petroleum hydrocarbons using gas chromatography (static headspace method)*

ISO 16558-2, *Soil quality — Risk-based petroleum hydrocarbons — Part 2: Determination of aliphatic and aromatic fractions of semi-volatile petroleum hydrocarbons using gas chromatography with flame ionization detection (GC/FID)*

ISO 18400-105, *Soil quality — Sampling — Part 105: Packaging, transport, storage and preservation of samples*

ISO 18512, *Soil quality — Guidance on long and short term storage of soil samples*

ISO 25177, *Soil quality — Field soil description*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 11074, ISO 15800 and ISO 25177 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

- 3.1**
aliphatic hydrocarbon
acyclic or cyclic, saturated or unsaturated carbon compound, excluding aromatic compounds
- 3.2**
aromatic hydrocarbon
hydrocarbon of which the molecular structure incorporates one or more planar sets of six carbon atoms that are connected by delocalized electrons, numbering the same as if they consisted of alternating single and double covalent bonds
- 3.3**
boiling point
BP
point at which the vapour pressure of a liquid equals the external pressure acting on the surface of a liquid
- Note 1 to entry: It is expressed in degrees Celsius.
- 3.4**
carcinogen
substance that causes the development of malignant cells in animals or humans
- 3.5**
compliance point
location (e.g. soil or groundwater) where the assessment criteria shall be measured and shall not be exceeded
- 3.6**
equivalent carbon number
empirically determined parameter related to the *boiling point* (3.3) of a chemical normalized to the boiling point of the *n*-alkanes or its retention time in a boiling point gas chromatographic (GC) column
- 3.7**
fraction
group of aromatic and/or aliphatic compounds with leaching and volatilization factors that differ by approximately one order of magnitude
- 3.8**
gas chromatography
analytical method that is used to separate and determine the components of complex mixtures based on partitioning between a gas phase and stationary phase
- 3.9**
hydrocarbon
compound of hydrogen and carbon which are the principal constituents of crude oil, refined petroleum products and products derived from the carbonization of coal (at high or low temperature)
- 3.10**
indicator compound
compound chosen to describe properties, primarily toxicity, of a petroleum mixture or *fraction* (3.7)
- Note 1 to entry: This method is often used to assess carcinogenic compounds.
- 3.11**
NSO compound
organic compound that contains nitrogen, sulphur and oxygen
- Note 1 to entry: NSO compounds occur in organic matter and crude oil. Asphaltenes are examples of NSO compound. NSO compounds can be separated from crude oil by polar solvents such as methanol.

3.12**partitioning**

extent to which a compound of a *hydrocarbon* (3.9) mixture separates into different media (or phases) based on its chemical and physical properties and the size and properties of the media in the specific situation

3.13**petroleum hydrocarbon**

organic compound comprised of carbon and hydrogen atoms arranged in varying structural configurations which make up the principal constituents of crude oil and petroleum products

Note 1 to entry: Mineral oil is a colloquial term for petroleum hydrocarbons or petroleum products.

3.14**polycyclic aromatic hydrocarbon****PAH**

compound whose molecules contain two or more simple aromatic rings fused together by sharing two neighbouring carbon atoms

Note 1 to entry: Naphthalene, anthracene, phenanthrene and benzo(a)pyrene.

3.15**surrogate compound**

(representative) compound with toxicological and/or properties indicative of a hydrocarbon fraction, which can therefore be used to represent the fraction in an exposure assessment

3.16**total petroleum hydrocarbon**

method-defined parameter, depending on the analytical method used to measure it

4 Principle

A petroleum hydrocarbon product typically consists of a mixture of a very large number of individual compounds. When assessing exposure and risk related to a mixture of compounds, such as in a petroleum hydrocarbon product, evaluation has to be made with respect to the migration, fate and toxicity of the different compounds in the mixture and the toxicity of the mixture. During transport in the subsurface, the composition of a mixture may change due to different rates of dissolution, volatilization, retardation, biodegradation, etc. acting on different component compounds. As a result, the toxicity of the resulting mixture may vary with both time and distance from the source zone.

Assessing the potential exposure to a mixture consisting of a large number of compounds is not feasible, neither in relation to the measurement of the concentration of all the compounds, in relation to the evaluation of the resulting mixture (after migration and degradation) in the relevant media (such as in the groundwater or in the indoor air), nor with respect to the resulting toxicity. A method, where only a number of compounds or surrogate compounds are measured and evaluated, is therefore preferable.

On the other hand, it is necessary when choosing the relevant compounds and surrogate compounds (such as relevant fractions of the total oil product) to ensure that the resulting evaluation of either overall exposure or toxicity is a reasonable estimate of the exposure and toxicity related to the oil product as a whole. Furthermore, selection of surrogate compounds should ensure that, if risk-management action is necessary, the risk-management applied for the surrogate is also likely to mitigate the risks associated with other (unquantified) substances present in the mixture.

Studies on migration, fate and toxicity of petroleum hydrocarbons show substantial differences between the properties of individual compounds and fractions of aliphatic and aromatic hydrocarbons. Similar differences exist between hydrocarbon compounds with different carbon content. The choice of surrogate compounds for assessing exposure and toxicity of petroleum hydrocarbons should be based on fractions of the total hydrocarbon mix in a mineral oil product and on individual compounds and fractions with similar properties.