

Redline version
compares Second edition to
First edition



Cranes — Access, guards and restraints —

Part 2: Mobile cranes

*Appareils de levage à charge suspendue — Moyens d'accès, dispositifs
de protection et de retenue —*

Partie 2: Grues mobiles

Sample Document

get full document from standards.iteh.ai



Reference number
ISO 11660-2:redline:2015(E)

© ISO 2015

IMPORTANT — PLEASE NOTE

This is a mark-up copy and uses the following colour coding:

- | | |
|---|---|
| Text example 1 | — indicates added text (in green) |
| Text example 2 | — indicates removed text (in red) |
|  | — indicates added graphic figure |
|  | — indicates removed graphic figure |
| 1.x ... | — Heading numbers containg modifications are highlighted in yellow in the Table of Contents |

All changes in this document have yet to reach consensus by vote and as such should only be used internally for review purposes.

DISCLAIMER

This Redline version provides you with a quick and easy way to compare the main changes between this edition of the standard and its previous edition. It doesn't capture all single changes such as punctuation but highlights the modifications providing customers with the most valuable information. Therefore it is important to note that this Redline version is not the official ISO standard and that the users must consult with the clean version of the standard, which is the official standard, for implementation purposes.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 General Terms and definitions	1
4 Definitions	2
5 General criteria	4
6.4 Performance criteria Access	5
6.1.4.1 General	5
6.2.4.2 Requirements	5
4.2.1 General design requirements for access	5
4.2.2 Compliance with ISO 11660-1	5
7 Steps	6
8 Ladders	8
9 Stairways	8
10 Handrails and handholds	9
11 Platforms, passageways, walkways, guardrails and foot barriers	10
12 Enclosure openings	11
13 Powered or manually actuated access devices	13
14 Guards and restraints	14
Annex A (informative) Examples of surfaces considered to be slip-resistant	15
Annex B (informative) Bibliography	16
Bibliography	17

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

~~Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.~~ The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

~~International Standard ISO 11660-2 was prepared by Technical Committee~~ The committee responsible for this document is ISO/TC 96, *Cranes*, Subcommittee SC 6, *Mobile cranes*.

This second edition cancels and replaces the first edition (ISO 11660-2:1994), which has been technically revised.

ISO 11660 consists of the following parts, under the general title *Cranes — Access, guards and restraints*:

- *Part 1: General*
- *Part 2: Mobile cranes*
- *Part 3: Tower cranes*
- *Part 4: Jib cranes*
- *Part 5: Bridge and gantry cranes*

~~Annexes A and B of this part of ISO 11660 are for information only.~~

Cranes — Access, guards and restraints —

Part 2: Mobile cranes

1 Scope

This part of ISO 11660 specifies criteria for steps, stairways, ladders, walkways, platforms, handrails, handholds, guardrails and entrance openings which permit access to and from operator, inspection or maintenance platforms on ~~establishes the particular requirements relating to access, guards and restraints for~~ mobile cranes as defined in ISO 4306-2¹ and parked in accordance with the manufacturer's instruction. It also presents requirements for guards and restraints as related to moving parts.

~~This part of ISO 11660-1 is also based on and partly in harmony with~~ establishes the general requirements for access to control stations and other areas of cranes as defined in ~~ISO 20660~~ ISO 4306-1, during normal operations, maintenance, inspection, erection and ~~ISO 2067~~. For mobile cranes fitted with a tower dismantling. It also deals with ~~ISO 11660-3~~ guards and ~~ISO 11660-4~~ should be consulted restraints in general, concerning the protection of persons on or near the crane with regard to moving parts, falling objects or live parts.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of referenced documents are indispensable for the application of this ISO 11660. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of document. For dated references only the edition cited applies. For undated references, ISO 11660 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards the latest edition of the referenced document (including any amendments) applies.

ISO ~~4306-2~~ 11660-1:2008¹, *Cranes — Vocabulary* Access, guards and restraints — Part 2: Mobile cranes: 1: General

ISO 11660-1: ~~4306-2~~², *Cranes — Access, guards and restraints* Vocabulary — Part 1: General: 2: Mobile cranes

3 ~~General~~ Terms and definitions

~~3.1~~ The requirements given in this part of ISO 11660 are based on one person, unladen, using the access system by himself, i.e. no other coworkers are on the access system, and on the 95th to 5th percentile human physical dimensions as presented in ISO 3411.

It shall also be recognized that some machine designs may require modifications or variances from the requirements presented in this part of ISO 11660.

For the purposes of this document, the terms and definitions given in ISO 11660-1 apply.

1) ~~To be published. (Revision of ISO 4306-2:1985)~~

2) ~~To be published.~~

~~4 Definitions~~

~~For the purposes of this part of ISO 11660, the following definitions apply:~~

~~4.1~~

~~access system~~

~~System provided on a machine for entrance to and exit from an operator, inspection or maintenance platform from and to the ground. The primary access system is the access system normally used, while the alternative access system is the access route used during anticipated emergency situations when the primary access system cannot be used.~~

~~4.2~~

~~jib walkway~~

~~Walkway used mainly on long jibs, such as on dragline cranes, which are inclined at angles up to 20° from the horizontal.~~

~~4.3~~

~~jib skywalk platform~~

~~Maintenance platform on jib base sections.~~

~~4.4~~

~~controlled descent device~~

~~Device which can automatically lower a person without power at a fixed speed as part of an alternative access system.~~

~~4.5~~

~~enclosure opening~~

~~Opening leading to or from an access system and large enough for a person to pass through.~~

~~4.5.1~~

~~primary opening~~

~~Opening normally used for access.~~

~~4.5.2~~

~~alternative opening~~

~~Opening for use during emergencies when the primary opening is not usable.~~

~~4.5.3~~

~~service opening~~

~~Opening for use during maintenance, service or inspection.~~

~~4.6~~

~~foot barrier~~

~~Device to prevent a person's foot from slipping off the edge of a platform or walkway.~~

~~4.7~~

~~guardrail~~

~~Device along the open sides of walkways or platforms to protect a person from falling.~~

~~4.8~~

~~handrail and handhold~~

~~Parts of an access system that may be grasped by the hand as an aid to body support and balance.~~

~~4.9~~

~~ladder~~

~~Access system or part of an access system, inclined from the horizontal at an angle greater than 50° but not more than 90°, consisting of a series of equally spaced steps that can accommodate one or both feet.~~

~~4.9.1~~

~~vertical ladder~~

~~Ladder whose angle of inclination from the horizontal is greater than 75°.~~

4.9.2**~~inclined ladder~~**

~~Ladder whose angle of inclination from the horizontal is greater than 50° but not more than 75°.~~

4.9.3**~~rung ladder~~**

~~Ladder consisting of side rails and rungs which can accommodate both feet, used for access where the angle of inclination from the horizontal exceeds 75°.~~

4.9.4**~~stepped ladder~~**

~~Ladder consisting of side rails and steps which can accommodate both feet, used for access where the angle of inclination from the horizontal exceeds 65°.~~

4.10**~~ladder fall limiting device~~**

~~Any device which minimizes or limits the length of fall from a ladder system.~~

4.11**~~operator's platform~~**

~~Area from which an operator controls the travel and work functions of the machine.~~

4.12**~~passageway~~**

~~Walkway with confining barriers on both sides that extend vertically above the walking surface to a height of at least 1 200 mm for erect walking or 300 mm for crawling.~~

4.13**~~platform~~**

~~Horizontal surface for the support of persons engaged in operation, maintenance, inspection or repair work.~~

4.14**~~ramp~~**

~~Plane inclined at an angle of 20° or less from the horizontal, without steps, but with cleats or other surface treatment for the purpose of traction.~~

4.15**~~cleat~~**

~~Device added to a walkway or ramp surface to improve traction.~~

4.16**~~rest platform~~****~~landing~~**

~~Platform used in conjunction with a ladder system for a person to rest on while standing.~~

4.17**~~riser height~~**

~~Height between two consecutive steps or rungs, measured from the tread surface of one step or rung to the tread surface of the next.~~

4.18**~~rung~~**

~~Device on which one or both feet may be placed, generally installed on vertical ladders or on a single foot step.~~

4.19**~~stairway~~**

~~Access system or part of an access system inclined from the horizontal at an angle greater than 33,7° but not more than 67° and consisting of four or more steps.~~