
**Plastics pipes and fittings —
Equipment for fusion jointing
polyethylene systems —**

**Part 1:
Butt fusion**

*Tubes et raccords en matières plastiques — Appareillage pour
l'assemblage par soudage des systèmes en polyéthylène —*

Partie 1: Soudage bout à bout

get full document from standards.iteh.ai



Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Design configurations	2
4.1 General.....	2
4.2 Configurations.....	2
5 Chassis and clamps	3
5.1 General.....	3
5.2 Guide elements.....	3
5.2.1 General.....	3
5.2.2 Rigidity under pressure.....	4
5.2.3 Rigidity under bending.....	5
5.2.4 Re-rounding action.....	6
6 Interface force transmission	6
6.1 General.....	6
6.2 Manual systems.....	7
6.3 Hydraulic and pneumatic systems.....	7
6.4 Electric systems.....	7
6.5 Performance.....	7
7 Planing tool	7
7.1 General.....	7
7.2 Performance.....	8
8 Heating plate	8
8.1 General.....	8
8.2 Dimensions.....	8
8.3 Materials and surface finish.....	9
8.4 Heating system.....	9
8.5 Performance.....	10
9 Power supply	10
10 Test methods	10
10.1 Chassis and clamps.....	10
10.1.1 Effectiveness of re-rounding (see Figure 3).....	10
10.1.2 Clamp alignment.....	11
10.2 Planing tool and check of gap after planing.....	12
10.3 Heating plate.....	12
10.3.1 Roughness check.....	12
10.3.2 Temperature control system check.....	13
10.3.3 Heat transfer efficiency.....	14
10.3.4 Guide elements and work-holding fixtures.....	14
11 Auxiliary equipment	16
12 Maintenance	16
13 Marking on the butt fusion machine	17
14 Other information to be provided by the manufacturer	17
Annex A (normative) Additional performance requirements for butt fusion machines with automatic controllers	18
Annex B (informative) Type classification scheme	19

Sample Document

get full document from standards.iteh.ai

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of the standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html

This document was prepared by Technical Committee ISO/TC 138, *Plastics pipes, fittings and valves for the transport of fluids*, Subcommittee SC 4, *Plastics pipes and fittings for the supply of gaseous fuels*.

This fourth edition cancels and replaces the third edition (ISO 12176-1:2012), which has been technically revised so that it applies to larger pipe diameters.

The modifications are the following:

- increase of the wall thickness and diameter;
- various clarifications such as the guide elements and work-holding fixtures;
- editorial changes have been introduced.

A list of all parts in the ISO 12176- series can be found on the ISO website.

Sample Document

get full document from standards.iteh.ai

Plastics pipes and fittings — Equipment for fusion jointing polyethylene systems —

Part 1: Butt fusion

1 Scope

This document specifies the general characteristics of, and performance requirements for, equipment for butt fusion jointing of polyethylene (PE) piping systems using electrically powered heater plates.

It is applicable to mechanical and pressure-activated equipment for butt fusion jointing of PE pipes and fittings either intended to be used for the supply of gaseous fuels, conforming to ISO 4437-2[1] and ISO 4437-3[2], or intended for the conveyance of water for human consumption (including raw water prior to treatment) and for the conveyance of water for general purposes, conforming to ISO 4427-2[3] and ISO 4427-3[4].

Butt fusion machines with an automatic controller are subject to additional requirements as given in [Annex A](#).

NOTE This document is also applicable to butt fusion machines for larger nominal pipe diameters and nominal wall thicknesses than given in this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4287, *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Terms, definitions and surface texture parameters*

ISO 11414, *Plastics pipes and fittings — Preparation of polyethylene (PE) pipe/pipe or pipe/fitting test piece assemblies by butt fusion*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

base framework

self-supporting entity composed of two or more guides and pipe clamps

Note 1 to entry: It provides the mechanism for heating and fusing the pipes and/or fittings.

3.2

frictional resistance of the butt fusion machine

force necessary to overcome friction in the whole mechanism without pipe

Note 1 to entry: See [6.1](#).

3.3

nominal outside diameter

d_n

numerical designation of size which is common to all components in a thermoplastics piping system other than flanges and components designated by thread size

Note 1 to entry: It is a convenient round number for reference purposes.

3.4

nominal wall thickness

e_n

numerical designation of the wall thickness of a component

Note 1 to entry: It is a convenient round number approximately equal to the manufacturing dimension in millimetres.

3.5

drag compensation

ability of the butt fusion machine to overcome mechanical and frictional forces, as well as forces caused by operating on site, in order to achieve and maintain the fusion parameters specified for the pipe

3.6

standard dimension ratio

SDR

ratio of the nominal outside diameter, d_n , of a pipe to its nominal wall thickness, e_n

[SOURCE: ISO 4427-1:2007, 3.1.1.15]

4 Design configurations

4.1 General

The normal ambient temperature range in which the butt fusion machine is intended to operate is $-10\text{ }^{\circ}\text{C}$ to $+40\text{ }^{\circ}\text{C}$. Use outside this temperature range shall be agreed upon between the user and the supplier of the machine.

4.2 Configurations

To conform to the requirements of this document, butt fusion machines may have different design configurations, as follows:

- a mechanical linkage system for force generation;
- a hydraulic hand-pump system for force generation;
- a semi-automatic externally powered system for force generation (manual pre-set of pressure);
- a semi-automatic system incorporating a device for monitoring and recording the fusion parameters;
- an automatic system that controls and records the fusion parameters.

Machines are generally designed for well-defined ranges of diameters, SDR ratios and fusion cycles.

Each component of the machine shall conform to relevant national safety regulations.

NOTE For example, the safety aspects for Europe are regulated in Reference [5].

Machines which record fusion data shall be capable of transferring the data for further use.

5 Chassis and clamps

5.1 General

The butt fusion machine shall be as maintenance-free as possible.

The base framework of the butt fusion machine shall provide rigidity and stability without unnecessary weight.

The butt fusion machine shall be sufficiently robust to withstand normal field use.

The chassis shall provide facilities for the alignment of and relative movement between pipes and/or fittings.

The butt fusion machine shall incorporate a facility for supporting the heating plate and planing tool when in use. This support shall not affect transmission of interface forces across the heating plate and shall not prevent proper alignment of the heating plate during the heating operation.

The butt fusion machine shall be capable of making satisfactory joints at ambient temperature and under normal worksite conditions with pipes and fittings at extremes of dimensional tolerances.

With butt fusion machines designed for use in narrow trenches, the design and construction of the clamps shall enable the butt fusion machine to be removed from the trench after fusion without damaging the PE pipe.

The base framework shall be fitted with a minimum of two clamps, one fixed and one moveable, to position the PE pipes during the fusion cycle. These clamps shall be designed to enable the pipes to be positioned or removed quickly.

The clamps shall grip the circumference of the pipes and fittings and shall be designed and dimensioned to avoid damage to the pipe or fitting surfaces.

To avoid human damage, the clamp jaws should preferably be designed so that they cannot close to less than a certain minimum distance apart.

No adjustment of the centreline of either pipe shall be required after changing the relevant parts to accommodate different pipe sizes. The clamps, inserts and liners shall not damage the pipe or fitting.

Clamps and/or liners for each pipe size should preferably be interchangeable between similar machines made by the same manufacturer.

The maximum number of removable clamping liners shall be three for machines for pipe diameters up to and including $d_n = 400$ mm, and four for machines for pipe diameters above $d_n = 400$ mm.

Operating instructions shall be available.

5.2 Guide elements

5.2.1 General

The sliding surfaces of the guide elements shall be protected from corrosion, e.g. by hard chromium plate.