
**Petroleum and related products —
Determination of spray ignition
characteristics of fire-resistant
fluids —**

Part 2:

**Spray test — Stabilised flame heat
release method**

*Produits pétroliers et produits connexes — Détermination
des caractéristiques d'inflammation des fluides difficilement
inflammables en jet pulvérisé —*

*Partie 2: Essai de pulvérisation — Méthode par dégagement de
chaleur d'une flamme stabilisée*

<https://standards.itech.ai/catalog/standards/iso/4d00fc60-12f3-4de2-9f2d-01455b3ffea9/iso-15029-2-2018>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 15029-2:2018

<https://standards.iteh.ai/catalog/standards/iso/4d00fc60-12f3-4de2-9f2d-01455b3ffea9/iso-15029-2-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	2
5 Reagents and materials	2
6 Apparatus	3
7 Sampling and sample preparation	11
8 Apparatus preparation	11
9 Procedure	12
9.1 Measurements at a propane flow rate of 0,13 Nm ³ /h	12
9.2 Measurements at a propane flow rate of 0,4 Nm ³ /h	13
9.3 Rejection of test data	13
9.4 Repeat testing	13
9.5 Number of tests	14
9.5.1 General	14
9.5.2 Calculation	14
9.5.3 Marginal values	14
9.5.4 Conclusion	14
10 Calculations	15
10.1 Ignitability factor	15
10.1.1 At propane flow rate of 0,13 Nm ³ /h	15
10.1.2 At propane flow rate of 0,4 Nm ³ /h	15
10.2 Flame length index	15
10.2.1 At propane flow rate of 0,13 Nm ³ /h	15
10.2.2 At propane flow rate of 0,4 Nm ³ /h	15
10.3 Smoke density	16
11 Expression of results	16
11.1 Individual results	16
11.2 Ranking system	16
12 Precision	16
13 Test report	16
Annex A (normative) Verification of propane pressure and flow rate	17
Annex B (normative) Verification of propane flame characteristics	18
Annex C (normative) Test apparatus calibration	23
Annex D (informative) Fire-resistant classification scheme	25
Annex E (informative) Examples of pro-forma for test results	26
Bibliography	29

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established, has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 28, *Petroleum and related products, fuels and lubricants from natural or synthetic sources*.

This first edition of ISO 15029-2 cancels and replaces ISO/TS 15029-2:2012 which has been technically revised. Definitions and some procedural steps have been further clarified based on comments received from the market. This method has now largely superseded the older procedure in ISO 15029-1 in specifications and fluid development. Unlike ISO 15029-1, this document is a method that can rank fluids in terms of their spray flammability and as several test rigs are available, is capable of the generation of some precision data.

A list of all parts in the ISO 15029 series can be found on the ISO website.

Petroleum and related products — Determination of spray ignition characteristics of fire-resistant fluids —

Part 2:

Spray test — Stabilised flame heat release method

WARNING — Use of this document can involve hazardous materials, operations and equipment. This document does not purport to address all of the safety problems associated with its use. It is the responsibility of users of this standard to ensure appropriate measures to safeguard the health and safety of personnel prior to application of the standard, and to determine the applicability of any other restrictions.

1 Scope

This document specifies a method by which the fire hazards of pressurised sprays of fire-resistant fluids can be compared. Two sizes of propane flame are used to ignite and stabilise combustion of an air-atomised release of fluid. Measurements related to the rate of heat release, length of flame and density of smoke give quantitative information on the fire behaviour of the fluid.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3170, *Petroleum liquids — Manual sampling*

ISO 3696:1987, *Water for analytical laboratory use — Specification and test methods*

ISO 9162, *Petroleum products — Fuels (class F) — Liquefied petroleum gases — Specifications*

IEC 60584-1, *Thermocouples — Part 1: EMF specifications and tolerances*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

stabilised spray flame

point at which the rate of energy release, flame length and other combustion properties, are steady as a function of time, so that sensible time-averaged values can be calculated

3.2

flame length

distance in millimetres from the vertical centre line of the gas burner to the furthest downstream point reached by the visible flame