
**Photography — Electronic still
picture imaging — Picture transfer
protocol (PTP) for digital still
photography devices**

*Photographie — Imagerie des prises de vue électroniques —
Protocole de transfert d'images (PTP) pour les appareils
photographiques électroniques numériques*

Sample Document

get full document from standards.iteh.ai



Reference number
ISO 15740:2013(E)

© ISO 2013

Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Digital still photography device model	5
4.1 Overview.....	5
4.2 Baseline requirements.....	6
5 Data format specification	6
5.1 General format.....	6
5.2 Data types.....	7
5.3 Simple types.....	9
5.4 Arrays.....	11
5.5 Data sets.....	12
6 Image and data object formats	21
6.1 Object usage.....	21
6.2 Thumbnail formats.....	22
6.3 ObjectFormatCodes.....	23
6.4 Object format version identification.....	23
6.5 Data object association.....	24
7 Transport requirements	26
7.1 Disconnection events.....	26
7.2 Reliable, error-free channel.....	27
7.3 Asynchronous event support.....	27
7.4 Device discovery and enumeration.....	27
7.5 Specific transports.....	27
8 Persistent storage	27
8.1 StorageID.....	27
8.2 Data object referencing.....	28
8.3 Receiver object placement.....	29
9 Communication protocol	30
9.1 Device roles.....	30
9.2 Sessions.....	30
9.3 Transactions.....	30
9.4 Operation flow.....	33
9.5 Vendor extensions.....	33
10 Operations	35
10.1 Operation overview.....	35
10.2 Operation parameters.....	35
10.3 OperationCode format.....	35
10.4 OperationCode summary.....	35
10.5 Operation descriptions.....	35
11 Responses	60
11.1 ResponseCode format.....	60
11.2 ResponseCode summary.....	60
11.3 Response descriptions.....	61
12 Events	66
12.1 Event usage.....	66
12.2 Event types.....	66

12.3	Event data set.....	66
12.4	EventCode format.....	67
12.5	EventCode summary.....	67
12.6	Event descriptions.....	67
13	Device properties.....	71
13.1	Device property usage.....	71
13.2	Values of a device property.....	71
13.3	Device property management requirements.....	72
13.4	Device property identification.....	72
13.5	Device property descriptions.....	76
14	Streaming (PTP v1.1 only).....	92
14.1	Streaming overview.....	92
14.2	Stream transfer.....	92
14.3	Multiplexing.....	92
14.4	Discovering and configuring stream capabilities.....	93
14.5	Data transfer mechanism.....	93
14.6	Packet layout.....	94
14.7	Frame layout.....	95
14.8	Enumerating supported streams.....	95
14.9	Retrieving stream information.....	95
15	Conformance section.....	95
Annex A (informative) Optional device features.....		98
Annex B (normative) Object referencing and format codes.....		100
Annex C (informative) Operation flow example scenarios.....		102
Annex D (informative) Filesystem implementation examples.....		106
Annex E (informative) Reference to OSI model.....		109
Annex F (informative) SendObject implementation example.....		112
Bibliography.....		115

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. www.iso.org/directives

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. www.iso.org/patents

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

The committee responsible for this document is ISO/TC 42, *Photography*.

This third edition cancels and replaces the second edition (ISO 15740:2008), of which it constitutes a minor revision with the following changes:

- as the vendor extension ID registry formerly maintained by the I3A has been transferred to another organization, term [3.21](#) (I3A) was removed and the remaining terms renumbered;
- in [9.5.1](#), the fourth and fifth sentences were amended and combined to reflect that a new organization assigns and maintains VendorExtensionIDs.

Introduction

This third edition of ISO 15740 (hereinafter designated PTP v1.1) provides optional support for new increased performance and compatibility. All new constructs are fully backward compatible with the first edition (hereinafter designated PTP v1.0) and are optional. See [5.5.2](#) for standard version.

For the purposes of this International Standard, digital still photography devices (DSPDs) are defined as devices with persistent storage which capture a digital two-dimensional image at a discrete point in time. Most DSPDs include interfaces that can be used to connect to a host computer or other imaging device, such as a printer. A number of high speed interface transports has been developed, including USB, TCP/IP and IEEE 1394 (FireWire). This International Standard is designed to provide requirements for communicating with DSPDs. This includes communications with any type of device, including host computers, direct printers and other DSPDs over a suitable transport. The requirements include standard image referencing behaviour, operations, responses, events, device properties, data sets and data formats to ensure interoperability. This International Standard also provides optional operations and formats, as well as extension mechanisms.

This International Standard specifies the following:

- behaviour requirements for DSPDs; this includes the baseline features a device needs to support in order to provide interoperability over conforming transports;
- functional requirements needed by a transport to facilitate the creation of a transport-dependent implementation specification that conforms to this International Standard;
- a high-level protocol for communicating with and between DSPDs consisting of operation, data and response phases;
- sets of suggested data codes and their usages including
 - OperationCodes,
 - ResponseCodes,
 - ObjectFormatCodes,
 - DevicePropCodes,
 - EventCodes,
 - required data sets and their usages,
 - a means of describing data object associations and filesystems and
 - mechanisms for implementing extensibility.

This International Standard does not attempt to define any of the following:

- any sort of device discovery, enumeration or transport aggregation methods; implementation of this functionality is left to the transports and the platforms upon which support for this International Standard is implemented;
- an application programming interface; this is left to the platforms upon which support for this International Standard is implemented.

This International Standard has been designed to appropriately support popular image formats used in digital still cameras, including the Exif and TIFF/EP formats defined in ISO 12234-1^[15] and ISO 12234-2, as well as the Design Rule for Camera Filesystem (DCF) and the Digital Print Order Format (DPOF).

The technical content of this International Standard is closely related to PIMA 15740:2000. The main difference is that PIMA 15740:2000 includes an informative annex describing a USB implementation of

ISO 15740. This information is not included in this International Standard, which instead references the USB still device class document developed by the Device Working Group of the USB Implementers Forum.

PTP v1.1 provides optional support for new increased performance and compatibility. All new constructs are fully backward compatible with PTP v1.0 and are optional.

— Performance Enhancements:

- Support for retrieval of ObjectHandles in enumerated chunks, via specification of three new optional operations and a new response code. This may reduce long response times for some initiators that possess large numbers of objects.
- Support for optional arbitrary resizing prior to image transmission via specification of a new operation GetResizedImageObject. In PTP v1.0, image sizes might be requested in full-resolution or thumbnail size only.
- Support for arrays of data sets. This can be used to reduce the number of required transactions necessary for device characterization from being a function of the number of objects on the device to one.
- An optional fast file characterization operation called GetFilesystemManifest that exploits data set arrays to request, in a single transaction, only the minimum data required to characterize a typical filesystem. Many initiators, particularly in printing scenarios, are interested in fast filesystem characterization for access to a specifically named file in a particular place. This capability can significantly improve end-user workflow latency. This single operation replaces the typical series of many GetObjectInfo requests with a binary filesystem manifest. This manifest is defined as a simple array of a subset of the standard ObjectInfo data set called the ObjectFilesystemInfo data set. This operation replaces the need for many GetObjectInfo calls, while also avoiding the need for responders to perform many internal file-opens on the fly, or to cache ObjectInfo image data that is often held persistently only “inside” internal image files (e.g. TIFF tags inside EXIF JPEGs), to quickly communicate only the fast filesystem information.

— Compatibility Enhancements:

- An optional mechanism to support multiple vendor extension sets. This is specified via the new VendorExtensionMap data set, and two new optional operations that may be invoked outside of a session (GetVendorExtensionMaps and GetVendorDeviceInfo).
- The optional fast file characterization method GetFilesystemManifest natively supports extremely large objects, by requiring 8-bytes for object size (UINT64), as opposed to the standard 4-bytes.
- A new standard ObjectFormatCode to support the Digital Negative file format (DNG).

— Feature Enhancement:

- An optional mechanism for handling streaming content. This is specified via the new StreamInfo data set, as well as the supporting GetStreamInfo and GetStream operations, as well as some optional new supporting DeviceProperties. This is described in a new Clause 14.

Sample Document

get full document from standards.iteh.ai

Photography — Electronic still picture imaging — Picture transfer protocol (PTP) for digital still photography devices

1 Scope

This International Standard provides a common communication protocol for exchanging images with and between digital still photography devices (DSPDs). This includes communication between DSPDs and host computers, printers, other digital still devices, telecommunications kiosks and image storage and display devices.

This protocol is transport- and platform-independent.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8601, *Data elements and interchange formats — Information interchange — Representation of dates and times*

ISO 12234-2, *Electronic still-picture imaging — Removable memory — Part 2: TIFF/EP image data format*

ISO/IEC 10646, *Information technology — Universal Coded Character Set (UCS)*

ISO/IEC 10918-1:1994, *Information technology — Digital compression and coding of continuous-tone still images: Requirements and guidelines*

IEC 61966-2-1, *Multimedia systems and equipment — Colour measurement and management — Part 2-1: Colour management — Default RGB colour space — sRGB*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

album

end-user-created object used to logically group data objects according to some user-defined criteria

Note 1 to entry: An album might or might not be a physical folder in a filesystem. In this International Standard, an album is a type of association.

3.2

association

logical construct used to expose a relationship between discrete objects

Note 1 to entry: Associations are used to indicate that separate data objects are related. Associations are represented like folders, and can be nested using a standard branched hierarchical tree structure.

EXAMPLE A time sequence, or user-defined groupings by content or capture session.

3.3

connection

transport-provided mechanism for establishing paths for transferring data between devices

3.4

datacode

16-bit unsigned integer whose Most Significant Nibble (4 bits) is used to indicate the category of code and whether the code value is standard or vendor-extended

3.5

data object

image or other type of data that typically exists in persistent storage of a DSPD or other device

3.6

dataset

transport-independent collection of one or more individual data items with known interpretations

Note 1 to entry: Data sets are not necessarily opaque nor atomic to transport implementations.

3.7

Design Rule for Camera Filesystem

DCF

standard convention for camera filesystems which specifies the file format, foldering and naming conventions in order to promote file interoperability between conforming digital photography devices

3.8

device discovery

act of determining the set of all devices present on a particular transport or platform that are physically or logically accessible

3.9

digital still photography device

DSPD

device with persistent storage which captures a two-dimensional digital still image

3.10

Digital Print Order Format

DPOF

standardized ASCII file stored on removable media along with the image files that indicates how many copies of which images should be printed

Note 1 to entry: DPOF also allows index prints, cropping, and text overlays to be specified.

3.11

enumeration

act of creating an ordered increasing numerical list that contains one representative element for each member of a set

3.12

Exif/JPEG

compressed file format for digital cameras in which the images are compressed using the baseline JPEG standard described in ISO 12234-2

Note 1 to entry: In Exif, metadata and thumbnail images are stored using TIFF tags within an application segment at the beginning of the JPEG file.

3.13

folder

optional sub-structure in a hierarchical storage area that can contain data objects

3.14**FlashPix**

image file format, defined in *FlashPix Format Specification*, using a structured storage file containing metadata and a tiled, hierarchical image representation

Note 1 to entry: The tiles in a FlashPix image are normally baseline JPEG images, and individual image tiles of a particular resolution can be easily accessed for rapid display and editing.

3.15**IEEE 1394**

high-speed serial bus standardized by the IEEE (Institute of Electrical and Electronics Engineers) currently having clock rates of 100, 200 and 400 Mbits/s

Note 1 to entry: IEEE 1394 is often referred to as FireWire.

3.16**image aspect ratio**

ratio of the image width to the image height

3.17**image capture device**

device for converting a scene or a fixed image, such as a print, film or transparency, to digital image data

3.18**image output device**

device that can render a digital image to hardcopy or softcopy media

3.19**in-band event**

event transmitted on the same logical connection as operations and responses

Note 1 to entry: Events are only asynchronous to the degree of data precision for which the transport implementation allows event interleaving.

3.20**initiator**

device that initiates a conversation by opening a session, and issues all formal operations to the responder

Note 1 to entry: The initiator is analogous to the client in the client/server paradigm.

3.21**Infrared Data Association****IrDA**

infrared wireless communication system that currently supports wireless communication at data rates between 9 600 bps and 4 Mbps

3.22**Joint Photographic Experts Group****JPEG**

specific image compression method defined in ISO/IEC 10918-1

3.23**LogicalStorageID**

least significant sixteen bits of a StorageID

Note 1 to entry: This value uniquely identifies one logical storage area within the physical store indicated in the PhysicalStorageID.

3.24**Most Significant Nibble****MSN**

most significant four bits of the most significant byte

3.25

object aggregation

act of taking one or more location-specific lists of objects that exist on a particular device and grouping them together in one set

3.26

ObjectHandle

device-unique 32-bit unsigned integer assigned by a device to each data object in local persistent storage which is provided to external devices

Note 1 to entry: External recipients of an ObjectHandle must use it to reference that piece of data in subsequent transactions. ObjectHandles are guaranteed to be persistent over at least a session.

3.27

out-of-band event

event transmitted on a different logical connection to that for operations and responses

Note 1 to entry: Out-of-band events are asynchronous from operation transactions.

3.28

personal computer

PC

any personal computing device, which may employ various hardware architectures and operating systems

3.29

PhysicalStorageID

most significant sixteen bits of a StorageID

Note 1 to entry: This value uniquely identifies one physical storage area on a device, although there may be more than one logical store per physical store.

3.30

Portable Network Graphics

PNG

extensible file format for lossless, portable, compressed storage of raster images

Note 1 to entry: PNG supports indexed colour, greyscale, truecolour and an optional alpha channel.

3.31

protocol

defined mechanisms for exchanging data between devices

3.32

pull model

use paradigm for DSPDs where the object receiver initiates the operation requests to transfer data objects from the sender

3.33

push model

use paradigm for DSPDs where the object sender initiates the operation requests to transfer data objects to the receiver

3.34

QuickDraw picture

file format consisting of sequences of saved drawing commands

Note 1 to entry: QuickDraw files are commonly referred to as PICT files.

3.35**responder**

device that responds to operations from the initiator

Note 1 to entry: The responder is analogous to a server in the client/server paradigm.

3.36**session**

logical connection between two devices defining a period of time during which obtained state information, such as handle persistence, may be relied upon

3.37**square pixel sampling**

image having equal sample spacing in the two orthogonal sampling directions

3.38**StorageID**

device-specific four-byte unsigned integer (UINT32) that represents a unique storage area that may contain data objects

Note 1 to entry: The most significant 16 bits of a StorageID represent the PhysicalStorageID, while the least significant 16 bits of a StorageID represent the LogicalStorageID.

3.39**transport aggregation**

act of taking one or more transport-specific list of conforming devices that are logically or physically accessible in a system and grouping them in one set that spans all transports across the particular system

3.40**transport**

means of attaching the digital capture device to some other digital device including a physical wire or a wireless connection

3.41**Universal Serial Bus****USB**

digital interface for connecting up to 127 devices in a tiered-star topology

4 Digital still photography device model**4.1 Overview**

Digital still photography devices (DSPDs) are used to acquire digitally encoded still images. These devices include a persistent storage capability so that any digital images and other data acquired by the device are preserved across power cycle operations unless they are specifically deleted.

A DSPD might support many different features. This International Standard supports devices with a wide range of potential features. However, a small number of features is required for conformance with this International Standard, while many others are optional. Subclause 4.2 describes the required features and functionality. [Annex A](#) describes features that are not required for conformance but which should be implementable using this International Standard and its extension mechanisms.

Standard data formats for datatypes and data sets are described in [Clause 5](#).

[Clause 6](#) describes required and optional support for particular image and non-image formats and metadata. [Clause 6](#) also describes methods for associating data objects.

A particular feature set places requirements on the transports used to connect the DSPD to other devices. [Clause 7](#) describes these requirements.

All DSPDs must store images in some form of storage area. [Clause 8](#) describes the usage of these stores, as well as the methods for referencing them.

[Clause 9](#) describes the roles of devices, sessions and transactions that transports are required to use in order to communicate with and/or between DSPDs. [Clause 10](#) lists the standard operations, their corresponding optional operation codes and their usages. Standard responses to operations are defined in [Clause 11](#). The use of events is mandatory in order to ensure synchronization between devices. [Clause 12](#) describes events and their usages.

In order to expose device controls and manipulate properties in a common way, a standard set of device properties and their usages have been defined in [Clause 13](#).

Clause 15 serves as a summary of the individual operations and events that are required to be supported by particular devices, as well as a checklist that can be used by implementers.

4.2 Baseline requirements

4.2.1 General

The requirements listed in [4.2.2](#) to [4.2.5](#) shall be met in order for a DSPD to conform to this International Standard.

4.2.2 Implementation of a suitable transport

The DSPD shall provide appropriate hardware and software support for at least one transport that meets the requirements specified in [Clause 7](#).

4.2.3 Thumbnail support

The DSPD shall provide support for thumbnails as described in [6.2](#).

4.2.4 Standard image and data reference behaviour

In order to ensure interoperability, it is necessary to define a standard mechanism for describing image and data objects present on a device. The DSPD shall meet the requirements described in [Clause 6](#).

4.2.5 Asynchronous event support

The DSPD shall be capable of generating and reacting to asynchronous events. [Clause 12](#) describes events and their usages.

5 Data format specification

5.1 General format

5.1.1 Multibyte data

For the purposes of interpretability, all data fields showing internal content representations shall be read from left to right, in order of decreasing byte significance, commonly referred to as big-endian notation. Therefore, the left-most byte shall represent the Most Significant Byte (MSB), and the right-most byte shall represent the Least Significant Byte (LSB). The most significant four bits of the MSB are referred to as the Most Significant Nibble (MSN), while the least significant four bits of the LSB are referred to as the Least Significant Nibble (LSN). The actual multibyte format used on the wire is transport-specific, while the actual multibyte format used at the application interface is platform-specific.

5.1.2 Bit format

Bit fields presented in this International Standard are numbered so that the least significant bit is at the zero position, holding the right-most position in the field; e.g. the most significant bit of a UINT32 would be referred to as bit 31, while the least significant bit would be referred to as bit 0.

5.1.3 Hexadecimal notation

This International Standard uses hexadecimal notation as a means of concisely describing multibyte fields. All hexadecimal byte fields are represented with the prefix "0x". Following this prefix are pairs of characters, where each pair represents one byte, with the most significant byte appearing first and the least significant byte appearing last.

5.2 Data types

5.2.1 Datatype summary

The types of data that are defined in this International Standard as having specific interpretations of their data content are listed in [Table 1](#).

Table 1 — Datatype summary

Name	Size (bytes)	Format	PTP Version
OperationCode	2	Datacode (UINT16)	1.0+
ResponseCode	2	Datacode (UINT16)	1.0+
EventCode	2	Datacode (UINT16)	1.0+
DevicePropCode	2	Datacode (UINT16)	1.0+
ObjectFormatCode	2	Datacode (UINT16)	1.0+
StorageID	4	Special (UINT32)	1.0+
ObjectHandle	4	Handle (UINT32)	1.0+
DateTime	Variable	String	1.0+
DeviceInfo	Variable	Dataset	1.0+
StorageInfo	Variable	Dataset	1.0+
ObjectInfo	Variable	Dataset	1.0+
DevicePropDesc	Variable	Dataset	1.0+
DevicePropDescEnum	Variable	Enumerated form of DevicePropDesc	1.0+
DevicePropDescRange	Variable	Range form of DevicePropDesc	1.0+
Object	Variable	Variable	1.0+
VendorExtensionMap	8	Dataset	1.1+
ObjectFilesystemInfo	Variable	Dataset	1.1+
StreamInfo	36	Dataset	1.1+
EnumID	4	Special (UINT32)	1.1+

5.2.2 Datacodes

Datacodes are 16-bit unsigned integers (UINT16) with specified interpretations, used for the purposes of enumeration. In order to aid in visual interpretation and potential transport debugging, and to simplify some transport implementations, the primary and vendor-defined datacodes for operations, responses,