
**Acoustics — Field measurement of
sound insulation in buildings and of
building elements —**

**Part 2:
Impact sound insulation**

*Acoustique — Mesurage in situ de l'isolation acoustique des
bâtiments et des éléments de construction —*

Partie 2: Isolation des bruits d'impacts

Document Preview

ISO 16283-2:2020

<https://standards.iteh.ai/catalog/standards/iso/2a85e311-5b74-4986-9442-5ec81c9910b4/iso-16283-2-2020>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 16283-2:2020

<https://standards.iteh.ai/catalog/standards/iso/2a85e311-5b74-4986-9442-5ec81c9910b4/iso-16283-2-2020>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Instrumentation	5
4.1 General	5
4.2 Calibration	5
4.3 Verification	5
5 Frequency range	6
5.1 Tapping machine as the impact source	6
5.2 Rubber ball as the impact source	6
6 General	6
7 Default procedure for sound pressure level measurement	7
7.1 General	7
7.2 Generation of sound field	7
7.2.1 General	7
7.2.2 Impact source positions for the tapping machine as impact source	7
7.2.3 Impact source positions for the rubber ball as impact source	8
7.3 Fixed microphone positions for the tapping machine or rubber ball as impact source	8
7.3.1 General	8
7.3.2 Number of measurements	8
7.3.3 Tapping machine operated at more than one position	8
7.3.4 Rubber ball operated at more than one position	9
7.4 Mechanized continuously moving microphone for the tapping machine as impact source	9
7.4.1 General	9
7.4.2 Number of measurements	10
7.4.3 Tapping machine operated at more than one position	10
7.5 Manually scanned microphone for the tapping machine as impact source	10
7.5.1 General	10
7.5.2 Number of measurements	10
7.5.3 Tapping machine operated at more than one position	10
7.5.4 Circle	10
7.5.5 Helix	10
7.5.6 Cylindrical-type	11
7.5.7 Three semicircles	11
7.6 Minimum distances for microphone positions	12
7.7 Averaging times for the tapping machine as impact source	12
7.7.1 Fixed microphone positions	12
7.7.2 Mechanized continuously moving microphone	13
7.7.3 Manually scanned microphone	13
7.8 Calculation of energy-average sound pressure levels	13
7.8.1 Fixed microphone positions for the tapping machine as impact source	13
7.8.2 Mechanized continuously moving microphone and manually scanned microphone for the tapping machine as impact source	13
7.8.3 Fixed microphone positions for the rubber ball as impact source	14
8 Low-frequency procedure for sound pressure level measurement for the tapping machine as impact source	14
8.1 General	14
8.2 Generation of sound field	14
8.2.1 General	14

8.2.2	Impact source positions	14
8.3	Microphone positions	14
8.4	Averaging time	15
8.5	Calculation of low-frequency energy-average impact sound pressure levels	15
9	Background noise (default and low-frequency procedure)	16
9.1	General	16
9.2	Correction to the signal level for background noise	17
10	Reverberation time in the receiving room (default and low-frequency procedure)	18
10.1	General	18
10.2	Generation of sound field	18
10.3	Default procedure	18
10.4	Low-frequency procedure	18
10.5	Interrupted noise method	19
10.6	Integrated impulse response method	19
11	Conversion to octave bands	19
12	Expression of results	20
13	Uncertainty	20
14	Test report	20
Annex A (normative)	Impact sources	21
Annex B (normative)	Requirements for loudspeakers used for reverberation time measurements	27
Annex C (informative)	Forms for the expression of results	28
Annex D (informative)	Additional guidance	32
Annex E (informative)	Horizontal measurements — Examples of suitable impact source and microphone positions	36
Annex F (informative)	Vertical measurements — Examples of suitable impact source and microphone positions	40
Bibliography		43

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 2, *Building acoustics*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 126, *Acoustic properties of building elements and of buildings*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This third edition cancels and replaces the second edition (ISO 16283-2:2018), which has been technically revised.

The main changes compared to the previous edition are as follows:

- a) [Clause 6](#), Note 3 removed;
- b) in the helical path ([7.5.5](#)) distance of the microphone position to the ceiling changed to minimum 0,5 m;
- c) $L'_{iA, Fmax, VT}$ added to the expression of results and to [Figure C.3](#).

A list of all parts in the ISO 16283 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

ISO 16283 (all parts) describes procedures for field measurements of sound insulation in buildings. Airborne, impact and façade sound insulation are described in ISO 16283-1, this document (ISO 16283-2) and ISO 16283-3, respectively.

Field sound insulation measurements that were described previously in ISO 140-4¹⁾, ISO 140-5²⁾, and ISO 140-7³⁾ were a) primarily intended for measurements where the sound field could be considered to be diffuse, and b) not explicit as to whether operators could be present in the rooms during the measurement. ISO 16283 (all parts) differs from ISO 140-4, ISO 140-5, and ISO 140-7 in that:

- a) it applies to rooms in which the sound field may or may not approximate to a diffuse field;
- b) it clarifies how operators can measure the sound field using a hand-held microphone or sound level meter;
- c) it includes additional guidance that was previously contained in ISO 140-14⁴⁾.

NOTE Survey test methods for field measurements of airborne and impact sound insulation are dealt with in ISO 10052.

Two impact sources are described: the tapping machine and the rubber ball. These impact sources do not exactly replicate all possible types of real impacts on floors or stairs in buildings.

The tapping machine can be used to assess a variety of light, hard impacts such as footsteps from walkers wearing hard-heeled footwear or dropped objects. A single number quantity can be calculated using the rating procedures in ISO 717-2. This single number quantity links the measured impact sound insulation using the tapping machine to subjective assessment of general impacts in dwellings that occur on floors or stairs in a building. The tapping machine is also well-suited to the prediction of impact sound insulation using ISO 12354-2. These two aspects facilitate the specification of impact sound insulation in national building requirements using only measurements with the tapping machine as an impact source.

The rubber ball can be used to assess heavy, soft impacts such as from walkers in bare feet or children jumping, as well as quantifying absolute values that can be related to human disturbance in terms of a Fast time-weighted maximum sound pressure level.

1) Withdrawn.

2) Withdrawn.

3) Withdrawn.

4) Withdrawn.

Acoustics — Field measurement of sound insulation in buildings and of building elements —

Part 2: Impact sound insulation

1 Scope

This document specifies procedures to determine the impact sound insulation using sound pressure measurements with an impact source operating on a floor or stairs in a building. These procedures are intended for room volumes in the range from 10 m³ to 250 m³ in the frequency range from 50 Hz to 5 000 Hz. The test results can be used to quantify, assess and compare the impact sound insulation in unfurnished or furnished rooms where the sound field may or may not approximate to a diffuse field.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3382-2, *Acoustics — Measurement of room acoustic parameters* — Part 2: Reverberation time in ordinary rooms

ISO 12999-1, *Acoustics — Determination and application of measurement uncertainties in building acoustics* — Part 1: Sound insulation

ISO 18233, *Acoustics — Application of new measurement methods in building and room acoustics*

ISO/IEC 17025, *General requirements for the competence of testing and calibration laboratories*

IEC 60942, *Electroacoustics — Sound calibrators*

IEC 61183, *Electroacoustics — Random-incidence and diffuse-field calibration of sound level meters*

IEC 61260 (all parts), *Electroacoustics — Octave-band and fractional-octave-band filters*

IEC 61672-1, *Electroacoustics — Sound level meters — Part 1: Specifications*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>