
**Geometrical product specifications
(GPS) — Filtration —**

**Part 1:
Overview and basic concepts**

*Spécification géométrique des produits (GPS) — Filtrage —
Partie 1: Vue d'ensemble et concepts de base*

Sample Document

get full document from standards.iteh.ai



Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 General discussion	5
4.1 General.....	5
4.2 Primary mathematical models.....	5
5 Filter designations	6
Annex A (informative) Illustrative examples	8
Annex B (informative) Masterplan for filtration standards — ISO 16610- series	14
Annex C (informative) Advantages and disadvantages of different filter types	17
Annex D (informative) Concept diagram	20
Annex E (informative) Relationship to the filtration matrix model	21
Annex F (informative) Relationship to the GPS matrix model	22
Bibliography	24

Sample Document

get full document from standards.iteh.ai

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary Information](#)

The committee responsible for this document is ISO/TC 213, *Dimensional and geometrical product specifications and verification*.

This first edition cancels and replaces ISO/TS 16610-1:2006 which has been technically revised.

ISO 16610 consists of the following parts, under the general title *Geometrical product specifications (GPS) — Filtration*:

- *Part 1: Overview and basic concepts*
- *Part 20: Linear profile filters: Basic concepts*
- *Part 21: Linear profile filters: Gaussian filters*
- *Part 22: Linear profile filters: Spline filters*
- *Part 28: Profile filters: End effects*
- *Part 29: Linear profile filters: Spline wavelets*
- *Part 30: Robust profile filters: Basic concepts*
- *Part 31: Robust profile filters: Gaussian regression filters*
- *Part 32: Robust profile filters: Spline filters*
- *Part 40: Morphological profile filters: Basic concepts*
- *Part 41: Morphological profile filters: Disk and horizontal line-segment filters*
- *Part 49: Morphological profile filters: Scale space techniques*
- *Part 60: Linear areal filters — Basic concepts*
- *Part 61: Linear areal filters — Gaussian filters*

- *Part 71: Robust areal filters: Gaussian regression filters*
- *Part 85: Morphological areal filters: Segmentation*

The following parts are planned:

- *Part 26: Linear profile filters: Filtration on nominally orthogonal grid planar data sets*
- *Part 27: Linear profile filters: Filtration on nominally orthogonal grid cylindrical data sets*
- *Part 45: Morphological profile filters: Segmentation*
- *Part 62: Linear areal filters: Spline filters*
- *Part 69: Linear areal filters: Spline wavelets*
- *Part 70: Robust areal filters: Basic concepts*
- *Part 72: Robust areal filters: Spline filters*
- *Part 80: Morphological areal filters: Basic concepts*
- *Part 81: Morphological areal filters: Sphere and horizontal planar segment filters*
- *Part 89: Morphological areal filters: Scale space techniques*

Sample Document

get full document from standards.iteh.ai

Introduction

This part of ISO 16610 is a geometrical product specification (GPS) standard and is to be regarded as a general GPS standard (see ISO/TR 14638). It influences chain links 3 and 6 in the GPS matrix structure.

The ISO/GPS Masterplan given in ISO 14638 gives an overview of the ISO/GPS system of which this part of ISO 16610 is a part of. The fundamental rules of ISO/GPS given in ISO 8015 apply to this part of ISO 16610 and the default decision rules given in ISO 14253-1 apply to the specifications made in accordance with this part of ISO 16610, unless otherwise indicated.

For more detailed information about the relation of this part of ISO 16610 to the GPS matrix model, see [Annex F](#).

This part of ISO 16610 also develops the terminology and concepts for GPS filtration. This part of ISO 16610 generalizes the concept of filtration. The series of ISO 16610 presents a toolbox of filtration techniques to enable the user to choose an appropriate filter for the functional requirements. They are fundamental International Standards upon which other ISO documents are built.

Sample Document

get full document from standards.iteh.ai

Geometrical product specifications (GPS) — Filtration —

Part 1: Overview and basic concepts

1 Scope

This part of ISO 16610 defines the basic terminology for GPS filtration and the framework for the fundamental procedures used in GPS filtration.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 17450-1:2011, *Geometrical product specifications (GPS) — General concepts — Part 1: Model for geometrical specification and verification*

ISO 17450-2:2012, *Geometrical product specifications (GPS) — General concepts — Part 2: Basic tenets, specifications, operators, uncertainties and ambiguities*

ISO/IEC Guide 99:2007, *International vocabulary of metrology — Basic and general concepts and associated terms (VIM)*

get full document from standards.iteh.ai

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC Guide 99, ISO 17450-1, ISO 17450-2, and the following apply.

3.1

integral feature

geometrical feature belonging to the real surface of the workpiece or to a surface model

Note 1 to entry: An integral feature is intrinsically defined, e.g. skin of the workpiece.

Note 2 to entry: For a statement of specifications, geometrical features obtained from partition of the surface model or of real surface of workpiece shall be defined. These features, called “integral features”, are models of the different physical parts of the workpiece that have specific functions, especially those in contact with adjacent workpieces.

Note 3 to entry: An integral feature can be identified, for example, by

- a partition of the surface model,
- a partition of another integral feature, or
- a collection of other integral features.

[SOURCE: ISO 17450-1:2011, 3.3.5]

3.1.1

surface portion

SP

portion of a partitioned *integral feature* ([3.1](#))

3.1.2

surface profile

line resulting from the intersection between a *surface portion* ([3.1.1](#)) and an ideal plane

Note 1 to entry: The orientation of the ideal plane is usually perpendicular to the tangent plane of the surface portion.

Note 2 to entry: The concept of profiles is under development and it is possible that the definition of surface profile will be revised.

3.2

primary mathematical model

set of nested hierarchical mathematical models of the *surface portion* ([3.1.1](#)), wherein each model in the set can be described by a finite number of parameters

Note 1 to entry: Examples include truncated Fourier series, curvature limited (zero to $\pm$ value) profiles, and limited Wolf pruning height (100 % to smaller positive percentage) segments.

Note 2 to entry: An example of a primary mathematical model using a truncated Fourier series is given in [A.1](#).

3.2.1

nesting index

NI

value indicating the relative level of nested hierarchy for a particular *primary mathematical model* ([3.2](#))

Note 1 to entry: Given a particular nesting index, models with lower indices contain more surface information, whereas models with higher nesting indices contain less surface information.

Note 2 to entry: By convention, as the nesting index approaches zero (or a series of all zeros), there exists a primary mathematical model that approximates the real surface of a workpiece to within any given measure of closeness.

Note 3 to entry: The cut-off wavelength for the Gaussian filter is an example of a nesting index (see [3.2.1.1](#)). For the morphological filter, the nesting index is the size of the structuring element (e.g. the radius of the disc) which is different from the wavelength concept that underlies the notion of “cut-off” (see [3.2.1.2](#) and [3.2.1.3](#)).

Note 4 to entry: The term nesting index is derived from a combination of index from index set and nesting from nested hierarchy, both of which are mathematical terms.

3.2.1.1

cut-off wavelength

particular type of *nesting index* ([3.2.1](#)) applicable to linear filters, used to separate surface components into long and short wavelengths

Note 1 to entry: See, for example, ISO 16610-21, ISO 16610-22, and ISO 16610-61.

3.2.1.2

vertical circular disc radius

particular type of *nesting index* ([3.2.1](#)) applicable to profile morphological filters with a structuring element in terms of a circular disc

Note 1 to entry: See, for example, ISO 16610-41 and ISO 16610-49.

3.2.1.3

horizontal line length

particular type of *nesting index* ([3.2.1](#)) applicable to profile morphological filters with a structuring element in terms of a horizontal line

Note 1 to entry: See, for example, ISO 16610-41 and ISO 16610-49.

3.2.1.4

sphere radius

particular type of *nesting index* ([3.2.1](#)) applicable to areal morphological filters with a structuring element in terms of a sphere radius

3.2.1.5**circular disc radius**

particular type of *nesting index* (3.2.1) applicable to areal morphological filters with a structuring element in terms of a circular disc

Note 1 to entry: See, for example, ISO 16610-40 and ISO 16610-41.

3.2.1.6**Wolf pruning height**

particular type of *nesting index* (3.2.1) applicable to areal segmentation filters used to discriminate between significant and non-significant surface features

Note 1 to entry: See, for example, ISO 16610-85.

3.2.2**degree of freedom**

primary mathematical model number of independent parameters required to fully describe a particular *primary mathematical model* (3.2)

3.3**primary surface****PS**

surface portion (3.1.1) obtained when the latter is represented as a specified *primary mathematical model* (3.2) with specified *nesting index* (3.2.1)

3.3.1**primary profile**

line resulting from the intersection between the *primary surface* (3.3) and an ideal plane

Note 1 to entry: The concept of profiles is under development and it is possible that the definition of primary profile will be revised.

3.4**primary mapping**

mapping indexed by the *nesting index* (3.2.1) used to identify a particular *primary surface* (3.3) with a specified *nesting index* (3.2.1) in order to represent a *surface portion* (3.1.1) that satisfies the sieve and projection criteria

Note 1 to entry: A primary mapping identifies surface portions which have “features” larger than a particular nesting index.

3.4.1**sieve criterion**

criterion where two *primary mappings* (3.4) applied one after another to a surface portion is entirely equivalent to only applying one of these two primary mappings to the surface portion namely that primary mapping with the highest *nesting index* (3.2.1)

3.4.2**projection criterion**

criterion wherein a *primary surface* (3.3) with a specified *nesting index* (3.2.1) is mapped onto itself using the *primary mapping* (3.4) with the same specified *nesting index* (3.2.1)

Note 1 to entry: This implies that if you apply the primary mapping twice with the same nesting index to a surface, one obtains the same surface as if the primary mapping was applied only once. For example, applying a closing filter with a circular structural element of a given radius twice to a profile results in the same filtered profile as if the closing filter is only applied once.