
**Timber structures — Test methods —
Floor vibration performance**

*Structures en bois — Méthodes d'essai — Comportement vibratoire
des planchers*

Sample Document

get full document from standards.iteh.ai



Reference number
ISO 18324:2016(E)

© ISO 2016

Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Abbreviated terms	2
5 Measurement of natural frequencies and modal damping ratios	2
5.1 General.....	2
5.2 Apparatus.....	3
5.3 Test procedures.....	4
5.3.1 General requirements and principles.....	4
5.3.2 Shaker test procedure.....	5
5.3.3 Impact test procedure.....	7
5.4 Modal analysis.....	9
6 Measurement of static deflection under a concentrated load	9
6.1 General.....	9
6.2 Apparatus.....	10
6.3 Test procedure.....	11
7 Environmental condition of test site	11
8 Test report	12
Bibliography	13

get full document from standards.iteh.ai

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 165, *Timber structures*.

Introduction

Dynamic properties of timber structures are of critical importance to designers since they govern how these structures respond to seismic, wind and in-service human-induced dynamic excitation. Seismic and wind can cause structural failure, while in-service human-induced motion generally causes serviceability problems related to human discomfort; this is also true to wind-induced building motion. Since occupants are constantly in contact with the floor system, vibration serviceability of floor systems is often of concern to designers of timber structures. Vibrational performance of a timber floor can be assessed using parameters such as natural frequencies, damping ratios, dynamic responses to an impulse (dynamic displacement, velocity, and acceleration), and static deflection under a concentrated load. These parameters have been found to correlate well with human perceptions. Among these parameters, natural frequencies, damping ratios, and static deflection under concentrated load are commonly used to evaluate timber floor vibrational performance. Design procedures have been developed, and in some cases implemented in design standards, for assessing vibration serviceability of timber floors. These design procedures usually include criteria for floor response parameters, such as those listed above, and mathematical procedures to calculate these parameters. As an alternative to calculation, it is also necessary to provide standardized procedures to measure these parameters experimentally. This is the prime motive for the development of this ISO test standard.

Natural frequencies and damping ratios of a test system can be measured using modal testing. ISO published a series of International Standards on the application of modal testing and analysis to determine natural frequencies, modal damping ratios, and other dynamic properties of an object. The theory of modal testing and analysis has been well documented in Reference.[4] This International Standard provides practical procedures that can be applied either in the laboratory or in the field to measure natural frequencies, modal damping ratios and static deflection under a concentrated load of a timber floor. It is assumed that users of the International Standard have the necessary equipment and fundamental knowledge to perform modal testing.

This International Standard does not address acceptance criteria for vibrational serviceability.

Sample Document

get full document from standards.iteh.ai

Timber structures — Test methods — Floor vibration performance

1 Scope

This International Standard specifies test procedures to measure natural frequencies, modal damping ratios and static deflection under a concentrated load of laboratory or field timber floors. These parameters have been found to correlate well with human perception to timber floor vibration response caused by human-induced excitation under normal use. It is intended that the test procedures can be applied in lieu of calculation to quantify some or all of the above parameters that are used to evaluate the vibrational serviceability of the test floor. The subsequent use of the measured parameters to evaluate vibrational serviceability is, however, outside the scope of this International Standard.

ISO published a series of International Standards on the application of modal testing and analysis to determine natural frequencies, modal damping ratios, and other dynamic properties of a structure. For the measurement of dynamic parameters such as natural frequencies and modal damping ratios, modal testing is proposed in this International Standard. It is assumed that the test operators possess the required equipment and fundamental knowledge to perform such a test. The theory of modal testing and analysis has been well documented in Reference [4].

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

coherence function

indicator of the degree of linearity at each frequency component between the input and output signals, i.e., the noise level at each frequency component in the frequency response function (FRF) spectrum

Note 1 to entry: The value of coherence function is one when there is no noise in the signal, and zero for pure noise in the measured signals.

3.2

damping

parameter relating to the dissipation of energy, or more precisely, to the conversion of the mechanical energy associated with a vibration to a form that is unavailable to the vibration

3.3

natural frequency

frequency, associated with a *vibration mode* (3.12), at which a system naturally vibrates once it has been set into motion with a transient excitation

3.4

frequency response function

response function expressed in frequency domain and normalized to the input force

Note 1 to entry: It is the summation of each mode in the modal space. It shows the response of a system to be a series of peaks. Each peak with identifiable centre-frequency is the natural frequency of the system vibrating as if it was a single degree-of-freedom system.