
**Geometrical product specifications
(GPS) — Population specification**

*Spécification géométrique des produits (GPS) — Spécification de
population*

Sample Document

get full document from standards.iteh.ai



Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Rules for establishing a population specification	3
4.1 General	3
4.2 Rules	3
4.2.1 Rule 1: Description of a population specification	3
4.2.2 Rule 2: Description of type of individual GPS specification (univariate or multivariate)	5
4.2.3 Rule 3	7
5 Symbol used to specify a population specification	8
6 Rules for indicating a population specification	11
Annex A (informative) Relation in the GPS matrix model	15
Bibliography	16

Sample Document

get full document from standards.iteh.ai

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. www.iso.org/directives

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. www.iso.org/patents

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 213, *Dimensional and geometrical product specifications and verification*.

get full document from standards.iteh.ai

Introduction

This International Standard is a Geometrical Product Specification (GPS) standard and is to be regarded as a global GPS standard (see ISO 14638). It influences all chain links of all chains of standards.

The ISO/GPS Masterplan given in ISO 14638 gives an overview of the ISO/GPS system of which this document is a part. The fundamental rules of ISO/GPS given in ISO 8015 apply to this document and the default decision rules given in ISO 14253-1 apply to specifications made in accordance with this document, unless otherwise indicated. For more detailed information on the relationship of this International standard to other standards and to the GPS matrix model, see [Annex A](#).

In order to define the permissible interval for a geometrical characteristic, the designer only defines a condition (a unilateral tolerance limit or a bilateral pair of tolerance limits) for each workpiece, by considering the worst case impact in an assembly.

But when the tolerancing is based on a set of hypotheses about the population of the workpieces, one or more additional requirements should be added to verify these hypotheses.

NOTE The intent of this International Standard is not to define calculation methods to determine tolerances, but to give the means to express the hypotheses to verify.

Sample Document

get full document from standards.iteh.ai

Sample Document

get full document from standards.iteh.ai

Geometrical product specifications (GPS) — Population specification

1 Scope

This International Standard defines rules to establish and to indicate population specifications, which are used to specify conditions on population characteristics, which are established from a set of characteristic values obtained one on each workpiece of a population of workpieces.

A population specification (as applied to a population of workpieces considered as a collection and not as individual items) can be seen as a complementary requirement to the individual specification (as applied to each workpiece considered as individual items). Population specifications express the statistical hypotheses used on the population of workpieces.

NOTE 1 A population specification is a complement to an individual GPS specification.

NOTE 2 This International Standard is not intended to mandate a given tolerancing method or how to calculate tolerance values. Its intent is to specify tools to allow the expression of population specifications.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1101, *Geometrical product specifications (GPS) — Geometrical tolerancing — Tolerances of form, orientation, location and run-out*

ISO 14405-1, *Geometrical product specifications (GPS) — Dimensional tolerancing — Part 1: Linear sizes*

ISO 17450-1, *Geometrical product specifications (GPS) — General concepts — Part 1: Model for geometrical specification and verification*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 17450-1 and the following apply.

3.1

population characteristic

statistic defined from the characteristic values, obtained on the population of workpieces or the population of assemblies

Note 1 to entry: Population characteristics are used to consider the population of workpieces.

Note 2 to entry: Population characteristics are only statistically meaningful when the values are based upon global individual characteristics, see Example 2.

EXAMPLE 1 The arithmetic mean and the standard deviation of a global individual characteristic on the population of workpieces, are population characteristics.