
**Functional pigments and extenders for
special applications —**

**Part 1:
Nanoscale calcium carbonate for
sealant application**

*Pigments et matières de charges fonctionnels pour applications
spéciales —*

Partie 1: Carbonate de calcium nanométrique pour les enduits

Sample Document

get full document from standards.iteh.ai



Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Requirements and test methods	2
5 Sampling	3
6 Determination of whiteness	3
6.1 Apparatus	3
6.2 Procedure	3
6.2.1 Sample preparation	3
6.2.2 Calibration of the apparatus	4
6.2.3 Determination	4
6.2.4 Calculation of whiteness	4
7 Marking and label	4
8 Test report	4
Bibliography	5

Sample Document

get full document from standards.iteh.ai

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 256, *Pigments, dyestuffs and extenders*.

ISO 18473 consists of the following parts, under the general title *Functional pigments and extenders for special applications*:

- *Part 1: Nanoscale calcium carbonate for sealant application*
- *Part 2: Nanoscale titanium dioxide for sunscreen application*

Introduction

Sealants are widely used to prevent the penetration of air, gas, or liquid in many industries including construction, automobile, and electronics. Extenders are essential part of sealant formulation to reduce cost and improve their rheological and mechanical properties. Content of extenders vary significantly and can be as high as 50 % (mass fraction). The most common extender in sealants is calcium carbonate (CaCO_3) because it is readily available and comes in various sizes which act as a rheological modifier, a reinforcing agent, and opacifier. Commercial calcium carbonate can be divided into ground calcium carbonate (GCC) and precipitated calcium carbonate (PCC), possesses three crystal structures including calcite, aragonite, and vaterite, and exists in various morphologies such as cubic, spherical, spindle, fibrous, needle-like, etc. Calcium carbonates with calcite crystal structure and cubic or spherical morphology are most widely used in sealant applications.

Nanoscale calcium carbonate (NCC) provides various sealants with improved performance and additional functionalities including thixotropy, flame resistance and improved durability and recyclability, and has become a major component in sealant formulation. Nanoscale calcium carbonate in the powdered form is readily manufactured nowadays, mostly through precipitation route to control the size and morphology. Surface treatment is crucial for utilizing NCC in sealants. Native CaCO_3 is hydrophilic. As a result, it tends to agglomerate in organic polymers and plasticizers. NCC, in particular, has a greater propensity for agglomeration because of its small size and large specific surface area. NCCs are surface treated to render them hydrophobic and improve their dispersibility in hydrophobic systems. Surface treatment also improves polymer matrix compatibility, thus improving interfacial adhesion between extender and polymer.

It has been found that the particle size, specific surface area, mass fraction, morphology, pH value, magnesium content, oil absorption value, moisture content, and other characteristics of supplied nanoscale calcium carbonate all have impact on the performance of the sealant incorporating these nanoparticles. The need to specify the characteristics of NCC which relate to sealant performance comes from the following facts. First, the agreements between customers and suppliers do not always cover all material characteristics that have influences on performance and/or processability of sealants or they have been interpreted differently by the customers and suppliers. Second, nanomaterials are relatively new. Material properties can depend on the techniques to measure them. Therefore, providing information regarding characteristics of nanoscale calcium carbonate in sealants will facilitate the communication between customers and suppliers.

This part of ISO 18473 lists the properties, measurements, and characteristics of nanoscale calcium carbonate and intends to aid its acceptance and application in sealants.