



**International
Standard**

ISO 19426-5

**Structures for mine shafts —
Part 5:
Shaft system structures**

Structures de puits de mine —

Partie 5: Structures des réseaux de puits

**Second edition
2026-09**

Sample Document

get full document from standards.iteh.ai

Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO 2026

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols	2
5 Materials	5
6 Nominal loads	5
6.1 Permanent loads	5
6.1.1 Self-weight	5
6.1.2 Brow beams and sidewall support structures	5
6.1.3 Pipe supports	6
6.1.4 Conveyor supports	6
6.2 Imposed loads and load effects	6
6.2.1 General	6
6.2.2 Guide support structures	6
6.2.3 Fixed flare guides	12
6.2.4 Station structures	12
6.2.5 Rock loading structures	13
6.2.6 Operational arresting structures	13
6.2.7 Station dropsets	14
6.2.8 Pipe supports	14
6.2.9 Rope guide and rubbing rope anchor supports	15
6.2.10 Brattice walls	15
6.2.11 Strain loading	15
6.2.12 Ladderway loading	15
6.2.13 Conveyance drop test loads	16
6.2.14 Earthquake loads	16
6.3 Emergency loads	16
6.3.1 Emergency arresting structures	16
6.3.2 Emergency stopping devices	16
6.3.3 Pipe supports	16
6.3.4 Spillage winch support and sheave support structures	17
6.3.5 Brattice walls	17
6.3.6 Impact load on protective platforms	17
7 Design procedures	17
7.1 Design loads	17
7.2 Design codes	18
7.3 Design of emergency arresting structures	18
7.4 Design of emergency stopping device supports	18
7.5 Special design requirements for shaft steelwork in different shaft zones	18
7.5.1 Shaft zones	18
7.5.2 Shaft steelwork within shaft zone A	18
7.5.3 Shaft steelwork within shaft zone B	18
7.5.4 Shaft steelwork within shaft zone C	18
7.5.5 Shaft steelwork within shaft zone D	18
7.6 Additional limit states	19
7.6.1 Lateral displacement of conveyance	19
7.6.2 Fatigue	19
7.6.3 Rebound velocity ratio	19
7.6.4 Amplification of loads and load effects	19
7.7 Provision for wear and corrosion	21

7.8	Design of protective platforms	21
8	Construction requirements	21
8.1	General.....	21
8.2	Construction tolerances.....	21
Annex A	(informative) Shaft zone classification.....	24
Annex B	(informative) Shaft condition classification	25
Annex C	(informative) Load factors and load combinations.....	28
Annex D	(informative) Protective platforms.....	31
Bibliography		36

Sample Document

get full document from standards.iteh.ai

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 82, *Mining*.

This second edition cancels and replaces the first edition (ISO 19426-5:2018), which has been technically revised.

The main changes are as follows:

- boxfront section removed;
- additional clarity on pipe support loads;
- construction tolerances updated.

A list of all parts in the ISO 19426 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Many mining companies and many of the engineering companies which provide designs for mines, operate globally, so ISO 19426 series was developed in response to a desire for a unified global approach to the safe and robust design of structures for mine shafts. The characteristics of ore bodies, such as their depth and shape, vary in different areas so different design approaches have been developed and proven with use over time in different countries. Bringing these approaches together in ISO 19426 series will facilitate improved safety and operational reliability.

The majority of the material in ISO 19426 series deals with the loads to be applied in the design of structures for mine shafts. Some principles for structural design are given, but for the most part, it is assumed that local standards will be used for the structural design. It is also recognized that typical equipment varies from country to country, so the clauses in ISO 19426 series do not specify the application of the principles to specific equipment. However, in some cases, examples demonstrating the application of the principles to specific equipment are provided in informative annexes.

Sample Document

get full document from standards.iteh.ai

Structures for mine shafts —

Part 5: Shaft system structures

1 Scope

This document specifies the loads, the load combinations and the design procedures for the design of shaft system structures in both vertical and decline shafts. The shaft system structures covered by this document include buntons, guides and rails, station structures, rock loading structures, brattice walls, conveyance and vehicle arresting structures and dropsets, services supports, rope guide anchor supports and box fronts.

Rock support is excluded from the scope of this document.

This document does not cover matters of operational safety, or the layout of the shaft system structures

This document adopts a limit states design philosophy.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2394, *General principles on reliability for structures*

ISO 3010, *Bases for design of structures — Seismic actions on structures*

ISO 12122, *Timber structures — Determination of characteristic values*

ISO 19338, *Performance requirements for standards on concrete structures*

ISO 19426-1, *Structures for mine shafts — Part 1: Vocabulary*

ISO 19426-4, *Structures for mine shafts — Part 4: Conveyances.*

ISO 22111, *Bases for design of structures — General requirements*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 19426-1 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org>

4 Symbols

A	frontal area of the conveyance (m^2)
a	gap at a joint in a rail (m) (see Table B.2)
B_f and B_w	two sides of the section in Table 3 , for aspect 3
b	height difference between two rails at a support to the rails (m) (see Table B.2)
D_n	self-weight of pipe including any lagging (N/m)
d	vertical or lateral differential at a joint in a rail (m) (see Table B.2)
d_i	deformation of the relevant structural component (m).
d_s	depth of the conveyance guide shoe (m)
E_r	emergency rope load
E_p	emergency load on a protective platform
e	maximum moving beam misalignment of the guide (m) (see Table B.1)
e'	modified moving beam misalignment of the guide (m)
F	design load or load effect (N , Nm)
F_B	dynamic load on the platform (kN)
F_F	load on station footwall structures (N , N/m^2)
F_p	load on personnel loading and access platform structures (N , N/m^2)
F_V	vertical load (N)
G_1 and G_2	permanent loads or load effects (N , Nm)
G_b	permanent load applied to brow beams (N , N/m^2)
G_c	conveyance self-weight load (N)
G_p	permanent load applied to pipe supports (N)
G_s	permanent load applied to sidewall support structure (N)
G_y	permanent load on conveyor supports (N)
g	acceleration due to gravity (m/s^2)
H	lateral imposed load (N)
H_f	guide roller load (N)
H_s	lateral slipper plate load (N)
h	overall width or depth of the section or height of the bulk material (m)
h_1, h_2	lever arm distances of the relevant slipper plate loads with respect to the relevant centroidal axes (m)
h_b	height of the ore pass (m)

h_d	height through which the rock falls; to be taken as the depth of the rock pass (m)
I_l, I	mass moments of inertia of the conveyance about the centroidal axes perpendicular to the relevant direction of the slipper plate load (kgm ²)
K	conveyance holding device support load (N)
k_b	lateral stiffness of the steelwork at the guide to buntion connection (N/m)
$\overline{k_b}$	non-dimensional lateral steelwork stiffness at the guide to buntion connection
k_g	lateral stiffness of the steelwork at the guide midspan (N/m)
k_r	roller assembly stiffness (N/m)
L	guide span, buntion to buntion (m)
L_C	member length (m)
L_p	assessed length of pipe supported on the pipe support (m)
$\bar{M}$	guide bending moment coefficient (obtained from Figure 2)
M_g	maximum guide bending moment (Nm)
m_e	proportion of the conveyance mass effectively acting at a slipper plate (kg)
m_r	mass of the largest rock (kg).
m_s	mass of the conveyance (empty or full) including the compensating sheave mass, if applicable (kg)
n	number of wheels on the conveyance
p	surface pressure on the layer of girders (kN/m ²)
P_a	load on arresting structures (N)
$\overline{P_b}$	slipper plate load coefficient (obtained from Figure 1)
P_{d1}, P_{d2}, P_{d3}	loads on station dropsets (N)
p_h	hydrostatic pressure (N/m ²)
P_p	vertical impact load on penthouse structures (N)
Q	conveyance payload (N)
Q_1	dominant imposed load or load effect, or the applied load causing fatigue (N, Nm)
Q_2 to Q_n	additional independent imposed loads or load effects (N, Nm)
Q_e	emergency load or load effect (N, Nm)
R_i	single rock impact load on the box front (N)
r_k	steelwork stiffness ratio = k_b/k_g
r_u	rebound velocity ratio (obtained from Figure 5)
$r_{u.1}$	rebound velocity ratio on the stiffer side (obtained from Figure 5)

$r_{u.2}$	rebound velocity ratio on the less stiff side (obtained from Figure 5)
s	penetration depth into the bulk material (m)
S_f	frequency of guide roller load application (percentage of buntons passed deemed to cause guide roller load application) (see Table B.1)
S_r	frequency of rail impact load application (percentage of rail joints passed deemed to cause rail impact load application) (see Table B.2)
S_s	frequency of slipper plate load applications (obtained from Table B.1)
T	slinging load (N)
T_s	static load applied to slinging anchorage (N)
U	load due to underslung equipment (N)
U_p	impact energy on a protective platform (J)
v	winding velocity (m/s)
W_a	wheel impact load arising from rail joint irregularity (N)
W_l	lateral wheel load acting normal to the rail (N)
W_n	conveyance wheel load acting normal to the rail (N)
Z_i	impact energy of the falling rock (J)
α_a	conveyance impact factor
α_{d1}	conveyance loading impact factor
α_{d2}	rail impact factor due to rail irregularities
α_{d3}	shaft impact factor due to the change in direction from the decline shaft to the station dropset
α_f	hopper door opening impact factor
α_i	proportion of potential energy transferred into impact energy on the box front
α_l	lateral wheel load factor (see Table B.2)
α_n	nominal slipper plate impact factor
α_r	shaft condition factor (see Table B.1)
α_s	sling impact factor
α_w	wheel dynamic factor
α_H	wheel horizontal load factor
β	dynamic load coefficient
β_s	slipper load amplification factor
δ_s	conveyance displacement coefficient (obtained from Figure 3)
γ_e	partial load factor for emergency loads

γ_{f1} to γ_{fn}	partial load factors for imposed loads
γ_{g1} and γ_{g2}	partial load factors for permanent loads
ε_t	transverse rock strain, as defined by rock engineering analysis
μ	friction factor between the hopper payload and the door
ρ	bulk density of ore pass contents, or the bulk density of hopper payload (kg/m ³)
Ψ_1 to Ψ_n	load combination factors
$\varnothing_d$	angle between the horizontal and the shaft decline
$\varnothing_s$	angle between the dropset and the shaft decline
Δ	total lateral displacement of a conveyance (m)
Δ_c	specified clearance between slipper plate and guide (m)
Δ_e	sum of guide gauge and slipper gauge variations, or the rail gauge variations (m) (see Table B.1 and Table B.2)
Δ_{e1}	maximum allowable guide gauge variation (m) (see Table B.1)
Δ_g	lateral guide displacement (m)
Δ_o	overlap allowance (m) which shall be taken as not less than 0,003 m
Δ_w	slipper plate wear (m) (see Table B.1)

5 Materials

Materials used in the construction of shaft system structures as structural steel should be as specified in EN 197-1 and EN 206-1 for concrete and ISO 12122 for timber. All materials used shall be properly graded materials.

6 Nominal loads

6.1 Permanent loads

6.1.1 Self-weight

Self-weight shall be assessed in accordance with ISO 22111.

6.1.2 Brow beams and sidewall support structures

Where required, the permanent load, G_b , applied to brow beams shall be assessed considering the rock over-break. For preliminary design purposes only this value shall be not less than a uniformly distributed load of 20 000 N/m².

The permanent load, G_s , applied to sidewall support structures shall be assessed considering the rock properties and over-break. For preliminary design purposes only this value shall be not less than a uniformly distributed load of 5 000 N/m².

For the final design, the loading shall be specified in consultation with the rock engineer, including consideration of fractured or weak rock or expansive rock conditions.

6.1.3 Pipe supports

The permanent load, G_p , applied to pipe supports shall be obtained using the following [Formula \(1\)](#):

$$G_p = L_p D_n \quad (1)$$

where

L_p is the assessed length of pipe supported on the pipe support. In the absence of better information, the assessed length, for vertical pipes, shall be taken to be the length of pipe from the support below the one in question to the support above the one in question (m);

for horizontal or inclined pipes, the assessed length shall be taken as the length of pipe from the support to the left of the one in question to the support to the right of the one in question (m);

D_n is the self-weight of pipe including any connections and lagging (N/m).

NOTE Pipes can also be subjected to lateral loads.

6.1.4 Conveyor supports

The permanent load, G_y , on conveyor supports shall be assessed in accordance with normal conveyor design practice.

6.2 Imposed loads and load effects

6.2.1 General

Shaft system structures shall be designed to resist the imposed loads as assessed in accordance with ISO 22111. In addition, they shall be designed to resist the loads defined in [6.2.2](#) to [6.2.14](#).

6.2.2 Guide support structures

6.2.2.1 Fixed guides in vertical shafts in shaft zone A (see [Annex A](#))

6.2.2.1.1 Lateral imposed loads, H , and maximum guide bending moment, M_g

It shall be assumed that only one of the loads defined in a) and b) can act at any one time:

a) Guide roller load (H_f):

The load normal to the guide face or the guide sides shall be taken as given in [Formula \(2\)](#):

$$H_f = k_r \Delta_c \quad (2)$$

where

k_r is the roller assembly stiffness (N/m);

Δ_c is the specified clearance between slipper plate and guide (m).

b) Lateral slipper plate load (H_s):

Slipper plate loads shall be assessed in two directions, namely, normal to the face of the guide and normal to the sides of the guide. These loads shall be assessed for both full and empty conveyances and shall be applied to the guide in the vicinity of the connection to the bunton, considering the action of only one slipper at a time, i.e. it is assumed that the slipper plate load normal to the face of the guide and the slipper plate load normal to the sides of the guide cannot occur simultaneously.

The lateral load between any slipper plate and the guide, H_s (N), shall be taken as: