
Cranes — Proof of competence of steel structures

Appareils de levage à charge suspendue — Vérification d'aptitude des charpentes en acier

Sample Document

get full document from standards.iteh.ai



Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Foreword.....	5
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviated terms	2
4 General	8
4.1 General principles	8
4.2 Documentation	8
4.3 Alternative methods	8
4.4 Materials of structural members	8
4.5 Bolted connections.....	11
4.5.1 Bolt materials.....	11
4.5.2 General	11
4.5.3 Shear and bearing connections	11
4.5.4 Friction grip type (slip resistant) connections	12
4.5.5 Connections loaded in tension.....	12
4.6 Pinned connections.....	12
4.7 Welded connections	12
4.8 Proof-of-competence for structural members and connections	13
5 Proof of static strength	13
5.1 General	13
5.2 Limit design stresses and forces	14
5.2.1 General	14
5.2.2 Limit design stress in structural members	14
5.2.3 Limit design forces in bolted connections	15
5.2.4 Limit design forces in pinned connections.....	23
5.2.5 Limit design stresses in welded connections	27
5.3 Execution of the proof.....	29
5.3.1 Proof for structural members	29
5.3.2 Proof for bolted connections	29
5.3.3 Proof for pinned connections.....	29
5.3.4 Proof for welded connections	30
6 Proof of fatigue strength	31
6.1 General	31
6.2 Limit design stresses	32
6.2.1 Characteristic fatigue strength	32
6.2.2 Weld quality.....	33
6.2.3 Requirements for fatigue testing.....	34
6.3 Stress histories	35
6.3.1 Determination of stress histories	35
6.3.2 Frequency of occurrence of stress cycles.....	35
6.3.3 Stress history parameter	36
6.3.4 Determination of stress history class, S	39
6.4 Execution of the proof.....	40
6.5 Determination of the limit design stress range	40
6.5.1 Applicable methods	40
6.5.2 Direct use of stress history parameter	40

6.5.3	Use of S classes	41
6.5.4	Independent concurrent normal and/or shear stresses	42
7	Proof of elastic stability	43
7.1	General.....	43
7.2	Lateral buckling of members loaded in compression.....	43
7.2.1	Critical buckling load	43
7.2.2	Limit compressive design force	44
7.3	Buckling of plate fields subjected to compressive and shear stresses	46
7.3.1	General.....	46
7.3.2	Limit design stress with respect to longitudinal stress σ_x	48
7.3.3	Limit design stress with respect to transverse stress σ_y	50
7.3.4	Limit design stress with respect to shear stress τ	51
7.4	Execution of the proof	52
7.4.1	Members loaded in compression	52
7.4.2	Plate fields	52
Annex A (informative)	Limit design shear force, $F_{v,Rd}$, in shank per bolt and per shear plane for multiple shear plane connections	54
Annex B (informative)	Preloaded bolts	55
Annex C (normative)	Design weld stresses, $\sigma_{w,Sd}$ and $\tau_{w,Sd}$	57
Annex D (normative)	Values of slope constant, m , and characteristic fatigue strength, $\Delta\sigma_c$, $\Delta\tau_c$	61
Annex E (normative)	Calculated values of limit design stress range, $\Delta\sigma_{Rd}$ and $\Delta\sigma_{Rd,1}$	85
Annex F (informative)	Evaluation of stress cycles — Example.....	87
Annex G (informative)	Calculation of stiffnesses for connections loaded in tension.....	89
Bibliography		92

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html

The committee responsible for this document is ISO/TC 96, *Cranes*, Subcommittee SC 10, *Design principles and requirements*.

This second edition cancels and replaces the first edition (ISO 20332:2008), which has been technically revised.

This corrected version of ISO 20332:2016 incorporates a correction in Formula (67).

Sample Document

get full document from standards.iteh.ai

Cranes — Proof of competence of steel structures

1 Scope

This International Standard sets forth general conditions, requirements, methods, and parameter values for performing proof-of-competence determinations of the steel structures of cranes based upon the limit state method. It is intended to be used together with the loads and load combinations of the applicable parts of ISO 8686.

This International Standard is general and covers cranes of all types. Other International Standards can give specific proof-of-competence requirements for particular crane types.

Proof-of-competence determinations, by theoretical calculations and/or testing, are intended to prevent hazards related to the performance of the structure by establishing the limits of strength, e.g. yield, ultimate, fatigue, and brittle fracture.

According to ISO 8686-1 there are two general approaches to proof-of-competence calculations: the *limit state* method, employing partial safety factors, and the *allowable stress* method, employing a global safety factor. Though it does not preclude the validity of allowable stress methodology, ISO 20332 deals only with the limit state method.

Proof-of-competence calculations for components of accessories (e.g. handrails, stairs, walkways, cabins) are not covered by this International Standard. However, the influence of such attachments on the main structure needs to be considered.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 148-1:2009, *Metallic materials — Charpy pendulum impact test — Part 1: Test method*

ISO 273:1979, *Fasteners — Clearance holes for bolts and screws*

ISO 286-2:2010, *Geometrical product specifications (GPS) — ISO code system for tolerances on linear sizes — Part 2: Tables of standard tolerance classes and limit deviations for holes and shafts*. Corrected by ISO 286-2:2010/Cor 1:2013.

ISO 404:1992, *Steel and steel products — General technical delivery requirements*

ISO 898-1:2013, *Mechanical properties of fasteners made of carbon steel and alloy steel — Part 1: Bolts, screws and studs with specified property classes — Coarse thread and fine pitch thread*

ISO 4042:1999, *Fasteners — Electroplated coatings*

ISO 4301-1:2016, *Cranes and lifting appliances — Classification — Part 1: General*

ISO 4306-1:2007, *Cranes — Vocabulary — Part 1: General*

ISO 5817:2014, *Welding — Fusion-welded joints in steel, nickel, titanium and their alloys (beam welding excluded) — Quality levels for imperfections*

ISO 7452:2013, *Hot-rolled steel plates — Tolerances on dimensions and shape*

ISO 7788:1985, *Steel — Surface finish of hot-rolled plates and wide flats — Delivery requirements*

ISO 8686-1:2012, *Cranes — Design principles for loads and load combinations — Part 1: General*

ISO 8686-2, *Cranes — Design principles for loads and load combinations — Part 2: Mobile cranes*

ISO 8686-3, *Cranes — Design principles for loads and load combinations — Part 3: Tower cranes*

ISO 8686-4, *Cranes — Design principles for loads and load combinations — Part 4: Jib cranes*

ISO 8686-5, *Cranes — Design principles for loads and load combinations — Part 5: Overhead travelling and portal bridge cranes*

ISO 9013:2002, *Thermal cutting — Classification of thermal cuts — Geometrical product specification and quality tolerances*

ISO 9587:2007, *Metallic and other inorganic coatings — Pretreatments of iron or steel to reduce the risk of hydrogen embrittlement*

ISO 12100, *Safety of machinery — Basic concepts, general principles for design — Risk assessment and risk reduction*

ISO 15330:1999, *Fasteners — Preloading test for the detection of hydrogen embrittlement — Parallel bearing surface method*

ISO 17659:2002, *Welding — Multilingual terms for welded joints with illustrations*

3 Terms, definitions, symbols and abbreviated terms

For the purposes of this document, the terms and definitions given in ISO 12100, ISO 17659, ISO 4306-1:2007, Clause 6, and the following terms, definitions, symbols and abbreviated terms (see Table 1) apply.

3.1

grade of steel

marking that defines the strength of steel, usually defining yield stress, f_y , sometimes also ultimate strength, f_u

3.2

quality of steel

marking that defines the impact toughness and test temperature of steel

Table 1 — Main symbols and abbreviations used in this International Standard

Symbol	Description
A	Cross-section
A_{eq}	Equivalent area for calculation
A_n	Net cross-sectional area at bolt or pin holes
A_r	Minor area of the bolt
A_s	Stress area of the bolt
a	Geometric dimension
a_{hi}	Geometric dimension for weld penetration
a_r	Effective weld thickness
b	Geometric dimension
c	Geometric dimension
D_A	Diameter of available cylinder of clamped material
D_i	Inner diameter of hollow pin
D_o	Outer diameter of hollow pin
d	Diameter (shank of bolt, pin)
d_h	Diameter of the hole
d_w	Diameter of the contact area of the bolt head
d_0	Diameter of the hole
E	Modulus of elasticity
e_1, e_2	Edge distances
F	Force
F_b	Tensile force in bolt
$F_{b,Rd}$	Limit design bearing force
$F_{b,Sd}, F_{bi,Sd}$	Design bearing force
ΔF_b	Additional force
F_{cr}	Reduction in the compression force due to external tension
$F_{cs,Rd}$	Limit design tensile force
F_d	Limit force
$F_{e,t}$	External force (on bolted connection)
F_k	Characteristic value (force)
F_p	Preloading force in bolt

Table 1 (continued)

Symbols	Description
$F_{p,d}$	Design preloading force
F_{Rd}	Limit design force
F_{Sd}	Design force of the element
$F_{s,Rd}$	Limit design slip force per bolt and friction interface
$F_{t1,Rd}, F_{t2,Rd}$	Limit design tensile forces per bolt
$F_{t,Sd}$	External tensile force per bolt
$F_{v,Rd}$	Limit design shear force per bolt/pin and shear plane
$F_{v,Sd}$	Design shear force per bolt/pin and shear plane
$F_{\sigma,\tau}$	Acting normal/shear force
f	Out-of-plane imperfection of plate field
$f_{b,Rd,x}$	Limit design compressive longitudinal stress
$f_{b,Rd,y}$	Limit design compressive transverse stress
$f_{b,Rd,\tau}$	Limit design buckling shear stress
f_d	Limit stress
f_k	Characteristic value (stress)
f_{Rd}	Limit design stress
f_u	Ultimate strength of material
f_{ub}	Ultimate strength of bolts
f_{uw}	Ultimate strength of the weld
$f_{w,Rd}$	Limit design weld stress
f_y	Yield stress of material or 0,2 % offset yield strength
f_{yb}	Yield stress of bolts
f_{yk}	Yield stress (minimum value) of base material or member
f_{yp}	Yield stress of pins
h	Thickness of workpiece
h_d	Distance between weld and contact area of acting load
I	Moment of inertia
K_b	Stiffness (slope) of bolt
K_c	Stiffness (slope) of flanges
k_m	Stress spectrum factor based on m of the detail under consideration

Table 1 (continued)

Symbols	Description
k^*	Specific spectrum ratio factor
k_{σ}, k_{τ}	Buckling factors for plate fields
L	Length of compressed member
l_k	Effective clamped length
l_m	Gauge length for imperfection of plate field
l_r	Effective weld length
l_w	Weld length
l_1	Effective length for tension without threat
l_2	Effective length for tension with threat
M_{Rd}	Limit design bending moment
M_{Sd}	Design bending moment
m	(Negative inverse) slope constant of $\log \sigma / \log N$ curve
N	Number of stress cycles to failure by fatigue
N_c	Compressive force
N_k	Critical buckling load of compressed member
N_{Rd}	Limit design compressive force
N_{Sd}	Design compressive force
N_{ref}	Number of cycles at the reference point
N_t	Total number of occurrences
NC	Notch class
NDT	Non-destructive testing
n_i	Number of stress cycles with stress amplitude of range i
n	Number of equally loaded bolts
P_s	Probability of survival
p_1, p_2	Distances between bolt centres
Q	Shear force
q_i	Impact toughness parameter
R_d	Design resistance
r	Radius of wheel
S	Class of stress history parameter, s
S_d	Design stresses or forces

Table 1 (*continued*)

Symbols	Description
s_m	Stress history parameter
T	Temperature
TIG	Tungsten inert gas
t	Thickness
U	Class of working cycles
u	Shape factor
v	Diameter ratio
W_{el}	Elastic section modulus
α	Characteristic factor for bearing connection
α_w	Characteristic factor for limit weld stress
γ_{mf}	Fatigue strength specific resistance factor
γ_m	General resistance factor
γ_p	Partial safety factor
γ_R	Total resistance factor
γ_{Rb}	Total resistance factor of bolt
γ_{Rc}	Total resistance factor for tension on sections with holes
γ_{Rm}	Total resistance factor of members
γ_{Rp}	Total resistance factor of pins
γ_{Rs}	Total resistance factor of slip-resistance connection
γ_s	Specific resistance factor
γ_{sb}	Specific resistance factor of bolt
γ_{sm}	Specific resistance factor of members
γ_{sp}	Specific resistance factor of pins
γ_{ss}	Specific resistance factor of slip-resistance connection
γ_{st}	Specific resistance factor for tension on sections with holes
$\Delta\delta_t$	Additional elongation
δ_p	Elongation from preloading
θ_i	Incline of diagonal members
κ	Dispersion angle
λ	Width of contact area in weld direction
μ	Slip factor

Table 1 (continued)

Symbols	Description
ν	Relative total number of stress cycles (normalized)
ν_D	Ratio of diameters
σ	Indicate the respective stress
$\Delta\sigma$	Stress range
$\Delta\sigma_i$	Stress range i
$\Delta\hat{\sigma}$	Maximum stress range
σ_b	Lower extreme value of stress cycle
$\Delta\sigma_c$	Characteristic fatigue strength (normal stress)
σ_e	Reference stress for plate buckling
σ_m	Constant mean stress selected for one-parameter classification of stress cycles
$\Delta\sigma_{Rd}$	Limit design stress range (normal)
$\Delta\sigma_{Rd,1}$	Limit design stress range for $k^* = 1$
σ_{Sd}	Design stress (normal)
$\Delta\sigma_{Sd}$	Design stress range (normal)
$\sigma_{Sd,x}$	Design compressive longitudinal stress
$\sigma_{Sd,y}$	Design compressive transverse stress
σ_u	Upper extreme value of stress cycle
$\sigma_{w, Sd}$	Design weld stress (normal)
σ_x, σ_y	Normal stress component in direction x, y
$\hat{\sigma}_a$	Maximum stress amplitude
$\min \sigma, \max \sigma$	Extreme values of stresses
τ	Shear stress
$\Delta\tau_c$	Characteristic fatigue strength (shear stress)
τ_{Sd}	Design stress (shear)
$\Delta\tau_{Sd}$	Design stress range (shear)
$\Delta\tau_{Rd}$	Limit design stress range (shear)
$\tau_{w, Sd}$	Design weld stress (shear)
ϕ_i	Dynamic factor
ψ	Stress ratio across plate fields

4 General

4.1 General principles

Proof-of-competence calculations shall be done for components, members, and details exposed to loading or repetitive loading cycles that could cause failure, cracking, or distortion interfering with crane functions.

NOTE See ISO 8686 for further information applicable to the various types of crane. Not all calculations are applicable for every crane type.

4.2 Documentation

The documentation of the proof-of-competence calculations shall include the following:

- design assumptions including calculation models;
- applicable loads and load combinations;
- material properties;
- weld quality classes in accordance with ISO 5817;
- properties of connecting elements;
- relevant limit states;
- results of the proof-of-competence calculations and tests when applicable.

4.3 Alternative methods

The competence may be verified by experimental methods in addition to or in coordination with the calculations. The magnitude and distribution of loads during tests shall correspond to the design loads and load combinations for the relevant limit states.

Alternatively, advanced and recognized theoretical or experimental methods generally may be used, provided that they conform to the principles of this International Standard.

4.4 Materials of structural members

It is recommended that steels in accordance with the following International Standards be used:

- ISO 630;
- ISO 6930-1;
- ISO 4950-1;
- ISO 4951-1, ISO 4951-2, and ISO 4951-3.

Where other steels are used, the specific values of strengths f_u and f_y shall be specified. The mechanical properties and the chemical composition shall be specified in accordance with ISO 404. Furthermore, the following conditions shall be fulfilled:

- the design value of f_y shall be limited to $f_u/1,05$ for materials with $f_u/f_y < 1,05$;
- the percentage elongation at fracture $A \geq 7\%$ on a gauge length $L_0 = 5,65 \times \sqrt{S_0}$ (where S_0 is the original cross-sectional area);
- the weldability or non-weldability of the material shall be specified and, if intended for welding, weldability demonstrated;
- if the material is intended for cold forming, the pertinent parameters shall be specified.

To allow the use of nominal values of plate thicknesses in the proof calculations, the minus tolerance of the plate shall be equal or better than that of class A of ISO 7452:2013. Otherwise, the actual minimum value of plate thickness shall be used.

When verifying the grade and quality of the steel (see referenced International Standards) used for tensile members, the sum of impact toughness parameters, q_i , shall be taken into account. Table 2 gives q_i for various influences. The required impact energy/test temperatures in dependence of $\sum q_i$ are shown in Table 3 and shall be specified by the steel manufacturer on the basis of ISO 148-1.

Sample Document

get full document from standards.iteh.ai