
**Road vehicles — Clock extension
peripheral interface (CXPI) —**

**Part 6:
Transport and network layer
conformance test plan**

*Véhicules routiers — Interface périphérique d'extension d'horloge
(CXPI) —*

Partie 6: Plan de test de conformité des couches transport et réseau

Document Preview

ISO 20794-6:2020

<https://standards.iteh.ai/catalog/standards/iso/32bd2adf-a703-4e3e-8656-8e63a6418cf7/iso-20794-6-2020>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 20794-6:2020

<https://standards.iteh.ai/catalog/standards/iso/32bd2adf-a703-4e3e-8656-8e63a6418cf7/iso-20794-6-2020>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	2
4.1 Symbols	2
4.2 Abbreviated terms	3
5 Conventions	3
6 General test specification considerations	3
6.1 General	3
6.2 Test conditions	4
6.3 IUT requirements	4
6.4 CTC definition	4
6.5 Test system set-up	5
6.6 Configuration of test system and IUT	6
6.6.1 General	6
6.6.2 IUT-specific set-up parameters	8
6.6.3 User_Specific configurations	8
6.6.4 T_FltMng1 configurations	8
6.6.5 T_FltMng2 configurations	8
6.6.6 N_ErrDet1 configurations	9
6.6.7 N_ErrDet2 configurations	9
6.6.8 W/S configurations	9
6.7 SUT initialisation	9
6.7.1 General	9
6.7.2 Default initialisation	9
7 Transport layer conformance test plan	9
7.1 General	9
7.2 4.CTC_1.1 – Master node – T_PDU and T_PCI data handling – T_PCItypes and T_PCI_DL	10
7.3 4.CTC_1.2 – Slave node – T_PDU and T_PCI data handling – T_PCItypes and T_PCI_DL	10
7.4 4.CTC_1.3 – Master node – T_PDU and T_PCI data handling (T_PCItypes and T_PCI_DLext)	11
7.5 4.CTC_1.4 – Slave node – T_PDU and T_PCI data handling (T_PCItypes and T_PCI_DLext)	12
7.6 4.CTC_1.5 – Master node – T_PDU and T_PCI data handling (T_PCItypes and T_PCI_DLext with short data field)	13
7.7 4.CTC_1.6 – Slave node – T_PDU and T_PCI data handling (T_PCItypes and T_PCI_DLext with short data field)	14
7.8 4.CTC_2.1 – Master node – TL Error detection test (T_PCItypes)	16
7.9 4.CTC_2.2 – Slave node – TL Error detection test (T_PCItypes)	17
7.10 4.CTC_2.3 – TL Error detection test (T_PCItypes) using error bit	18
7.11 4.CTC_2.4 – Master node – TL Error detection test (T_PCI_DL)	19
7.12 4.CTC_2.5 – Slave node – TL Error detection test (T_PCI_DL)	20
7.13 4.CTC_2.6 – TL Error detection test (T_PCI_DL) using error bit	21
7.14 4.CTC_2.7 – Master node – TL Error detection test (T_PCI_DLext)	22
7.15 4.CTC_2.8 – Slave node – TL Error detection test (T_PCI_DLext)	23
7.16 4.CTC_2.9 – TL Error detection test (T_PCI_DLext) using error bit	24
8 Network layer conformance test	24
8.1 General	24
8.2 3.CTC_3.1 – Master node – N_PDU specification test (N_NAD)	25
8.3 3.CTC_3.2 – Slave node – N_PDU specification test (N_NAD)	26

8.4	3.CTC_3.3 – Reception logic test (in the case of $T_PID = 1F_{16}$ and $N_NAD = 00_{16}$).....	27
8.5	3.CTC_4.1 – Master node – NL error detection (N_As timeout).....	28
8.6	3.CTC_4.2 – Slave node – NL error detection (N_As timeout).....	28
Bibliography		30

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

[ISO 20794-6:2020](https://standards.itih.ai/catalog/standards/iso/32bd2adf-a703-4e3e-8656-8e63a6418cf7/iso-20794-6-2020)

<https://standards.itih.ai/catalog/standards/iso/32bd2adf-a703-4e3e-8656-8e63a6418cf7/iso-20794-6-2020>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*.

A list of all parts in the ISO 20794 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

ISO 20794 (all parts) specifies the application (partly), application layer, transport layer, network layer, data link layer and physical layer requirements of an in-vehicle network called “clock extension peripheral interface (CXPI)”.

CXPI is an automotive low-speed single wire network. It is an enabler for reducing vehicle weight and fuel consumption by reducing wire counts to simple devices like switches and sensors.

CXPI serves as and is designed for automotive control applications, for example door control group, light switch and HVAC (Heating Ventilation and Air Condition) systems.

The CXPI services, protocols and their key characteristics are specified in different parts according to the OSI layers.

- Application and application layer:
 - application measurement and control data communication to exchange information between applications in different nodes based on message communication;
 - wake-up and sleep functionality;
 - two kinds of communication methods can be selected at system design by each node:
 - i) the event-triggered method, which supports application measurement- and control-based (event-driven) slave node communication; and
 - ii) the polling method, which supports slave node communication based on a periodic master schedule;
 - performs error detection and reports the result to the application;
 - application error management.
- Transport layer and network layer: [ISO 20794-6:2020](https://standards.iteh.ai/catalog/standards/iso/32bd2adf-a703-4e3e-8656-8e63a6418cf7/iso-20794-6-2020)
 - transforms a message into a single packet;
 - adds protocol control information for diagnostic and node configuration into each packet;
 - adds packet identifier for diagnostic and node configuration into each packet;
 - performs error detection and reports the result to higher OSI layers.
- Data link layer and physical layer:
 - provides long and short data frames;
 - adds a frame identifier into the frame;
 - adds frame information into the frame;
 - adds a cyclic redundancy check into the frame;
 - performs byte-wise arbitration and reports the arbitration result to higher OSI layers;
 - performs frame type detection in reception function;
 - performs error detection and reports the result to higher OSI layers;
 - performs Carrier Sense Multiple Access (CSMA);
 - performs Collision Resolution (CR);