
**Road vehicles — In-vehicle Ethernet —
Part 3:
Optical 1-Gbit/s physical entity
requirements and conformance test
plan**

Véhicules routiers — Ethernet embarqué —

*Partie 3: Exigences et plan d'essais de conformité de la couche
physique optique à 1-Gbit/s*

iTech Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 21111-3:2020](https://standards.iteh.ai/catalog/standards/iso/fdc28bf4-2b6e-418f-98d0-48c7cd0d74c3/iso-21111-3-2020)

<https://standards.iteh.ai/catalog/standards/iso/fdc28bf4-2b6e-418f-98d0-48c7cd0d74c3/iso-21111-3-2020>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 21111-3:2020](https://standards.iteh.ai/catalog/standards/iso/fdc28bf4-2b6e-418f-98d0-48c7cd0d74c3/iso-21111-3-2020)

<https://standards.iteh.ai/catalog/standards/iso/fdc28bf4-2b6e-418f-98d0-48c7cd0d74c3/iso-21111-3-2020>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Abbreviated terms	2
5 Wake-up and synchronised link sleep functionality	4
5.1 General.....	4
5.2 PHY service interface for a GEPOF entity.....	5
5.3 Neighbour PHY service interface for a GEPOF entity.....	7
5.4 Conciliation service interface.....	9
5.4.1 General.....	9
5.4.2 CON_WakeUpSleepPacket.request.....	11
5.4.3 CON_WakeUpSleepPacket.indication.....	11
5.4.4 CON_WakeUpSleepPacketACK.indication.....	12
5.4.5 CON_SignalDetected.indication.....	12
5.4.6 CON_OAMActive.indication.....	12
5.5 FFME service interface.....	13
5.5.1 General.....	13
5.5.2 FFME_PowerDownStatus.request.....	15
5.5.3 FFME_PowerDownStatus.indication.....	15
5.5.4 FFME_WakeUp.indication.....	15
5.6 802-3bv service interface.....	16
5.6.1 General.....	16
5.6.2 802-3bv_PowerDownStatus.request.....	18
5.6.3 802-3bv_RXDETECT.indication.....	18
5.7 WUSME Sublayer.....	18
5.7.1 General.....	18
5.7.2 WUSME wake-up functionality.....	18
5.7.3 WUSME synchronised link sleep functionality.....	21
5.7.4 PHY_SleepStatus.indication generation.....	23
5.8 FFME sublayer.....	23
5.8.1 General.....	23
5.8.2 FFME power state functionality.....	23
5.9 Conciliation sublayer.....	26
5.9.1 General.....	26
5.9.2 Conciliation sublayer variables.....	26
5.9.3 CRC16 computation.....	26
5.9.4 Generating ISO/IEC/IEEE 8802-3:2017/Amd 9:2018, Clause 45 stimuli from CON_WakeUpSleepPacket.request.....	27
5.9.5 Generating CON_WakeUpSleepPacket.indication from ISO/IEC/IEEE 8802-3:2017/Amd 9:2018, Clause 45 stimuli.....	27
5.9.6 Generating CON_WakeUpSleepPacketACK.indication from ISO/IEC/IEEE 8802-3:2017/Amd 9:2018, Clause 45 stimuli.....	28
5.9.7 Generating CON_SignalDetected.indication from ISO/IEC/IEEE 8802- 3:2017/Amd 9:2018, Clause 45 stimuli.....	28
5.9.8 Conciliation sublayer constants.....	28
6 PICS proforma	29
6.1 General.....	29
6.2 Major capabilities/options.....	29
6.3 Wake-up and synchronised link sleep PICS items.....	29
7 Test plan	30

7.1	Test plan scope.....	30
7.2	Test plan architecture.....	30
7.3	Test plan organization.....	32
7.4	Test case sections.....	32
7.5	Test case reference tables.....	33
7.5.1	Block 1: test mode and loopback test cases.....	33
7.5.2	Block 2: PCS, PMA, PMD and MDI test cases.....	34
7.5.3	Block 3. EEE, OAM and wake-up and synchronised link sleep test cases.....	37
7.6	Test setups.....	38
7.6.1	General.....	38
7.6.2	Test setup 1: TS_BASE.....	42
7.6.3	Test setup 2: TS_EXTEND.....	43
7.6.4	Test setup 3: TS_SIGPOW.....	44
7.6.5	Test setup 4: TS_AOPTX.....	44
7.6.6	Test setup 5: TS_ER.....	44
7.6.7	Test setup 6: TS_CW.....	44
7.6.8	Test setup 7: TS_SW.....	44
7.6.9	Test setup 8: TS_RT_FT.....	44
7.6.10	Test setup 9: TS_OS.....	44
7.6.11	Test setup 10: TS_NOD_POD.....	44
7.6.12	Test setup 11: TS_DIST.....	45
7.6.13	Test setup 12: TS_RIN.....	45
7.6.14	Test setup 13: TS_MPD.....	45
7.6.15	Test setup 14: TS_TJ.....	45
7.6.16	Test setup 15: TS_2LP.....	45
7.6.17	Test setup 16: TS_AOPRX.....	45
7.6.18	Test setup 17: TS_LOOP.....	46
7.7	Block 1 test cases: test modes and loopbacks.....	47
7.7.1	General.....	47
7.7.2	LBT_1: Loopback control.....	47
7.7.3	LBT_2: GMII loopback.....	48
7.7.4	LBT_3: PMD loopback.....	50
7.7.5	TMT_1: Test mode configuration general.....	52
7.7.6	TMT_2: Test mode 1 transmission.....	53
7.7.7	TMT_4: Test mode 2 transmission.....	55
7.7.8	TMT_5: Test mode 3 transmission.....	56
7.7.9	TMT_6: Test mode 4 transmission.....	57
7.7.10	TMT_7: Test mode 5 transmission.....	58
7.7.11	TMT_8: Test mode 6 transmission.....	59
7.7.12	TMT_3: Test mode 1 reception.....	60
7.7.13	LBT_4: Line loopback.....	62
7.8	Block 2 test cases: Mandatory functionality.....	64
7.8.1	General.....	64
7.8.2	PCST_1: PCS transmission signalling.....	64
7.8.3	PCST_2: PCS transmission PHD.....	65
7.8.4	PCST_3: Transmission PCS payload data.....	69
7.8.5	PCST_4: PCS reception header and payload data.....	72
7.8.6	PCST_5: PCS transmission alignment.....	73
7.8.7	PCST_6: PCS reception alignment.....	75
7.8.8	PMAT_1: Transmission PMA power scaling test.....	77
7.8.9	PMAT_2: THP transmission.....	80
7.8.10	PMAT_3: State diagrams – Transmit PHD commit point.....	82
7.8.11	PMAT_4: State diagrams – Receive PHD commit point.....	84
7.8.12	PMAT_5: State diagrams – TX control.....	86
7.8.13	PMAT_6: State diagrams – RX control.....	88
7.8.14	PMAT_7: State diagrams – Link monitor.....	92
7.8.15	PMAT_8: State diagrams – PHD monitor.....	96
7.8.16	PMAT_9: State diagrams – Adaptive THP TX.....	100

7.8.17	PMAT_10: State diagrams – Adaptive THP request	103
7.8.18	PMAT_11: State diagrams – Quality monitor state diagram	106
7.8.19	PMAT_12: Synchronisation	110
7.8.20	PMAT_13: Equalization and BER measurement	112
7.8.21	PMDT_1: PMD transmit function – Electrical to optical	114
7.8.22	PMDT_2: PMD transmit function – Power control	116
7.8.23	PMDT_3: PMD receive function – Optical to electrical	117
7.8.24	PMDT_4: PMD signal detect function	119
7.8.25	PMD_MDIT_1: Transmitter optical specifications – AOP	120
7.8.26	PMD_MDIT_2: Transmitter optical specifications – ER	121
7.8.27	PMD_MDIT_3: Transmitter optical specifications – Centre wavelength	122
7.8.28	PMD_MDIT_4: Transmitter optical specifications – Spectral width	123
7.8.29	PMD_MDIT_5: Transmitter optical specifications – Rise time	123
7.8.30	PMD_MDIT_6: Transmitter optical specifications – Fall time	124
7.8.31	PMD_MDIT_7: Transmitter optical specifications – Signal overshoot	125
7.8.32	PMD_MDIT_8: Transmitter optical specifications – Positive output droop	126
7.8.33	PMD_MDIT_9: Transmitter optical specifications – Negative output droop	127
7.8.34	PMD_MDIT_10: Transmitter optical specifications – Signal distortion	127
7.8.35	PMD_MDIT_11: Transmitter optical specifications – Relative intensity noise	128
7.8.36	PMD_MDIT_12: Transmitter optical specifications – Transmitter off transition time	129
7.8.37	PMD_MDIT_13: Transmitter optical specifications – Transmitter on transition time	132
7.8.38	PMD_MDIT_14: Transmitter optical specifications – Modal power distribution	134
7.8.39	PMD_MDIT_15: Transmitter optical specifications – Timing jitter	135
7.8.40	PMD_MDIT_16: Receiver optical specifications – AOP for a minimum BER	136
7.8.41	PMD_MDIT_17: Receiver optical specifications – Damage threshold power	137
7.8.42	DLYT_1: Transmission plus reception delay	138
7.9	Block 3 test cases: Optional functionality	139
7.9.1	General	139
7.9.2	EEET_1: Enter to LPI mode transmit operation	140
7.9.3	EEET_2: EEE capability exchange	143
7.9.4	EEET_3: Loop test for LPI mode	145
7.9.5	EEET_4: Resume from LPI mode transmit operation	148
7.9.6	OAMT_1: State diagrams – OAM transmit control	150
7.9.7	OAMT_2: State diagrams – OAM receive control	155
7.9.8	OAMT_3: Loop test for OAMPDU transmission and reception	159
7.9.9	WUST_1: WUSME synchronised link sleep state diagram – Synchronised link sleep ACK	165
7.9.10	WUST_2: WUSME synchronised link sleep state diagram – SLEEP_ACK packet reception	169
7.9.11	WUST_3: WUSME synchronised link sleep state diagram – SLEEP packet reception	173
7.9.12	WUST_4: WUSME synchronised link sleep state diagram – Sleep rejection	176
7.9.13	WUST_5: WUSME wake-up state diagram	182
	Bibliography	186

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*.

A list of all parts in the ISO 21111 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The ISO 21111 series includes in-vehicle Ethernet requirements and test plans that are disseminated in other International Standards and complements them with additional test methods and requirements. The resulting requirement and test plans are structured in different documents following the Open Systems Interconnection (OSI) reference model and grouping the documents that depend on the physical media and bit rate used.

In general, the Ethernet requirements are specified in ISO/IEC/IEEE 8802-3. The ISO 21111 series provides supplemental specifications (e.g. wake-up, I/O functionality), which are required for in-vehicle Ethernet applications. In road vehicles, Ethernet networks are used for different purposes requiring different bit-rates. Currently, the ISO 21111 series specifies the 1-Gbit/s optical and 100-Mbit/s electrical physical layer.

The ISO 21111 series contains requirement specifications and test methods related to the in-vehicle Ethernet. This includes requirement specifications for physical layer entity (e.g. connectors, physical layer implementations) providers, device (e.g. electronic control units, gateway units) suppliers, and system (e.g. network systems) designers. Additionally, there are test methods specified for conformance testing and for interoperability testing.

Safety (electrical safety, protection, fire, etc.) and electromagnetic compatibility (EMC) requirements are out of the scope of the ISO 21111 series.

The structure of the specifications given in the ISO 21111 series complies with the Open Systems Interconnection (OSI) reference model specified in ISO/IEC 7498-1^[1] and ISO/IEC 10731^[5].

ISO 21111-1 defines the terms which are used in this series of standards and provides an overview of the standards for in-vehicle Ethernet including the complementary relations to ISO/IEC/IEEE 8802-3, the document structure, type of physical entities, in-vehicle Ethernet specific functionalities and so on.

ISO 21111-2 specifies the interface between reconciliation sublayer and physical entity including reduced gigabit media independent interface (RGMI), and the common physical entity wake-up and synchronized link sleep functionalities, independent from physical media and bit rate.

This document specifies supplemental requirements to a physical layer capable of transmitting 1-Gbit/s over plastic optical fibre compliant with ISO/IEC/IEEE 8802-3, with specific application to communications inside road vehicles, and a test plan for physical entity conformance testing.

ISO 21111-4 specifies the optical components requirements and test methods for 1-Gbit/s optical in-vehicle Ethernet.

ISO 21111-5 specifies, for 1-Gbit/s optical in-vehicle Ethernet, requirements on the physical layer at system level, requirements on the interoperability test set-ups, the interoperability test plan that checks the requirements for the physical layer at system level, requirements on the device-level physical layer conformance test set-ups, and device-level physical layer conformance test plan that checks a set of requirements for the OSI physical layer that are relevant for device vendors.

ISO 21111-6 specifies advanced features of an ISO/IEC/IEEE 8802-3 in-vehicle Ethernet physical layer (often also called transceiver), e.g. for diagnostic purposes for in-vehicle Ethernet physical layers. It specifies advanced physical layer features, wake-up and sleep features, physical layer test suite, physical layer control requirements and conformance test plan, physical sublayers test suite and physical sublayers requirements and conformance test plan.

ISO 21111-7 specifies the implementation for ISO/IEC/IEEE 8802-3:2017/Amd 1:2017, which defines the interface implementation for automotive applications together with requirements on components used to realize this Bus Interface Network (BIN). ISO 21111-7 also defines further testing and system requirements for systems implemented according to the system specification. In addition, ISO 21111-7 defines the channels for tests of transceivers with a test wiring harness that simulates various electrical communication channels.