

International Standard

ISO 21771-2

Cylindrical involute gears and gear pairs —

Part 2:

Calculation and measurement of indarids tooth thickness and backlash

Roues dentées et engrenages cylindriques en développante de cercle —

Partie 2: Calcul et mesurage de l'épaisseur de dent et du jeu de battement ISO 21771-2:2025

https://standards.iteh.ai/catalog/standards/iso/861da4f1-daa6-49da-9846-3274d5f3869e/iso-21771-2-2025

First edition 2025-12

iTeh Standards (https://standards.iteh.ai) Document Preview

<u> ISO 21771-2:2025</u>

https://standards.iteh.ai/catalog/standards/iso/861da4f1-daa6-49da-9846-3274d5f3869e/iso-21771-2-2025



COPYRIGHT PROTECTED DOCUMENT

© ISO 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org

Website: www.iso.org
Published in Switzerland

4.1General134.2Datum surfaces and the datum axis144.3Gear tooth thickness specification systems144.3.1Types of tooth thickness specification systems144.3.2Non-datum related tooth thickness154.3.3Axis related tooth thickness154.3.4Relationship between the measurement methods and specification systems154.3Axis related tooth thickness154.3Mean tooth thickness154.4Gear tooth thickness measurement methods164.5Reporting of gear tooth thickness174.6Measurement diameter versus contact diameter174.7Gear geometry calculations174.7.1Use of radians or degrees174.7.2Reference diameter184.7.3Transverse pressure angle184.7.4Lead angle184.7.5Normal tooth thickness from manufacturing profile shift coefficient184.7.6Base delimeter194.7.7Base helix angle194.7.9Normal pitch at the reference diameter d_y 194.7.1Lead of a helical gear194.7.1Lead of a helical gear194.7.1Helix angle at calculation diameter d_y 204.7.15Transverse pressure angle at calculation diameter d_y 204.7.15Transverse pressure angle at calculation diameter d_y 204.7.15Transverse pressure angle at calculation diamete	Con	Contents				
1 Scope 1 2 Normative references 1 3 Terms, definition and symbols 1 3.1 Terms and definitions 1 3.2 Symbols and definitions 13 3.3 Units and conventions 13 3.3.1 Units 13 4.2 Datum surfaces and the datum axis 14 4.1 General 13 4.2 Datum surfaces and the datum axis 14 4.3 Cear tooth thickness specification systems 14 4.3 Cear tooth thickness specification systems 14 4.3 A spiral state of tooth thickness specification systems 14 4.3 A spiral state of tooth thickness 15 4.3.3 Axis related tooth thickness 15 4.3.4 A spiral state of thickness 15 4.3.5 Mon-datum related tooth thickness 15 4.3.4 Relationship between the measurement methods and specification systems 15 4.3.5 Main tooth thickness 15	Forew	ord		vii		
2 Normative references 1 31 Terms, definition and symbols 1 3.1 Terms and definitions 6 3.3 Units and conventions 13 3.3.1 Units 13 3.3.2.2 Conventions 13 4 Application 13 4.1 General 13 4.2 Datum surfaces and the datum axis 14 4.3 Carr tooth thickness specification systems 14 4.2 Datum surfaces and the datum axis 13 4.3 Lagential State of Sta	Intro	duction		viii		
2 Normative references 1 31 Terms, definition and symbols 1 3.1 Terms and definitions 6 3.3 Units and conventions 13 3.3.1 Units 13 3.3.2.2 Conventions 13 4 Application 13 4.1 General 13 4.2 Datum surfaces and the datum axis 13 4.3 4.3 Carr tooth thickness specification systems 14 4.2 Datum surfaces and the datum axis 13 4.3 4.3 Types of tooth thickness specification systems 14 4.3.1 Types of tooth thickness specification systems 14 4.3.2 Non-datum related tooth thickness 15 4.3.3 Axis related tooth thickness 15 4.3.4 Relationship between the measurement methods and specification systems 15 4.3.5 Mean tooth thickness 15 4.4.6 Gear tooth thickness 15 4.5 Reporting of gear tooth thickness <td< th=""><th>1</th><th>Scope</th><th></th><th>1</th></td<>	1	Scope		1		
3.1 Terms and definitions		-				
3.1 Terms and definitions						
3.2 Symbols and definitions 13 3.3 Units and conventions 13 3.3.1 Units 13 3.3.2 Conventions 13 3.3.2 Conventions 13 3.3.2 Conventions 13 3.3.2 Conventions 13 44 Application 13 41.1 General 13 42.2 Datum surfaces and the datum axis 14 43.2 Court of thickness specification systems 14 43.4 Gear tooth thickness specification systems 14 43.1 Types of tooth thickness specification systems 14 43.2 Non-datum related tooth thickness 15 43.3 Axis related tooth thickness 15 43.3 Axis related tooth thickness 15 43.5 Man tooth thickness 15 43.5 Man tooth thickness 15 43.5 Man tooth thickness 15 44.6 Gear tooth thickness measurement methods 16 45 Reporting of gear tooth thickness 17 47.6 Gear geometry calculations 17 47.1 Use of radians or degrees 17 47.2 Reference diameter 17 47.2 Reference diameter 18 47.4 Lead angle 18 47.5 Normal tooth thickness from manufacturing profile shift coefficient 18 47.8 Normal pitch at calculation diameter dy 19 47.71 Normal pitch at the reference diameter 19 47.71 Normal pitch at the reference diameter 19 47.71 Axial pitch 20 47.71 Axial pitch 20 47.71 Axial pitch 20 47.71 Axial pitch 20 47.71 Tooth thickness calculation diameter dy 20 47.71 Tooth thickness calculation diameter dy 20 47.71 Tooth thickness calculation diameter dy 20 47.71 Tooth thickness calculations 20 47.71 Tooth thickness calculations 20 47.71 Tooth thickness calculation diameter dy 20 47.71 Tooth thickness calculations 20 47.71 Tooth thickness calculations 20 47.71 Tooth thickness calculations 20 47.71 47.	3					
3.3 Units and conventions 13 3.3.1 Units 13 3.3.2 Conventions 13 3.3.2 Conventions 13 3.3.2 Conventions 13 3.3.2 Conventions 13 4.1 General 13 4.1 General 13 4.2 Datum surfaces and the datum axis 14 4.3 Gear tooth thickness specification systems 14 4.3.1 Types of tooth thickness specification systems 14 4.3.2 Non-datum related tooth thickness 15 4.3.3 Axis related tooth thickness 15 4.3.4 Relationship between the measurement methods and specification systems 15 4.3.5 Mean tooth thickness 15 4.3.6 Measurement diameter wersus contact diameter 16 4.5 Reporting of gear tooth thickness 17 4.6 Measurement diameter versus contact diameter 17 4.7 Use of radians or degrees 17 4.7 Effective diameter 18 4.7 4.7 Effective diameter 18 4.7 Effective diameter 18 4.7 Effective diameter 18 4.7 Effective diameter 18 4.7 Effective diameter 19		_				
3.3.1 Units 3.3.2 Conventions 13 4.1 General 13 4.2 Datum surfaces and the datum axis 14 4.3 Convention thickness specification systems 14 4.3.1 Types of tooth thickness specification systems 14 4.3.2 Non-datum related tooth thickness 15 4.3.3 Axis related tooth thickness 15 4.3.4 Relationship between the measurement methods and specification systems 15 4.3.5 Mean tooth thickness 15 4.3.5 Mean tooth thickness 15 4.3.5 Mean tooth thickness 16 4.3.5 Mean tooth thickness 17 4.3 Gear tooth thickness measurement methods 16 4.5 Reporting of gear tooth thickness 17 4.7 Gear geometry calculations 17 4.7 Use of radians or degrees 17 4.7 Use of radians or degrees 17 4.7 Use of radians or degrees 18 4.7 4.7 Reference diameter 19 4.7 4.7 4.7 Reference diameter 19 4.7 4.7 4.7 Reference diameter 19 4.7						
4 Application 13 4.1 General 13 4.2 Datum surfaces and the datum axis 14 4.3 Gear tooth thickness specification systems 14 4.3.1 Types of tooth thickness specification systems 14 4.3.2 Non-datum related tooth thicknesss 15 4.3.3 Axis related tooth thickness 15 4.3.4 Relationship between the measurement methods and specification systems 15 4.3.5 Mean tooth thickness 15 4.4 Gear tooth thickness measurement methods 16 4.5 Reporting of gear tooth thickness 17 4.6 Measurement diameter versus contact diameter 17 4.7 Gear geometry calculations 17 4.7.1 Use of radians or degrees 17 4.7.2 Reference diameter 18 4.7.3 Transverse pressure angle 18 4.7.4 Lead angle 18 4.7.5 Normal both thickness from manufacturing profile shift coefficient 18 4.7.6 Base diameter 19 4.7.8 Normal pitch a						
4.1General134.2Datum surfaces and the datum axis144.3Gear tooth thickness specification systems144.3.1Types of tooth thickness specification systems144.3.2Non-datum related tooth thickness154.3.3Axis related tooth thickness154.3.4Relationship between the measurement methods and specification systems154.3.5Mean tooth thickness154.4Gear tooth thickness measurement methods164.5Reporting of gear tooth thickness174.6Measurement diameter versus contact diameter174.7Gear geometry calculations174.7.1Use of radians or degrees174.7.2Reference diameter184.7.3Transverse pressure angle184.7.4Lead angle184.7.5Normal tooth thickness from manufacturing profile shift coefficient184.7.6Base diameter194.7.9Normal pitch at the reference diameter d_y 194.7.1Lead of a helical gear194.7.1Lead of a helical gear194.7.1Lead of a helical gear194.7.1Transverse pressure angle at calculation diameter d_y 204.7.1Transverse pressure angle at calculation diameter d_y 204.7.1Tooth thickness calculations204.7.1Tooth thickness calculations225Measurement by pitch (index)245.			3.3.2 Conventions	13		
4.1General134.2Datum surfaces and the datum axis144.3Gear tooth thickness specification systems144.3.1Types of tooth thickness specification systems144.3.2Non-datum related tooth thickness154.3.3Axis related tooth thickness154.3.4Relationship between the measurement methods and specification systems154.3.5Mean tooth thickness154.4Gear tooth thickness measurement methods164.5Reporting of gear tooth thickness174.6Measurement diameter versus contact diameter174.7Gear geometry calculations174.7.1Use of radians or degrees174.7.2Reference diameter184.7.3Transverse pressure angle184.7.4Lead angle184.7.5Normal tooth thickness from manufacturing profile shift coefficient184.7.6Base diameter194.7.9Normal pitch at the reference diameter d_y 194.7.1Lead of a helical gear194.7.1Lead of a helical gear194.7.1Lead of a helical gear194.7.1Transverse pressure angle at calculation diameter d_y 204.7.1Transverse pressure angle at calculation diameter d_y 204.7.1Tooth thickness calculations204.7.1Tooth thickness calculations225Measurement by pitch (index)245.	4	Application				
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$			General	13		
$ \begin{array}{c} 4.3.1 & \text{Types of tooth thickness specification systems} \\ 4.3.2 & \text{Non-datum related tooth thickness} \\ 4.3.3 & \text{Axis related tooth thickness} \\ 4.3.4 & \text{Relationship between the measurement methods and specification systems} \\ 1.5 & 4.3.5 & \text{Mean tooth thickness} \\ 4.4 & \text{Gear tooth thickness measurement methods} \\ 1.5 & \text{Reporting of gear tooth thickness} \\ 1.7 & \text{Reporting of gear tooth thickness} \\ 1.7 & \text{Measurement diameter versus contact diameter} \\ 1.7 & \text{Measurement diameter versus contact diameter} \\ 1.7 & \text{Los of radians or degrees} \\ 1.7 & \text{Los of radians or degrees} \\ 1.7 & \text{Los of Normal tooth thickness from manufacturing profile shift coefficient} \\ 1.8 & 4.7.2 & \text{Reference diameter} \\ 1.9 & 4.7.4 & \text{Lead angle} \\ 1.0 & 4.7.5 & \text{Normal tooth thickness from manufacturing profile shift coefficient} \\ 1.0 & 4.7.5 & \text{Normal pitch at the reference diameter} \\ 1.0 & 4.7.1 & \text{Dormal pitch at the reference diameter} \\ 1.0 & 4.7.1 & \text{Normal pitch at calculation diameter } d_y \\ 1.0 & 4.7.1 & \text{Load of a helical gear} \\ 1.1 & 4.7.1 & \text{Load of a helical gear} \\ 1.2 & 4.7.1 & \text{Transverse pressure angle at calculation diameter } d_y \\ 1.7 & 4.7.1 & \text{Transverse pressure angle at calculation diameter } d_y \\ 1.7 & 4.7.1 & \text{Transverse pressure angle at calculation diameter } d_y \\ 1.7 & 4.7.1 & \text{Transverse pressure angle at calculation diameter } d_y \\ 1.7 & 4.7.1 & \text{Transverse pressure angle at calculation diameter } d_y \\ 1.7 & 4.7 & \text{Space width calculations} \\ 2.0 & 4.7 & 4.7 & \text{Space width calculations} \\ 2.0 & 4.7 & \text$						
$ \begin{array}{c} 4.3.2 & \text{Non-datum related tooth thickness} \\ 4.3.3 & \text{Axis related tooth thickness} \\ 4.3.5 & \text{Relationship between the measurement methods and specification systems} \\ 4.3.5 & \text{Mean tooth thickness} \\ 4.4.6 & \text{Gear tooth thickness} \\ 4.6 & \text{Measurement diameter versus contact diameter} \\ 4.7 & \text{Gear geometry calculations} \\ 4.7.1 & \text{Use of radians or degrees} \\ 4.7.2 & \text{Reference diameter} \\ 4.7.3 & \text{Transverse pressure angle} \\ 4.7.4 & \text{Lead angle} \\ 4.7.5 & \text{Normal tooth thickness from manufacturing profile shift coefficient} \\ 4.7.6 & \text{Base diameter} \\ 4.7.7 & \text{Normal tooth thickness from manufacturing profile shift coefficient} \\ 4.7.8 & \text{Normal pitch at the reference diameter} \\ 4.7.9 & \text{Normal pitch at the reference diameter} \\ 4.7.9 & \text{Normal pitch at talculation diameter} d_y \\ 4.7.10 & \text{Normal base pitch} \\ 4.7.11 & \text{Lead of a helical gear} \\ 4.7.12 & \text{Axial pitch} \\ 4.7.13 & \text{The involute function} \\ 4.7.14 & \text{Helix angle at calculation diameter} d_y \\ 4.7.15 & \text{Tooth thickness calculations} \\ 4.7.16 & \text{Tooth thickness calculations} \\ 4.7.17 & \text{Space width calculations} \\ 4.7.18 & \text{Space width calculations} \\ 4.7.19 & \text{Space width calculations} \\ 4.7.10 & \text{Space width calculations} \\ 4.7.11 & \text{Space of measurement} \\ 4.7.12 & \text{Space width calculations} \\ 4.7.13 & \text{The involute function} \\ 4.7.14 & \text{Tooth thickness calculations} \\ 4.7.15 & \text{Tooth thickness calculations} \\ 4.7.16 & \text{Tooth thickness calculations} \\ 4.7.17 & \text{Space width calculations} \\ 4.7.18 & \text{Space meant by pitch (index)} \\ 4.7.19 & \text{Space width calculations} \\ 4.7.10 & \text{Tooth thickness calculations} \\ 4.7.11 & \text{Tooth thickness calculations} \\ 4.7.12 & \text{Tooth thickness calculations} \\ 4.7.13 & \text{Tooth thickness calculations} \\ 4.7.14 & \text{Tooth thickness calculations} \\ 4.7.15 & \text{Tooth thickness calculations} \\ 4.7.16 & \text{Tooth thickness calculations} \\ 4.7.17 & \text{Tooth thickness calculations} \\ 4.7.18 & \text{Tooth thickness calculations} \\ 4.7.19 & \text{Tooth thickness calculations} \\ 4.7.1$		4.3				
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$						
$ \begin{array}{c} 4.3.4 \\ 4.3.5 \\ 4.3.5 \\ 4.3.5 \\ 4.3.5 \\ 4.4 \\ 6 \\ 6 \\ 4.5 \\ 6 \\ 4.5 \\ 6 \\ 6 \\ 10 \\ 6 \\ 2 \\ 10 \\ 10 \\ 10 \\ 10 \\ 10 \\ 10 \\ 10 $						
$ \begin{array}{c} 4.3.5 \text{Mean tooth thickness} & 15 \\ 4.4 \text{Gear tooth thickness measurement methods} & 16 \\ 4.5 \text{Reporting of gear tooth thickness} & 16 \\ 4.6 \text{Measurement diameter versus contact diameter} & 17 \\ 4.6 \text{Measurement diameter versus contact diameter} & 17 \\ 4.7 \text{Gear geometry calculations} & 17 \\ 4.7.1 \text{Use of radians or degrees} & 17 \\ 4.7.2 \text{Reference diameter} & 18 \\ 4.7.3 \text{Transverse pressure angle} & 18 \\ 4.7.4 \text{Lead angle} & 18 \\ 4.7.5 \text{Normal tooth thickness from manufacturing profile shift coefficient} & 18 \\ 4.7.6 \text{Base diameter} & 19 \\ 4.7.6 \text{Base diameter} & 19 \\ 4.7.1 \text{Normal pitch at the reference diameter} & 19 \\ 4.7.9 \text{Normal pitch at calculation diameter} d_y & 19 \\ 4.7.10 \text{Normal pitch at calculation diameter} d_y & 19 \\ 4.7.11 \text{Lead of a helical gear} & 19 \\ 4.7.12 \text{Axial pitch} & 20 \\ 4.7.13 \text{The involute function} & 20 \\ 4.7.15 \text{Transverse pressure angle at calculation diameter} d_y & 20 \\ 4.7.16 \text{Tooth thickness calculations} & 20 \\ 4.7.17 \text{Space width calculations} & 22 \\ 5 \text{Measurement by pitch (index)} & 24 \\ 5.1 \text{Principle of measurement} & 24 \\ 5.2 \text{Underlying assumptions and limitations} & 24 \\ 5.3 \text{Advantages and disadvantages of measurement by pitch} & 24 \\ 5.4 \text{Selection of measurement} & 25 \\ 6.1.2 \text{Tight mesh centre distance} & 25 \\ 6.1.3 \text{Product gear test radius} & 29 \\ 6.1.4 \text{Total radial composite deviation} & 29 \\ 6.2 \text{Underlying assumptions and limitations} & 29 \\ 6.2 Underlying assum$						
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$			4.3.5 Mean tooth thickness	15		
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$						
4.7 Gear geometry calculations 17 4.7.1 Use of radians or degrees 17 4.7.2 Reference diameter 18 4.7.3 Transverse pressure angle 18 4.7.4 Lead angle 18 4.7.5 Normal tooth thickness from manufacturing profile shift coefficient 18 4.7.6 Base diameter 19 4.7.7 Base helix angle 19 4.7.8 Normal pitch at the reference diameter 19 4.7.9 Normal pitch at calculation diameter d_y 19 4.7.1 Normal base pitch 19 4.7.1 Lead of a helical gear 19 4.7.12 Axial pitch 20 4.7.13 The involute function 20 4.7.15 Transverse pressure angle at calculation diameter d_y 20 4.7.16 Tooth thickness calculations 20 4.7.17 Space width calculations 22 5 Measurement by pitch (index) 24 5.1 Principle of measurement 24 5.1 Principle of measurement diameter 25			Reporting of gear tooth thickness	17		
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$						
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$		4./	4.7.1 Use of radians or degrees	1/		
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$			4.7.2 Reference diameter	17		
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$						
$ \begin{array}{c} 4.7.6 \\ \text{https://stand.} & 4.7.7 \\ \text{el Base helix angle.} & 4.7.1 \\ 4.7.8 \\ \text{Normal pitch at the reference diameter.} & 19 \\ 4.7.9 \\ \text{Normal pitch at calculation diameter } d_y & 19 \\ 4.7.10 \\ \text{Normal base pitch.} & 19 \\ 4.7.11 \\ \text{Lead of a helical gear.} & 19 \\ 4.7.12 \\ \text{Axial pitch.} & 20 \\ 4.7.13 \\ \text{The involute function.} & 20 \\ 4.7.14 \\ \text{Helix angle at calculation diameter } d_y & 20 \\ 4.7.15 \\ \text{Transverse pressure angle at calculation diameter } d_y & 20 \\ 4.7.16 \\ \text{Tooth thickness calculations.} & 20 \\ 4.7.17 \\ \text{Space width calculations.} & 22 \\ \hline $			4.7.4 Lead angle	18		
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$			4.7.5 Normal tooth thickness from manufacturing profile shift coefficient	18		
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$						
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$						
4.7.10 Normal base pitch 19 4.7.11 Lead of a helical gear 19 4.7.12 Axial pitch 20 4.7.13 The involute function 20 4.7.14 Helix angle at calculation diameter d_y 20 4.7.15 Transverse pressure angle at calculation diameter d_y 20 4.7.16 Tooth thickness calculations 20 4.7.17 Space width calculations 22 5 Measurement by pitch (index) 22 5.1 Principle of measurement 24 5.2 Underlying assumptions and limitations 24 5.3 Advantages and disadvantages of measurement by pitch 24 5.4 Selection of measurement diameter 25 6.1 Principle of measurement diameter 25 6.1.1 Main principles 25 6.1.2 Tight mesh centre distance 28 6.1.2 Tight mesh centre distance 28 6.1.3 Product gear test radius 29 6.1.4 Total radial composite deviation 29 6.2 Underlying assumptions and limitations						
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$						
$\begin{array}{cccccccccccccccccccccccccccccccccccc$			4.7.11 Lead of a helical gear	19		
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$						
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$						
4.7.16 Tooth thickness calculations 20 4.7.17 Space width calculations 22 5 Measurement by pitch (index) 24 5.1 Principle of measurement 24 5.2 Underlying assumptions and limitations 24 5.3 Advantages and disadvantages of measurement by pitch 24 5.4 Selection of measurement diameter 25 6 Measurement with a master gear on a double flank tester 25 6.1 Principle of measurement 25 6.1.1 Main principles 25 6.1.2 Tight mesh centre distance 28 6.1.3 Product gear test radius 29 6.1.4 Total radial composite deviation 29 6.2 Underlying assumptions and limitations 29			$4.7.14$ Helix angle at calculation diameter d_y	20		
4.7.17Space width calculations225Measurement by pitch (index)245.1Principle of measurement245.2Underlying assumptions and limitations245.3Advantages and disadvantages of measurement by pitch245.4Selection of measurement diameter256Measurement with a master gear on a double flank tester256.1Principle of measurement256.1.1Main principles256.1.2Tight mesh centre distance286.1.3Product gear test radius296.1.4Total radial composite deviation296.2Underlying assumptions and limitations29			4.7.15 Transverse pressure angle at calculation diameter a_y	20		
5Measurement by pitch (index)245.1Principle of measurement245.2Underlying assumptions and limitations245.3Advantages and disadvantages of measurement by pitch245.4Selection of measurement diameter256Measurement with a master gear on a double flank tester256.1Principle of measurement256.1.1Main principles256.1.2Tight mesh centre distance286.1.3Product gear test radius296.1.4Total radial composite deviation296.2Underlying assumptions and limitations29						
5.1Principle of measurement245.2Underlying assumptions and limitations245.3Advantages and disadvantages of measurement by pitch245.4Selection of measurement diameter256Measurement with a master gear on a double flank tester256.1Principle of measurement256.1.1Main principles256.1.2Tight mesh centre distance286.1.3Product gear test radius296.1.4Total radial composite deviation296.2Underlying assumptions and limitations29	_	Maga	•			
5.2Underlying assumptions and limitations245.3Advantages and disadvantages of measurement by pitch245.4Selection of measurement diameter256Measurement with a master gear on a double flank tester256.1Principle of measurement256.1.1Main principles256.1.2Tight mesh centre distance286.1.3Product gear test radius296.1.4Total radial composite deviation296.2Underlying assumptions and limitations29	5					
5.3 Advantages and disadvantages of measurement by pitch 24 5.4 Selection of measurement diameter 25 6 Measurement with a master gear on a double flank tester 25 6.1 Principle of measurement 25 6.1.1 Main principles 25 6.1.2 Tight mesh centre distance 28 6.1.3 Product gear test radius 29 6.1.4 Total radial composite deviation 29 6.2 Underlying assumptions and limitations 29						
5.4 Selection of measurement diameter 25 Measurement with a master gear on a double flank tester 25 6.1 Principle of measurement 25 6.1.1 Main principles 25 6.1.2 Tight mesh centre distance 28 6.1.3 Product gear test radius 29 6.1.4 Total radial composite deviation 29 6.2 Underlying assumptions and limitations 29						
6.1Principle of measurement256.1.1Main principles256.1.2Tight mesh centre distance286.1.3Product gear test radius296.1.4Total radial composite deviation296.2Underlying assumptions and limitations29		5.4				
6.1Principle of measurement256.1.1Main principles256.1.2Tight mesh centre distance286.1.3Product gear test radius296.1.4Total radial composite deviation296.2Underlying assumptions and limitations29	6	Measi	rement with a master gear on a double flank tester	25		
6.1.1 Main principles256.1.2 Tight mesh centre distance286.1.3 Product gear test radius296.1.4 Total radial composite deviation296.2 Underlying assumptions and limitations29	-					
6.1.3 Product gear test radius 29 6.1.4 Total radial composite deviation 29 6.2 Underlying assumptions and limitations 29			6.1.1 Main principles	25		
6.1.4 Total radial composite deviation						
6.2 Underlying assumptions and limitations						
		6.2				

	6.4	Master gear design considerations	
		6.4.1 Criteria for proper meshing	
		6.4.2 Additional recommendations	
	6.5	Skew angle for double flank testing	
		6.5.1 General	
		6.5.2 Skew angle for parallel axis gear pairs	
		6.5.3 Skew angle for crossed axis gear pairs	
	6.6	Calculation of tight mesh centre distance limits for crossed axis gears	
		6.6.1 Preliminary calculations	
		6.6.2 Tight mesh centre distance limits for crossed axis gears	
	6.7	Tight mesh centre distance limits for parallel axis gears:	35
		6.7.1 General	
		6.7.2 For the non-datum related system:	
		6.7.3 For the axis related system:	
		6.7.4 Differences between axis related and non-datum related systems	36
	6.8	Product gear test radius limits from tight mesh centre distance limits	37
		6.8.1 General	
		6.8.2 Master gear test radius	
		6.8.3 Product gear test radius limits	38
	6.9	Axis related normal tooth thickness from double flank test results	
		6.9.1 General	
		6.9.2 Crossed axis external gear axis related tooth thickness from test results	
		6.9.3 Parallel axis gear axis related tooth thickness	38
7	Meas	surement with a master gear on a single flank tester	39
-	7.1	Principle of measurement	39
	7.2	Underlying assumptions and limitations and and and a	39
	7.3	Advantages and disadvantages of single flank composite measurement	39
	7.4	Master gear design considerations	40
	7.5	Axis related tooth thickness from single flank test results	40
O	Cnan	measurement	
8	8.1	Principle of measurement	40 40
	8.2	Underlying assumptions and limitations	
	8.3	Advantages and disadvantages of span measurement	
	8.4	Span massurement limits	42 12
	8.5	Span measurement limits Number of teeth spanned	-2-20/43
	0.5	8.5.1 Limitations	43 12
		8.5.2 Maximum and minimum number of teeth spanned	43 12
	8.6	Angle of rock	43 1.5
	8.7	Tooth thickness from span measurement	
	8.8	Measurement diameter	
9		surement using three ball span device	
	9.1	Principle of measurement	
	9.2	Underlying assumptions and limitations	
	9.3	Advantages and disadvantages of three ball span device measurement	
	9.4	Number of teeth spanned	
	9.5	Selection of the ball diameter	
	9.6	Calculations with specified ball diameter	
	9.7	Normal tooth thickness from a measurement using a three ball span device	51
10	Meas	surement over or between balls or pins	51
	10.1	Principle of measurement	
	10.2	Underlying assumptions and limitations	
	10.3	Advantages and disadvantages of over balls or pins measurement	
	10.4	Selection of the ball or pin diameter	
		10.4.1 General	
		10.4.2 Transverse base space width half angles	
		10.4.3 Maximum ball or pin diameter	
		10.4.4 Ball or pin diameter for contact at the root involute limit diameter	

		10.4.5 Ball or pin diameter that will be tangent to the tip diameter	56
		10.4.6 Ball or pin diameter that will be tangent to the root diameter	57
		10.4.7 Minimum usable ball diameter	57
		10.4.8 Selection of ball or pin diameter to specify	57
		10.4.9 Calculation for racks	58
	10.5	Calculations with specified ball or pin diameter (symmetric pressure angles)	60
	10.6	Gears with asymmetric pressure angles	
		10.6.1 General	61
		10.6.2 Calculations with specified ball or pin diameter	61
	10.7	Measurement over one ball or pin	
		10.7.1 General	
		10.7.2 Basic inspection limits for measurement over one ball or pin	63
		10.7.3 Axis related normal tooth thickness from one ball or pin measurement	64
		10.7.4 Contact diameter from the measurement over one ball or pin	
	10.8	Measurement over two balls or pins	
		10.8.1 General	
		10.8.2 Basic inspection limits for measurement over two balls or pins	
		10.8.3 Normal tooth thickness from a measurement over two balls or pins	66
		10.8.4 Contact diameter from the measurement over two balls or pins.	66
	10.9	Two pin transverse measurement on helical gear, odd number of teeth	66
		10.9.1 General	
		10.9.2 Transverse measurement with two free floating pins	66
		10.9.3 Measurement with two pins rotating around the micrometer axis	68
		10.9.4 Basic inspection limits for the two-pin transverse method	70
		10.9.5 Normal tooth thickness from a two-pin transverse method measurement	70
	10.10	Free pin measurement over two pins, helical gear, odd number of teeth	70
		10.10.1 General	70
		10.10.2 Basic inspection limits for the free pin method	71
		10.10.3 Non-datum related normal tooth thickness from free pin measurement	72
	10.11	Transverse plane measurement method over three balls or pins	72
		10.11.1 General	72
		10.11.2 Factors for gears with even or odd numbers of teeth	74
		10.11.3 Measurement limits using the transverse plane method for three balls or pins	
		10.11.4 Normal tooth thickness from a transverse plane method measurement	74
		10.11.5 Contact diameter from the transverse plane method	74
	10.12	Axial plane three pin method	74
		10.12.1 General	74
		10.12.2 Measurement limits using the axial plane three pin method	75
		10.12.3 Normal tooth thickness from axial plane method measurement	
		10.12.4 Contact diameter from the axial plane three pin method	76
11	Mooci	rement with measuring blocks	76
11	11.1	Principle of measurement	
		Underlying assumptions and limitations	
	11.2	Adventages and disadventages of using blocks	70 77
	11.3	Advantages and disadvantages of using blocks	
	11.4	Measuring block sets	
	11.5		
	11.6	Tooth thickness from block measurements	
12	Chord	lal measurement	79
	12.1	General	
	12.2	Measurements with a gear tooth calliper (in the normal plane)	80
		12.2.1 Principle of measurement	
		12.2.2 Underlying assumptions and limitations	81
		12.2.3 Advantages and disadvantages of chordal measurement	81
		12.2.4 Method for calculation	82
		12.2.5 Preliminary calculations for chordal measurements	
		12.2.6 Chordal addendum	83
		12.2.7 Minimum contact diameter	
		12.2.8 Minimum normal tooth thickness at diameter $d_{\rm vmin}$	83
		<i>y</i>	

		12.2.9 Normal chordal tooth thickness measurement limits	
		12.2.10 Adjustment of chordal addendum at time of measurement	
		12.2.11 Normal tooth thickness from a chordal measurement	
	12.3	Chordal measurement with an optical device (in the transverse plane)	84
		12.3.1 Principle of measurement	
		12.3.2 Underlying assumptions and limitations	
		12.3.3 Advantages and disadvantages of chordal measurement with optical device	
		12.3.4 Method for calculation	85
		12.3.5 Transverse pressure angle at the desired contact diameter	86
		12.3.6 Maximum transverse tooth thickness	
		12.3.7 Chordal radius	
		12.3.8 Minimum contact diameter	86
		12.3.9 Minimum transverse tooth thickness at diameter, d_{yt} min	86
		12.3.10 Transverse chordal tooth thickness measurement limits	
		12.3.11 Conversion of chordal radius to chordal addendum	
	12.4	12.3.12 Normal tooth thickness from a chordal measurement	
		Chordal measurement with a coordinate measurement machine	
13	Back	ash in parallel axis and crossed axis gear pairs	88
	13.1	General	88
	13.2	Factors that influence backlash	89
	13.3	Backlash for parallel axis gears in the axis related system	90
	13.4	Backlash for parallel axis gears in the non-datum related system	91
	13.5	Backlash in crossed axis gears	93
	13.6	Other potential influences on backlash	
	13.7	Ways to express backlash	
		13.7.1 Circumferential backlash	96
		13.7.2 Transverse backlash	
		13.7.3 Normal backlash	96
		13.7.5 Radial backlash	
		13.7.6 Angular backlash C	97 07
	13.8	Variations in backlash	
Anne	$\mathbf{x} \mathbf{A}$ (inf	ormative) Tooth thickness measurement using analytical machines	99
Anne		formative) Establishing tooth thickness specifications in the non-datum related	
		m	
		ormative) Establishing tooth thickness specifications in the axis related system	
	•	formative) Calculation method for the inverse involute function	
	-	ormative) Example calculations	
Biblio	graph	y	140

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 60, Gears.

A list of all parts in the ISO 21771 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

ISO 21771-2:2025

https://standards.iteh.ai/catalog/standards/iso/861da4f1-daa6-49da-9846-3274d5f3869e/iso-21771-2-2025