INTERNATIONAL STANDARD

ISO 2269

Second edition
1992-04-15

Shipbuilding — Class A magnetic compasses, azimuth reading devices and binnacles — Tests and certification

Construction navale — Compas magnétiques, alidades et habitacles de classe A — Essais et certification

Sample Document
get full document from standards.iteh.ai

Reference number
ISO 2269:1992(E)

ISO 2269:1992 • https://standards.iteh.ai/catalog/standards/iso/e47b18d2-3edd-45b3-84d0-2fbd38f4cb66/iso-2269-1992

Contents

Page

Section 1 General 1

1.1 Scope 1

1.2 Normative references 1

1.3 Definitions 1

1.4 Test conditions 1

1.5 Certification 1

Section 2 Testing and certification of class A compasses 2

2.1 General 2

2.2 Compass and gimballing checks and tests 2

Section 3 Testing and certification of azimuth reading devices, class A 9

3.1 General 9

3.2 Azimuth reading device checks and tests 9

Section 4 Type-testing and certification of class A binnacles 12

4.1 General 12

4.2 Binnacles 12

Annexes

A Type-test and individual test certificate for compasses 17

B Type-test certificate for bearing instruments 19

C Type-test certificate for binnacles 21

Sample Document
get full document from standards.iteh.ai

© ISO 1992
All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

ISO 2269:1992 • https://standards.iteh.ai/catalog/standards/iso/e47b18d2-3edd-45b3-84d0-2fbd38f4cb66/iso-2269-1992

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Sample Document
get full document from standards.iteh.ai

International Standard ISO 2269 was prepared by Technical Committee ISO/TC 8, *Shipbuilding and marine structures*, Sub-Committee SC 18, *Advanced navigational instruments and systems*.

This second edition cancels and replaces the first edition (ISO 2269:1973), of which it constitutes a technical revision, limited to class A magnetic compasses, azimuth reading devices and binnacles; tests and certification of class B magnetic compasses form the subject of ISO 10316.

Annexes A, B and C form an integral part of this International Standard.

ISO 2269:1992 • https://standards.iteh.ai/catalog/standards/iso/e47b18d2-3edd-45b3-84d0-2fbd38f4cb66/iso-2269-1992

Sample Document

This page intentionally left blank

get full document from standards.iteh.ai

ISO 2269:1992 • https://standards.iteh.ai/catalog/standards/iso/e47b18d2-3edd-45b3-84d0-2fbd38f4cb66/iso-2269-1992

Shipbuilding — Class A magnetic compasses, azimuth reading devices and binnacles — Tests and certification

Section 1: General

1.1 Scope

This International Standard specifies type-test and individual test methods, and gives the acceptable limits of the characteristics necessary to guarantee conformity of magnetic compasses, azimuth reading devices and binnacles to the general specifications given in ISO 449.

1.2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 449:1979, *Shipbuilding — Magnetic compasses and binnacles, class A.*

ISO 1069:1973, *Magnetic compasses and binnacles for sea navigation — Vocabulary.*

1.3 Definitions

For the purposes of this International Standard, the definitions given in ISO 1069 apply.

Unless otherwise stated, H is to be understood as the horizontal component of the magnetic flux density, in microtesla (μT), at the place of examination.

1.4 Test conditions

Type-testing shall be carried out before the instruments covered come into regular service. For type-testing, new devices only will be accepted.

Individual testing shall be carried out before installation on-board ship; it is also desirable periodically and after repair. For individual testing, all devices shall be in a clean and serviceable state when submitted for testing.

Unless otherwise stated, all tests shall be carried out at a temperature of 20 °C ± 3 °C.

1.5 Certification

Devices which have passed the type-tests or the individual tests and comply with the requirements shall be so certified in the language of the test authority and in English.

Each type-test certificate is valid exclusively for the model tested. In case of alterations or technical improvements which affect its compliance with ISO 449, the model shall be given a new identification number or mark and the type-test repeated. All alterations shall be submitted to the original test authority who will decide whether a new type-test is necessary (see annexes A, B and C).

Copies of the certificate shall be issued on demand. They shall explicitly be marked "copy".

Acceptance of type-test certificates and individual test certificates between countries will be a matter for mutual agreement.

Sample Document
get full document from standards.iteh.ai

ISO 2269:1992 • https://standards.iteh.ai/catalog/standards/iso/e47b18d2-3edd-45b3-84d0-2fbd38f4cb66/iso-2269-1992

Section 2: Testing and certification of class A compasses

2.1 General

2.1.1 Types of compasses to be tested

Testing shall be carried out on all class A compasses, with or without a transmitting system. All compasses, other than those compasses without gimbals which are used as steering compasses only, shall be tested with their gimbal rings and outer gimbal bearings.

2.1.2 Manufacturer's statement

The manufacturer shall produce a written statement covering those requirements which cannot be ascertained during a type-test (see annex A). The statement shall include the following points:

a) the coercivity and magnetic moment of the directional magnets;

b) that the paint inside the compass is of good quality and that over a period of two years it is not likely to deteriorate to such an extent as to make the compass unusable, either as a result of the change of temperature over the range of − 30 °C to + 60 °C or any other cause (for example the legibility of graduations shall not be impaired by discolouration or blistering);

c) under the conditions described in b), that the compass liquid is not likely to show any appreciable discolouration such as to render the compass unusable;

d) whether toughened or non-toughened glass is used for the top and bottom glass covers and its thickness; alternatively, when a material other than glass is used, that its strength is equivalent to that of non-toughened glass of 4,5 mm thickness;

e) that the material of the compass card will not distort;

f) that the moment of inertia of the directional system is approximately the same about all horizontal axes passing through the bearing surface of the pivot jewel;

g) the vertical distance between the mid-plane of the magnets of the directional system and the inner gimbal axis of the compass supplied;

h) the supporting force on the pivot at 20 °C;

i) that the inner and outer bearings of the gimbal rings are of the same type;

j) the length of bar magnets or diameter of ring magnet forming the directional system.

In order to check that the manufacturer's statement above has been fulfilled, sample checks may be carried out.

2.1.3 Marking

2.1.3.1 Verify that

a) compasses are marked in a conspicuous place on the compass card and the verge ring with the name of the manufacturer, or other means of identification;

b) compass card and gimbal ring are marked with a serial number;

c) the compass verge ring is marked with type and serial number.

2.1.3.2 The markings given in 2.1.3.1 shall be noted on the certificate.

2.1.3.3 If other than alcohol, the type of liquid used shall be indicated on the bowl in the vicinity of the filling plug.

2.2 Compass and gimballing checks and tests

2.2.1 Construction and material

2.2.1.1 Condition of compass bowl

The compass shall be inspected to see that it is undamaged and mechanically perfect. The liquid shall be colourless and free from turbidity and formation of flocks. There shall be no leaks. The paint, including that on the compass card, shall be free from cracks and blisters.

2.2.1.2 Non-magnetic properties (type-test only)

Compass bowls and gimballing shall be tested to verify their non-magnetic properties (see 2.2.7.4).

2.2.1.3 Condition at high temperature

The compass shall be warmed slowly from room temperature to 60 °C ± 2 °C and kept at least 8 h at this temperature. After this period, the compass

Sample Document
Document from standards.iteh.ai

ISO 2269:1992 • https://standards.iteh.ai/catalog/standards/iso/e47b18d2-3edd-45b3-84d0-2fbd38f4cb66/iso-2269-1992

shall not show any mechanical damage, leakage or bubbles. The compass liquid and paint shall not show any deterioration, and the directional system shall not be deformed. The compass shall operate satisfactorily.

The directional system shall always be in contact with its pivot.

2.2.1.4 Condition at low temperature

The compass shall be slowly cooled to $-30\ °C \pm 2\ °C$ and kept at least 8 h at this temperature. After this period the compass shall not show any mechanical damage or deformation, leakage or bubbles. The liquid in the bowl shall not freeze, discolour or separate into its ingredients. A formation of flocks or ice shall not have occurred within the liquid and the directional system shall not be deformed. There shall be no deterioration in the function of the compass.

The directional system shall always be in contact with its pivot.

2.2.1.5 Thickness of top and bottom glass covers (type-test only)

When made of non-toughened glass, the glass covers of compasses (including compasses that have no gimbals outside the bowl) shall have a thickness of at least 4,5 mm.

When toughened glass is used, the thickness shall be at least 3 mm.

When material other than glass is used, its properties shall be at least as strong as above [see 2.1.2 d)].

The thickness of the glass may be measured by means of a micrometer. As this requires the opening of the compass, it shall be done when the other examinations have been carried out.

2.2.1.6 Transmitting system

A transmitting system shall not interfere with reading the card or taking bearings with an azimuth reading device.

2.2.2 Compass gimballing

2.2.2.1 Plane of gimbal axes (type-test only)

The gimbal axes shall lie in one plane, within a tolerance of 1 mm.

This test may be carried out from a fixed horizontal reference plane by means of a suitable scale.

2.2.2.2 Angle of gimbal axes and intersection of vertical planes passing through them (type-test only)

The angle formed by the outer and inner gimbal axes shall be $90° \pm 1°$. The vertical planes through the gimbal axes shall intersect to within 1 mm of the pivot point. Any end play shall not cause these tolerances to be exceeded.

The outer gimbal axis shall be in the fore and aft direction.

Measurement of the axes angles may be made by means of the test stand graduation, when first one then the other gimbal axis is brought into the vertical plane of view passing through the graduation centre by turning the compass support.

Determination of the intersection line may be carried out on a test stand by measuring the displacement of the compass support in a direction perpendicular to either of the gimbal axes.

2.2.2.3 Freedom of movement within gimbal ring

When the gimbal ring is in the horizontal plane, the compass bowl shall freely revolve about the inner axis up to $\pm 40°$.

The measurement may be carried out by a clinometer placed on the top glass cover or verge ring.

2.2.2.4 Horizontal position

The compass bowl shall be balanced so that its verge ring or top glass cover settles in the horizontal plane to within 2° when the gimbal ring is fixed in a horizontal position. This shall be so whether the azimuth reading device or other attachment or magnifier is in position or not.

Measurement shall be carried out by placing a spirit level of suitable sensitivity on the top glass or its verge ring.

2.2.2.5 Friction of inner gimbal axis

When the gimbal ring is kept in the horizontal position and the compass bowl is inclined by $\pm 5°$, it shall return to within 2° of the horizontal plane.

The test may be carried out by means of a clinometer or spirit level.

2.2.2.6 Inner and outer gimbal bearings (type-test only)

The bearings of the inner and outer gimbal axes shall be of the same type.

Sample Document
get full document from standards.iteh.ai

ISO 2269:1992 • https://standards.iteh.ai/catalog/standards/iso/e47b18d2-3edd-45b3-84d0-2fbd38f4cb66/iso-2269-1992