
**Elastomeric seismic-protection
isolators —**

**Part 2:
Applications for bridges —
Specifications**

*Appareils d'appuis structuraux en élastomère pour protection
sismique —*

Partie 2: Applications pour ponts — Spécifications

Document Preview

ISO 22762-2:2018

<https://standards.itech.ai/catalog/standards/iso/ef94e141-585d-494f-9988-b72a67907711/iso-22762-2-2018>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 22762-2:2018

<https://standards.iteh.ai/catalog/standards/iso/ef94e141-585d-494f-9988-b72a67907711/iso-22762-2-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols	3
5 Classification	6
5.1 General	6
5.2 Classification by construction	6
5.3 Classification by tolerances on shear stiffness	7
6 Requirements	7
6.1 General	7
6.2 Type tests and routine tests	7
6.3 Functional requirements	10
6.4 Design compressive force and design shear displacement	10
6.5 Performance requirements	10
6.5.1 General	10
6.5.2 Compressive properties	11
6.5.3 Rotation properties	11
6.5.4 Shear properties	11
6.5.5 Tensile properties	12
6.5.6 Dependencies of shear properties	13
6.5.7 Shear displacement capacity	14
6.5.8 Durability	14
6.5.9 Cyclic compressive fatigue properties	15
6.5.10 Reaction force characteristics at low-rate deformation	15
6.6 Rubber material requirements	15
6.6.1 General	15
6.6.2 Tensile properties	15
6.6.3 Properties after ageing in air	16
6.6.4 Hardness	17
6.6.5 Adhesion properties	17
6.6.6 Compression set	17
6.6.7 Ozone resistance	18
6.6.8 Other properties	18
6.7 Dimensional requirements	18
6.8 Requirements on steel used for flanges and reinforcing plates	18
7 Design rules	18
7.1 General	18
7.2 Shape factor	20
7.2.1 First shape factor	20
7.2.2 Second shape factor	20
7.3 Compressive and shear properties	21
7.3.1 Compressive stiffness	21
7.3.2 Shear stiffness and equivalent damping ratio	21
7.4 Shear strain due to horizontal displacements	22
7.5 Total local shear strain	22
7.5.1 Local shear strain due to compressive force	22
7.5.2 Local shear strain due to compressive force	22
7.5.3 Total local shear strain	23
7.6 Tensile stress on reinforcing steel plates	23
7.7 Stability	23

7.7.1	Maximum compressive stress in non-seismic condition	23
7.7.2	Rotation performance check	23
7.7.3	Buckling check	24
7.7.4	Tensile stress on isolator	24
7.8	Force, moment and deformation affecting structures	24
7.8.1	Shear force affecting structures due to movement	24
7.8.2	Resistance to rotation	24
7.8.3	Compressive displacement due to compressive force	25
7.9	Design of fixings	25
7.9.1	External forces affecting joint members	25
7.9.2	Fixings and stresses to be checked	25
7.9.3	Allowable stress	26
8	Manufacturing tolerances	26
8.1	General	26
8.2	Measuring instruments	26
8.3	Plan dimensions of isolator body	27
8.3.1	Measurement method (see Figure 1)	27
8.3.2	Tolerances	27
8.4	Product height	28
8.4.1	Measurement method	28
8.4.2	Tolerances	29
8.5	Flatness of products	30
8.5.1	Measurement method	30
8.5.2	Tolerances	30
8.6	Horizontal offset	30
8.6.1	Measurement method	30
8.6.2	Tolerances	30
8.7	Plan dimensions of flanges	30
8.8	Flange thickness	31
8.9	Tolerances on positions of flange bolt holes	31
9	Marking and labelling	32
9.1	Information to be provided	32
9.2	Additional requirements	32
9.3	Marking and labelling examples	33
10	Test methods	33
11	Quality assurance	33
Annex A (normative)	Tensile stress in reinforcing steel plate	34
Annex B (normative)	Buckling stability	36
Annex C (normative)	Allowable tensile stress in isolator	37
Annex D (informative)	Dependency of ultimate properties on shape factor	38
Annex E (informative)	Minimum recommended tensile properties for rubber materials	42
Annex F (informative)	Compressive stiffness	43
Annex G (informative)	Determination of shear properties of elastomeric isolators	47
Annex H (informative)	Determination of local shear strain due to compression	52
Annex I (informative)	Maximum compressive stress	55
Bibliography		56

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 45, *Rubber and rubber products*, Subcommittee SC 4, *Products (other than hoses)*.

This third edition cancels and replaces the second edition (ISO 22762-2:2010), which has been technically revised.

The main changes compared to the previous edition are as follows:

- the definitions of some symbols in [Clause 4](#) have been changed.

A list of all parts in the ISO 22762 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

ISO 22762 series includes two parts related to specifications for isolators, i.e. ISO 22762-2 for bridges and ISO 22762-3 for buildings. This is because the isolator requirements for bridges and buildings are quite different, although the basic concept of the two products is similar. Therefore, ISO 22762-2 and the relevant clauses in ISO 22762-1 are used when ISO 22762 (all parts) is applied to the design of bridge isolators whereas ISO 22762-3 and the relevant clauses of ISO 22762-1 are used when it is applied to building isolators.

The main differences to be noted between isolators for bridges and isolators for buildings are the following.

- a) Isolators for bridges are mainly rectangular in shape and those for buildings are circular in shape.
- b) Isolators for bridges are designed to be used for both rotation and horizontal displacement, while isolators for buildings are designed for horizontal displacement only.
- c) Isolators for bridges are designed to perform on a daily basis to accommodate length changes of bridges caused by temperature changes as well as during earthquakes, while isolators for buildings are designed to perform only during earthquakes.
- d) Isolators for bridges are designed to withstand dynamic loads caused by vehicles on a daily basis as well as earthquakes, while isolators for buildings are mainly designed to withstand dynamic loads caused by earthquakes only.

For structures other than buildings and bridges (e.g. tanks), the structural engineer uses either ISO 22762-2 or ISO 22762-3, depending on the requirements of the structure.

iTech Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 22762-2:2018](https://standards.iteh.ai/catalog/standards/iso/ef94e141-585d-494f-9988-b72a67907711/iso-22762-2-2018)

<https://standards.iteh.ai/catalog/standards/iso/ef94e141-585d-494f-9988-b72a67907711/iso-22762-2-2018>

Elastomeric seismic-protection isolators —

Part 2: Applications for bridges — Specifications

1 Scope

This document specifies minimum requirements and test methods for elastomeric seismic isolators used for bridges, as well as rubber material used in the manufacture of such isolators.

It is applicable to elastomeric seismic isolators used to provide bridges with protection from earthquake damage. The isolators covered consist of alternate elastomeric layers and reinforcing steel plates, which are placed between a superstructure and its substructure to provide both flexibility for decoupling structural systems from ground motion and damping capability to reduce displacement at the isolation interface and the transmission of energy from the ground into the structure at the isolation frequency.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 630 (all parts), *Structural steels*

ISO 22762-1:2018, *Elastomeric seismic-protection isolators — Part 1: Test methods*

3 Terms and definitions

ISO 22762-2:2018

<https://standards.iteh.ai/catalog/standards/iso/ef94e141-585d-494f-9988-b72a67907711/iso-22762-2-2018>

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

breaking

rupture of *elastomeric isolator* (3.9) due to compression- (or tension-) shear loading

3.2

buckling

state when *elastomeric isolators* (3.9) lose their stability under compression-shear loading

3.3

compressive stiffness

K_v

compressive stiffness for all types of rubber bearings

3.4

cover rubber

rubber wrapped around the outside of inner rubber and reinforcing steel plates before or after curing of *elastomeric isolators* (3.8) for the purposes of protecting the inner rubber from deterioration due to oxygen, ozone and other natural elements and protecting the reinforcing plates from corrosion