
**Parallel shank jobber and stub series
drills and Morse taper shank drills**

*Forets à queue cylindrique courts et extra-courts et forets à queue
cône Morse*

Sample Document

get full document from standards.iteh.ai



Reference number
ISO 235:2016(E)

© ISO 2016

Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Interchangeability	1
5 Parallel shank twist drills, stub series	2
6 Parallel shank twist drills, jobber series	5
7 Morse taper shank twist drills	9
Annex A (informative) Relationship between designations in this document and ISO 13399 (all parts)	19
Bibliography	20

Sample Document

get full document from standards.iteh.ai

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 29, *Small tools*, Subcommittee SC 2, *Holding tools, adaptive items and interfaces*.

This third edition cancels and replaces the second edition (ISO 235:1980), of which it constitutes a minor revision, notably with the addition of [Annex A](#), which gives the relationship between the designations of this document and the ISO 13399 series. It also incorporates the Technical Corrigendum ISO 235:1980/Cor 1:1996.

Parallel shank jobber and stub series drills and Morse taper shank drills

1 Scope

This document specifies the dimensions of the following three types of drills:

- a) parallel shank drills, stub series;
- b) parallel shank drills, jobber series;
- c) Morse taper shank drills.

It comprises, for each type of drill mentioned above, three tables giving, respectively:

- a) the dimensions in millimetres;
- b) the dimension in inches;
- c) the corresponding lengths, in millimetres and in inches, set out as functions of diameter steps.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

4 Interchangeability

The numerical tables have been drawn up in such a way as to ensure that the standard dimensions in millimetres and inches correspond as closely as possible.

To this end, the complete range of diameters has been subdivided into a number of steps, the limits of which have been derived from the preferred number series for the metric values and converted directly from those for the inch values; the lengths and taper shank dimensions remain the same for the metric and the inch value within a given step.

The recommended diameters in the two systems of units of measurement differ, however, and the number of recommended diameters in a given step also differs in one system from that in the other.

Finally, the tolerance on the diameter of the cutting portion has been standardized solely on the basis of the metric value of h8, converted directly into inches for inch drills.

5 Parallel shank twist drills, stub series




Figure 1

Table 1

Dimensions in millimetres

d	l_1	l	d	l_1	l	d	l_1	l	d	l_1	l
0,50	3	20	9,50	40	84	18,50	64	127	27,50	81	162
0,80	5	24	9,80	43	89	18,75			27,75		
1,00	6	26	10,00			19,00			28,00		
1,20	8	30	10,20	47	95	19,25	66	131	28,25	84	168
1,50	9	32	10,50			19,50			28,50		
1,80	11	36	10,80			19,75			28,75		
2,00	12	38	11,00	51	102	20,00	68	136	29,00	87	174
2,20	13	40	11,20			20,25			29,25		
2,50	14	43	11,50			20,50			29,50		
2,80	16	46	11,80	54	107	20,75	70	141	29,75	90	180
3,00			12,00			21,00			30,00		
3,20	18	49	12,20			21,25	72	146	30,25	93	186
3,50	20	52	12,50	56	111	21,50			30,50		
3,80	22	55	12,80			21,75			30,75	96	193
4,00			13,00			22,00	75	151	31,00		
4,20			13,20	58	115	22,25			31,25		
4,50	24	58	13,50			22,50	78	156	31,50	100	200
4,80	26	62	13,80	60	119	22,75			31,75		
5,00			14,00			23,00			32,00		
5,20			14,25	62	123	23,25			32,50		
5,50	28	66	14,50			23,50			33,00		
5,80			14,75			23,75	75	151	33,50	93	186
6,00			15,00	58	115	24,00			34,00		
6,20	31	70	15,25			24,25	78	156	34,50	96	193
6,50			15,50			24,50			35,00		
6,80			15,75	60	119	24,75			35,50		
7,00	34	74	16,00			25,00			36,00	100	200
7,20			16,25	62	123	25,25			36,50		
7,50			16,50			25,50			37,00		
7,80	37	79	16,75			25,75	78	156	37,50		
8,00			17,00	60	119	26,00			38,00		
8,20			17,25			26,25			38,50		
8,50			17,50	62	123	26,50			39,00	100	200
8,80			17,75			26,75			39,50		

Table 1 (continued)

d	l_1	l	d	l_1	l	d	l_1	l	d	l_1	l
9,00	40	84	18,00			27,00	81	162	40,00		
9,20			18,25	64	127	27,25					

When intermediate sizes are needed, reference is to be made to [Table 3](#) for the corresponding lengths.

Cutting portion

- Tolerance on diameter, d , measured near the point: h8.

For dimensions in inches, direct conversion into inches of the metric values of the tolerance h8.

- Back taper: at the manufacturer's discretion.
- Hand of cutting, unless otherwise specified: right.

Shank: these drills are normally made without driving tenon.

For tolerances on lengths, see [Table 3](#).

Table 2

Dimensions in inches

d	l_1	l	d	l_1	l	d	l_1	l		
1/32	3/16	15/16	17/32	2 1/8	4 7/32	1 1/32	3 1/16	6 1/8		
3/64	5/16	1 3/16	35/64			1 3/64	3 3/16	6 3/8		
1/16	13/32	1 11/32	9/16	2 7/32	4 3/8	1 1/16		3 5/16	6 5/8	
5/64	15/32	1 1/2	37/64			1 5/64				
3/32	9/16	1 11/16	19/32	1 3/32						
7/64	5/8	1 13/16	39/64	2 9/32	4 17/32	1 7/64				
1/8	11/16	1 15/16	5/8	2 3/8	4 11/16	1 1/8				
9/64	25/32	2 1/16	41/64			1 9/64				
5/32	7/8	2 5/32	21/32			1 5/32				
11/64	15/16	2 9/32	43/64	2 7/16	4 27/32	1 11/64	3 7/16	6 27/32		
3/16	1 1/32	2 7/16	11/16			1 3/16				
13/64			45/64	1 13/64						
7/32	1 1/8	2 19/32	23/32	2 1/2	5	1 7/32	3 17/32	7 3/32		
15/64			47/64			1 15/64				
1/4	1 7/32	2 3/4	3/4	2 19/32	5 5/32	1 1/4				
17/64	1 5/16	2 29/32	49/64			1 17/64				
9/32			25/32			1 9/32				
19/64	1 7/16	3 1/8	51/64	2 11/16	5 11/32	1 19/64			3 21/32	7 5/16
5/16			13/16			1 5/16				
21/64			53/64			1 21/64				
11/32	1 9/16	3 5/16	27/32	2 3/4	5 9/16	1 11/32	3 25/32	7 19/32		
23/64			55/64			1 23/64				
3/8	1 11/16	3 1/2	7/8	2 27/32	5 3/4	1 3/8				
25/64			57/64			1 25/64				
13/32			29/32			1 13/32				
27/64	1 27/32	3 3/4	59/64	2 15/16	5 15/16	1 27/64	3 25/32	7 19/32		
7/16			15/16			1 7/16				
29/64			61/64			1 29/64				
15/32			31/32			1 15/32				