

---

---

**Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Engineering methods for small movable sources in reverberant fields**

Part 1:  
**Comparison method for a hard-walled test room**

*Acoustique — Détermination des niveaux de puissance et d'énergie acoustiques émis par les sources de bruit à partir de la pression acoustique — Méthodes d'expertise en champ réverbéré applicables aux petites sources transportables*

*Partie 1: Méthode par comparaison en salle d'essai à parois dures*



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

# Sample Document

get full document from [standards.iteh.ai](http://standards.iteh.ai)



## **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

**Contents**

Page

<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>2</b>
<b>4 Test room and size of noise source under test</b> .....	<b>6</b>
<b>5 Instrumentation and measurement equipment</b> .....	<b>7</b>
<b>6 Definition, location, installation, and operation of noise source under test</b> .....	<b>8</b>
<b>7 Measurement procedure</b> .....	<b>10</b>
<b>8 Determination of sound power levels and sound energy levels</b> .....	<b>12</b>
<b>9 Measurement uncertainty</b> .....	<b>16</b>
<b>10 Information to be recorded</b> .....	<b>19</b>
<b>11 Test report</b> .....	<b>21</b>
<b>Annex A (normative) Sound power level and sound energy level under reference meteorological conditions</b> .....	<b>22</b>
<b>Annex B (normative) Calculation of A-weighted sound power levels and A-weighted sound energy levels from octave band levels</b> .....	<b>24</b>
<b>Annex C (informative) Guidelines on the development of information on measurement uncertainty</b> ....	<b>26</b>
<b>Bibliography</b> .....	<b>35</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 3743-1 was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

This second edition cancels and replaces the first edition (ISO 3743-1:1994), which has been technically revised.

ISO 3743 consists of the following parts, under the general title *Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Engineering methods for small movable sources in reverberant fields*:

- *Part 1: Comparison method for a hard-walled test room*
- *Part 2: Methods for special reverberation test rooms*

## Introduction

This part of ISO 3743 is an element of the series ISO 3740<sup>[1]</sup> to ISO 3747<sup>[7]</sup>, which specify various methods for determining the sound power levels and sound energy levels of noise sources including machinery, equipment and their sub-assemblies. The selection of one of the methods from the series for use in a particular application depends on the purpose of the test to determine the sound power level or sound energy level and on the facilities available. General guidelines to assist in the selection are provided in ISO 3740<sup>[1]</sup>. ISO 3740<sup>[1]</sup> to ISO 3747<sup>[7]</sup> give only general principles regarding the operating and mounting conditions of the machinery or equipment for the purposes of the test. It is important that test codes be established for individual kinds of noise source, in order to give detailed requirements for mounting, loading, and operating conditions under which the sound power levels or sound energy levels are to be obtained.

The method given in this part of ISO 3743 is based on a comparison of the sound pressure levels in octave frequency bands of a noise source under test with those of a calibrated reference sound source; A-weighted sound power levels or sound energy levels may be calculated from the octave-band levels. The method is applied in a hard-walled test room with prescribed acoustical characteristics, where it can be used for small items of portable equipment. Such a room allows either the sound power levels or the sound energy levels of the noise source under test to be determined, depending on the character of the noise emitted by the source. However, this kind of test room is not suitable for larger pieces of stationary equipment which, due to their manner of operation or installation, cannot readily be moved. The application of the method for use where the equipment or machinery is found *in situ* is described in ISO 3747<sup>[7]</sup>.

The methods specified in this part of ISO 3743 permit the determination of the sound power level and the sound energy level in frequency bands and/or with frequency A-weighting applied.

This part of ISO 3743 describes a method of accuracy grade 2 (engineering grade) as defined in ISO 12001. For applications where greater accuracy is required, reference can be made to ISO 3741<sup>[2]</sup> or an appropriate part of ISO 9614<sup>[15][17]</sup>. If the relevant criteria for the measurement environment specified in this part of ISO 3743 are not met, it might be possible to refer to another standard from this series, or to an appropriate part of ISO 9614<sup>[15][17]</sup>.

# Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)

# Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Engineering methods for small movable sources in reverberant fields

## Part 1: Comparison method for a hard-walled test room

### 1 Scope

#### 1.1 General

This part of ISO 3743 specifies methods for determining the sound power level or sound energy level of a noise source by comparing measured sound pressure levels emitted by this source (machinery or equipment) mounted in a hard-walled test room, the characteristics of which are specified, with those from a calibrated reference sound source. The sound power level (or, in the case of noise bursts or transient noise emission, the sound energy level) produced by the noise source, in frequency bands of width one octave, is calculated using those measurements. The sound power level or sound energy level with A-weighting applied is calculated using the octave-band levels.

#### 1.2 Types of noise and noise sources

The method specified in this part of ISO 3743 is suitable for all types of noise (steady, non-steady, fluctuating, isolated bursts of sound energy, etc.) defined in ISO 12001.

The noise source under test may be a device, machine, component or sub-assembly. The maximum size of the source depends upon the size of the room used for the acoustical measurements (see 4.2).

#### 1.3 Test environment

The test environment that is applicable for measurements made in accordance with this part of ISO 3743 is a hard-walled test room with prescribed acoustical characteristics.

#### 1.4 Measurement uncertainty

Information is given on the uncertainty of the sound power levels and sound energy levels determined in accordance with this part of ISO 3743, for measurements made in frequency octave bands and for A-weighted frequency calculations performed on them. The uncertainty conforms to ISO 12001:1996, accuracy grade 2 (engineering grade).

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5725 (all parts), *Accuracy (trueness and precision) of measurement methods and results*

ISO 6926, *Acoustics — Requirements for the performance and calibration of reference sound sources for the determination of sound power levels*

ISO 12001:1996, *Acoustics — Noise emitted by machinery and equipment — Rules for the drafting and presentation of a noise test code*

ISO/IEC Guide 98-3, *Uncertainty in measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

IEC 60942:2003, *Electroacoustics — Sound calibrators*

IEC 61260:1995, *Electroacoustics — Octave-band and fractional-octave-band filters*

IEC 61672-1:2002, *Electroacoustics — Sound level meters — Part 1: Specifications*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

#### 3.1 sound pressure

$p$   
difference between instantaneous pressure and static pressure

NOTE 1 Adapted from ISO 80000-8:2007<sup>[19]</sup>, 8-9.2.

NOTE 2 Sound pressure is expressed in pascals.

#### 3.2 sound pressure level

$L_p$   
ten times the logarithm to the base 10 of the ratio of the square of the sound pressure,  $p$ , to the square of a reference value,  $p_0$ , expressed in decibels

$$L_p = 10 \lg \frac{p^2}{p_0^2} \text{ dB} \quad (1)$$

where the reference value,  $p_0$ , is 20  $\mu\text{Pa}$

[ISO/TR 25417:2007<sup>[18]</sup>, 2.2]

NOTE 1 If specific frequency and time weightings as specified in IEC 61672-1 and/or specific frequency bands are applied, this is indicated by appropriate subscripts; e.g.  $L_{pA}$  denotes the A-weighted sound pressure level.

NOTE 2 This definition is technically in accordance with ISO 80000-8:2007<sup>[19]</sup>, 8-22.

#### 3.3 time-averaged sound pressure level

$L_{p,T}$   
ten times the logarithm to the base 10 of the ratio of the time average of the square of the sound pressure,  $p$ , during a stated time interval of duration,  $T$  (starting at  $t_1$  and ending at  $t_2$ ), to the square of a reference value,  $p_0$ , expressed in decibels

$$L_{p,T} = 10 \lg \left[ \frac{\frac{1}{T} \int_{t_1}^{t_2} p^2(t) dt}{p_0^2} \right] \text{ dB} \quad (2)$$

where the reference value,  $p_0$ , is 20  $\mu\text{Pa}$

NOTE 1 In general, the subscript “ $T$ ” is omitted since time-averaged sound pressure levels are necessarily determined over a certain measurement time interval.

NOTE 2 Time-averaged sound pressure levels are often A-weighted, in which case they are denoted by  $L_{pA,T}$ , which is usually abbreviated to  $L_{pA}$ .

NOTE 3 Adapted from ISO/TR 25417:2007<sup>[18]</sup>, 2.3.

### 3.4 single event time-integrated sound pressure level

$L_E$

ten times the logarithm to the base 10 of the ratio of the integral of the square of the sound pressure,  $p$ , of an isolated single sound event (burst of sound or transient sound) over a stated time interval  $T$  (starting at  $t_1$  and ending at  $t_2$ ) to a reference value,  $E_0$ , expressed in decibels

$$L_E = 10 \lg \left[ \frac{\int_{t_1}^{t_2} p^2(t) dt}{E_0} \right] \text{ dB} \quad (3)$$

where the reference value,  $E_0$ , is  $(20 \mu\text{Pa})^2 \text{ s} = 4 \times 10^{-10} \text{ Pa}^2 \text{ s}$

NOTE 1 This quantity can be obtained by  $L_{p,T} + 10 \lg \frac{T}{T_0}$  dB, where  $T_0 = 1$  s

NOTE 2 When used to measure sound immission, this quantity is usually called “sound exposure level” (see ISO/TR 25417:2007<sup>[18]</sup>).

### 3.5 measurement time interval

$T$

portion or a multiple of an operational period or operational cycle of the noise source under test for which the time-averaged sound pressure level is determined

NOTE Measurement time interval is expressed in seconds.

### 3.6 comparison method

method by which the sound power level or sound energy level of a noise source under test is determined from a comparison of the sound pressure levels produced by the source under test with those of a reference sound source of known sound power output, when both sources are operated in the same environment

**3.7**  
**hard-walled test room**  
room in which the acoustical reflectivity of all room surfaces (including the floor and ceiling) is high over the frequency range of interest

**3.8**  
**reverberant sound field**  
that portion of the sound field in the test room over which the influence of sound received directly from the source is negligible

**3.9**  
**sound absorption coefficient**  
 $\alpha$   
at a given frequency and for specified conditions, the relative fraction of sound power incident upon a surface which is not reflected

**3.10**  
**reference sound source**  
sound source meeting specified requirements

NOTE For the purposes of this International Standard, the requirements are those specified in ISO 6926:1999, Clause 5.

**3.11**  
**frequency range of interest**  
for general purposes, the frequency range of octave bands with nominal mid-band frequencies from 125 Hz to 8 000 Hz

NOTE For special purposes, the frequency range can be reduced, provided that the test environment, reference sound source, and instrument specifications are satisfactory for use over the modified frequency range. The frequency range can be extended downwards as far as the 63 Hz octave band, but cannot be extended upwards beyond the 8 000 Hz band. Any reduced or extended frequency range is clearly indicated as such in the report.

**3.12**  
**reference box**  
hypothetical right parallelepiped terminating on the floor of the test room on which the noise source under test is located, that just encloses the source including all the significant sound radiating components and any test table on which the source is mounted

NOTE If required, the smallest possible test table can be used for compatibility with emission sound pressure measurements at bystander positions in accordance with the ISO 11200 to ISO 11204 series.

**3.13**  
**background noise**  
noise from all sources other than the noise source under test

NOTE Background noise includes contributions from airborne sound, noise from structure-borne vibration, and electrical noise in the instrumentation.

**3.14**  
**background noise correction**  
 $K_1$   
correction applied to the measured sound pressure levels to account for the influence of background noise

NOTE 1 Background noise correction is expressed in decibels.

NOTE 2 The background noise correction is frequency dependent; the correction in the case of a frequency band is denoted  $K_{1f}$ , where  $f$  denotes the relevant mid-band frequency, and that in the case of A-weighting is denoted  $K_{1A}$ .

### 3.15 sound power

$P$

through a surface, product of the sound pressure,  $p$ , and the component of the particle velocity,  $u_n$ , at a point on the surface in the direction normal to the surface, integrated over that surface

[ISO 80000-8:2007<sup>[19]</sup>, 8-16]

NOTE 1 Sound power is expressed in watts.

NOTE 2 The quantity relates to the rate per time at which airborne sound energy is radiated by a source.

### 3.16 sound power level

$L_W$

ten times the logarithm to the base 10 of the ratio of the sound power of a source,  $P$ , to a reference value,  $P_0$ , expressed in decibels

$$L_W = 10 \lg \frac{P}{P_0} \text{ dB} \quad (4)$$

where the reference value,  $P_0$ , is 1 pW

NOTE 1 If a specific frequency weighting as specified in IEC 61672-1 and/or specific frequency bands are applied, this should be indicated by appropriate subscripts; e.g.  $L_{WA}$  denotes the A-weighted sound power level.

NOTE 2 This definition is technically in accordance with ISO 80000-8:2007<sup>[19]</sup>, 8-23.

[ISO/TR 25417:2007<sup>[18]</sup>, 2.9]

### 3.17 sound energy

$J$

integral of the sound power,  $P$ , over a stated time interval of duration  $T$  (starting at  $t_1$  and ending at  $t_2$ )

$$J = \int_{t_1}^{t_2} P(t) dt \quad (5)$$

NOTE 1 Sound energy is expressed in joules.

NOTE 2 The quantity is particularly relevant for non-stationary, intermittent sound events.

[ISO/TR 25417:2007<sup>[18]</sup>, 2.10]

### 3.18 sound energy level

$L_J$

ten times the logarithm to the base 10 of the ratio of the sound energy,  $J$ , to a reference value,  $J_0$ , expressed in decibels

$$L_J = 10 \lg \frac{J}{J_0} \text{ dB} \quad (6)$$

where the reference value,  $J_0$ , is 1 pJ

NOTE If a specific frequency weighting as specified in IEC 61672-1 and/or specific frequency bands are applied, this should be indicated by appropriate subscripts; e.g.  $L_{JA}$  denotes the A-weighted sound energy level.

[ISO/TR 25417:2007<sup>[18]</sup>, 2.11]

## 4 Test room and size of noise source under test

### 4.1 Reference box

In order to assist in specification of the size of the test room, the reference box shall first be delineated. The reference box is a hypothetical surface defined by the smallest right parallelepiped that just encloses the noise source under test. The noise source under test shall be taken to include all significant sources of sound emission, including auxiliary equipment which cannot either be removed or adequately quietened, and the reference box shall be extended appropriately. When defining the dimensions of the reference box, elements protruding from the source which are not significant radiators of sound may be disregarded.

### 4.2 Volume of test room and size of noise source under test

The volume of the test room shall be at least 40 m<sup>3</sup>, and at least 40 times the volume of the reference box.

In rooms with volumes between 40 m<sup>3</sup> and 100 m<sup>3</sup>, the largest dimension of the reference box shall not exceed 1,0 m. In rooms with volumes greater than 100 m<sup>3</sup>, the largest dimension of the reference box shall not exceed 2,0 m.

### 4.3 Acoustical properties of test room

A hard-walled room shall be used. This means that the sound absorption coefficient of any portion of any boundary surface shall not exceed 0,20 at all frequencies within the frequency range of interest. Most ordinary, unfurnished rooms without special acoustical treatment (e.g. acoustical ceilings and/or absorptive wall coverings) comply with this requirement. Table 1 gives guidelines.

Table 1 — Acceptable and unacceptable rooms

Acceptable rooms	Unacceptable rooms
Nearly empty rooms with smooth hard walls and ceiling made of concrete, brick, plaster or tile	Rooms with upholstered furniture, machinery or industrial rooms with a small amount of sound absorptive material on ceiling or walls (e.g. partially absorptive ceiling)
Partly empty rooms, rooms with smooth hard walls	Rooms with some sound absorptive materials on both ceiling and walls
Rooms without upholstered furniture, right cuboid machinery rooms or industrial rooms, no sound absorptive materials on surfaces	Rooms with large amounts of sound absorptive materials on either ceiling or walls
Irregularly shaped rooms without upholstered furniture, irregularly shaped machinery rooms or industrial rooms, no sound absorptive materials on surfaces	

### 4.4 Criterion for acoustic adequacy of test room

The suitability of a test room can differ from one noise source under test to another. The requirements for the room are most critical when a highly directional sound source is to be evaluated. When testing the general suitability of a test room, the procedure described hereafter shall be followed.