
**Construction drawings — Simplified
representation of concrete reinforcement**

*Dessins de construction — Représentation simplifiée des armatures de
béton*

Sample Document

get full document from standards.iteh.ai



Reference number
ISO 3766:2003(E)

© ISO 2003

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

Sample Document

get full document from standards.iteh.ai

© ISO 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope.....	1
2 Normative references	1
3 Requirements to reinforcement construction drawings.....	1
4 Placement information and representation.....	2
4.1 Reinforcement without prestressing	2
4.2 Prestressed reinforcement.....	7
5 Marking.....	8
6 Bending information for unprestressed reinforcement bars	8
6.1 General	8
6.2 Indication of bar shapes.....	9
6.3 Coding system (optional).....	11
7 Bar schedule.....	17
7.1 General	17
7.2 Shape schedule.....	17
7.3 Bending schedule	17
7.4 Combined schedules.....	18
7.5 Title block.....	18
Annex A (informative) Mat schedule — Example	21

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 3766 was prepared by Technical Committee ISO/TC 10, *Technical product documentation*, Subcommittee SC 8, *Construction documentation*.

This third edition cancels and replaces the second edition (ISO 3766:1995) and ISO 4066:1994, which have been technically revised.

Sample Document

get full document from standards.iteh.ai

Construction drawings — Simplified representation of concrete reinforcement

1 Scope

This International Standard specifies the simplified representation and the characterization of reinforcement in reinforced and in prestressed concrete for use in construction drawings. It also establishes a system for the scheduling of reinforced bars, comprising

- a method for specifying dimensions,
- a coding system for bar shapes,
- a schedule of preferred shapes, and
- a shape schedule and bending schedule.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 128-23:1999, *Technical drawings — General principles of presentation — Part 23: Lines on construction drawings*

ISO 10209-4:1999, *Technical product documentation — Vocabulary — Part 4: Terms relating to construction documentation*

3 Requirements to reinforcement construction drawings

The construction parts shall be provided with the main dimensions, the concrete reinforcement shall be drawn and all parts shall be represented unambiguously and clearly in scaled plans, elevations and sections. The representations shall correspond with the indications in the structural calculations and should, where applicable, contain all dimensions required for the construction of the members and the verification of the calculations.

Drawings used for off-site casting and factory production are excepted from this provision.

Reference shall be referred to accessory drawings. For drawings modified later, all concerned drawings shall be modified as well.

The following characterizations (general information and placement information) of the reinforcement bars shall be given on the drawing:

- required concrete strength class, the exposure class and further requirements to the concrete given in reference standards;

- type of reinforcing steel and prestressed steel given in reference standards;
- bar mark, number, diameter, shape and position of the reinforcement bars; distance between the bars and overlap length at joints; arrangement, dimensions and development of welding points by specification of the joining metal, jarring plates, position of the concreting gap;
- type of the prestressing system; number, type and position of the tendons; number, type and position of the tendon anchoring and tendon coupling; bar mark, number, diameter, shape and position of the accessory not prestressed concrete reinforcement; type and diameter of the encasing tubes; specification of the intrusion grout;
- measures for securing the position of the concrete reinforcement and the tendons (e.g. kind and arrangement of the bar chairs, as well as arrangement, dimensions and shape for the support of the upper concrete reinforcement layer and the tendons);
- the layer dimension c_V which derives from the nominal dimension c_{nom} of the concrete cover, as well as the allowance in design for tolerance Δc of the concrete cover;
- the joint development;
- special measures for quality assurance, if required.

The following information on bending the reinforcement bars shall be given on the drawing or on separate documents such as a bar schedule:

- if the shape coding system according to 6.3 is applied, bending shapes of the reinforcement bars shall refer unambiguously to the shape numbers, hence the graphical representation may be unscaled;
- single length, sectional lengths and, if applicable, bending angles of the reinforcement bars shall be indicated (for typifying bending shapes, Table 5 shall be taken into account, and in every case the reference standard mandrel or radii shall be represented on the drawing);
- the mandrel diameters or radii.








Manufacturing tolerances shall be taken into account in dimensioning the reinforcement components, in order to reach the desired concrete cover in the ready-made structure.

4 Placement information and representation

4.1 Reinforcement without prestressing

The representation and drawing conventions of concrete reinforcements without prestressing shall be in accordance with Table 1.

Table 1 — Representation and drawing conventions of concrete reinforcements without prestressing

No.	Description	Representation
1	<p>Views</p> <p>a) General representation of bar by a continuous extra-wide line</p> <p>b) Bent reinforcement bar</p> <p>1) representation as a polygonal continuous line or</p> <p>2) representation as a continuous line made up of straight lines and arcs</p> <p>c) Bundle of bars drawn using a single line, with end markings indicating number of bars in bundle</p> <p>EXAMPLE Bundle of three identical bars.</p>	
2	<p>Section of bar</p> <p>a) section of single reinforcement bar</p> <p>b) bundle of two reinforcement bars</p> <p>c) bundle of three reinforcement bars</p>	
3	<p>Bar with hook anchoring</p> <p>a) elevation of bar terminating in a 90° bend</p> <p>b) elevation of bar terminating in a bend between 90° and 180°</p> <p>c) elevation of bar terminating in a 180° bend</p>	
4	<p>Straight bars lying in a row or a plane to indicate the ends of the bars, showing corresponding bar marks using narrow line</p>	
5	<p>End anchorage with plates</p> <p>a) elevation or plan view</p> <p>b) section or end view</p>	
6	<p>Bar bent at a right angle away from viewer</p>	
7	<p>Bar bent at a right angle towards viewer</p>	
8	<p>Overlapping stack of reinforcement bars</p> <p>a) <i>without</i> marking bar ends by a slash and bar marks</p> <p>b) <i>with</i> marking bar ends by a slash and bar marks</p>	