
International Standard



3895

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Road vehicles — Screened and waterproof spark-plug and its connection — Type 2

Véhicules routiers — Bougie d'allumage blindée et étanche et sa connexion — Type 2

Third edition — 1986-03-15

Sample Document

get full document from standards.iteh.ai

UDC 621.43.045

Ref. No. ISO 3895-1986 (E)

Descriptors : road vehicles, internal combustion engines, controlled ignition engines, ignition systems, spark plugs, dimensions.

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 3895 was prepared by Technical Committee ISO/TC 22, *Road vehicles*.

This third edition cancels and replaces the second edition (ISO 3895-1979), of which it constitutes a minor revision.

Users should note that all International Standards undergo revision from time to time and that any reference made herein to any other International Standard implies its latest edition, unless otherwise stated.

Road vehicles — Screened and waterproof spark-plug and its connection — Type 2

1 Scope

This International Standard specifies the essential dimensional characteristics of a spark-plug type used with spark ignition engines.

2 Field of application

The requirements of this International Standard apply to screened and waterproof spark-plugs and their connections, type 2.

3 References

ISO 68, *ISO general purpose screw threads — Basic profile.*

ISO 261, *ISO general purpose metric screw threads — General plan.*

ISO 965/1, *ISO general purpose metric screw threads — Tolerances — Part 1 : Principles and basic data.*

ISO 965/3, *ISO general purpose metric screw threads — Tolerances — Part 3 : Deviations for constructional threads.*

ISO 3412, *Road vehicles — Screened and waterproof spark plug and its connection — Type 1.*

ISO 3896, *Road vehicles — Screened and waterproof spark-plug and its connection — Type 3.*

4 Required characteristics for spark-plug and housing in the cylinder head

4.1 Dimensions and thread (see figure)

4.1.1 Plug reach and installed height

Dimensions in millimetres

Type of reach	A	B max.	C (see 4.1.2)
Short reach	12,5 ± 0,2	70	1,1 to 1,7
Long reach	20,3 ± 0,2	65	2,0 to 2,3

4.1.2 Gasket

When the spark-plugs have been tightened with a torque of 48 N.m (threads clean, smooth and dry), the gasket thickness shall correspond to dimension C in the table in 4.1.1. If the gaskets are of a different thickness, a corresponding adjustment to dimension A shall be made.

4.1.3 Thread

4.1.3.1 Dimension limits

Dimensions in millimetres

Dimension	Plug thread (on finished plug) 6e		Tapped hole in cylinder head 6H
	max.	min.	
Major diameter	max.	17,933	not specified
	min.	17,697	18,000
Pitch diameter	max.	16,959	17,216
	min.	16,819	17,026
Minor diameter	max.	16,092	16,676
	min.	15,845*	16,376

* With a root radius $\geq 0,150$ mm (0,1 P).

4.1.3.2 Tolerance classes

The tolerance classes of thread M18 × 1,5 of the finished spark-plugs and of the corresponding tapped holes in the cylinder head are as follows :

- 6e for spark-plugs (see note 2);
- 6H for tapped holes in the cylinder head.

NOTES

1 The threads M18 × 1,5 of the spark-plugs and the corresponding tapped holes in the cylinder head shall conform to ISO 68, ISO 261, ISO 965/1 and ISO 965/3.

2 In order that the spark-plugs complying with this International Standard can be fitted in existing cylinder heads also in limiting cases, the value for the *maximum truncation* of the minor diameter of the spark-plug base has been slightly reduced with respect to the ISO value.