

# INTERNATIONAL STANDARD

**ISO**  
**3965**

Second edition  
1990-02-15

---

---

## **Agricultural wheeled tractors — Maximum speeds — Method of determination**

*Tracteurs agricoles à roues — Vitesses maximales — Méthode de  
détermination*

Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)



Reference number  
ISO 3965:1990(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 3965 was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*.

This second edition cancels and replaces the first edition (ISO 3965:1977), of which it constitutes a minor revision, now incorporating a specimen test report.

Annex A forms an integral part of this International Standard.

© ISO 1990

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization

Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

# Agricultural wheeled tractors — Maximum speeds — Method of determination

## 1 Scope

This International Standard specifies a method for calculating the maximum design speed and a method for measuring the maximum travel speed of agricultural wheeled tractors.

## 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 789-1:1981, *Agricultural tractors — Test procedures — Part 1: Power tests*.

ISO 4251-1:1988, *Tyres and rims (existing series) for agricultural tractors and machines — Part 1: Tyre designation and dimensions*.

## 3 Maximum design speed calculation

Calculate the maximum design speed from parameters as specified by the manufacturer, i.e.

- the rated engine rotational frequency (rated engine speed) ("rated" is defined in ISO 789-1);
- the transmission gear ratio for the highest (fastest) forward gear;
- the dynamic radius index, calculated in accordance with ISO 4251-1, of the maximum size drive wheel tyres recommended by the tractor manufacturer for road use.

## 4 Maximum travel speed measurement

### 4.1 Test requirements

#### 4.1.1 Tractor

4.1.1.1 The fuel specified in the operation manual shall be used.

4.1.1.2 The settings for the carburettor and ignition and/or the fuel injection pump, the engine power and the no-load engine rotational frequency shall be as specified by the manufacturer.

4.1.1.3 Front-wheel drive or any additional (power) driving axle shall only be engaged when recommended by the manufacturer for road use.

4.1.1.4 The tyres shall be of the same stated size as those used to calculate maximum design speed (clause 3). The tyres shall be new and inflated to the pressure indicated by the tractor manufacturer for road use.

4.1.1.5 The tractor shall be in working order, with full fuel tanks, radiators and with an operator, but without removable ballast weights, special equipment or loads.

#### 4.1.2 Test roadway

4.1.2.1 The roadway shall be straight and allow the maximum speed to be maintained for a minimum test distance of 100 m.

4.1.2.2 The surface shall be dry, smooth concrete, or similar finish, swept clean.

4.1.2.3 The surface shall not have more than 1,5 % slope in the direction of travel and not more than 1,5 % slope at right-angles to the direction of travel.