
**Measurement of fluid flow in closed
conduits — Velocity area method
using Pitot static tubes**

*Mesurage du débit des fluides dans les conduites fermées — Méthode
d'exploration du champ des vitesses au moyen de tubes de Pitot doubles*

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 3966:2020](https://standards.iteh.ai/catalog/standards/iso/487c72f8-306a-4dd6-a734-c275e6578d39/iso-3966-2020)

<https://standards.iteh.ai/catalog/standards/iso/487c72f8-306a-4dd6-a734-c275e6578d39/iso-3966-2020>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 3966:2020

<https://standards.iteh.ai/catalog/standards/iso/487c72f8-306a-4dd6-a734-c275e6578d39/iso-3966-2020>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
1 Scope	1
2 Normative references	1
3 Terms, definitions and symbols	1
3.1 Terms and definitions	1
3.2 Symbols	2
4 Principle	3
4.1 General principle	3
4.1.1 Graphical integration of the velocity area (see Clause 9)	4
4.1.2 Numerical integration of the velocity area (see Clause 10)	4
4.1.3 Arithmetical methods (see Clause 11)	4
4.2 Measurement of the measuring cross-section	4
4.2.1 Circular cross-sections	4
4.2.2 Rectangular cross-sections	4
4.3 Measurement of local velocities	5
4.3.1 Method of exploring traverse section	5
4.3.2 Reference measurement	5
4.3.3 Checking of velocity distribution	5
4.4 Location and number of measuring points in the cross-section	6
4.4.1 General requirements	6
4.4.2 Circular cross-sections	6
4.4.3 Rectangular cross-sections	6
5 Design of Pitot tubes	7
5.1 General description	7
5.2 Criteria to be fulfilled by the Pitot tube	7
6 Requirements for use of Pitot tubes	8
6.1 Selection of the measuring cross-section	8
6.1.1 Location of the measuring cross-section (of selection)	8
6.1.2 Avoidance of asymmetry, swirl and turbulences	8
6.1.3 Maximum flow deviation	8
6.1.4 Preliminary traverse tests	9
6.2 Devices for improving flow conditions	9
6.2.1 Anti-swirl device	9
6.2.2 Profile developer	9
6.2.3 Positioning/Location of devices	9
6.2.4 Provisional guiding installation	9
6.3 Limits of use	9
6.3.1 Nature of the fluid	9
6.3.2 Range of velocities	9
6.3.3 Nature of the flow	10
6.3.4 Dimensional limitations	10
6.3.5 Influence of turbulence	10
6.4 Performance of measurements	10
6.4.1 Measurement of differential pressure	10
6.4.2 Differential pressure fluctuations	10
6.4.3 Determination of fluid density	11
6.5 Inspection and maintenance of the Pitot tube	11
7 Positioning of Pitot tube	11
8 Velocity computation	11
8.1 Verification of conditions for a measurement	11
8.2 Formulae for velocity computation	12

9	Determination of the discharge velocity by graphical integration of the velocity area	13
9.1	Circular cross-section	14
9.2	Rectangular cross-sections	15
10	Determination of the discharge velocity by numerical integration of the velocity area	17
10.1	Circular cross-sections	17
10.2	Rectangular cross-sections	19
11	Determination of the discharge velocity by arithmetic methods	19
11.1	“Log-linear” method	20
11.1.1	Circular cross-sections	20
11.1.2	Rectangular cross-sections	20
11.2	Log-Chebyshev method	22
11.2.1	Circular cross-sections	22
11.2.2	Rectangular cross-sections	22
12	Corrections of local velocity measurements	23
12.1	Correction for stem blockage	23
12.1.1	Case where the correction can be neglected	23
12.1.2	Estimation of the correction of local velocity measurement	23
12.1.3	Estimation of the overall correction of the flow-rate value (application to arithmetic methods)	25
12.2	Correction for transverse velocity gradient	25
12.2.1	Correction for measuring point position	26
12.2.2	Overall correction of flow rate	26
12.3	Correction for turbulence	27
12.4	Correction for head loss	28
13	Errors	28
13.1	Definition of the error	28
13.2	Errors in the estimation of the local velocity	28
13.2.1	Random errors	28
13.2.2	Systematic errors	29
13.3	Errors in the estimation of flow rate	30
13.3.1	Random errors	30
13.3.2	Systematic errors	30
13.4	Definition of the standard deviation	31
13.5	Definition of the tolerance	31
13.6	Calculation of standard deviation	32
13.6.1	Standard deviation on local velocity measurement	32
13.6.2	Standard deviation on flow-rate measurement	33
Annex A (normative)	Pitot tubes	34
Annex B (normative)	Correction to the measuring position of Pitot tubes used in a transverse velocity gradient	40
Annex C (normative)	Study concerning turbulence correction	42
Annex D (normative)	Damping of pressure gauges	45
Annex E (normative)	Measurements with a Pitot tube in a compressible fluid	47
Annex F (normative)	Determination of coefficient m for extrapolation near the wall	51
Annex G (informative)	Example of calculation of the uncertainty on the flow-rate measurement by means of Pitot tubes	52
Bibliography		55

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 30, *Measurement of fluid flow in closed conduits*, Subcommittee SC 5, *Velocity and mass methods*.

This third edition cancels and replaces the second edition (ISO 3966:2008), which has been technically revised.

The main changes compared to the previous edition are as follows:

- All the mathematical formulae have been numbered;
- The essential [Formula 4](#) has been corrected from $\Delta\rho/p$ to $\Delta p/p$;
- The related [Table 2](#) is corrected likewise;
- The last sentence in [8.2](#) “for selected values of g and the $\Delta\rho/p$” was corrected accordingly;
- In [11.2.2](#) in the 2nd paragraph ef is corrected by e or f .
- [Figure A.5](#) was changed editorially, the millimetre-grid has been removed.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Measurement of fluid flow in closed conduits — Velocity area method using Pitot static tubes

1 Scope

This document specifies a method for the determination in a closed conduit of the volume rate of flow of a regular flow

- a) of a fluid of substantially constant density or corresponding to a Mach number not exceeding 0,25,
- b) with substantially uniform stagnation temperature across the measuring cross-section,
- c) running full in the conduit, and
- d) under steady flow conditions.

In particular, it deals with the technology and maintenance of Pitot static tubes, with the calculation of local velocities from measured differential pressures and with the computation of the flow rate by velocity integration.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2186, *Fluid flow in closed conduits — Connections for pressure signal transmissions between primary and secondary elements*

[ISO 3966:2020](https://standards.iteh.ai/catalog/standards/iso/487c72f8-306a-4dd6-a734-c275e6578d39/iso-3966-2020)

3 Terms, definitions and symbols

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1.1

Pitot static tube

"Pitot tube"

tubular device consisting of a cylindrical head attached perpendicularly to a stem allowing measurement of a differential pressure from which the flow rate of the fluid in which it is inserted can be determined, and which is provided with static pressure tapping holes (drilled all around the circumference of the head at one or more cross-sections) and with a total pressure hole (facing the flow direction at the tip of the axially symmetrical nose of the head)

3.1.2

static pressure tapping

group of holes for the measurement of fluid static pressure