
**Acoustics — Methods for calculating
loudness —**

**Part 2:
Moore-Glasberg method**

Acoustique — Méthode de calcul d'isotonie —

Partie 2: Méthode Moore-Glasberg

Sample Document

get full document from standards.iteh.ai



Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 General	5
5 Specifications of signals	5
5.1 General	5
5.2 Complex tone	5
5.3 Noise consisting of bands of pink or white noise of defined width	5
5.4 Mixture of discrete sinusoidal components and bands of pink or white noise	6
5.5 Sound specified in terms of the sound pressure levels in 29 adjacent one-third-octave bands	6
6 Instrumentation	6
7 Description of the method	7
7.1 Introduction	7
7.2 Determination of sound spectrum at the tympanic membrane	7
7.2.1 General	7
7.2.2 Free field and diffuse field transfer functions for sound picked up by a single microphone	8
7.2.3 Earphones	8
7.2.4 Signal recorded at eardrum	8
7.2.5 Head and torso simulator	8
7.2.6 Interpolation and extrapolation	8
7.3 Determination of sound spectrum at the oval window	9
7.4 Transformation of sound spectrum into excitation pattern	10
7.5 Transformation of excitation pattern into specific loudness	13
7.5.1 Introduction	13
7.5.2 Reference excitation at the reference threshold of hearing	14
7.5.3 Gain of the cochlear amplifier for inputs with low sound pressure levels	14
7.5.4 Calculation of specific loudness from excitation when $E_{\text{THRQ}}/E_0 \leq E/E_0$	15
7.5.5 Calculation of specific loudness from excitation when $E_{\text{THRQ}}/E_0 > E/E_0$	15
7.5.6 Calculation of specific loudness from excitation when $E > 10^{10}$	15
8 Calculation of loudness and loudness level	16
8.1 Calculation of monaural and binaural loudness (diotic and dichotic stimuli)	16
8.2 Relationship between loudness level and loudness	17
8.3 Calculation of the reference threshold of hearing	18
9 Uncertainty of calculated loudness for stationary sounds	18
10 Data reporting	19
Annex A (informative) Comments regarding binaural loudness	20
Annex B (informative) Results for specific test signals	21
Annex C (informative) Software for the calculation of loudness	26
Bibliography	27

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html

This document was prepared by Technical Committee ISO/TC 43, *Acoustics*.

A list of all parts in the ISO 532- series, published under the general title *Acoustics — Methods for calculating loudness*, can be found on the ISO website.

Introduction

Loudness and loudness level are two perceptual attributes of sound describing absolute and relative sensations of sound strength perceived by a person under specific listening conditions. Due to inherent individual differences among people, both loudness and loudness level have the nature of statistical estimators characterized by their respective measures of central tendency and dispersion determined for a specific sample of the general population.

The object of the ISO 532- series is to specify calculation procedures based on physical properties of sound for estimating loudness and loudness level of sound as perceived by persons with otologically normal hearing under specific listening conditions. Each procedure seeks single numbers that can be used in many scientific and technical applications to estimate the perceived loudness and loudness level of sound without conducting separate human observer studies for each application. Because loudness is a perceived quantity, the perception of which may vary among people, any calculated loudness value represents only an estimate of the average loudness as perceived by a group of individuals with otologically normal hearing

ISO 532-1 and ISO 532-2 specify two different methods for calculating loudness which may yield different results for given sounds. Since no general preference for one or the other method can presently be stated, it is up to the user to select the method which appears most appropriate for the given situation. Some major features of each of the methods are described below to facilitate the choice.

This document is limited to calculation of loudness and loudness level of stationary sounds and the calculations are based on the spectral properties of a sound. This calculation method is based on Moore-Glasberg loudness calculation algorithms [14-17]. It starts by converting a specified signal spectrum into a series of sinusoidal components representing that spectrum. This series is then transformed into a specific loudness pattern by applying four consecutive transformations, each of which is directly related to physiological and psychological characteristics of the human hearing system. Loudness is calculated from the specific loudness pattern.

This document describes the calculation procedures leading to estimation of loudness and loudness level and provides an executable computer program and code. The software provided with this document is entirely informative and provided for the convenience of the user. Use of the provided software is not required for conformance with this document.

The Moore-Glasberg method is limited to stationary sounds and can be applied to tones, broadband noises and complex sounds with sharp line spectral components. The method in this document differs from those in ISO 532:1975. Method A of ISO 532:1975 (Stevens loudness[18]) was removed as this method was not often used and its predictions were not accurate for sounds with strong tonal components. The method described in this document also improves the precision of calculated loudness in the low frequency range and allows for calculation of loudness under conditions where the sound differs at the two ears. It has been shown that this method provides a good match to the contours of equal loudness level as defined in ISO 226:2003 and the reference threshold of hearing as defined in ISO 389-7:2005.

The Zwicker method in ISO 532-1 can be applied for stationary and arbitrary non-stationary sounds. The method for stationary sounds in ISO 532-1 differs slightly from the methods included in the previous ISO 532:1975, method B, by specifying corrections for low frequencies and by restricting the description of the approach to numerical instructions only, thus allowing a unique software description. For reasons of continuity, the method given in ISO 532-1 is in accordance with ISO 226:1987 instead of the later revised version, ISO 226:2003.

NOTE Equipment or machinery noise emissions/immissions can also be judged by other quantities defined in various International Standards (see e.g. ISO 1996-1, ISO 3740, ISO 9612 and ISO 11200).

Sample Document

get full document from standards.iteh.ai

Acoustics — Methods for calculating loudness —

Part 2: Moore-Glasberg method

1 Scope

This document specifies a method for estimating the loudness and loudness level of stationary sounds as perceived by otologically normal adult persons under specific listening conditions. It provides an algorithm for the calculation of monaural or binaural loudness for sounds recorded using a single microphone, using a head and torso simulator, or for sounds presented via earphones. The method is based on the Moore-Glasberg algorithm.

NOTE 1 Issues of binaural calculations are discussed in Annex A.

NOTE 2 Users who wish to study the details of the calculation method can review or implement the source code, which is entirely informative and provided with this document for the convenience of the user.

This method can be applied to tones, broadband noises and complex sounds with sharp line spectral components, for example transformer hum or fan noise.

NOTE 3 It has been shown (see Reference [15]) that this method provides a good match to the contours of equal loudness level as defined in ISO 226:2003 and the reference threshold of hearing as defined in ISO 389-7:2005.

The evaluation of the harmful effect of sound events is outside the scope of this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61260-1:2014, *Electroacoustics — Octave-band and fractional-octave-band filters — Part 1: Specifications*

IEC 61672-1:2013, *Electroacoustics — Sound level meters — Part 1: Specifications*

IEC/TS 60318-7, *Electroacoustics — Simulators of human head and ear — Part 7: Head and torso simulator for the measurement of hearing aids*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <http://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1 sound pressure level

L_p
ten times the logarithm to the base 10 of the ratio of the square of the sound pressure, p , to the square of a reference value, p_0 , expressed in decibels

$$L_p = 10 \lg \frac{p^2}{p_0^2} \text{ dB}$$

where the reference value, p_0 , in gases is 20 μPa

Note 1 to entry: Because of practical limitations of the measuring instruments, p^2 is always understood to denote the square of a frequency-weighted, frequency-band-limited or time-weighted sound pressure. If specific frequency and time weightings as specified in IEC 61672-1 and/or specific *frequency bands* (3.2) are applied, this should be indicated by appropriate subscripts, for example $L_{p,AS}$ denotes the A-weighted sound pressure level with time weighting S (slow). Frequency weightings such as A-weighting should not be used when specifying sound pressure levels for the purpose of *loudness* (3.17) calculation using the current procedure.

Note 2 to entry: This definition is technically in accordance with ISO 80000-8:2007, 8.

3.2 frequency band

continuous set of frequencies lying between two specified limiting frequencies

Note 1 to entry: A frequency band is characterized by two values that define its position in the frequency spectrum, for instance its lower and upper cut-off frequencies.

Note 2 to entry: Frequency is expressed in Hz.

[SOURCE: IEC 60050-702:1992, 702-01-02]

3.3 filter

device or mathematical operation that, when applied to a complex signal, passes energy of signal components of certain frequencies while substantially attenuating energy of signal components of all other frequencies

3.4 cut-off frequency

lowest (f_l) or highest (f_h) frequency beyond which the response of the *filter* (3.3) to a sinusoidal signal does not exceed -3 dB relative to the maximum response measured between (f_l) and (f_h)

3.5 one-third-octave band

frequency band (3.2) with the centre frequency f_T and the width of one-third of an octave

Note 1 to entry: The subscript T instead of c is used to specify the centre frequency in the special case of a one-third-octave band.

Note 2 to entry: Width of one-third of an octave as specified in IEC 61260-1.

3.6 band-reject filter

filter (3.3) that rejects signal energy within a certain *frequency band* (3.2) and passes most of the signal energy outside of this frequency band

Note 1 to entry: A narrow band-reject filter is also called a notch filter.

3.7 band level

L_{pb}
sound pressure level (3.1) of sound contained within a restricted frequency band (b)

3.8**one-third-octave-band level** L_T

sound pressure level (3.1) of sound contained within a *frequency band* (3.2) with the width of one-third of an octave

3.9**sound spectrum**

representation of the magnitudes (and sometimes of the phases) of the components of a complex sound as a function of frequency

3.10**spectrum density level****spectrum level**

level of the limit, as the width of the *frequency band* (3.2) approaches zero, of the quotient of a specified quantity distributed within a frequency band, by the width of the band, expressed in decibels

Note 1 to entry: The words “spectrum level” should be preceded by a descriptive modifier describing the measured quantity.

Note 2 to entry: For illustration, the sound pressure spectrum level L_{ps} at the midband frequency is obtained practically by

$$L_{pbs} = 10 \lg \left[\left(p_b^2 / \Delta f \right) / \left(p_0^2 / \Delta_0 f \right) \right] \text{dB}$$

where p_b^2 is the time-mean-square sound pressure measured through a *filter* (3.3) system, p_0 the reference sound pressure, Δf the bandwidth of the filter system, and $\Delta_0 f$ the reference bandwidth of 1 Hz. For computational purposes, with L_{pb} for the band *sound pressure level* (3.1) observed through the filter, the above relation becomes

$$L_{pbs} = L_{pb} - 10 \lg [\Delta f / \Delta_0 f] \text{dB}$$

3.11**auditory filter**

filter (3.3) within the human cochlea describing the frequency resolution of the auditory system, with characteristics that are usually estimated from the results of masking experiments

3.12**otologically normal person**

person in a normal state of health who is free from all signs or symptoms of ear disease and from obstructing wax in the ear canals, and who has no history of undue exposure to noise, exposure to potentially ototoxic drugs or familial hearing loss

[SOURCE: ISO 226:2003, 3.1]

3.13**equivalent rectangular bandwidth of the auditory filter for otologically normal persons** ERB_n

auditory filter (3.11) bandwidth determined by measuring tone detection thresholds in wideband noise passed through band-reject (notch) filters of various bandwidths

Note 1 to entry: The subscript n indicates that the value applies for persons with otologically normal hearing.

Note 2 to entry: The multi-letter abbreviated term presented in italics and with a subscript is used here instead of a symbol to maintain an established notation and to avoid confusion.

Note 3 to entry: Bandwidth is measured in Hertz (Hz).