
Calculation of load capacity of spur and helical gears —

Part 1: Basic principles, introduction and general influence factors

*Calcul de la capacité de charge des engrenages cylindriques à
dentures droite et hélicoïdale —*

*Partie 1: Principes de base, introduction et facteurs généraux
d'influence*

Document Preview

ISO 6336-1:2019

<https://standards.iteh.ai/catalog/standards/iso/e5f28cea-4bec-44ff-b855-73123e9fb8ac/iso-6336-1-2019>



iTeh Standards
(<https://standards.itih.ai>)
Document Preview

ISO 6336-1:2019

<https://standards.itih.ai/catalog/standards/iso/e5f28eea-4bec-44ff-b855-73123e9fb8ac/iso-6336-1-2019>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	2
3 Terms, definitions, symbols and abbreviated terms	2
3.1 Terms and definitions	2
3.2 Symbols and abbreviated terms	2
4 Basic principles	11
4.1 Application	11
4.1.1 Surface durability (pitting)	11
4.1.2 Tooth bending strength	11
4.1.3 Tooth flank fracture	12
4.1.4 Strength and quality of materials	12
4.1.5 Service life under variable load	12
4.1.6 Scuffing	12
4.1.7 Wear	12
4.1.8 Micropitting	12
4.1.9 Plastic-yielding	12
4.1.10 Specific applications	12
4.1.11 Safety factors	13
4.1.12 Testing	15
4.1.13 Manufacturing tolerances	15
4.1.14 Implied accuracy	15
4.1.15 Other considerations	15
4.1.16 Influence factors	16
4.1.17 Numerical formulae	18
4.1.18 Succession of factors in the course of calculation	18
4.1.19 Determination of allowable values of gear deviations	18
4.2 Tangential load, torque and power	18
4.2.1 General	18
4.2.2 Nominal tangential load, nominal torque and nominal power	19
4.2.3 Equivalent tangential load, equivalent torque and equivalent power	19
4.2.4 Maximum tangential load, maximum torque and maximal power	19
5 Application factor, K_A	19
5.1 General	19
5.2 Method A — Factor K_{A-A}	20
5.2.1 Factor K_{A-A}	20
5.2.2 Factor K_{HA-A} for pitting along ISO 6336-2	20
5.2.3 Factor K_{FA-A} for tooth root breakage along ISO 6336-3	20
5.2.4 Factor K_{FFA-A} for tooth flank fracture along ISO/TS 6336-4	20
5.2.5 Factor $K_{\theta A-A}$ for scuffing along ISO/TS 6336-20/ISO/TS 6336-21	21
5.2.6 Factor $K_{\lambda A-A}$ for micropitting along ISO/TS 6336-22	21
5.3 Method B — Factor K_{A-B}	21
5.3.1 General	21
5.3.2 Guide values for application factor, K_{A-B}	21
6 Internal dynamic factor, K_v	24
6.1 General	24
6.2 Parameters affecting internal dynamic load and calculations	24
6.2.1 Design	24
6.2.2 Manufacturing	24
6.2.3 Transmission perturbation	25
6.2.4 Dynamic response	25

6.2.5	Resonances	25
6.2.6	Application of internal dynamic factor for low loaded gears	26
6.3	Principles and assumptions	26
6.4	Methods for determination of dynamic factor	27
6.4.1	Method A — Factor K_{v-A}	27
6.4.2	Method B — Factor K_{v-B}	27
6.4.3	Method C — Factor K_{v-C}	27
6.5	Determination of dynamic factor using Method B: K_{v-B}	28
6.5.1	General	28
6.5.2	Running speed ranges	28
6.5.3	Determination of resonance running speed (main resonance) of a gear pair	29
6.5.4	Dynamic factor in subcritical range ($N \leq N_S$)	31
6.5.5	Dynamic factor in main resonance range ($N_S < N \leq 1,15$)	34
6.5.6	Dynamic factor in supercritical range ($N \geq 1,5$)	34
6.5.7	Dynamic factor in intermediate range ($1,15 < N < 1,5$)	34
6.5.8	Resonance speed determination for specific gear designs	35
6.5.9	Calculation of reduced mass of gear pair with external teeth	37
6.6	Determination of dynamic factor using Method C: K_{v-C}	38
6.6.1	General	38
6.6.2	Graphical values of dynamic factor using Method C	39
6.6.3	Determination by calculation of dynamic factor using Method C	42
7	Face load factors, $K_{H\beta}$ and $K_{F\beta}$	43
7.1	Gear tooth load distribution	43
7.2	General principles for determination of face load factors, $K_{H\beta}$ and $K_{F\beta}$	43
7.2.1	General	43
7.2.2	Face load factor for contact stress, $K_{H\beta}$	44
7.2.3	Face load factor for tooth root stress, $K_{F\beta}$	44
7.3	Methods for determination of face load factor — Principles, assumptions	44
7.3.1	General	44
7.3.2	Method A — Factors $K_{H\beta-A}$ and $K_{F\beta-A}$	44
7.3.3	Method B — Factors $K_{H\beta-B}$ and $K_{F\beta-B}$	45
7.3.4	Method C — Factors $K_{H\beta-C}$ and $K_{F\beta-C}$	45
7.4	Determination of face load factor using Method B: $K_{H\beta-B}$	45
7.4.1	Number of calculation points	45
7.4.2	Definition of $K_{H\beta}$	45
7.4.3	Stiffness and elastic deformations	45
7.4.4	Static displacements	49
7.4.5	Assumptions	49
7.4.6	Computer program output	49
7.5	Determination of face load factor using Method C: $K_{H\beta-C}$	49
7.5.1	General	49
7.5.2	Effective equivalent misalignment, $F_{\beta y}$	51
7.5.3	Running-in allowance, y_{β} , and running-in factor, χ_{β}	51
7.5.4	Mesh misalignment, f_{ma}	61
7.5.5	Component of mesh misalignment caused by case deformation, f_{ca}	63
7.5.6	Component of mesh misalignment caused by shaft displacement, f_{be}	63
7.6	Determination of face load factor for tooth root stress using Method B or C: $K_{F\beta}$	64
8	Transverse load factors $K_{H\alpha}$ and $K_{F\alpha}$	65
8.1	Transverse load distribution	65
8.2	Determination methods for transverse load factors — Principles and assumptions	65
8.2.1	General	65
8.2.2	Method A — Factors $K_{H\alpha-A}$ and $K_{F\alpha-A}$	65
8.2.3	Method B — Factors $K_{H\alpha-B}$ and $K_{F\alpha-B}$	66
8.3	Determination of transverse load factors using Method B — $K_{H\alpha-B}$ and $K_{F\alpha-B}$	66
8.3.1	General	66
8.3.2	Determination of transverse load factor by calculation	66
8.3.3	Transverse load factors from graphs	67

8.3.4	Limiting conditions for $K_{H\alpha}$	67
8.3.5	Limiting conditions for $K_{F\alpha}$	67
8.3.6	Running-in allowance, y_α	68
9	Tooth stiffness parameters, c' and c_γ	71
9.1	Stiffness influences	71
9.2	Determination methods for tooth stiffness parameters — Principles and assumptions	71
9.2.1	General	71
9.2.2	Method A — Tooth stiffness parameters c'_A and $c_{\gamma-A}$	72
9.2.3	Method B — Tooth stiffness parameters c'_B and $c_{\gamma-B}$	72
9.3	Determination of tooth stiffness parameters, c' and c_γ according to Method B	72
9.3.1	General	72
9.3.2	Single stiffness, c'	73
9.3.3	Mesh stiffness, c_γ	77
10	Parameter of Hertzian contact	77
10.1	Local radius of relative curvature	77
10.2	Reduced modulus of elasticity, E_r	78
10.3	Local Hertzian contact stress, $p_{\text{dyn,CP}}$	78
10.3.1	Method A	78
10.3.2	Method B	79
10.4	Half of the Hertzian contact width, b_H	80
10.5	Load distribution along the path of contact	80
10.5.1	Definition of contact points, CP, on the path of contact	80
10.5.2	Load sharing factor, X_{CP}	82
10.6	Sum of tangential velocity, $v_{\Sigma, \text{CP}}$	90
11	Lubricant parameters at given temperature	91
11.1	General	91
11.2	Kinematic viscosity at a given temperature, ν_θ	91
11.3	Density of the lubricant at a given temperature θ , ρ_θ	92
Annex A (normative)	Additional methods for determination of f_{sh} and f_{ma}	93
Annex B (informative)	Guide values for crowning and end relief of teeth of cylindrical gears	96
Annex C (informative)	Guide values for $K_{H\beta-C}$ for crowned teeth of cylindrical gears	99
Annex D (informative)	Derivations and explanatory notes	102
Annex E (informative)	Analytical determination of load distribution	106
Annex F (informative)	General symbols used for calculation of load capacity of spur and helical gears	128
Bibliography		133

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 60, *Gears*, Subcommittee SC 2, *Gear capacity calculation*.

This third edition cancels and replaces the second edition (ISO 6336-1:2006), which has been technically revised. It also incorporates the Technical Corrigendum ISO 6336-1:2006/Cor.1:2008.

The main changes compared to the previous edition are as follows:

- incorporation of ISO/TS 6336-4, ISO/TS 6336-20, ISO/TS 6336-21 and ISO/TS 6336-22 into [Clause 4](#) (failure mode);
- update of application factors in [Clause 5](#);
- integration of [Clause 10](#) "Parameters of Hertzian contact";
- integration of [Clause 11](#) "Lubricant parameters at given temperature".

A list of all parts in the ISO 6336 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

ISO 6336 (all parts) consists of International Standards, Technical Specifications (TS) and Technical Reports (TR) under the general title *Calculation of load capacity of spur and helical gears* (see [Table 1](#)).

- International Standards contain calculation methods that are based on widely accepted practices and have been validated.
- Technical Specifications (TS) contain calculation methods that are still subject to further development.
- Technical Reports (TR) contain data that is informative, such as example calculations.

The procedures specified in parts 1 to 19 of the ISO 6336 series cover fatigue analyses for gear rating. The procedures described in parts 20 to 29 of the ISO 6336 series are predominantly related to the tribological behavior of the lubricated flank surface contact. Parts 30 to 39 of the ISO 6336 series include example calculations. The ISO 6336 series allows the addition of new parts under appropriate numbers to reflect knowledge gained in the future.

Requesting standardized calculations according to the ISO 6336 series without referring to specific parts requires the use of only those parts that are currently designated as International Standards (see [Table 1](#) for listing). When requesting further calculations, the relevant part or parts of the ISO 6336 series need to be specified. Use of a Technical Specification as acceptance criteria for a specific design need to be agreed in advance between the manufacturer and the purchaser.

Table 1 — Parts of the ISO 6336 series (status as of DATE OF PUBLICATION)

Calculation of load capacity of spur and helical gears	International Standard	Technical Specification	Technical Report
<i>Part 1: Basic principles, introduction and general influence factors</i>	X		
<i>Part 2: Calculation of surface durability (pitting)</i>	X		
<i>Part 3: Calculation of tooth bending strength</i>	X		
<i>Part 4: Calculation of tooth flank fracture load capacity</i>		X	
<i>Part 5: Strength and quality of materials</i>	X		
<i>Part 6: Calculation of service life under variable load</i>	X		
<i>Part 20: Calculation of scuffing load capacity (also applicable to bevel and hypoid gears) — Flash temperature method</i> (replaces: ISO/TR 13989-1)		X	
<i>Part 21: Calculation of scuffing load capacity (also applicable to bevel and hypoid gears) — Integral temperature method</i> (replaces: ISO/TR 13989-2)		X	
<i>Part 22: Calculation of micropitting load capacity</i> (replaces: ISO/TR 15144-1)		X	
<i>Part 30: Calculation examples for the application of ISO 6336 parts 1,2,3,5</i>			X
<i>Part 31: Calculation examples of micropitting load capacity</i> (replaces: ISO/TR 15144-2)			X

This document and the other parts of the ISO 6336 series provide a coherent system of procedures for the calculation of the load capacity of cylindrical involute gears with external or internal teeth. The ISO 6336 series is designed to facilitate the application of future knowledge and developments, also the exchange of information gained from experience.