
Calculation of load capacity of spur and helical gears —

Part 2: Calculation of surface durability (pitting)

*Calcul de la capacité de charge des engrenages cylindriques à
dentures droite et hélicoïdale —*

*Partie 2: Calcul de la tenue en fatigue à la pression de contact
(écaillage)*

Document Preview

ISO 6336-2:2019

<https://standards.iteh.ai/catalog/standards/iso/0050664a-5825-4ed5-82c8-a39035e0b0a0/iso-6336-2-2019>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 6336-2:2019

<https://standards.iteh.ai/catalog/standards/iso/0050664a-5825-4ed5-82c8-a39035e0b0a0/iso-6336-2-2019>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviated terms	2
3.1 Terms and definitions	2
3.2 Symbols and abbreviated terms	2
4 Pitting damage and safety factors	6
5 Basic formulae	7
5.1 General	7
5.2 Safety factor for surface durability (against pitting), S_H	8
5.3 Contact stress, σ_H	8
5.4 Permissible contact stress, σ_{HP}	9
5.4.1 General	9
5.4.2 Determination of permissible contact stress, σ_{HP} — Principles, assumptions and application	10
5.4.3 Permissible contact stress, σ_{HP} : Method B	10
5.4.4 Permissible contact stress for limited and long life: Method B	11
6 Zone factor, Z_H, and contact factors, Z_B and Z_D	13
6.1 General	13
6.2 Zone factor, Z_H	14
6.2.1 General	14
6.2.2 Graphical values	14
6.2.3 Determination by calculation	14
6.3 Contact factors, Z_B and Z_D , for $\varepsilon_\alpha \leq 2$	14
6.4 Contact factors, Z_B and Z_D , for $\varepsilon_\alpha > 2$	17
7 Elasticity factor, Z_E	17
8 Contact ratio factor, Z_ε	18
8.1 General	18
8.2 Determination of contact ratio factor, Z_ε	18
8.2.1 Graphical values	18
8.2.2 Determination by calculation	19
8.3 Calculation of transverse contact ratio, ε_α , and overlap ratio, ε_β	20
8.3.1 Transverse contact ratio, ε_α	20
8.3.2 Overlap ratio, ε_β	20
9 Helix angle factor, Z_β	21
10 Strength for contact stress	21
10.1 General	21
10.2 Allowable stress numbers (contact), $\sigma_{H \text{ lim}}$: Method B	21
10.3 Allowable stress number values: Method B	22
11 Life factor, Z_{NT} (for flanks)	22
11.1 General	22
11.2 Life factor, Z_{NT} : Method A	22
11.3 Life factor, Z_{NT} : Method B	22
12 Influence of lubricant film, factors Z_L, Z_v and Z_R	24
12.1 General	24
12.2 Influence of lubricant film: Method A	24
12.3 Influence of lubricant film, factors Z_L , Z_v and Z_R : Method B	24
12.3.1 General	24

12.3.2	Factors Z_L , Z_v and Z_R for reference stress.....	25
12.3.3	Factors Z_L , Z_v and Z_R for static stress.....	30
13	Work hardening factor, Z_W	30
13.1	General.....	30
13.2	Work hardening factor, Z_W : Method A.....	30
13.3	Work hardening factor, Z_W : Method B.....	31
13.3.1	Surface-hardened steel pinion with through-hardened steel gear	31
13.3.2	Through-hardened steel pinion with through-hardened steel gear	33
13.3.3	Surface-hardened steel pinion with ductile iron gear	34
14	Size factor, Z_X	36
	Bibliography	37

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

ISO 6336-2:2019

<https://standards.itih.ai/catalog/standards/iso/0050664a-5825-4ed5-82c8-a39035e0b0a0/iso-6336-2-2019>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 60, *Gears*, Subcommittee SC 2, *Gear capacity calculation*.

This third edition cancels and replaces the second edition (ISO 6336-2:2006), which has been technically revised. It also incorporates the Technical Corrigendum ISO 6336-2:2006/Cor.1:2008.

The main changes compared to the previous edition are as follows:

- modification of the helix angle factor Z_{β} ;
- integration of [13.3.3](#) "Surface-hardened steel pinion with ductile iron gear".

A list of all parts in the ISO 6336 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

This corrected version of ISO 6336-2:2019 incorporates the following corrections:

- the decimal sign in [Formula \(43\)](#) has been removed;
- the equals signs have been added in [Formulae \(54\)](#) and [\(55\)](#).

Introduction

ISO 6336 (all parts) consists of International Standards, Technical Specifications (TS) and Technical Reports (TR) under the general title *Calculation of load capacity of spur and helical gears* (see [Table 1](#)).

- International Standards contain calculation methods that are based on widely accepted practices and have been validated.
- Technical Specifications (TS) contain calculation methods that are still subject to further development.
- Technical Reports (TR) contain data that is informative, such as example calculations.

The procedures specified in parts 1 to 19 of the ISO 6336 series cover fatigue analyses for gear rating. The procedures described in parts 20 to 29 of the ISO 6336 series are predominantly related to the tribological behavior of the lubricated flank surface contact. Parts 30 to 39 of the ISO 6336 series include example calculations. The ISO 6336 series allows the addition of new parts under appropriate numbers to reflect knowledge gained in the future.

Requesting calculation according to the ISO 6336 series without referring to specific parts requires the use of only those parts that are designated as International Standards (see [Table 1](#) for listing). If Technical Specifications (TS) are requested as part of the load capacity calculation they need to be specified. Use of a Technical Specification as acceptance criteria for a specific design is subject to commercial agreement.

Table 1 — Parts of the ISO 6336 series (status as of DATE OF PUBLICATION)

Calculation of load capacity of spur and helical gears	International Standard	Technical Specification	Technical Report
<i>Part 1: Basic principles, introduction and general influence factors</i>	X		
<i>Part 2: Calculation of surface durability (pitting)</i>	X		
<i>Part 3: Calculation of tooth bending strength</i>	X		
<i>Part 4: Calculation of tooth flank fracture load capacity</i>		X	
<i>Part 5: Strength and quality of materials</i>	X		
<i>Part 6: Calculation of service life under variable load</i>	X		
<i>Part 20: Calculation of scuffing load capacity (also applicable to bevel and hypoid gears) — Flash temperature method</i> (replaces: ISO/TR 13989-1)		X	
<i>Part 21: Calculation of scuffing load capacity (also applicable to bevel and hypoid gears) — Integral temperature method</i> (replaces: ISO/TR 13989-2)		X	
<i>Part 22: Calculation of micropitting load capacity</i> (replaces: ISO/TR 15144-1)		X	
<i>Part 30: Calculation examples for the application of ISO 6336 parts 1,2,3,5</i>			X
<i>Part 31: Calculation examples of micropitting load capacity</i> (replaces: ISO/TR 15144-2)			X

Hertzian pressure, which serves as a basis for the calculation of the contact stress, is the basic principle used in this document for the assessment of the surface durability of cylindrical gears. It is a significant indicator of the stress generated during tooth flank engagement. However, it is not the sole cause of pitting, and nor are the corresponding subsurface shear stresses. There are other contributory influences, for example, coefficient of friction, direction and magnitude of sliding and the influence of lubricant on the distribution of pressure. Development has not yet advanced to the stage of directly