



**International
Standard**

ISO 6940

**Textile fabrics — Burning behaviour
— Determination of ease of ignition
of vertically oriented specimens**

*Étoffes — Comportement au feu — Détermination de la facilité
d'allumage d'éprouvettes orientées verticalement*

**Third edition
2026-05**

**Corrected version
2026-06**

Sample Document

get full document from standards.iteh.ai

Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO 2026

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	1
5 Apparatus	2
5.6 Timing devices	2
6 Cautionary measure	4
6.1 Construction of testing equipment	4
6.2 Location of test apparatus	4
6.3 Health and safety of test operators	4
7 Sampling	5
7.1 Number of test specimens	5
7.2 Test specimen holder pin location marks	5
7.3 Test specimen size	5
8 Conditioning and testing atmosphere	5
8.1 Conditioning	5
8.2 Testing atmosphere	5
9 Setting up the apparatus	6
9.1 Procedure A (Surface ignition)	6
9.1.1 Mounting of the test specimen	6
9.1.2 Operating position of the burner	6
9.1.3 Flame adjustment — Horizontal reach	6
9.1.4 Flame position	6
9.2 Procedure B (Bottom edge ignition)	6
9.2.1 Mounting of the test specimen	6
9.2.2 Operating position of the burner	6
9.2.3 Flame adjustment — vertical flame height	7
9.2.4 Flame position	7
10 Test procedure	8
10.1 Surface ignition	8
10.2 Bottom edge ignition	9
11 Calculation of the mean ignition time	10
12 Precision	10
13 Test report	10
Annex A (normative) Description and construction of the burner	12
Annex B (informative) Calculation of mean ignition time — Work example	13
Annex C (informative) Experimental techniques	14
Bibliography	15

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 38, *Textiles*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 248, *Textiles and textile products*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This third edition cancels and replaces the second edition (ISO 6940:2004), which has been technically revised.

The main changes are as follows:

- [Figure 1](#) b) has been corrected with the proper angular dimension line and the shape of the tip of the gas jet;
- [Figure 3](#) a) and b) have been revised to show the test specimen clear;
- this revision aims to clarify without any structural changes.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

This corrected version of ISO 6940:2026 incorporates the following correction:

- in [9.1.4](#), incorrect reference to [Figure 3 d\)](#) has been corrected to [Figure 3 a\)](#).

Introduction

This method is one of two closely related methods of test for the inflammability of textiles. It determines the ease of ignition as defined in ISO 4880 [1]. The other method measures flame spread time ISO 6941 [2].

The method specified in this document assesses the properties of textile fabrics in response to flame contact under controlled conditions. There is a possibility that results do not apply in situations where there is restricted air supply or exposure to large sources of intense heat.

The influence of seams on the behaviour of textile fabrics can be determined by this method, the seam being positioned within the test specimen to be subjected to the test flame. Whenever practicable, trimmings are tested as part of the textile fabric assembly on which they are, or will be, used.

Sample Document

get full document from standards.iteh.ai

Sample Document

get full document from standards.iteh.ai

Textile fabrics — Burning behaviour — Determination of ease of ignition of vertically oriented specimens

1 Scope

This document specifies a method for the measurement of ease of ignition of vertically oriented textile fabrics and industrial products in the form of single or multi-component textile fabrics (coated, quilted, multilayered, sandwich constructions, and similar combinations), when subjected to a small, defined flame.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4880, *Burning behaviour of textiles and textile products — Vocabulary*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4880 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

flame application time

time for which the *ignition* (3.3) flame is applied to the test specimen

3.2

afterflame time

length of time for which a material continues to flame under specified test conditions, after the *ignition* (3.3) source has been removed

Note 1 to entry: Afterflame time is measured to the nearest second and afterflame times of less than 1,0 s is recorded as zero.

3.3

ignition

initiation of combustion

3.4

sustained combustion

flaming of the test specimen which gives an *afterflame time* (3.2) of 5 s or more or which reaches the top or vertical edges in less than 5 s

4 Principle

A defined flame from a specified burner is applied to the surface or bottom edge of test specimens which are vertically oriented.