

## International **Standard**

**ISO 7856** 

Intelligent transport systems — Remote support for low speed automated driving systems (RS-LSADS) — Performance requirements, system requirements and performance test procedures

Systèmes de transport intelligents — Téléassistance pour les systèmes de conduite automatisée à basse vitesse (RS-LSADS) — Exigences de performance, exigences du système et procédures d'essai de performance

https://standards.iteh.ai/catalog/standards/iso/9dcb26d4-ac3b-4423-b666-aec19ec03d6c/iso-7856-2025

First edition 2025-06

# iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 7856:2025

https://standards.iteh.ai/catalog/standards/iso/9dcb26d4-ac3b-4423-b666-aec19ec03d6c/iso-7856-2025



#### COPYRIGHT PROTECTED DOCUMENT

© ISO 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Coı	<b>Contents</b> Pag						
Fore	word			v			
Intr	oductio	n		vi			
1	Scop	e		1			
2	-	Normative references					
3	Terms and definitions						
4	Symbols and abbreviated terms 4.1 Symbols						
	4.2		viated terms				
5	RS-I	SADS architecture					
	Functions of RS-LSADS						
6	6.1	General General					
	6.2		te monitoring				
	6.3		te assistance				
	6.4	Remo	te driving	6			
7	RS-LSADS functional scenarios						
	7.1	Remo	te support scenarios	7			
		7.1.1	Scenario 1: Re-starting after stopping at the bus bay	7			
		7.1.2	Scenario 2: Entering the unsignalized intersection	8			
		7.1.3 7.1.4	Scenario 3: Entering the signalized intersection (signal information only) Scenario 4: Entering the signalized intersection (signal information and both	9			
		7.1.1	lateral directions check)	9			
		7.1.5	Scenario 5: Bypassing obstacles that block the vehicle path	10			
		7.1.6	Scenario 6: Out of ODD due to environmental conditions	11			
8	System requirements 8.1 General						
		Gener	al Document 1 1 C vic v	12			
	8.2		ADS state transition diagram				
		8.2.1	State functional descriptions				
htt	ps://star		State transition descriptions				
9		Communication performance for remote support					
	9.1 9.2		al cy in remote support				
	9.3		o-end information latency				
	9.4		nation update rate				
	9.5 Distance error due to latency						
	9.6		nunication messages for remote support				
		9.6.1 9.6.2	Vehicle dataLSADS data				
		9.6.2	Driving environment data				
		9.6.4	Driving environment audio and video information				
		9.6.5	Passenger status onboard audio and video information	20			
		9.6.6	Remote assistance data				
		9.6.7	Remote driving control data				
		9.6.8 9.6.9	Infrastructure sensors data  Infrastructure audio and video information				
10	RS-LSADS performance requirements						
	10.1		te monitoring performanceEnd-to-end communication requirement during remote assistance standby or	21			
		10.1.1	remote driving standby	21			
	10.2		te assistance performance	21			
		10.2.1	Monitoring data for remote assistant	21			
		10.2.2	Roles of remote assistant	21			

		10.2.3	Remote assistant response to RFI	22		
		10.2.4	Remote assistance HMI, and video field of view and audio	23		
			End-to-end communication requirements during remote assistance			
		10.2.6	Data storage requirements for remote assistance	23		
	10.3		e driving performance			
			Monitoring data for remote driver			
			Remote driving response to RFD			
			Remote driving HMI, video field of view and audio			
			End-to-end communication requirements during remote driving			
			Limitations of remote driving			
			Alert and warning in remote driving			
		10.3.7	Data storage requirements for remote driving	25		
11	Scena	ario evaluation test procedures				
	11.1		1			
	11.2	Test co	nditions	26		
		11.2.1	Subject vehicle conditions	26		
		11.2.2	Target vehicle or objects conditions	26		
		11.2.3	Environmental conditions	26		
		11.2.4	End-to-end communication setup for scenario tests	26		
	11.3	Test pr	ocedures	27		
		11.3.1	General	27		
		11.3.2	Tests for remote assistance	27		
		11.3.3	Tests for Remote driving	38		
Annex A (informative) An Example of RS-LSADS Implementation						
Annex B (informative) An example of the interaction between the control centre and the vehicle for LSADS equipped vehicle mobility service						
Annex			e) Examples of remote support required scenarios and specific operations	49		
Pihliography				<b>57</b>		

#### ISO 7856-2025

https://standards.iteh.ai/catalog/standards/iso/9dcb26d4-ac3b-4423-b666-aec19ec03d6c/iso-7856-2025

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="https://www.iso.org/directives">www.iso.org/directives</a>).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <a href="https://www.iso.org/patents">www.iso.org/patents</a>. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by Technical Committee ISO/TC 204, *Intelligent transport systems*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

ISO 7856:2025

https://standards.iteh.ai/catalog/standards/iso/9dcb26d4-ac3b-4423-b666-aec19ec03d6c/iso-7856-2025

#### Introduction

For the sustainable operation of mobility services using automated driving systems (ADS), it can be necessary to provide additional support for the functioning of the ADS in order to enable mobility services to continue beyond the constraints of the operational design domain (ODD). Such additional support can include human remote support, i.e. actions by humans outside the vehicle. The low speed of low speed automated driving systems (LSADS) equipped vehicles simplifies the provision of remote support.

In this document, remote support is defined as a combination of remote assistance and remote driving.

Currently, individual development and demonstration projects for remote support of LSADS are implemented in several regions and countries, including UK, US, CA, DE, FR, AU, KR, and JP, amongst others. One example of such an implementation is given in <u>Annex A</u>.

This document indicates the technical requirements of remote support for LSADS (RS-LSADS) and is intended to provide a common basis for RS-LSADS development.

ISO/SAE PAS 22736 (SAE J3016) defines remote assistance and remote driving. In addition, in ISO 22737 external entity input is described. This document is intended to complement ISO 22737 by defining scenarios and requirements for remote assistance and remote driving.

# iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 7856:2025

https://standards.iteh.ai/catalog/standards/iso/9dcb26d4-ac3b-4423-b666-aec19ec03d6c/iso-7856-2025

# Intelligent transport systems — Remote support for low speed automated driving systems (RS-LSADS) — Performance requirements, system requirements and performance test procedures

#### 1 Scope

This document describes remote support provided to LSADS operated at Level 4 automation on predefined routes by a remotely located human in order to facilitate safe trip continuation. "Remote support" refers to the provision of information, or temporary performance of the dynamic driving task (DDT), and remote monitoring required for these functions.

This document is applicable to RS-LSADS in vehicles that provide passenger transport or logistics services on predefined routes.

This document specifies:

- the terms and definitions related to RS-LSADS and the system architecture of RS-LSADS;
- functions of RS-LSADS, which are: remote monitoring, remote assistance and remote driving that is operated under very limited conditions, and conditions under which they need to be activated;
- the performance requirements, system requirements and performance test procedures of RS-LSADS;
- the data to be communicated between vehicles and the remote support facility (but not protocols or other aspects of communication system).

This document is applicable to remote support of operational and tactical functions during continuous operations, but does not apply to strategic functions or to RS-LSADS daily startup or shutdown.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/SAE PAS 22736, Taxonomy and definitions for terms related to driving automation systems for on-road motor vehicles

ISO 22737, Intelligent transport systems — Low-speed automated driving (LSAD) systems for predefined routes — Performance requirements, system requirements and performance test procedures

ISO/SAE 21434, Road vehicles — Cybersecurity engineering

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/SAE PAS 22736, ISO 22737 and the followings apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>