
**Belt drives — Electrical conductivity of
antistatic endless synchronous belts
— Characteristics and test method**

*Transmissions par courroies — Conductibilité électrique des
courroies synchrones sans fin, anti-électrostatiques — Spécification
et méthode d'essai*

Sample Document

get full document from standards.iteh.ai



Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Electrical resistance — specification	1
3.1 General	1
3.2 Resistance value	2
3.3 Minimum value of electrical resistance	2
4 Selection and preparation of belts for test	2
4.1 Laboratory test	2
4.2 Production test	2
5 Test method	3
5.1 Apparatus — insulation tester	3
5.2 Electrodes and contacts for laboratory and production tests	3
5.3 Test procedures	3
5.3.1 Laboratory test	3
5.3.2 Production test	3
5.3.3 Test timing	3
5.3.4 Interpretation of results	3
Annex A (informative) Electrical conductive coating	5
Bibliography	6

Sample Document

get full document from standards.iteh.ai

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 41, *Pulleys and belts (including veebelts)*, Subcommittee SC 4, *Synchronous belt drives*.

This second edition cancels and replaces the first edition (ISO 9563:1990), which has been technically revised.

Belt drives — Electrical conductivity of antistatic endless synchronous belts — Characteristics and test method

1 Scope

This International Standard specifies the maximum and minimum electrical resistance of antistatic endless and open ended synchronous belts. This International Standard provides guidelines to allow testing of synchronous belts to prove their static conductive (dissipative) properties as well as a corresponding production control test method.

The application of this International Standard is limited to new belts intended to be used in an explosive atmosphere or in situations where there is a fire risk. The test is intended to ensure that the belt is sufficiently conductive to dissipate charges of electricity which may form on it in service.

In the case of a production control test, the decision is left to national standards or agreement between interested parties as to whether the test shall be carried out on each belt in a batch or on only a percentage of belts in a batch.

For each proof test, the belt manufacturer shall determine which type of electrode and conductive coating material shall be used.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 23529, *Rubber — General procedures for preparing and conditioning test pieces for physical test methods*

3 Electrical resistance — specification

3.1 General

In general, the resistance of new antistatic belts should not exceed the maximum value as calculated in [3.2](#).