
**Solar energy — Solar thermal
collectors — Test methods**

Énergie solaire — Capteurs thermiques solaires — Méthodes d'essai

Sample Document

get full document from standards.iteh.ai



Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	viii
Introduction	ix
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols	2
5 General	5
5.1 Test overview — Sequence of the tests	5
5.2 Testing of collectors with specific attributes	6
5.2.1 General	6
5.2.2 Collectors using external power sources and collectors with active or passive measures for normal operation and self-protection	6
5.2.3 Collectors co-generating thermal and electrical power	7
5.2.4 Wind and/or infrared sensitive collectors (WISC)	7
5.2.5 Façade collectors	7
5.2.6 Air and liquid heating collectors	8
6 Internal pressure tests for fluid channels	8
6.1 Objective	8
6.2 Fluid channels made of non-polymeric materials	8
6.2.1 Apparatus and procedure	8
6.2.2 Test conditions	8
6.3 Fluid channels made of polymeric materials	8
6.3.1 Apparatus and procedure	8
6.3.2 Test conditions	9
6.4 Results and reporting	9
7 Air leakage rate test (air heating collectors only)	9
7.1 Objective	9
7.2 Apparatus and procedure	9
7.3 Test conditions	10
7.4 Results and reporting	10
8 Rupture or collapse test (air heating collectors only)	10
8.1 Objective	10
8.2 Apparatus and procedure	10
8.2.1 General	10
8.2.2 Closed-loop collectors	11
8.2.3 Open to ambient collectors	11
8.3 Results and reporting	11
9 Standard stagnation temperature	11
9.1 Objective	11
9.2 Testing under stagnation conditions	12
9.3 Measurement and extrapolation of standard stagnation temperature	12
9.4 Determining standard stagnation temperature using efficiency parameters	12
9.5 Results and reporting	13
10 Exposure and half-exposure test	13
10.1 Objective	13
10.2 Initial outdoor exposure	13
10.3 Method 1	14
10.4 Method 2	14
10.5 Method 3	14
10.6 Test conditions	14

10.7	Results and reporting.....	15
11	External thermal shock.....	15
11.1	Objective.....	15
11.2	Apparatus and procedure.....	15
11.3	Test conditions.....	15
11.4	Results and reporting.....	16
12	Internal thermal shock test (Liquid heating collectors only).....	16
12.1	Objective.....	16
12.2	Apparatus and procedure.....	16
12.3	Test conditions.....	16
12.4	Results and reporting.....	16
13	Rain penetration test.....	16
13.1	Objective.....	16
13.2	Apparatus and procedure.....	16
13.3	Test conditions.....	17
13.4	Results and reporting.....	19
14	Freeze resistance test.....	19
14.1	Objective.....	19
14.2	Freeze resistant collectors.....	19
14.2.1	General.....	19
14.2.2	Test conditions.....	19
14.3	Heatpipe collectors.....	19
14.3.1	General.....	19
14.3.2	Test conditions.....	20
14.3.3	Results and reporting.....	20
15	Mechanical load test with positive or negative pressure.....	20
15.1	Objective.....	20
15.2	Apparatus and procedure.....	20
15.2.1	Mounting.....	20
15.2.2	Methods for the application of the loads.....	21
15.2.3	Particular specifications for tracking collectors or other specific collector types.....	22
15.3	Test conditions.....	22
15.4	Results and reporting.....	22
16	Impact resistance test.....	22
16.1	Objective.....	22
16.2	Test procedure.....	22
16.3	Impact location.....	22
16.4	Method 1: Impact resistance test using ice balls.....	23
16.4.1	Apparatus.....	23
16.4.2	Ice balls.....	23
16.4.3	Specific aspects of the test procedure using ice balls.....	23
16.5	Method 2: Impact resistance test using steel balls.....	23
16.6	Results and reporting.....	24
17	Final inspection.....	24
17.1	Objective.....	24
17.2	Test procedure.....	24
17.3	Results and reporting.....	25
18	Test report.....	25
19	Thermal performance testing.....	25
19.1	General.....	25
19.2	Performance test using a solar irradiance simulator.....	25
19.2.1	General.....	25
19.2.2	Solar irradiance simulator for performance testing.....	25
19.2.3	Solar irradiance simulator for the measurement of incidence angle modifiers.....	26

20	Collector mounting and location	27
20.1	General	27
20.2	Collector orientation outdoors	27
20.3	Shading from direct solar irradiance	27
20.4	Diffuse and reflected solar irradiance	27
20.5	Thermal irradiance	28
20.6	Surrounding air speed	28
21	Instrumentation	28
21.1	Solar radiation measurement	28
21.1.1	Pyranometer	28
21.2	Thermal radiation measurement	29
21.2.1	General	29
21.2.2	Measurement of thermal irradiance outdoors	29
21.2.3	Measurement of thermal irradiance indoors	29
21.3	Temperature measurements	29
21.3.1	General	29
21.3.2	Heat transfer fluid temperatures (Liquid heating collectors)	29
21.3.3	Volume flow weighted mean temperature $\vartheta_{m,th}$ (Air heating collectors)	30
21.3.4	Measurement of ambient air temperature	30
21.4	Flow rate measurement	31
21.4.1	Measurement of mass flow rate (liquid)	31
21.4.2	Measurement of collector fluid flow rate (Air heating collectors)	31
21.5	Measurement of air speed over the collector	31
21.5.1	General	31
21.5.2	Required accuracy	32
21.6	Elapsed time measurement	32
21.7	Humidity measurement (Air collectors)	32
21.8	Collector dimensions	32
22	Test installation	32
22.1	Liquid heating collectors	32
22.1.1	General	32
22.1.2	Heat transfer fluid	33
22.1.3	Pipe work and fittings	33
22.1.4	Pump and flow control devices	34
22.2	Air heating collectors	34
22.2.1	General	34
22.2.2	Closed loop test circuit	34
22.2.3	Open to ambient test circuit	35
22.2.4	Heat transfer fluid	35
22.2.5	Test ducts	35
22.2.6	Fan and flow control devices	36
22.2.7	Air preconditioning apparatus	36
22.2.8	Humidity ratio	36
23	Thermal performance test procedures	36
23.1	General	36
23.2	Preconditioning of the collector	37
23.3	Test conditions	37
23.3.1	General	37
23.3.2	Flow rates	37
23.3.3	Steady-state method	37
23.3.4	Quasi dynamic test	38
23.4	Test procedure	38
23.4.1	General	38
23.4.2	Steady-state testing of liquid heating collector	38
23.4.3	Steady-state testing of air heating collectors	38
23.4.4	Steady-state testing of WISC collectors	39
23.4.5	Quasi dynamic testing	39

23.5	Measurements.....	39
23.5.1	General.....	39
23.5.2	Additional measurements during tests in solar irradiance simulators.....	40
23.5.3	Data acquisition requirements.....	40
23.6	Test period.....	40
23.6.1	Steady-state testing.....	40
23.6.2	Quasi dynamic testing.....	41
24	Computation of the collector parameters.....	44
24.1	Liquid heating collectors.....	44
24.1.1	General.....	44
24.1.2	Steady-state test method for liquid heating collectors.....	45
24.1.3	Quasi dynamic test method for liquid heating collectors.....	45
24.1.4	Data analysis.....	45
24.2	Air heating collectors.....	46
24.2.1	General.....	46
24.2.2	Steady-state test method for closed loop air heating collectors.....	46
24.2.3	Steady-state test method for open to ambient air heating collectors.....	46
24.2.4	Steady-state test method for open to ambient air heating WISC collectors.....	46
24.3	Standard reporting conditions (SRC).....	46
24.4	Standard uncertainties.....	47
24.5	Reference area conversion.....	47
25	Determination of the effective thermal capacity and the time constant.....	47
25.1	General.....	47
25.2	Measurement of the effective thermal capacity with irradiance.....	47
25.3	Measurement of the effective thermal capacity using the quasi dynamic method.....	48
25.4	Calculation method for the determination of the effective thermal capacity.....	48
25.5	Determination of collector time constant.....	48
26	Determination of the incident angle modifier (IAM).....	49
26.1	General.....	49
26.2	Modelling.....	50
26.2.1	Steady-state.....	51
26.2.2	Quasi dynamic.....	52
26.3	Test procedures.....	52
26.3.1	Steady-state liquid heating collectors.....	52
26.3.2	Air collectors.....	52
26.4	Calculation of the collector incidence angle modifier.....	53
26.5	Reporting.....	53
27	Determination of the pressure drop.....	53
27.1	General.....	53
27.2	Liquid heating collectors.....	53
27.2.1	Apparatus and procedure.....	53
27.2.2	Pressure drop caused by fittings.....	54
27.2.3	Test conditions.....	54
27.3	Air heating collectors.....	54
27.3.1	Apparatus and procedure.....	54
27.4	Calculation and presentation of results.....	55
	Annex A (normative) Test reports.....	56
	Annex B (normative) Steady-state and quasi dynamic model.....	80
	Annex C (normative) Density and heat capacity of water.....	81
	Annex D (informative) Assessment of the standard uncertainty in solar collector testing.....	82
	Annex E (informative) Measurement of the velocity weighted mean temperature.....	86
	Annex F (informative) Material efficiency aspects.....	88
	Annex G (informative) Area conversion of thermal performance parameters.....	89

Bibliography	90
---------------------------	-----------

Sample Document

get full document from standards.iteh.ai

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 312, *Thermal solar systems and components*, in collaboration with ISO Technical Committee TC 180, *Solar energy*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition ISO 9806:2013, which has been technically revised.

Introduction

This document defines procedures for testing fluid heating solar collectors for thermal performance, reliability, durability and safety under well-defined and repeatable conditions. It contains performance test methods for conducting tests outdoors under natural solar irradiance and natural and simulated wind and for conducting tests indoors under simulated solar irradiance and wind. Outdoor tests can be performed either steady-state or as all-day measurements, under changing weather conditions.

Collectors tested according to this document represent a wide range of applications, e.g. glazed flat plate collectors and evacuated tube collectors for domestic water and space heating, collectors for heating swimming pools or for other low temperature systems or tracking concentrating collectors for thermal power generation and process heat applications. This document is applicable to collectors using liquids, as well as air as heat transfer fluid. Similarly, collectors using external power sources for normal operation and/or safety purposes (overheating protection, environmental hazards, etc.), as well as hybrid devices generating thermal power and electrical power are also considered.

Sample Document

get full document from standards.iteh.ai

Sample Document

get full document from standards.iteh.ai

Solar energy — Solar thermal collectors — Test methods

1 Scope

This document specifies test methods for assessing the durability, reliability, safety and thermal performance of fluid heating solar collectors. The test methods are applicable for laboratory testing and for *in situ* testing.

This document is applicable to all types of fluid heating solar collectors, air heating solar collectors, hybrid solar collectors co-generating heat and electric power, as well as to solar collectors using external power sources for normal operation and/or safety purposes. It does not cover electrical safety aspects or other specific properties directly related to electric power generation.

This document is not applicable to those devices in which a thermal storage unit is an integral part to such an extent that the collection process cannot be separated from the storage process for making the collector thermal performance measurements.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 9060, *Solar energy — Specification and classification of instruments for measuring hemispherical solar and direct solar radiation*

ISO 9488, *Solar energy — Vocabulary*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 9488 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1

longitudinal plane

plane defined by the normal to the plane of the collector and the concentrator axis, or the largest symmetry line for flat biaxial geometries

3.2

maximum operating temperature

maximum temperature allowed during collector or system normal operation specified by the manufacturer

3.3

outgassing

process in which any material releases gases when it is exposed to elevated temperatures and/or reduced pressure

**3.4
reflector**

surface intended for reflecting radiant energy

**3.5
transversal plane**

plane defined by the normal to the plane of the collector and the line orthogonal to the concentrator axis, or the shortest symmetry line for flat biaxial geometries

**3.6
trigger temperature**

temperature value at which the safety controls are activated for fail-safe operating condition

4 Symbols

A_G	Gross area of collector as defined in the ISO 9488	m^2
a_1	Heat loss coefficient	$W/(m^2 \cdot K)$
a_2	Temperature dependence of the heat loss coefficient	$W/(m^2 \cdot K^2)$
a_3	Wind speed dependence of the heat loss coefficient	$J/(m^3 \cdot K)$
a_4	Sky temperature dependence of the heat loss coefficient	—
a_5	Effective thermal capacity	$J/(m^2 \cdot K)$
a_6	Wind speed dependence of the zero loss efficiency	s/m
a_7	Wind speed dependence of IR radiation exchange	$W/(m^2 \cdot K^4)$
a_8	Radiation losses	$W/(m^2 \cdot K^4)$
b_u	Collector efficiency coefficient (wind dependence)	s/m
C	Effective thermal capacity of collector	J/K
C_R	Geometric concentration ratio	—
c_f	Specific heat capacity of heat transfer fluid	$J/(kgK)$
$c_{f,i}$	Specific heat capacity of heat transfer fluid at the collector inlet	$J/(kgK)$
$c_{f,e}$	Specific heat capacity of heat transfer fluid at the collector outlet	$J/(kgK)$
$c_{f,a}$	Specific heat capacity of the ambient air	$J/(kgK)$
E_L	Longwave irradiance ($\lambda > 3 \mu m$)	W/m^2
G_{hem}	Hemispherical solar irradiance	W/m^2
G_S	Hemispherical solar irradiance for the calculation for the standard stagnation temperature	W/m^2
G_m	Average measured hemispherical solar irradiance	W/m^2
G''	Net irradiance	W/m^2
G_b	Direct solar irradiance (beam irradiance)	W/m^2

G_d	Diffuse solar irradiance	W/m ²
H	Irradiation on collector plane for exposure test	MJ/m ²
$K_{\text{hem}}(\theta_L, \theta_T)$	Incidence angle modifier for hemispherical solar radiation	—
$K_b(\theta_L, \theta_T)$	Incidence angle modifier for direct solar irradiance	—
$K_{\theta L}$	Incidence angle modifier in the longitudinal plane	—
$K_{\theta T}$	Incidence angle modifier in the transversal plane	—
K_d	Incidence angle modifier for diffuse solar radiation	—
$\dot{m}$	Mass flow rate of heat transfer fluid	kg/s
$\dot{m}_{\text{min}}$	Minimum mass flow by the performance test	kg/h
$\dot{m}_{\text{max}}$	Maximum mass flow by the performance test	kg/h
$\dot{m}_e$	Downstream air mass flow rate	kg/s
$\dot{m}_i$	Upstream air mass flow rate	kg/s
$\dot{m}_l$	Leakage air mass flow rate	kg/s
$p_{f,e}$	Static pressure of the heat transfer fluid (air) at the outlet of the solar collector	Pa
$p_{f,i}$	Static pressure of the heat transfer fluid (air) at the inlet of the solar collector	Pa
p_{abs}	Absolute pressure of the ambient air	Pa
$\dot{Q}$	Useful power extracted from collector	W
$\dot{Q}_{\text{Peak}}$	Peak power. Power output of the collector for normal incidence, $G_b = 850 \text{ W/m}^2$, $G_d = 150 \text{ W/m}^2$ and $\vartheta_m - \vartheta_a = 0 \text{ K}$	W
R_D	Gas constant for water vapour	461,4 J/(kgK)
R_L	Gas constant for air	287,1 J/(kgK)
T	Absolute temperature	K
t	Time	s
u	Surrounding air speed	m/s
u'	Reduced surrounding air speed $u' = u - 3 \text{ m/s}$	m/s
U	Measured overall heat loss coefficient of collector with reference to $(\vartheta_m - \vartheta_a)/G_{\text{hem}}$	W/(m ² K)
V_f	Fluid capacity of the collector	m ³
$\dot{V}$	Volumetric flow	m ³ /s

$\dot{V}_e$	Volumetric flow at the outlet of the solar collector	m ³ /s
$\dot{V}_i$	Volumetric flow at the inlet of the solar collector	m ³ /s
$\dot{V}_l$	Volumetric leakage flow rate	m ³ /s
$X_{W,a}$	Water content of the ambient air	kg H ₂ O/kg dry air
$X_{W,e}$	Water content of the air at the exit of the solar collector	kg H ₂ O/kg dry air
$X_{W,i}$	Water content of the air at the inlet of the solar collector	kg H ₂ O/kg dry air
Δp	Pressure difference between fluid inlet and outlet	Pa
Δt	Time interval	s
ΔT	Temperature difference between fluid outlet and inlet ($\vartheta_e - \vartheta_{in}$)	K
γ	Solar azimuth angle	°
η_b	Collector efficiency based on beam irradiance G_b	—
η_{hem}	Collector efficiency based on hemispherical irradiance G_{hem}	—
$\eta_{0,b}$	Peak collector efficiency (η_b at $\vartheta_m - \vartheta_a = 0$ K) based on beam irradiance G_b	—
$\eta_{0,hem}$	Peak collector efficiency ($\eta_{0,hem}$ at $\vartheta_m - \vartheta_a = 0$ K) based on hemispherical irradiance G_{hem}	—
$\eta_{hem,\dot{m}_i}$	Collector efficiency, with reference to mass flow $\dot{m}_i$	—
θ	Angle of incidence	°
θ_L	Longitudinal angle of incidence: angle between the normal to the plane of the collector and incident sunbeam projected into the longitudinal plane	°
θ_T	Transversal angle of incidence: angle between the normal to the plane of the collector and incident sunbeam projected into the transversal plane	°
ϑ_a	Ambient air temperature	°C
ϑ_{am}	Measured ambient air temperature	°C
ϑ_{as}	Ambient air temperature for the standard stagnation temperature	°C
ϑ_e	Collector outlet temperature	°C
ϑ_i	Collector inlet temperature	°C
ϑ_m	Mean temperature of heat transfer fluid	°C
ϑ_{max_op}	Maximum operating temperature	°C
ϑ_{stg}	Standard stagnation temperature	°C
ϑ_{sky}	Atmospheric or sky temperature	°C

$\vartheta_{\text{trigger}}$	Trigger temperature for safety activation	°C
$\vartheta_{\text{m,th}}$	Volume flow weighted mean temperature	°C
$\vartheta_{\text{mp,e}}$	Fluid temperate at the downstream air mass flow meter	°C
$\vartheta_{\text{mp,i}}$	Fluid temperate at the upstream air mass flow meter	°C
ϑ_{sm}	Average measured absorber temperature	°C
λ	Wavelength	µm
ρ	Density of heat transfer fluid	kg/m ³
ρ_{l}	Density of air	kg/m ³
σ	Stefan-Boltzmann constant	W/(m ² K ⁴)
τ_{c}	Collector time constant	s
τ	Transmittance	—
$(\tau\alpha)$	Effective transmittance-absorptance product	—

5 General

5.1 Test overview — Sequence of the tests

A full test sequence for solar thermal collectors including durability test and thermal performance measurements is proposed in [Table 1](#). This test sequence may be modified or only single tests may be performed as required. For some tests, however, a certain preconditioning or a half-exposure test (see [Clause 10](#)) is mandatory. For all test sequences and single tests, the final inspection (see [Clause 17](#)) is recommended as concluding test for the proper identification and description of the test sample, as well as to identify problems or deficiencies.

Table 1 — Test list

Clause	Test
Clause 7	Air leakage rate test ^f
Clause 8	Rupture or collapse test ^f
Clause 9	Standard stagnation temperature
Clause 10	Exposure test ^b
Clause 11	External thermal shock test ^b
Clause 12	Internal thermal shock test ^{b,e}
Clause 13	Rain penetration test ^f
Clause 14	Freeze resistance test ^{c,f}
Clause 6	Internal pressure test for fluid channels ^{a,d,e}
Clause 15	Mechanical load test ^f
Clause 16	Impact resistance test ^g
Clause 17	Final inspection